

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Page 1/16

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- Trade name: EN 1100 STONE CHIP KG
- Article number: 1025
- · Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- $\cdot \, \textbf{Product category} \, \text{PC9a} \,$ Coatings and paints, thinners, paint removers
- Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- Environmental release category ERC2 Formulation into mixture
- Article category AC1 Vehicles
- · Application of the substance / the mixture Surface protection
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

EN Chemicals S.A. 57 009 Kalochori Thessalonikil, GREECE T: +30 2310 755 428 F: +30 2310 755 428 info@enchemicals.com www.enchemicals.com

· Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited Address: 388 Church Street, Penrose, Auckland Ph (09) 525 1000; Fax (09) 525 1009

• Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

2 Hazards identification

\cdot Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.





Page 2/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

Repr. 1AH360 May damage fertility or the unborn child.STOT RE 2H373 May cause damage to organs through prolonged or repeated exposure.

Skin Irrit. 2 H315 Causes skin irritation.

Acute Tox. 5 H333 May be harmful if inhaled.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

•Additional information:

6.9B Substances that are harmful to human target organs or systems

- 6.1E Substances that are acutely toxic May be harmful, aspiration hazard
- 6.3A Substances that are irritating to the skin
- 9.1D Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action
- 9.1C Substances that are harmful in the aquatic environment
- 9.1D Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action

· Label elements

• GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

toluene

Solvent naphtha (petroleum), light arom.

· Hazard statements

H225 Highly flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H360 May damage fertility or the unborn child.

- H373 May cause damage to organs through prolonged or repeated exposure.
- H412 Harmful to aquatic life with long lasting effects.



Page 3/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

· Precautionary statements

P210Keep away from heat/sparks/open flames/hot surfaces. No smoking.P241Use explosion-proof electrical/ventilating/lighting equipment.P260Do not breathe dust/fume/gas/mist/vapours/spray.P303+P361+P353IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.P405Store locked up.P501Dispose of contents/container in accordance with local/regional/national/international regulations.• Other hazards• Results of PBT and vPvB assessment• PBT: Not applicable.

• **vPvB:** Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of hazardous substances

· Dangerous components:

| CAS: 64742-49-0 | Naphtha (petroleum), hydrotreated light | 20-<25% |
|--|--|---------|
| EINECS: 265-151-9 Index number: 649-328- | Flam. Liq. 2, H225 Asp. Tox. 1, H304 | |
| CAS: 108-88-3 EINECS: 203-625-9 Index number: 601-021-0 RTECS: XS 5250000 | toluene Flam. Liq. 2, H225 Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315 Acute Tox. 5, H303 | 15-‹20% |
| CAS: 64742-95-6 EINECS: 265-199-0 Index number: 649-356- | Solvent naphtha (petroleum), light arom. Flam. Liq. 3, H226 00-4 Asp. Tox. 1, H304 Aquatic Chronic 2, H411 Acute Tox. 4, H332; STOT SE 3, H335-H336 Acute Tox. 5, H313; Aquatic Acute 2, H401 | 2.5-‹5% |
| CAS: 13463-67-7 EINECS: 236-675-5 • Additional informatio | titanium dioxide Acute Tox. 5, H333 Dn: For the wording of the listed hazard phrases refer to section 16. | <2.5% |



Page 4/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

4 First aid measures

- $\cdot \, \text{Description}$ of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water.
- After swallowing: If symptoms persist consult doctor.

Information for doctor:

- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced. • Advice for firefighters
- Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
- Speial protective equipment and fire fighting procedures: Mouth respiratory protective device.
- ·Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system. HAZ CHEM CODE: 3YE

* 6 Accidental release measures

- · Personal precautions, protective equipment and emergency procedures
- Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

 \cdot Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.



Page 5/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

Ensure adequate ventilation.

·Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

·Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

Keep respiratory protective device available.

· Conditions for safe storage, including any incompatibilities

- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.

· Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

· Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WES (New Zealand) Long-term value: 188 mg/m³, 50 ppm skin IOELV (EU) Short-term value: 384 mg/m³, 100 ppm Long-term value: 192 mg/m³, 50 ppm Skin



Page 6/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

· Regulatory information

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices IOELV (EU): (EU) 2019/1831

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

• Material of gloves


The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves

• Eye protection:





Page 7/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

-

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

· Body protection: Protective work clothing

9 Physical and chemical properties *

| · Information on basic physical and chemical properties | mical properties |
|---|--|
| General Information | |
| · Appearance: | |
| Form: | Fluid |
| Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| ·pH-value: | Not determined. |
| · Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range | :36 °C |
| ·Flash point: | < 0 °C |
| ·Flammability (solid, gas): | Not applicable. |
| • Autoignition temperature: | 535 °C |
| · Decomposition temperature: | Not determined. |
| • Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Risk of explosion by shock, friction, fire or other sources of ignition. |
| · Explosion limits: | |
| Lower: | 1.2 Vol % |
| Upper: | 7 Vol % |
| ·Vapour pressure at 20 °C: | 29 hPa |
| Density at 20 °C: | 1.196 g/cm ³ |
| ·Relative density | Not determined. |
| ·Vapour density | Not determined. |
| · Evaporation rate | Not determined. |
| ·Solubility in / Miscibility with | |
| water: | Fully miscible. |
| · Partition coefficient: n-octanol/water: | Not determined. |
| | Continue o |



Page 8/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

| ·Viscosity: Dynamic: Kinematic: | Not determined. Not determined. |
|---|---|
| Solvent content: Organic solvents: Water: VOC (EC) | 44.6 % 0.1 % 533.8 g/l |
| Solids content (volume): • Other information | 8.5 % No further relevant information available. |

10 Stability and reactivity

· **Reactivity** No further relevant information available.

- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · **Incompatible materials:** No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- ·Information on toxicological effects
- · Acute toxicity

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

| | / | |
|------------|---------------|-----------------------|
| Oral | LD50 | 26,217 mg/kg (rat) |
| Dermal | LD50 | >131,259 mg/kg (rab) |
| Inhalative | LC50/4 h | >243 mg/l (rat) |
| 108-88-3 | toluene | |
| Oral | LD50 | 5,000 mg/kg (rat) |
| Dermal | LD50 (static) | 12,124 mg/kg (rabbit) |
| Inhalative | LC50/4 h | 5,320 mg/l (mouse) |

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral LD50 >6,800 mg/kg (rat)



Page 9/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

Dermal LD50 >3,400 mg/kg (rab)

Inhalative LC50/4 h >10.2 mg/l (rat)

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)

Dermal LD50 >10,000 mg/kg (rabbit)

Inhalative LC50/4 h >6.82 mg/l (rat)

· Primary irritant effect:

• Skin corrosion/irritation Irritant to skin and mucous membranes.

- · Serious eye damage/irritation No irritating effect.
- **Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.

·Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Repr. 1A

12 Ecological information

· Toxicity

• Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- · Behaviour in environmental systems:
- **Bioaccumulative potential** No further relevant information available.
- Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- ·Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.



Page 10/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

Harmful to aquatic organisms

· Results of PBT and vPvB assessment

- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- ·**vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- $\cdot \ Other \ adverse \ effects$ No further relevant information available.

*13 Disposal considerations

- ·Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

| · UN-Number | |
|--|--------------------------------------|
| | |
| · ADR, IMDG, IATA | UN1263 |
| ·UN proper shipping name | |
| ·ADR | UN1263 PAINT, special provision 640D |
| · IMDG, IATA | PAINT |
| Transport hazard class(es) | |
| · ADR | |
| | |
| · Class | 3 (F1) Flammable liquids. |
| ·Label | 3 |
| ·IMDG, IATA | |
| | |
| · Class | 3 Flammable liquids. |
| ·Label | 3 |
| | Continue on page 11 |
| | |



Page 11/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

| · Packing group | |
|--|--|
| · ADR, IMDG, IATA | II |
| ·Environmental hazards: | |
| · Marine pollutant: | No |
| · Special precautions for user | Warning: Flammable liquids. |
| [.] Hazard identification number (Kemler code): | 33 |
| · EMS Number: | F-E,S-E |
| · Stowage Category | B |
| · Transport in bulk according to Annex II of Marpol and | |
| the IBC Code | Not applicable. |
| ·Transport/Additional information: | |
| ·ADR | |
| ·Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| · Transport category | 2 |
| ·Tunnel restriction code | D/E |
| ·IMDG | |
| ·Limited quantities (LQ) | 5L |
| Excepted quantities (EQ) | Code: E2 |
| | Maximum net quantity per inner packaging: 30 ml |
| | Maximum net quantity per outer packaging: 500 ml |
| ·IATA | |
| Remarks: | HAZ CHEM CODE: 3YE |
| · UN "Model Regulation": | UN 1263 PAINT, SPECIAL PROVISION 640D, 3, II |

15 Regulatory information

•3YE

· Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· New Zealand Inventory of Chemicals

64742-49-0 Naphtha (petroleum), hydrotreated light

108-88-3 toluene

Continue on page 12 NZ —



Page 12/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

9003-55-8 resin

64742-95-6 Solvent naphtha (petroleum), light arom.

68131-99-7 polymer

13463-67-7 titanium dioxide

67-64-1 acetone

7732-18-5 water, distilled, conductivity or of similar purity

1333-86-4 Carbon black

14808-60-7 Quartz (SiO2)

· HSNO Approval numbers

HSNO Approval number HSR 002662 Group standard name Surface Coatings and Colourandts (Flammable) Group Standard 2006 HSNO Hazard classification Refer to section 2

108-88-3 toluene: HSR001227

64742-95-6 Solvent naphtha (petroleum), light arom.: HSR001503

• **GHS** label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



· Signal word Danger

·Hazard-determining components of labelling:

toluene

Solvent naphtha (petroleum), light arom.

· Hazard statements

H225 Highly flammable liquid and vapour.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P260 Do not breathe dust/fume/gas/mist/vapours/spray.



Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.P405Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU

- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H313 May be harmful in contact with skin.
- H315 Causes skin irritation.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H360 May damage fertility or the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H401 Toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

· Department issuing SDS: Department of Quality Control

· Contact:

EN Chemicals S.A. 57 009 Kalochori Thessalonikil, GREECE T: +30 2310 755 428 F: +30 2310 755 428 info@enchemicals.com www.enchemicals.com



Page 14/16

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstract: Soniac (division of the American Chemical Society)

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 5: Acute toxicity - oral – Category 5

Acute Tox. 4: Acute toxicity - inhalation – Category 4

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard - Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3

* Data compared to the previous version altered.



Page 15/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

Annex: Exposure scenario

- · Short title of the exposure scenario
- Sector of Use SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities
- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- **Description of the activities / processes covered in the Exposure Scenario** See section 1 of the annex to the Safety Data Sheet.
- Conditions of use According to directions for use.
- **Duration and frequency** Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Used amount per time or activity** Smaller than 100 g per application.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure Use only on hard ground.
- · Other operational conditions affecting worker exposure

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols. Avoid contact with the skin.



Page 16/16

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 1100 STONE CHIP KG

Pregnant women should strictly avoid inhalation or skin contact.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

\cdot Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· Environmental protection measures

· Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point. Do not allow to reach sewage system.

· Soil

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

• **Disposal measures** Ensure that waste is collected and contained.

- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- · **Consumer** This product is to be used by professional technitians only.
- Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.