



Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

SECTION 1: Identification of the substance/mixture and of the company/undertaking

· 1.1 Product identifier

· Trade name: Cut Force PRO

· Article number: 22203

· 1.2 Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- · Application of the substance / the mixture Abrasive and polishing compound
- · 1.3 Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

Menzerna polishing compounds GmbH & Co. KG

Industriestraße 25 76470 ÖTIGHEIM

GERMANY

sds@menzerna.com Tel.: +49 (0) 7222 9157-0 www.menzerna.com

- · Further information obtainable from: Product and Environmental Safety Department
- · 1.4 Emergency telephone number: CHEMTREC: +1 703-741-5970 / 1-800-424-9300 CCN 842438

SECTION 2: Hazards identification

- · 2.1 Classification of the substance or mixture
- · Classification according to Regulation (EC) No 1272/2008

The product is not classified, according to the CLP regulation.

- · 2.2 Label elements
- · Labelling according to Regulation (EC) No 1272/2008 Void
- · Hazard pictograms Void
- · Signal word Void
- · Hazard statements Void
- · Additional information:

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, 2-methyl-2H-isothiazol-3-one. May produce an allergic reaction.

EUH210 Safety data sheet available on request.

- 2.3 Other hazards
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.

SECTION 3: Composition/information on ingredients

- · 3.2 Mixtures
- **Description:** Mixture of substances listed below with nonhazardous additions.

| · Dangerous components: | | |
|---------------------------|---|--------------------|
| CAS: 64742-55-8 | Distillates (petroleum), hydrotreated light paraffinic | 2.5-10% |
| EINECS: 265-158-7 | ♦ Asp. Tox. 1, H304 | |
| Reg.nr.: 01-2119487077-29 | | |
| CAS: 2634-33-5 | 1,2-benzisothiazol-3(2H)-one | <0.05% |
| EINECS: 220-120-9 | ♦ Acute Tox. 2, H330; ♦ Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400; Aquatic Chronic 2, H411; ♠ Acute Tox. 4, | |
| Reg.nr.: 01-2120761540-60 | Acute 1, H400; Aquatic Chronic 2, H411; 🔥 Acute Tox. 4, | |
| | H302; Skin Irrit. 2, H315; Skin Sens. 1, H317 | |
| | Specific concentration limit: Skin Sens. 1; H317: C ≥ 0.05 % | |
| · | | (Contd. on page 2) |

(Contd. on page 2)





Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

Trade name: Cut Force PRO

| | | (Contd. of page 1) |
|-------------------|---|--------------------|
| CAS: 2682-20-4 | 2-methyl-2H-isothiazol-3-one | ≥0-<0.0015% |
| EINECS: 220-239-6 | Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 2, H330; Skin Corr. 1B, H314; Eye Dam. 1, H318; Aquatic Acute 1, H400 (M=10); Aquatic Chronic 2, H411; Skin Sens. 1A, H317, EUH071 Specific concentration limit: Skin Sens. 1A; H317: C ≥ 0.0015 | |

· Additional information:

CAS: 64742-55-8: Note L: The harmonised classification as a carcinogen is made unless it can be shown that the substance contains less than 3% dimethyl sulphoxide extract as measured by method IP 346 ("Determination of polycyclic aromatics in unused lubricating oils and asphalt-free petroleum fractions - Dimethyl Sulphoxide Extraction Refractive Index Method", Institute of Petroleum, London).Result: : DMSO extract < 3% according to method IP 346

For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

- · 4.1 Description of first aid measures
- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.

If skin irritation continues, consult a doctor.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· After swallowing:

Rinse out mouth and then drink plenty of water.

If symptoms persist consult doctor.

4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treat according to symptoms.

SECTION 5: Firefighting measures

- · 5.1 Extinguishing media
- · Suitable extinguishing agents: Water spray, foam, dry powder or carbon dioxide.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture No further relevant information available.
- · 5.3 Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Ensure adequate ventilation. Use personal protection recommended in section 8.

- 6.2 Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

(Contd. on page 3)





Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

Trade name: Cut Force PRO

(Contd. of page 2)

· 6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection: No special measures required.
- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles:

Store in a well-ventilated place. Storage temperature: between 5°C and 30°C.

- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · 7.3 Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · 8.1 Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

At this time, the remaining constituent has no known exposure limits.

| · DNELs | | | | |
|--|--|-------------------------|---------------------------------------|--|
| CAS: 64742-55-8 Distillates (petroleum), hydrotreated light paraffinic | | | | |
| Inhalative | Inhalative DNEL, general population, inhalativ | | 1.19 mg/m3 | |
| | DNEL, worker, inhalativ | | 5.58 mg/m3 | |
| CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one | | | | |
| Dermal | DNEL, gene | eral population, dermal | 0.345 mg/kg KG/d (general population) | |
| | DNEL, work | cer, dermal | 0.966 mg/kg KG/d (worker) | |
| Inhalative | e DNEL, general population, inhalativ | | 1.2 mg/m3 (general population) | |
| | DNEL, worker, inhalativ | | 6.81 mg/m3 (worker) | |
| ·PNECs | | | | |
| CAS: 263 | 4-33-5 1,2-b | enzisothiazol-3(2H)-on | е | |
| PNEC (Se | wage plant) | 1.03 mg/l | | |
| PNEC (fre | shwater) | 4.03 μg/l | | |
| PNEC (se | awater) | 0.000403 mg/l | | |
| sediment (freshwater) 0. | | 0.0499 mg/kg | | |
| Sediment (seawater) | | 0.00499 mg/kg | | |
| soil 3 mg/kg | | | Ah | |

- Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- · Appropriate engineering controls No further data; see section 7.

(Contd. on page 4)





Version number 1.3 (replaces version 1.2) Revision: 26.04.2023 Printing date 26.04.2023

Trade name: Cut Force PRO

(Contd. of page 3)

· Individual protection measures, such as personal protective equipment

· General protective and hygienic measures:

Wash hands before breaks and at the end of work.

The design of body protection equipment must be selected specifically for the workplace, depending on the concentration and quantity of hazardous substances.

Respiratory protection:

Not necessary when used as intended. Ventilate work area well. Respiratory protection is required in case

of dusts/vapours/aerosols as well as increased concentration in the air (filter class according to DIN EN 141). Observe wearing time limitations.

Hand protection

As a rule, one does not come into direct contact with the product during use.

Protective gloves must not be worn if there is a risk of the protective glove being drawn into rotating or linearly moving machine parts.

Recommendation for short-term exposure: chemical-resistant protective gloves (according to the specifications of VO (EU) No. 2016/425 and DIN EN 374).

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.45 mm

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

≥ 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· Eve/face protection

Frame goggles with side protection (according to DIN EN 166:2001, Personal eye protection -Requirements).

Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

• 9.1 Information on basic physical and chemical properties

· General Information

· Physical state Fluid · Colour: White

· Odour: Characteristic · Odour threshold: Not determined. · Melting point/freezing point: Undetermined.

· Boiling point or initial boiling point and boiling

range

conductivity or of similar purity) Not applicable. · Flammability

· Lower and upper explosion limit

· Lower: Not determined. · Upper: Not determined. >100 °C (>212 °F) · Flash point: Not determined. · Decomposition temperature:

pH at 20 °C (68 °F)

(Contd. on page 5)

100 °C (212 °F) (CAS: 7732-18-5 water, distilled,





Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

Trade name: Cut Force PRO

(Contd. of page 4)

| | (Contd. of page 4) |
|---|---|
| · Viscosity: | |
| · Kinematic viscosity | Not determined. |
| · Kinematic viscosity | |
| · Dynamic at 20 °C (68 °F): | 7,500-15,000 mPas |
| · Solubility | |
| · water: | Not miscible or difficult to mix. |
| · Partition coefficient n-octanol/water (log value) | Not determined. |
| Vapour pressure: | Not determined. |
| · Vapour pressure: | |
| · Density and/or relative density | |
| Density at 20 °C (68 °F): | 1.13 g/cm³ (9.43 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · 9.2 Other information | DMSO extract < 3% according to method IP 346 |
| · Appearance: | Ç |
| · Form: | Viscous |
| · Important information on protection of health | |
| and environment, and on safety. | |
| · Ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product does not present an explosion hazard. |
| · Solvent content: | |
| · VOC (EC) | 0.00 % |
| Change in condition | |
| · Softening point/range | |
| Oxidising properties | Not determined. |
| · Evaporation rate | Not determined. |
| · Information with regard to physical hazard | |
| classes | |
| · Explosives | Void |
| Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| Flammable liquids | Void |
| Flammable solids | Void |
| Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids · Pyrophoric solids | Void Void |
| Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit flammable | |
| gases in contact with water | Void |
| Oxidising liquids | Void |
| · Oxidising solids | Void |
| · Organic peroxides | Void |
| · Corrosive to metals | Void |
| Desensitised explosives | Void |
| Doonoliou oxploored | v OIM |

SECTION 10: Stability and reactivity

· 10.1 Reactivity None under normal conditions.





Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

Trade name: Cut Force PRO

(Contd. of page 5)

- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- · 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- · 10.6 Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

- · 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008
- · Acute toxicity Based on available data, the classification criteria are not met.

| · LD/LC5 | · LD/LC50 values relevant for classification: | | |
|----------|--|---------------------------------|--|
| CAS: 64 | CAS: 64742-55-8 Distillates (petroleum), hydrotreated light paraffinic | | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| Dermal | LD50 | >2,000 mg/kg (rabbit) | |
| CAS: 26 | 634-33 ₋ | -5 1,2-benzisothiazol-3(2H)-one | |
| Oral | LD50 | 670-784 mg/kg (rat) | |
| Dermal | LD50 | >2,000 mg/kg (rat) | |

- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- · Serious eye damage/irritation Based on available data, the classification criteria are not met.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.
- · 11.2 Information on other hazards
- Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

· 12.1 Toxicity

| · Aquatic toxicity: | | |
|---|---|--|
| CAS: 2634-33-5 1,2-benzisothiazol-3(2H)-one | | |
| LC50/96h | 2.2 mg/l (Oncorhynchus mykiss) | |
| EC50 (48h) (static) | 0.643 mg/l (daphnia) | |
| EC50 (72h) | 0.11 mg/l (Selenastrum capricornutum) | |
| EC50 (96h) (static) | 0.9893 mg/l (Mysidopsis bahia) | |
| NOEC (72h) | 0.0403 mg/l (Pseudokirchneriella subcapitata) | |
| NOEC (96h) (static) | 0.25 mg/l (Mysidopsis bahia) | |
| NOEC (21d) | 1.2 mg/l (daphnia) | |
| NOEC (28d) | 0.21 mg/l (Oncorhynchus mykiss) | |
| ErC50 (72h) | 0.11 mg/l (Selenastrum capricornutum) | |

· 12.2 Persistence and degradability No further relevant information available.





Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

Trade name: Cut Force PRO

(Contd. of page 6)

Page 7/9

- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · 12.5 Results of PBT and vPvB assessment
- · **PBT:** Not applicable.
- · vPvB: Not applicable.
- · 12.6 Endocrine disrupting properties

The product does not contain substances with endocrine disrupting properties.

- 12.7 Other adverse effects
- · Additional ecological information:
- · General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

SECTION 13: Disposal considerations

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Waste disposal key:

Waste codes should be determined in consultation with the customer, supplier and disposal.

- · Uncleaned packaging:
- · Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

| Void |
|-----------------|
| Void |
| |
| Void |
| Void |
| Not applicable. |
| Not applicable. |
| Not applicable. |
| Void |
| |

SECTION 15: Regulatory information

• **15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture** Regulation 1907/2006/EC, REACH concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals (in the currently valid version)

(Contd. on page 8)





Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

Trade name: Cut Force PRO

(Contd. of page 7)

Regulation 1272/2008/EC, on Classification, Labelling and Packaging of substances and mixtures (in the currently valid version)

- Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- DIRECTIVE 2011/65/EU on the restriction of the use of certain hazardous substances in electrical and electronic equipment – Annex II

None of the ingredients is listed.

- · REGULATION (EU) 2019/1148
- · Annex I RESTRICTED EXPLOSIVES PRECURSORS (Upper limit value for the purpose of licensing under Article 5(3))

None of the ingredients is listed.

Annex II - REPORTABLE EXPLOSIVES PRECURSORS

None of the ingredients is listed.

Regulation (EC) No 273/2004 on drug precursors

None of the ingredients is listed.

Regulation (EC) No 111/2005 laying down rules for the monitoring of trade between the Community and third countries in drug precursors

None of the ingredients is listed.

· 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This safety data sheet complies with Regulation (EC) No 1907/2006, Article 31, as amended by Regulation (EU) 2020/878.

The information in the safety data sheet applies only to the product described in connection with its intended use. The information is based on the current state of our knowledge. In particular, they serve to describe our product with regard to the hazards it presents and the applicable safety precautions. They do not represent any assurance of product and quality properties. The information in this safety data sheet is required in accordance with Article 31 and Annex II of Regulation (EC) No 1907/2006.

· Relevant phrases

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H314 Causes severe skin burns and eye damage.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H318 Causes serious eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

EUH071 Corrosive to the respiratory tract.

- · Department issuing SDS: Product and Environmental Safety Department
- · Date of previous version: 29.03.2023
- · Version number of previous version: 1.2
- · Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

(Contd. on page 9)



Page 9/9

Safety data sheet according to 1907/2006/EC, Article 31

Printing date 26.04.2023 Version number 1.3 (replaces version 1.2) Revision: 26.04.2023

Trade name: Cut Force PRO

(Contd. of page 8)

GHS: Globally Harmonised System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH)
PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 4: Acute toxicity – Category 4

Acute Tox. 2: Acute toxicity - Category 2

Skin Corr. 1B: Skin corrosion/irritation – Category 1B
Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation - Category 1

Skin Sens. 1: Skin sensitisation - Category 1 Skin Sens. 1A: Skin sensitisation – Category 1A Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard - Category 2

* Data compared to the previous version altered.

- FU ---