

Page 1/11

Safety Data Sheet

in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

SECTION 1: Identification of the substance or mixture and of the supplier

· Product identifier

- Trade name: Super Heavy Cut Compound 300, PO 300
- Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Abrasive and polishing compound
- · Details of the supplier of the safety data sheet
- Manufacturer/Supplier: Menzerna polishing compounds GmbH & Co. KG Industriestraße 25 76470 ÖTIGHEIM GERMANY sds@menzerna.com Tel.: +49 (0) 7222 9157-0 www.menzerna.com

New Zealand Distributor: Wyatt Machine Tools Rupes (NZ) Limited 388 Church Street, Penrose, Auckland, New Zealand Ph (09) 525 1000

· Further information obtainable from: info@wyatt.co.nz

• Emergency telephone number: 0800 992 881 (0800WYATT1)

SECTION 2: Hazards identification

Classification of the substance or mixture

health hazard

STOT RE 2 H373 May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.
 Acute Tox. 5 H333 May be harmful if inhaled.
 Acute 2 H402 Harmful to equation life.

Aquatic Acute 3 H402 Harmful to aquatic life.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

· Label elements

· GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



· Signal word Warning

 Hazard-determining components of labelling: Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)



Page 2/11

Safety Data Sheet

in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

(Contd. of page 1)

Trade name: Super Heavy Cut Compound 300, PO 300

· Hazard statements

May be harmful if inhaled.

May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid release to the environment.

IF INHALED: Call a POISON CENTER/doctor if you feel unwell.

Get medical advice/attention if you feel unwell.

Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards
- · Results of PBT and vPvB assessment
- **PBT:** Not applicable.
- vPvB: Not applicable.

SECTION 3: Composition/Information on ingredients

· Mixtures

• Description: Mixture: consisting of the following components.

| [·] Dangerous components: | | | |
|---|--|---------------|--|
| CAS: 64742-55-8 | Distillates (petroleum), hydrotreated light paraffinic | 10-25% | |
| EINECS: 265-158-7 | 🚸 Asp. Tox. 1, H304; Acute Tox. 5, H313 | | |
| CAS: 64742-94-5 | Hydrocarbons, C10, aromatics, <1% naphthalene | 2.5-10% | |
| EC number: 918-811-1 | Asp. Tox. 1, H304; Aquatic Chronic 2, H411; STOT SE 3, H336; Flam. Liq. 4, H227; Acute Tox. 5, H313; Acute Tox. 5, H333 | | |
| CAS: 64742-82-1 EC number: 919-164-8 | Hydrocarbons, C10-C13, n-alkanes, isoalkanes,cyclics, aromatics (2-25%) | ≥2.5-<10% | |
| | STOT RE 1, H372; Asp. Tox. 1, H304; () Acute Tox. 4, H332; Flam. Liq. 4, H227; Acute Tox. 5, H313; Aquatic Chronic 3, H412 | | |
| CAS: 69011-36-5 | Isotridecaanol, ethoxylated | <1% | |
| | 🛞 Acute Tox. 3, H301; 📀 Eye Dam. 1, H318 | | |
| CAS: 52-51-7 | bronopol (INN) | ≥0.025-<0.25% | |
| EINECS: 200-143-0 | ♦ Eye Dam. 1, H318; ♦ Aquatic Acute 1, H400; Aquatic Chronic 1, H410; ♦ Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; STOT SE 3, H335 | | |
| . Additional information | · | | |

Additional information:

Distillates (petroleum), hydrotreated light paraffinic: DMSO Extract < 3% according Method IP 346 For the wording of the listed hazard phrases refer to section 16.

SECTION 4: First aid measures

Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- · After skin contact:

Immediately wash with water and soap and rinse thoroughly.



Page 3/11

Safety Data Sheet

in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

(Contd. of page 2)

Trade name: Super Heavy Cut Compound 300, PO 300

If skin irritation continues, consult a doctor.

- After eye contact:
- Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing:
- Rinse out mouth and then drink plenty of water.
- If symptoms persist consult doctor.
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- Indication of any immediate medical attention and special treatment needed Treat according to symptoms.

SECTION 5: Fire fighting measures

- · Extinguishing media
- Suitable extinguishing agents: Water spray, foam, dry powder or carbon dioxide.
- For safety reasons unsuitable extinguishing agents: Water with full jet
- Special hazards arising from the substance or mixture Nitrogen oxides (NOx)
- Advice for firefighters
- Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures
 Keep unnecessary personnel away. Ensure adequate ventilation. Use personal protection recommended in section 8.

Environmental precautions:

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose contaminated material as waste according to item 13.

- Ensure adequate ventilation.
- Reference to other sections
 See Section 7 for information on safe handling.
 See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

SECTION 7: Handling and storage

• **Precautions for safe handling** Ensure good ventilation/exhaustion at the workplace. Prevent formation of aerosols.

No special precautions are necessary if used correctly.

Information about fire - and explosion protection: Keep respiratory protective device available.



NZ —

Safety Data Sheet

in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Trade name: Super Heavy Cut Compound 300, PO 300

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:
- Store in a well-ventilated place. Storage temperature: between 5°C and 30°C.
- · Information about storage in one common storage facility: Not required.
- · Further information about storage conditions: None.
- · Specific end use(s) No further relevant information available.

SECTION 8: Exposure controls/personal protection

- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

The following constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit.

| CAS: 134 | 4-28-1 aluminium oxide (25-50%) | | | |
|---|---------------------------------------|-------------------------------|--|--|
| WES Lon | WES Long-term value: 10 mg/m³ | | | |
| CAS: 56-8 | 31-5 glycerol (≤2.5%) | | | |
| WES Lon mis | ig-term value: 10 mg/m³ t | | | |
| CAS: 102 | -71-6 Triethanolamine (≤2.5%) | | | |
| WES Lon | ig-term value: 5 mg/m³ | | | |
| ·DNELs | | | | |
| CAS: 647 | 42-55-8 Distillates (petroleum), hyd | drotreated light paraffinic | | |
| Inhalative | DNEL, general population, inhalativ | 1.19 mg/m3 | | |
| | DNEL, worker, inhalativ | 5.58 mg/m3 | | |
| CAS: 64742-94-5 Hydrocarbons, C10, aromatics, <1% naphthalene | | | | |
| Oral | DNEL, general population, oral | 7.5 mg/kg KG/d | | |
| Dermal | DNEL, general population, dermal | 7.5 mg/kg KG/d | | |
| | DNEL, worker, dermal | 12.5 mg/kg KG/d | | |
| Inhalative | DNEL, general population, inhalativ | 32 mg/m3 | | |
| | DNEL, worker, inhalativ | 150 mg/m3 | | |
| | I information: The lists valid during | the making were used as basis | | |

• Additional information: The lists valid during the making were used as basis.

- · Exposure controls
- Appropriate engineering controls No further data; see item 7.
- · Individual protection measures, such as personal protective equipment
- General protective and hygienic measures:
- Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

- Store protective clothing separately.
- Respiratory protection:

Use suitable respiratory protective device only when aerosol or mist is formed. Filter A/P2

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

(Contd. of page 3)

Revision: 08.03.2022

Page 4/11



Page 5/11

Safety Data Sheet in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

(Contd. of page 4)

Trade name: Super Heavy Cut Compound 300, PO 300

· Hand protection

Protective gloves

Normally one does not come into direct contact with the product during use. At the risk of entanglement of protective glove in rotating or linear moving machine parts protective gloves should not be worn. Recommendation for short-term exposure: Use chemical resistant gloves.

· Material of gloves

Nitrile rubber, NBR

Recommended thickness of the material: $\geq 0.45~\text{mm}$

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Penetration time of glove material

≥ 480 min

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- · Eye/face protection Safety glasses
- · Body protection: Protective work clothing

SECTION 9: Physical and chemical properties

| Information on basic physical and chemical properties | | | |
|---|-----------------------------------|--|--|
| General Information | | | |
| · Physical state | Fluid | | |
| · Colour: | White | | |
| · Odour: | Characteristic | | |
| · Odour threshold: | Not determined. | | |
| Melting point/freezing point: | Undetermined. | | |
| Boiling point or initial boiling point and boiling | | | |
| range | >100 °C (>212 °F) | | |
| · Flammability | Not applicable. | | |
| · Lower and upper explosion limit | | | |
| · Lower: | Not determined. | | |
| · Upper: | Not determined. | | |
| · Flash point: | >100 °C (>212 °F) | | |
| Decomposition temperature: | Not determined. | | |
| · pH at 20 °C (68 °F) | 7-10 | | |
| · Viscosity: | | | |
| · Kinematic viscosity | Not determined. | | |
| · Dynamic at 20 °C (68 °F): | 9,000-14,000 mPas | | |
| · Solubility | | | |
| · water: | Not miscible or difficult to mix. | | |
| · Partition coefficient n-octanol/water (log value) | Not determined. | | |
| · Vapour pressure: | Not determined. | | |
| | (Contd. on page 6) | | |



Page 6/11

Safety Data Sheet in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

Trade name: Super Heavy Cut Compound 300, PO 300

| | (Contd. of page |
|--|---|
| Density and/or relative density | |
| · Density at 20 °C (68 °F): | 1.3 g/cm³ (10.85 lbs/gal) |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| • Other information | |
| · Appearance: | |
| · Form: | Viscous |
| Important information on protection of health | |
| and environment, and on safety. | |
| Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product does not present an explosion hazard. |
| Solvent content: | |
| · VOC (EC) | ≤13.51 % |
| Change in condition | |
| · Softening point/range | |
| • Oxidising properties | Not determined. |
| Evaporation rate | Not determined. |
| · Information with regard to physical hazard | |
| classes | |
| · Explosives | Void |
| · Flammable gases | Void |
| Aerosols | Void |
| Oxidising gases | Void |
| Gases under pressure | Void |
| · Flammable liquids | Void |
| · Flammable solids | Void |
| · Self-reactive substances and mixtures | Void |
| · Pyrophoric liquids | Void |
| · Pyrophoric solids | Void |
| • Self-heating substances and mixtures | Void |
| Substances and mixtures, which emit flammab | |
| gases in contact with water | Void |
| · Oxidising liquids | Void |
| · Oxidising solids | Void |
| Organic peroxides | Void |
| · Corrosive to metals | Void |
| ⁻ Desensitised explosives | Void |

SECTION 10: Stability and reactivity

· Reactivity None under normal conditions.

- · Chemical stability
- Thermal decomposition / conditions to be avoided:
- No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- \cdot Incompatible materials: No further relevant information available.



Page 7/11

Safety Data Sheet

in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

(Contd. of page 6)

Trade name: Super Heavy Cut Compound 300, PO 300

· Hazardous decomposition products: No dangerous decomposition products known.

SECTION 11: Toxicological information

· Information on hazard classes as defined in Regulation (EC) No 1272/2008

· Acute toxicity May be harmful if inhaled.

· LD/LC50 values relevant for classification:

| CAS: 647 | 42-55-8 Di | stillates (petroleum), hydrotreated light paraffinic | |
|---|---|--|--|
| Oral | LD50 | >5,000 mg/kg (rat) | |
| Dermal | LD50 | >2,000 mg/kg (rabbit) | |
| CAS: 64742-94-5 Hydrocarbons, C10, aromatics, <1% naphthalene | | | |
| Oral | LD50 | >5,000 mg/kg (rat) | |
| Dermal | LD50 | >2,000 mg/kg (rabbit) | |
| Inhalative | LC50/4 h | >4,688 mg/l (rat) | |
| CAS: 647 | CAS: 64742-82-1 Hydrocarbons, C10-C13, n-alkanes, isoalkanes,cyclics, aromatics (2-25%) | | |
| Oral | LD50 | >15,000 mg/kg (rat) | |
| Dermal | LD50 | >3,400 mg/kg (rabbit) | |
| Inhalative | LC50/4 h | >13.1 mg/l (rat) | |
| CAS: 52-5 | 51-7 brono | pol (INN) | |
| Oral | LD50 | 305 mg/kg (rat) | |
| STOT-repeated exposure | | | |
| May cause damage to the central nervous system through prolonged or repeated exposure. Route of | | | |

exposure: Inhalation.

· Information on other hazards

· Endocrine disrupting properties

None of the ingredients is listed.

SECTION 12: Ecological information

| · Toxicity | |
|-----------------|---|
| · Aquatic toxic | ity: |
| CAS: 64742-9 | 04-5 Hydrocarbons, C10, aromatics, <1% naphthalene |
| EL50 (48h) | 3-10 mg/l (daphnia) |
| EL50 (72h) | 11 mg/l (Pseudokirchneriella subcapitata) |
| LL50 (96h) | 2-5 mg/l (Oncorhynchus mykiss) |
| NOELR (72h) | 2.5 mg/l (Pseudokirchneriella subcapitata) |
| CAS: 64742-8 | 2-1 Hydrocarbons, C10-C13, n-alkanes, isoalkanes,cyclics, aromatics (2-25%) |
| EC50 (72h) | 0.53 mg/l (al) |
| EC50 (21d) | 0.328 mg/l (Invertebraten, aquatisch) |
| EL50 (48h) | 22 mg/l (Invertebraten, aquatisch) |
| EL50 (21d) | 1.19 mg/l (Invertebraten, aquatisch) |
| LL50 (96h) | 30 mg/l (fi) |
| | (Contd. on page 8) |
| | NZ |



Safety Data Sheet in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

Page 8/11

NZ —

Trade name: Super Heavy Cut Compound 300, PO 300

| | (Contd. of page 7) | |
|-----------------------------|--|--|
| ErC50 (72h) | 0.94 mg/l (al) | |
| CAS: 52-51-7 bronopol (INN) | | |
| LC50/96h | 3 mg/l (Oncorhynchus mykiss) | |
| EC50 (3h) | 13 mg/l (Kläranlage) | |
| EC50 (48h) | 1.04 mg/l (dah) | |
| EC50 (72h) | 0.068 mg/l (al) | |
| NOEC (72h) | 0.0025 mg/l (al) | |
| NOEC (21d) | 0.06 mg/l (dah) | |
| NOEC (28d) | 2.61 mg/l (Oncorhynchus mykiss) | |
| Dorcistonco | and dogradability. No further relevant information available | |

· Persistence and degradability No further relevant information available.

 \cdot Bioaccumulative potential No further relevant information available.

- Mobility in soil No further relevant information available.
- · Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- · Endocrine disrupting properties
- The product does not contain substances with endocrine disrupting properties.
- · Other adverse effects
- · Remark: Harmful to fish
- · Additional ecological information:
- · General notes:

Danger to drinking water if even small quantities leak into the ground.

Do not allow product to reach ground water, water course or sewage system.

Harmful to aquatic organisms

SECTION 13: Disposal considerations

- · Waste treatment methods
- · Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system. Must be specially treated adhering to official regulations.

· Waste disposal key:

Waste codes should be determined in consultation with the customer, supplier and disposal.

- · Uncleaned packaging:
- Recommendation:

Packagings that may not be cleansed are to be disposed of in the same manner as the product.

SECTION 14: Transport information

| UN number or ID number ADR/RID, ADN, IMDG, IATA | Void | |
|---|------|--------------------|
| UN proper shipping name ADR/RID, ADN, IMDG, IATA | Void | |
| | | (Contd. on page 9) |



Page 9/11

Safety Data Sheet in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

Trade name: Super Heavy Cut Compound 300, PO 300

| | | (Contd. of page 8) |
|--|---------------------------|--------------------|
| Transport hazard class(es) | | |
| · ADR/RID, ADN, IMDG, IATA · Class | Void | |
| Packing group ADR/RID, IMDG, IATA | Void | |
| · Environmental hazards: | Not applicable. | |
| · Special precautions for user | Not applicable. | |
| Maritime transport in bulk according instruments | to IMO Not applicable. | |
| · UN "Model Regulation": | Void | |

SECTION 15: Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

| · New Zealand Inventory of Chemicals | | | |
|--------------------------------------|-----------------------------|-----------|--|
| All ingredients are listed. | | | |
| · HSNO Approval numbers | | | |
| CAS: 69011-36-5 | Isotridecaanol, ethoxylated | HSR003551 | |
| CAS: 52-51-7 bronopol (INN) HSR00 | | HSR003563 | |

GHS label elements

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



· Signal word Warning

· Hazard-determining components of labelling:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, aromatics (2-25%)

Hazard statements

May be harmful if inhaled.

May cause damage to the central nervous system through prolonged or repeated exposure. Route of exposure: Inhalation.

Harmful to aquatic life with long lasting effects.

Precautionary statements

Do not breathe dust/fume/gas/mist/vapours/spray.

Avoid release to the environment.

IF INHALED: Call a POISON CENTER/doctor if you feel unwell. Get medical advice/attention if you feel unwell.

Dispose of contents/container in accordance with local/regional/national/international regulations.



Page 10/11

Safety Data Sheet

in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

Trade name: Super Heavy Cut Compound 300, PO 300

(Contd. of page 9)

- · Directive 2012/18/EU
- Named dangerous substances ANNEX I None of the ingredients is listed.
- · Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

The details of the safety data sheet apply only to the product described in the context of its intended use. The information is based on the current state of our knowledge. It is intended to describe our product in view of the risks posed by it and the relevant precautionary measures. It does not represent an assurance of product and quality characteristics. The information in this safety data sheet is required under Article 31 and Annex II of Regulation EC (VO) no. 1907/2006.

· Reasons for alterations Void

Relevant phrases

H227 Combustible liquid.

- H301 Toxic if swallowed.
- H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

- H312 Harmful in contact with skin.
- H313 May be harmful in contact with skin.
- H315 Causes skin irritation.
- H318 Causes serious eye damage.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H372 Causes damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.
- H412 Harmful to aquatic life with long lasting effects.

· Department issuing SDS: Product and Environmental Safety Department

Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) DNEL: Derived No-Effect Level (REACH) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Liq. 4: Flammable liquids - Category 4 Acute Tox. 3: Acute toxicity – Category 3 Acute Tox. 5: Acute toxicity – Category 5 Acute Tox. 4: Acute toxicity – Category 4 Skin Irrit. 2: Skin corrosion/irritation - Category 2 Eye Dam. 1: Serious eye damage/eye irritation - Category 1 STOT SE 3: Specific target organ toxicity (single exposure) - Category 3



Safety Data Sheet in accordance with HSNO

Printing date 14.03.2022

Version number 8.1 (replaces version 8.0)

Revision: 08.03.2022

Page 11/11

– NZ —

Trade name: Super Heavy Cut Compound 300, PO 300

| STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1 Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3 Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard – Category 1 Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3 | (Contd. of page 10) |
|---|---------------------|
| ·* Data compared to the previous version altered. | 17 |