

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard
Issue date: 11/23/2022 Revision date: 22/01/2024 Version: 2.0

SECTION 1: Identification

1.1. Identification

Product form : Mixture
Trade name : XC-2 – XTRA CUT COMPOUND
Code name : 9.XC2/1KG – 9.XC2/4,5KG – 9.XC2 – 9.XC2/4L

1.2. Recommended use and restrictions on use

Recommended use : Abrasive and polishing compound
Restrictions on use : All other uses

1.3.1 Manufacturer

RUPES SPA
Via Marconi 3A
Loc. Vermezzo 20071 Vermezzo con Zelo (MI), Italy
PH: +3902946941
info_rupes@rupes.it

1.3.2 Supplier/Distributor

Wyatt Machine Tools Rupes (NZ) Limited
388 Church Street, Penrose, Auckland, New Zealand
PH: (09) 525 1000
Email: info@wyatt.co.nz

1.4. Emergency telephone number

24 hour emergency number : NZ Emergency 0800 992 881 (0800WYATT1)

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 4 H227 Combustible liquid
Full text of H statements : see section 16

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Signal word (GHS US) : Warning
Hazard statements (GHS US) : H227 - Combustible liquid
Precautionary statements (GHS US) : P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P280 - Wear protective gloves.
P370+P378 - In case of fire: Use carbon dioxide (CO₂), extinguishing powder, foam to extinguish.
P403+P235 - Store in a well-ventilated place. Keep cool.
P501 - Dispose of contents/container to an approved waste disposal plant.

2.3. Other hazards which do not result in classification

No additional information available

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

2.4. Unknown acute toxicity (GHS US)

No additional information available

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	CAS-No.: Mixture	10 – 20
Non-Hazardous Ingredients	CAS-No.: Mixture	80 – 90

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Move the affected person to fresh air. Get medical attention if symptoms occur.
First-aid measures after skin contact	: Gently wash with plenty of soap and water. Get medical advice if skin irritation persists.
First-aid measures after eye contact	: Rinse eyes with water as a precaution. Get medical attention if irritation develops and persists.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

Inhalation	: May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin	: May cause slight irritation to the skin.
Eyes	: May cause minor eye irritation.
Ingestion	: May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Most Important Symptoms/Effects	: May cause minor eye irritation. May cause slight irritation to the skin.

4.3. Immediate medical attention and special treatment, if necessary

Not required.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

Suitable extinguishing media	: Carbon dioxide (CO ₂). Dry powder. Foam. Use extinguishing media appropriate for surrounding fire.
Unsuitable extinguishing media	: Do not use water jet.

5.2. Specific hazards arising from the chemical

Fire hazard	: Combustible liquid.
Hazardous decomposition products in case of fire	: Toxic fumes may be released.

5.3. Special protective equipment and precautions for fire-fighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment.
--------------------------------	--

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Wear suitable protective clothing. Avoid contact with eyes, skin and clothing.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Wipe up with absorbent material (for example cloth).
Other information : Place in a suitable container for disposal in accordance with the waste regulations (see Section 13).

6.4. Reference to other sections

No additional information available

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Avoid contact with eyes, skin and clothing. Wash hands with water and soap. Ensure adequate ventilation.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : No special storage required.
Incompatible materials : Strong oxidizers. None known.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

XC-2	
USA - ACGIH - Occupational Exposure Limits	
Local name	Fuel oil No. 2, as total hydrocarbons
ACGIH OEL TWA	100 mg/m ³ (IFV - Inhalable fraction and vapor)
Remark (ACGIH)	TLV® Basis: Dermatitis. Notations: Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans)
Regulatory reference	ACGIH 2022
Hydrocarbons, C10-C12, isoalkanes, <2% aromatics (Mixture)	
No additional information available	

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

8.2. Appropriate engineering controls

Appropriate engineering controls : No particular/specific measures required.
Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Wear suitable gloves

Eye protection:

Use suitable eye protection

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. In operations where exposure limits are exceeded or exposure levels are excessive, an approved respirator should be used. Respirator selection and use should be based on contaminant type, form and concentration. Follow applicable regulations and good Industrial Hygiene practice.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: White. Paste.
Color	: White
Odor	: Characteristic
Odor threshold	: No data available
pH	: 8.5 – 9.5
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: 73 – 75 °C
Relative evaporation rate (butyl acetate=1)	: No data available
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: No data available
Relative vapor density at 20°C	: No data available
Relative density	: 1.20 g/ml
Solubility	: No data available
Partition coefficient n-octanol/water (Log Pow)	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: > 20.5 mm ² /s
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Direct sunlight.

10.5. Incompatible materials

Oxidizing agent. None known.

10.6. Hazardous decomposition products

Carbon oxides (CO, CO₂). Nitrogen oxides.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics (Mixture)	
LD50 dermal rat	> 2000 mg/kg body weight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal rabbit	≥ 3160 mg/kg body weight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Skin corrosion/irritation : Not classified
Serious eye damage/irritation : Not classified
Respiratory or skin sensitization : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified
STOT-repeated exposure : Not classified
Aspiration hazard : Not classified
Viscosity, kinematic : > 20.5 mm²/s

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics (Mixture)	
Viscosity, kinematic	1.19 mm ² /s Temp.: '20°C' Parameter: 'kinematic viscosity (in mm ² /s)'

Inhalation : May cause minor irritation to the respiratory tract and to other mucous membranes.
Skin : May cause slight irritation to the skin.
Eyes : May cause minor eye irritation.
Ingestion : May cause gastrointestinal irritation, nausea, vomiting and diarrhea.
Most Important Symptoms/Effects : May cause minor eye irritation. May cause slight irritation to the skin.

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects. Avoid release to the environment.

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

No additional information available

12.4. Mobility in soil

No additional information available

12.5. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Disposal methods

Regional legislation (waste) : Dispose of in accordance with applicable federal, state, and local regulations.
Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.

SECTION 14: Transport information

In accordance with DOT / TDG / IMDG / IATA

DOT	TDG	IMDG	IATA
14.1. UN number			
NA1993	Not applicable	Not applicable	Not applicable
14.2. Proper Shipping Name			
Combustible liquid, n.o.s. (Hydrocarbons)	Not applicable	Not applicable	Not applicable
14.3. Transport hazard class(es)			
Combustible liquid	Not applicable	Not applicable	Not applicable
14.4. Packing group			
III	Not applicable	Not applicable	Not applicable
14.5. Environmental hazards			
Dangerous for the environment: No	Not applicable	Not applicable	Not applicable
No supplementary information available			

14.6. Special precautions for user

DOT
UN-No.(DOT) : NA1993

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

DOT Special Provisions (49 CFR 172.102)	:	148 - For domestic transportation, this entry directs to § 173.66 for: a. The standards for transporting a single bulk hazardous material for blasting by cargo tank motor vehicles (CTMV); and b. The standards for CTMVs capable of transporting multiple hazardous materials for blasting in bulk and non-bulk packagings (i.e, a multipurpose bulk truck (MBT)). IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672). T1 - 1.5 178.274(d)(2) Normal..... 178.275(d)(2) TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.
DOT Packaging Exceptions (49 CFR 173.xxx)	:	150
DOT Packaging Non Bulk (49 CFR 173.xxx)	:	203
DOT Packaging Bulk (49 CFR 173.xxx)	:	241
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	:	60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	:	220 L
DOT Vessel Stowage Location	:	A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

TDG

No data available

IMDG

No data available

IATA

No data available

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. US Federal regulations

All components of this product are present and listed as Active on the United States Environmental Protection Agency Toxic Substances Control Act (TSCA) inventory, except for:

Hydrocarbons, C10-C12, isoalkanes, <2% aromatics	CAS-No. Mixture	10 – 20%
--	-----------------	----------

15.2. International regulations

CANADA

No additional information available

NEW ZEALAND

HSNO Group Standard: Cleaning Products Subsidiary HSR002530.

Regulatory Information: (NZ) Statement: This substance is not classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

EU-Regulations

No additional information available

XC-2

Safety Data Sheet

According to 29CFR 1910.1200 OSHA Hazard Communication Standard

National regulations

XC-2

All chemical substances in this product are listed in the EPA (Environment Protection Agency) TSCA (Toxic Substances Control Act) Inventory

15.3. US State regulations

California Proposition 65 - This product does not contain any substances known to the state of California to cause cancer, developmental and/or reproductive harm

SECTION 16: Other information


According to 29CFR 1910.1200 OSHA Hazard Communication Standard

Revision date : 22/01/2024

Full text of H-phrases

H227	Combustible liquid
------	--------------------

NFPA health hazard : 1 - Materials that, under emergency conditions, can cause significant irritation.
NFPA fire hazard : 1 - Materials that must be preheated before ignition can occur.
NFPA reactivity : 0 - Material that in themselves are normally stable, even under fire conditions.



Hazard Rating
Health : 1 Slight Hazard
Flammability : 1 Slight Hazard
Physical : 0 Minimal Hazard

Indication of changes:

new version.

Safety Data Sheet (SDS), USA / NZ

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.