



FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878
Issue date: 3/13/2023 Revision date: 4/12/2022 Supersedes version of: 7/19/2019 Version: 1.4

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Trade name : FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND
Product code : PRA101, PRA118, PRA124, PRA518
Product group : Blend
Other means of identification : UPC 78072760430, 78072715147, 78072715148, 78072729474

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Professional use, Consumer use
Use of the substance/mixture : Abrasive polishing compound

1.2.2. Uses advised against

Restrictions on use : This material should not be used for any other purpose than the identified uses without expert advice. Improper use may cause potential health, safety and environmental risks, Polishes and wax blends

1.3. Details of the supplier of the safety data sheet

Manufacturer

Farecla Products Limited
Broadmeads
Ware, SG12 9HS – Hertfordshire
UK
T +44 (0)19 2046 5041 (8:30-16:30 Monday to Friday) - F +44 (0)19 2046 6557
technical@farecla.com - www.farecla.com

Only Representative

Saint-Gobain Coating Solutions
50 rue du Mourelet Z.I. Courtine Moure Fraix, B.P.
FR- 90966 84093 Avignon – Cedex
France
qualité-ehs.coating-solutions@saint-gobain.com

1.4. Emergency telephone number

Emergency number : +44 (0)19 2046 5041 (8:30-16:30 Monday to Friday)

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
Malta	Medicines & Poisons Info Office	Mater Dei Hospital Msida MSD 2090 Msida	+356 2545 6508	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Not Classified

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Adverse physicochemical, human health and environmental effects

To our knowledge, this product does not present any particular risk, provided it is handled in accordance with good occupational hygiene and safety practice.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Contains	: Glycerol
Precautionary statements (CLP)	: P102 - Keep out of reach of children.
EUH-statements	: EUH210 - Safety data sheet available on request. EUH208 - Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.

Nordic countries regulation

Denmark

MAL code : 00-1

2.3. Other hazards

Other hazards which do not result in classification : If in eyes: this material may cause mechanical irritation.

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

Contains no PBT/vPvB substances $\geq 0.1\%$ assessed in accordance with REACH Annex XIII

Component	
Aluminium Oxide (1344-28-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Sodium Nitrate (7631-99-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Glycerol (56-81-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Component	
White mineral oil (petroleum)(8042-47-5)	The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Aluminium Oxide	CAS-No.: 1344-28-1 EC-No.: 215-691-6 REACH-no: 01-2119529248-35	30 - 50	Not Classified
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics	CAS-No.: 64742-47-8 EC-No.: 926-141-6 REACH-no: 01-2119456620-43	10 - 30	Asp. Tox. 1, H304
White mineral oil (petroleum)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 2119487078-27	1 - 10	Not Classified
Glycerol	CAS-No.: 56-81-5 EC-No.: 200-289-5 REACH-no: 01-2119471987-18	1 - 10	Not Classified
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics	CAS-No.: 1174522-19-0 EC-No.: 919-029-3 REACH-no: 01-2119457735-29	1 - 10	Asp. Tox. 1, H304
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	< 0.05	Acute Tox. 4 (Oral), H302 Skin Irrit. 2, H315 Eye Dam. 1, H318 Skin Sens. 1, H317 Aquatic Acute 1, H400
Benzyl benzoate	CAS-No.: 120-51-4 EC-No.: 204-402-9 EC Index-No.: 607-085-00-9 REACH-no: 01-2119976371-33	< 0.015	Acute Tox. 4 (Oral), H302 Aquatic Acute 1, H400 Aquatic Chronic 2, H411
Sodium hydroxide	CAS-No.: 1310-73-2 EC-No.: 215-185-5 EC Index-No.: 011-002-00-6 REACH-no: 01-2119457892-27	< 0.005	Skin Corr. 1A, H314 Eye Dam. 1, H318
Sodium Nitrate	CAS-No.: 7631-99-4 EC-No.: 231-554-3 REACH-no: 01-2119488221-41	< 0.003	Ox. Sol. 3, H272 Eye Irrit. 2, H319
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	< 0.0015	Acute Tox. 3 (Oral), H301 Acute Tox. 2 (Dermal), H310 Acute Tox. 2 (Inhalation), H330 Skin Corr. 1C, H314 Eye Dam. 1, H318 Skin Sens. 1A, H317 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Specific concentration limits:

Name	Product identifier	Specific concentration limits
White mineral oil (petroleum)	CAS-No.: 8042-47-5 EC-No.: 232-455-8 REACH-no: 2119487078-27	(0 ≤ C < 100) Asp. Tox. 1, H304
1,2-benzisothiazol-3(2H)-one	CAS-No.: 2634-33-5 EC-No.: 220-120-9 EC Index-No.: 613-088-00-6 REACH-no: 01-2120761540-60	(0.05 ≤ C ≤ 100) Skin Sens. 1, H317
Sodium hydroxide	CAS-No.: 1310-73-2 EC-No.: 215-185-5 EC Index-No.: 011-002-00-6 REACH-no: 01-2119457892-27	(0.5 ≤ C < 2) Eye Irrit. 2, H319 (0.5 ≤ C < 2) Skin Irrit. 2, H315 (2 ≤ C < 5) Skin Corr. 1B, H314 (5 ≤ C < 100) Skin Corr. 1A, H314
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	CAS-No.: 55965-84-9 EC-No.: 911-418-6 EC Index-No.: 613-167-00-5 REACH-no: 01-2120764691-48	(0.0015 ≤ C ≤ 100) Skin Sens. 1A, H317 (0.06 ≤ C < 0.6) Skin Irrit. 2, H315 (0.06 ≤ C < 0.6) Eye Irrit. 2, H319 (0.6 ≤ C ≤ 100) Skin Corr. 1C, H314 (0.6 ≤ C ≤ 100) Eye Dam. 1, H318

Comments : Contains amongst other ingredients: >30% zeolites; 15-30% aliphatic hydrocarbons; <5% nonionic surfactants, fragrance, Methylchloroisothiazolinone, Methylisothiazolinone, Benzisothiazolinone. Contains fragrance allergen: 0.015% Benzyl Benzoate. For more ingredient information visit www.farecla.com

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. If experiencing respiratory symptoms: Call a poison center or a doctor.

First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing. If skin irritation occurs: Get medical advice/attention.

First-aid measures after eye contact : Rinse eyes with water as a precaution. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Call a poison center or a doctor if you feel unwell. Rinse mouth out with water. Do not induce vomiting. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation : May cause headache, nausea and irritation of respiratory tract.

Symptoms/effects after skin contact : Contact during a long period may cause light irritation. Itching.

Symptoms/effects after eye contact : May cause eye irritation. redness, itching, tears.

Symptoms/effects after ingestion : May cause irritation to the digestive tract. Ingestion may cause nausea and vomiting.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media : None known.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Not flammable.
Hazardous decomposition products in case of fire : Toxic fumes may be released. Carbon monoxide. Carbon dioxide. Nitrogen oxides.

5.3. Advice for firefighters

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Stop leak if safe to do so. Evacuate area.

6.1.1. For non-emergency personnel

Protective equipment : Wear recommended personal protective equipment.
Emergency procedures : Ventilate spillage area.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Prevent entry to sewers and public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material. Absorb spilled material with sand or earth. Shovel or sweep up and put in a closed container for disposal. Clean contaminated surfaces with an excess of water.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Wear personal protective equipment.
Hygiene measures : Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store in a well-ventilated place. Keep cool. Keep at temperatures above freezing. Allowing freezing conditions may degrade product.
Incompatible products : Oxidizing agent. Strong acids.
Information on mixed storage : Store away from foodstuffs.
Storage area : Store away from heat. Store in a well-ventilated place.

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

7.3. Specific end use(s)

Refer to Section 1.2 - Relevant identified uses.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

Aluminium Oxide (1344-28-1)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	5 mg/m ³ (respirable fraction, smoke)
MAK (OEL STEL)	10 mg/m ³ (respirable fraction, smoke)
Belgium - Occupational Exposure Limits	
Local name	Aluminium (métal et composés insolubles, fraction alvéolaire) # Aluminium (metaal en onoplosbare verbindingen, inadembare fractie)
OEL TWA	1 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	10 mg/m ³ (total dust, inhalable particles) 4 mg/m ³ (respirable dust)
Denmark - Occupational Exposure Limits	
OEL TWA [1]	5 mg/m ³ (total) 2 mg/m ³ (respirable)
Estonia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (total dust) 4 mg/m ³ (respirable dust)
France - Occupational Exposure Limits	
Local name	Aluminium (Trioxyde de di-)
VME (OEL TWA)	10 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Greece - Occupational Exposure Limits	
Local name	Αλουμίνα, α-
OEL TWA	10 mg/m ³ αναπν. 5 mg/m ³ εισπν.
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	6 mg/m ³ (respirable dust)
Ireland - Occupational Exposure Limits	
Local name	Aluminium oxides
OEL TWA [1]	10 mg/m ³ total inhalable dust 4 mg/m ³ respirable dust

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aluminium Oxide (1344-28-1)	
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
OEL TWA	6 mg/m ³ (disintegration aerosol)
Lithuania - Occupational Exposure Limits	
IPRV (OEL TWA)	5 mg/m ³ (inhalable fraction) 2 mg/m ³ (respirable fraction)
Poland - Occupational Exposure Limits	
Local name	Tritlenek glinu
NDS (OEL TWA)	2.5 mg/m ³ w przeliczeniu na Al: frakcja wdychalna 1.2 mg/m ³ w przeliczeniu na Al: frakcja respirabilna
Remark	Frakcja wdychalna – frakcja aerozolu wnikająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia. Frakcja respirabilna – frakcja aerozolu wnikająca do dróg oddechowych, która stwarza zagrożenie dla zdrowia po zdeponowaniu w obszarze wymiany gazowej.
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (particulate matter containing no Asbestos and <1% Crystalline silica)
OEL chemical category	A4 - Not Classifiable as a Human Carcinogen
Romania - Occupational Exposure Limits	
OEL TWA	2 mg/m ³ (aerosols) 3 mg/m ³ (dust (Aluminium and Aluminium oxides)) 1 mg/m ³ (fume (Aluminium and Aluminium oxides))
OEL STEL	5 mg/m ³ (aerosols) 10 mg/m ³ (dust (Aluminium and Aluminium oxides)) 3 mg/m ³ (fume (Aluminium and Aluminium oxides))
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	4 mg/m ³ (inhalable dust)
Spain - Occupational Exposure Limits	
Local name	Óxido de aluminio (Corindón)
VLA-ED (OEL TWA) [1]	10 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
NGV (OEL TWA)	5 mg/m ³ (total dust) 2 mg/m ³ (respirable fraction)
United Kingdom - Occupational Exposure Limits	
Local name	Aluminium oxides
WEL TWA (OEL TWA) [1]	10 mg/m ³ inhalable dust 4 mg/m ³ respirable dust
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Norway - Occupational Exposure Limits	
Local name	Aluminiumoksid
Grenseverdi (OEL TWA) [1]	10 mg/m ³

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aluminium Oxide (1344-28-1)	
Korttidsverdi (OEL STEL)	15 mg/m ³ (equal to the limit value for Nuisance dust)
Remark	1) Grenseverdien er fastsatt lik verdien for sjenerende støv.
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	Aluminium oxyde / Aluminiumoxid [Korund]
MAK (OEL TWA) [1]	3 mg/m ³ (a) / (a)
KZGW (OEL STEL)	24 mg/m ³ (respirable dust, smoke)
Critical toxicity	Formel / Formal
Notation	B / B
Remark	NIOSH
Regulatory reference	www.suva.ch, 01.01.2023
Switzerland - BAT	
Local name	Aluminium oxyde / Aluminiumoxid
BAT	50 µg/g creatinine (0.21 µmol/mmol cr.; Paramètre biologique: Aluminium; Substrat d'examen: Urine; Moment du prélèvement: Exposition de longue durée: après plusieurs périodes de travail.) / (0.21 µmol/mmol cr.; Biologischer Parameter: Aluminium; Untersuchungsmaterial: Urin; Probennahmezeitpunkt: Bei Langzeitexposition: nach mehreren vorangegangenen Schichten.)
Regulatory reference	Ordonnance 832.30 (OPA), article 50 al. 3, www.suva.ch/valeurs-limites / Verordnung 832.30 (VUV), Art. 50 Abs. 3, www.suva.ch/grenzwerte
USA - ACGIH - Occupational Exposure Limits	
ACGIH OEL TWA	1 mg/m ³
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
Switzerland - Occupational Exposure Limits	
Local name	Distillats légers de pétrole, hydrotraités (vapeurs) / Destillate (Erdöl), mit Wasserstoff behandelte, leichte (Dampf)
MAK (OEL TWA) [1]	350 mg/m ³
MAK (OEL TWA) [2]	50 ppm (vapour)
KZGW (OEL STEL)	700 mg/m ³
KZGW (OEL STEL) [ppm]	100 ppm (vapour)
Critical toxicity	SNC / ZNS
Notation	SS _c / SS _c
Remark	OSHA
Regulatory reference	www.suva.ch, 01.01.2023
White mineral oil (petroleum) (8042-47-5)	
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Weißes Mineralöl (Erdöl)
AGW (OEL TWA) [1]	5 mg/m ³ (A)
Peak exposure limitation factor	4(II)

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

White mineral oil (petroleum) (8042-47-5)	
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Switzerland - Occupational Exposure Limits	
Local name	Huile de paraffine / Weissöl, pharmazeutisch
MAK (OEL TWA) [1]	5 mg/m ³ (i) / (e)
Critical toxicity	Poumons / Lunge
Notation	SS _c / SS _c
Remark	NIOSH, DFG
Regulatory reference	www.suva.ch, 01.01.2023
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	0.05 mg/m ³ (5-Chloro-2-methyl-2,3-dihydroisothiazol-3-one and 2-methyl-2,3-dihydroisothiazol-3-one mixture in ratio 3:1)
OEL chemical category	Skin sensitizer
Switzerland - Occupational Exposure Limits	
Local name	2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle et 2,3-dihydro-isothiazol-3-one de 2-méthyle [2,3-Dihydro-isothiazol-3-one de 5-chloro-2-méthyle, 2,3-Dihydro-isothiazol-3-one de 2-méthyle] / 5-Chlor-2-methyl-2,3-dihydro-isothiazol-3-on und 2-Methyl-2,3-dihydroisothiazol-3-on [2-Methyl-2,3-dihydroisothiazol-3-on, 5-Chlor-2-methyl-2,3-dihydroisothiazol-3-on]
MAK (OEL TWA) [1]	0.2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	0.4 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	S, SS _c / S, SS _c
Regulatory reference	www.suva.ch, 01.01.2023
Sodium Nitrate (7631-99-4)	
Czech Republic - Occupational Exposure Limits	
PEL (OEL TWA)	6 mg/m ³ (dust)
Sodium hydroxide (1310-73-2)	
Austria - Occupational Exposure Limits	
MAK (OEL TWA)	2 mg/m ³ (inhalable fraction)
MAK (OEL STEL)	4 mg/m ³ (inhalable fraction)
Belgium - Occupational Exposure Limits	
Local name	Sodium (hydroxyde de) # Natriumhydroxide
OEL TWA	2 mg/m ³

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sodium hydroxide (1310-73-2)	
Remark	M: la mention "M" indique que lors d'une exposition supérieure à la valeur limite, des irritations apparaissent ou un danger d'intoxication aiguë existe. Le procédé de travail doit être conçu de telle façon que l'exposition ne dépasse jamais la valeur limite. Lors des mesurages, la période d'échantillonnage doit être aussi courte que possible afin de pouvoir effectuer des mesurages fiables. Le résultat des mesurages est calculé en fonction de la période d'échantillonnage. # M: de vermelding "M" duidt aan dat bij de blootstelling boven de grenswaarde irritatie optreedt of er gevaar bestaat voor acute vergiftiging. Het werkproces moet zo zijn ontworpen dat de blootstelling de grenswaarde nooit overschrijdt. Bij een controle geldt dat de bemonsterde periode zo kort mogelijk moet zijn om een betrouwbare meting te kunnen verrichten. Het meetresultaat wordt dan gerelateerd aan de beschouwde periode.
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Bulgaria - Occupational Exposure Limits	
Local name	Натриева основа
OEL TWA	2 mg/m ³ (алкални аерозоли)
Remark	• (Химични агенти, за които са определени гранични стойности във въздуха на работната среда за Европейската общност)
Regulatory reference	Наредба № 13 от 30.12.2003 г. за защита на работещите от рискове, свързани с експозиция на химични агенти при работа (изм. и доп. ДВ. бр. 47 от 2021 г., в сила от 04.06.2021 г.)
Croatia - Occupational Exposure Limits	
KGVI (OEL STEL)	2 mg/m ³
Czech Republic - Occupational Exposure Limits	
Local name	Hydroxid sodný
PEL (OEL TWA)	1 mg/m ³
NPK-P (OEL C)	2 mg/m ³
Remark	I - dráždí sliznice (oči, dýchací cesty), respektive kůži.
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Denmark - Occupational Exposure Limits	
OEL C	2 mg/m ³
Estonia - Occupational Exposure Limits	
OEL TWA	1 mg/m ³
OEL STEL	2 mg/m ³
Finland - Occupational Exposure Limits	
Local name	Natriumhydroksidi
HTP (OEL C)	2 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Sodium (hydroxyde de)
VME (OEL TWA)	2 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sodium hydroxide (1310-73-2)	
Greece - Occupational Exposure Limits	
Local name	Υδροξείδιο του νατρίου
OEL TWA	2 mg/m ³
OEL STEL	2 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Hungary - Occupational Exposure Limits	
AK (OEL TWA)	2 mg/m ³
CK (OEL STEL)	2 mg/m ³
Ireland - Occupational Exposure Limits	
Local name	Sodium hydroxide
OEL STEL	2 mg/m ³
Regulatory reference	Chemical Agents Code of Practice 2021
Latvia - Occupational Exposure Limits	
OEL TWA	0.5 mg/m ³
Lithuania - Occupational Exposure Limits	
NRV (OEL C)	2 mg/m ³
Poland - Occupational Exposure Limits	
Local name	Wodorotlenek sodu
NDS (OEL TWA)	0.5 mg/m ³
NDSCh (OEL STEL)	1 mg/m ³
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL C	2 mg/m ³
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	2 mg/m ³
Spain - Occupational Exposure Limits	
Local name	Hidróxido de sodio
VLA-EC (OEL STEL)	2 mg/m ³
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT
Sweden - Occupational Exposure Limits	
Local name	Natriumhydroxid
NGV (OEL TWA)	1 mg/m ³ inhalerbar fraktion
KTV (OEL STEL)	2 mg/m ³ inhalerbar fraktion
Remark	3 (Med inhalerbar fraktion menas den mängd partiklar, av totalmängden partiklar i luften, som man inandas genom näsa och mun)
Regulatory reference	Hygieniska gränsvärden (AFS 2018:1)

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Sodium hydroxide (1310-73-2)	
United Kingdom - Occupational Exposure Limits	
Local name	Sodium hydroxide
WEL STEL (OEL STEL)	2 mg/m ³
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE
Norway - Occupational Exposure Limits	
Local name	Natriumhydroksid
Takverdi (OEL C) [1]	2 mg/m ³
Regulatory reference	FOR-2021-06-28-2248
Switzerland - Occupational Exposure Limits	
Local name	Soude caustique / Natriumhydroxid [Aetznatron]
MAK (OEL TWA) [1]	2 mg/m ³ (i) / (e)
KZGW (OEL STEL)	2 mg/m ³ (i) / (e)
Critical toxicity	VRS, Peau, Yeux / OAW, Haut, Auge
Notation	SS _c / SS _c
Remark	NIOSH, OSHA
Regulatory reference	www.suva.ch, 01.01.2023
USA - ACGIH - Occupational Exposure Limits	
Local name	Sodium hydroxide
ACGIH OEL C	2 mg/m ³
Remark (ACGIH)	TLV® Basis: URT, eye, & skin irr
Regulatory reference	ACGIH 2023
Glycerol (56-81-5)	
Belgium - Occupational Exposure Limits	
Local name	Glycérine (brouillard) # Glycerine (nevel)
OEL TWA	10 mg/m ³
Regulatory reference	Koninklijk besluit/Arrêté royal 11/05/2021
Croatia - Occupational Exposure Limits	
GVI (OEL TWA) [1]	10 mg/m ³
Czech Republic - Occupational Exposure Limits	
Local name	Glycerol, mlha
PEL (OEL TWA)	10 mg/m ³
PEL (OEL TWA) [ppm]	2.6 ppm
NPK-P (OEL C)	15 mg/m ³
NPK-P (OEL C) [ppm]	3.9 ppm
Regulatory reference	Nařízení vlády č. 361/2007 Sb. (Předpis 195/2021 Sb.)
Estonia - Occupational Exposure Limits	
OEL TWA	10 mg/m ³

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Glycerol (56-81-5)	
Finland - Occupational Exposure Limits	
Local name	Glyseroli
HTP (OEL TWA) [1]	20 mg/m ³
Regulatory reference	HTP-ARVOT 2020 (Sosiaali- ja terveystieteiden ministeriö)
France - Occupational Exposure Limits	
Local name	Glycérine (aérosols de)
VME (OEL TWA)	10 mg/m ³
Remark	Valeurs recommandées/admises
Regulatory reference	Circulaire du Ministère du travail (réf.: INRS ED 984, 2016)
Germany - Occupational Exposure Limits (TRGS 900)	
Local name	Glycerin
AGW (OEL TWA) [1]	200 mg/m ³ (E)
Peak exposure limitation factor	2(I)
Remark	DFG - Senatskommission zur Prüfung gesundheitsschädlicher Arbeitsstoffe der DFG (MAK-Kommission); Y - Ein Risiko der Fruchtschädigung braucht bei Einhaltung des Arbeitsplatzgrenzwertes und des biologischen Grenzwertes (BGW) nicht befürchtet zu werden
Regulatory reference	TRGS900
Greece - Occupational Exposure Limits	
Local name	Γλυκερίνη
OEL TWA	10 mg/m ³
Regulatory reference	Π.Δ. 90/1999 - Προστασία της υγείας των εργαζομένων που εκτίθενται σε ορισμένους χημικούς παράγοντες κατά τη διάρκεια της εργασίας τους
Poland - Occupational Exposure Limits	
Local name	Glicerol
NDS (OEL TWA)	10 mg/m ³ frakcja wdychalna
Remark	Frakcja wdychalna – frakcja aerozolu wnikaająca przez nos i usta, która po zdeponowaniu w drogach oddechowych stwarza zagrożenie dla zdrowia.
Regulatory reference	Dz. U. 2018 poz. 1286
Portugal - Occupational Exposure Limits	
OEL TWA	10 mg/m ³ (mist)
Slovakia - Occupational Exposure Limits	
NPHV (OEL TWA) [1]	11 mg/m ³
Slovenia - Occupational Exposure Limits	
OEL TWA	200 mg/m ³ (inhalable fraction)
OEL STEL	400 mg/m ³ (inhalable fraction)
Spain - Occupational Exposure Limits	
Local name	Glicerina
VLA-ED (OEL TWA) [1]	10 mg/m ³ nieblas
Regulatory reference	Límites de Exposición Profesional para Agentes Químicos en España 2022. INSHT

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Glycerol (56-81-5)

United Kingdom - Occupational Exposure Limits

Local name	Glycerol
WEL TWA (OEL TWA) [1]	10 mg/m ³ mist
WEL STEL (OEL STEL)	30 mg/m ³ (calculated-mist)
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE

Switzerland - Occupational Exposure Limits

Local name	Glycérine / Glycerin
MAK (OEL TWA) [1]	50 mg/m ³ (i) / (e)
KZGW (OEL STEL)	100 mg/m ³ (i) / (e)
Critical toxicity	VRS / OAW
Notation	SS _c / SS _c
Regulatory reference	www.suva.ch, 01.01.2023

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Chemical goggles or safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Examples of preferred glove barrier materials include: Butyl rubber. Natural rubber ("latex"). Neoprene. Nitrile/butadiene rubber ("nitrile" or "NBR"). Polyethylene. Ethyl vinyl alcohol laminate ("EVAL"). Polyvinyl alcohol ("PVA"). Polyvinyl chloride ("PVC" or "vinyl").

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. The fine-dust mask with exhale Valve is recommended to use when dust and mist exceed exposure limits in air, according to EN149:2001 + A1:2009 FFP2 NR standard. The respiratory mask should be worn when respiratory hazards has been identified and evaluated. Respiratory protection should be always determined on quantitative exposure assessments.

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment. Prevent entry into waterways, sewers, basements or confined areas.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Colour	: white.
Appearance	: Thick liquid.
Odour	: pleasant.
Odour threshold	: Not available
Melting point	: < 0 °C
Freezing point	: Not available
Boiling point	: > 100 °C
Flammability	: Not applicable
Explosive properties	: Product is not explosive.
Oxidising properties	: Non oxidizing material according to EC criteria.
Explosive limits	: Not available
Lower explosion limit	: Not applicable.
Upper explosion limit	: Not applicable.
Flash point	: > 93 °C
Auto-ignition temperature	: Not available
Decomposition temperature	: Not available
pH	: 9 – 10
Viscosity, kinematic	: 20000 mm ² /s 20°C
Viscosity, dynamic	: 20000 cP Brookfield viscometer
Solubility	: Dispersible in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not available
Vapour pressure at 50°C	: Not available
Density	: Not available
Relative density	: 1.27
Relative vapour density at 20°C	: Not available
Particle characteristics	: Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

VOC content : 210.5 g/l (16.5%)

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport.

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

Strong oxidizers. Strong acids.

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not Classified.
Acute toxicity (dermal) : Not Classified
Acute toxicity (inhalation) : Not Classified

Aluminium Oxide (1344-28-1)	
LD50 oral rat	> 15900 mg/kg bodyweight
LC50 Inhalation - Rat	> 2.3 mg/l air
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
LD50 oral rat	> 5000 mg/kg
LD50 dermal rat	> 5000 mg/kg
LC50 Inhalation - Rat	> 20 mg/l/4h
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 3160 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5266 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity), Remarks on results: other:
White mineral oil (petroleum) (8042-47-5)	
LD50 oral rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 dermal rabbit	> 2000 mg/kg bodyweight Animal: rabbit, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	> 5 mg/l air Animal: rat, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LD50 oral rat	490 mg/kg bodyweight
LD50 oral	670 mg/kg

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

1,2-benzisothiazol-3(2H)-one (2634-33-5)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LD50 dermal	4115 mg/kg bodyweight
LC50 Inhalation - Rat (Dust/Mist)	100 mg/l

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LD50 oral rat	66 mg/kg bodyweight
LD50 dermal rat	> 1008 mg/kg bodyweight Animal: rat, Guideline: EPA OPP 81-2 (Acute Dermal Toxicity), Guideline: OECD Guideline 402 (Acute Dermal Toxicity)
LC50 Inhalation - Rat	0.17 mg/l air

Sodium Nitrate (7631-99-4)

LD50 oral rat	≈ 3430 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LD50 oral	3700 mg/kg
LD50 dermal rat	> 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity)

Sodium hydroxide (1310-73-2)

LD50 dermal rabbit	325 mg/kg Source: ECHA
--------------------	------------------------

Glycerol (56-81-5)

LD50 oral rat	27 mg/kg bodyweight Animal: rat, Animal sex: female
LD50 dermal rabbit	> 10 g/kg
LD50 dermal	56750 mg/kg
LC50 Inhalation - Rat	5.85 mg/l

Benzyl benzoate (120-51-4)

LD50 oral rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity), Remarks on results: other:
LD50 dermal rabbit	4000 mg/kg

Skin corrosion/irritation : Not Classified
pH: 9 – 10

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

pH	3.43 Temp.: 20 °C Concentration: 10 g/L
----	---

Sodium Nitrate (7631-99-4)

pH	7 Temp.: 25 °C Remarks on result: 'other:'
----	--

Sodium hydroxide (1310-73-2)

pH	12 – 14
----	---------

Glycerol (56-81-5)

pH	5.5 – 8
----	---------

Serious eye damage/irritation : Not Classified
pH: 9 – 10

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
pH	3.43 Temp.: 20 °C Concentration: 10 g/L
Sodium Nitrate (7631-99-4)	
pH	7 Temp.: 25 °C Remarks on result: 'other:'
Sodium hydroxide (1310-73-2)	
pH	12 – 14
Glycerol (56-81-5)	
pH	5.5 – 8
Respiratory or skin sensitisation	: Not Classified
Germ cell mutagenicity	: Not Classified
Carcinogenicity	: Not Classified
Reproductive toxicity	: Not Classified
Aluminium Oxide (1344-28-1)	
NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)	
NOAEL (animal/male, F0/P)	≥ 3000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
NOAEL (animal/female, F0/P)	≥ 1500 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 (One-Generation Reproduction Toxicity Study)
NOAEL (animal/female, F1)	≥ 2000 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: OECD Guideline 415 [One-Generation Reproduction Toxicity Study (before 9 October 2017)]
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
NOAEL (animal/female, F1)	56.6 mg/kg bodyweight Animal: rat, Animal sex: female, Guideline: EPA OPPTS 870.3800 (Reproduction and Fertility Effects)
STOT-single exposure	: Not Classified
STOT-repeated exposure	: Not Classified
Aluminium Oxide (1344-28-1)	
LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.015 mg/l air Animal: rat, Guideline: OECD Guideline 452 (Chronic Toxicity Studies)
NOAEC (inhalation, rat, dust/mist/fume, 90 days)	0.07 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)	
NOAEL (oral, rat, 90 days)	≥ 5000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents)
NOAEL (dermal, rat/rabbit, 90 days)	> 495 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 411 (Subchronic Dermal Toxicity: 90-Day Study)
NOAEC (inhalation, rat, vapour, 90 days)	> 10.4 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
White mineral oil (petroleum) (8042-47-5)	
NOAEL (oral, rat, 90 days)	≥ 1200 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 453 (Combined Chronic Toxicity / Carcinogenicity Studies)

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)

LOAEL (dermal, rat/rabbit, 90 days)	0.525 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: EPA OPP 82-3 (Subchronic Dermal Toxicity 90 Days)
-------------------------------------	--

Sodium Nitrate (7631-99-4)

NOAEL (oral, rat, 90 days)	≥ 1500 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
----------------------------	--

Benzyl benzoate (120-51-4)

NOAEL (dermal, rat/rabbit, 90 days)	781 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 410 (Repeated Dose Dermal Toxicity: 21/28-Day Study)
-------------------------------------	--

Aspiration hazard : Not Classified

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Viscosity, kinematic	20000 mm ² /s 20°C
----------------------	-------------------------------

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)

Hydrocarbon	Yes
-------------	-----

Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics (1174522-19-0)

Viscosity, kinematic	3.3 – 20 mm ² /s (20°C)
----------------------	------------------------------------

White mineral oil (petroleum) (8042-47-5)

Viscosity, kinematic	2 mm ² /s @ 40°C
----------------------	-----------------------------

Hydrocarbon	Yes
-------------	-----

Sodium hydroxide (1310-73-2)

Viscosity, kinematic	Not applicable
----------------------	----------------

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms nor to cause long-term adverse effects in the environment.
Hazardous to the aquatic environment, short-term (acute)	: Not Classified
Hazardous to the aquatic environment, long-term (chronic)	: Not Classified
Not rapidly degradable	

Aluminium Oxide (1344-28-1)

LC50 - Fish [1]	1.16 mg/l
EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
LC50 - Fish [1]	2.2 mg/l
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
LC50 - Fish [1]	≈ 16.7 mg/l Test organisms (species): <i>Cyprinodon variegatus</i>
LC50 - Fish [2]	2.15 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>)
EC50 - Crustacea [1]	2.94 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 - Crustacea [2]	2.9 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 - Other aquatic organisms [1]	2.94 mg/l waterflea
EC50 - Other aquatic organisms [2]	0.11 mg/l
ErC50 algae	150 µg/l
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
LC50 - Fish [1]	0.19 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>)
LC50 - Fish [2]	0.28 mg/l Test organisms (species): <i>Lepomis macrochirus</i>
EC50 - Crustacea [1]	0.16 mg/l Test organisms (species): <i>Daphnia magna</i>
EC50 - Crustacea [2]	0.0052 mg/l (<i>Skeletonema costatum</i>) (OECD 201)
EC50 72h - Algae [1]	0.048 mg/l (<i>Pseudokirchneriella subcapitata</i>) (OECD 201)
NOEC (chronic)	0.1 mg/l Test organisms (species): <i>Daphnia magna</i> Duration: '21 d'
NOEC chronic fish	0.098 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>) Duration: '28 d'
NOEC chronic crustacea	0.004 mg/l 21 d (<i>Daphnia</i>) (OECD 211)
NOEC chronic algae	0.0012 mg/l 72 h (<i>Pseudokirchneriella subcapitata</i>) (OECD 201)
Sodium Nitrate (7631-99-4)	
LC50 - Fish [1]	1559 mg/l Test organisms (species): other:
LC50 - Fish [2]	1354 mg/l Test organisms (species): other:
EC50 - Crustacea [1]	8609 mg/l
Sodium hydroxide (1310-73-2)	
LC50 - Fish [1]	125 mg/l
EC50 - Crustacea [1]	40.4 mg/l Test organisms (species): <i>Ceriodaphnia</i> sp.
Glycerol (56-81-5)	
LC50 - Fish [1]	54000 mg/l Test organisms (species): <i>Oncorhynchus mykiss</i> (previous name: <i>Salmo gairdneri</i>)
EC50 - Crustacea [1]	> 10000 mg/l
Benzyl benzoate (120-51-4)	
LC50 - Fish [1]	2.32 mg/l Test organisms (species): <i>Danio rerio</i> (previous name: <i>Brachydanio rerio</i>)
EC50 - Crustacea [1]	3.09 mg/l Test organisms (species): <i>Daphnia magna</i>

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.2. Persistence and degradability

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND	
Persistence and degradability	Readily biodegradable.
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
Persistence and degradability	No persistence data available for this product.
Glycerol (56-81-5)	
Biochemical oxygen demand (BOD)	0.87 g O ₂ /g substance
Chemical oxygen demand (COD)	1.16 g O ₂ /g substance
ThOD	1.217 g O ₂ /g substance

12.3. Bioaccumulative potential

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND	
Bioaccumulative potential	No indication of bio-accumulation potential.
Aluminium Oxide (1344-28-1)	
Bioaccumulative potential	No bioaccumulation data available.
Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics (64742-47-8)	
Partition coefficient n-octanol/water (Log Kow)	6 – 8.2
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
BCF - Fish [1]	6.62
Partition coefficient n-octanol/water (Log Pow)	-0.9 – 0.99
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
BCF - Fish [1]	41 – 54
Bioconcentration factor (BCF REACH)	3.6 (calculated) S 1177
Partition coefficient n-octanol/water (Log Pow)	0.75
Sodium Nitrate (7631-99-4)	
Partition coefficient n-octanol/water (Log Pow)	-3.8
Sodium hydroxide (1310-73-2)	
Partition coefficient n-octanol/water (Log Pow)	-3.88 Source: SRC
Glycerol (56-81-5)	
BCF - Fish [1]	(no bioaccumulation)
Partition coefficient n-octanol/water (Log Pow)	-1.75
Partition coefficient n-octanol/water (Log Kow)	-1.76
Benzyl benzoate (120-51-4)	
Partition coefficient n-octanol/water (Log Pow)	4

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

12.4. Mobility in soil

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND	
Ecology - soil	Readily absorbed into soil.
1,2-benzisothiazol-3(2H)-one (2634-33-5)	
Surface tension	72.6 mN/m
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.97
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0.81 – 1
Glycerol (56-81-5)	
Surface tension	63.4 mN/m
Organic Carbon Normalized Adsorption Coefficient (Log Koc)	0

12.5. Results of PBT and vPvB assessment

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	
Component	
Aluminium Oxide (1344-28-1)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
1,2-benzisothiazol-3(2H)-one (2634-33-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone (55965-84-9)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Sodium Nitrate (7631-99-4)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII
Glycerol (56-81-5)	This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste treatment methods : Dispose of contents/container in accordance with licensed collector's sorting instructions.
European List of Waste (LoW) code : 08 04 12 - adhesive and sealant sludges other than those mentioned in 08 04 11

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA / ADN / RID

ADR	IMDG	IATA	ADN	RID
14.1. UN number or ID number				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.2. UN proper shipping name				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.3. Transport hazard class(es)				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.4. Packing group				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
14.5. Environmental hazards				
Not regulated	Not regulated	Not regulated	Not regulated	Not regulated
No supplementary information available				

14.6. Special precautions for user

Overland transport

Not regulated

Transport by sea

Not regulated

Air transport

Not regulated

Inland waterway transport

Not regulated

Rail transport

Not regulated

14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

CESIO recommendations

: The surfactant(s) contained in this preparation complies(comply) with the biodegradability criteria as laid down in Regulation (EC) No.648/2004 on detergents. Data to support this assertion are held at the disposal of the competent authorities of the Member States and will be made available to them, at their direct request or at the request of a detergent manufacturer.

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

REACH Annex XVII (Restriction List)

EU restriction list (REACH Annex XVII)		
Reference code	Applicable on	Entry title or description
3(b)	Hydrocarbons, C11-C14, n-alkanes, isoalkanes, cyclics, <2% aromatics ; Hydrocarbons, C16-C20, n-alkanes, isoalkanes, cyclics, < 2% aromatics ; 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10
3(c)	5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone	Substances or mixtures fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: Hazard class 4.1

REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

REACH Candidate List (SVHC)

Contains no substance(s) listed on the REACH Candidate List

PIC Regulation (Prior Informed Consent)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

POP Regulation (Persistent Organic Pollutants)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Ozone Regulation (1005/2009)

Contains no substance(s) listed on the Ozone Depletion list (Regulation EU 1005/2009 on substances that deplete the ozone layer)

VOC Directive (2004/42)

VOC content : 210.5 g/l (16.5%)

Explosives Precursors Regulation (2019/1148)

Contains substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

ANNEX II REPORTABLE EXPLOSIVES PRECURSORS

List of substances on their own or in mixtures or in substances for which suspicious transactions and significant disappearances and thefts are to be reported to the relevant national contact point within 24 hours.

Name	CAS-No.	Combined Nomenclature code (CN)	Combined Nomenclature code for mixture without constituents which would determine classification under another CN code
Sodium nitrate	7631-99-4	3102 50 00	ex 3824 99 96

Please see https://ec.europa.eu/home-affairs/system/files/2021-11/list_of_competent_authorities_and_national_contact_points_en.pdf

Drug Precursors Regulation (273/2004)

Contains no substance(s) listed on the Drug Precursors list (Regulation EC 273/2004 on the manufacture and the placing on market of certain substances used in the illicit manufacture of narcotic drugs and psychotropic substances)

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.1.2. National regulations

France

Occupational diseases	
Code	Description
RG 65	Eczematiform lesions of allergic mechanism
RG 66	Occupational rhinitis and asthma
RG 84	Conditions caused by liquid organic solvents for professional use: saturated or unsaturated aliphatic or cyclic liquid hydrocarbons and mixtures thereof; liquid halogenated hydrocarbons; nitrated derivatives of aliphatic hydrocarbons; alcohols; glycols, glycol ethers; ketones; aldehydes; aliphatic and cyclic ethers, including tetrahydrofuran; esters; dimethylformamide and dimethylacetamine; acetonitrile and propionitrile; pyridine; dimethylsulfone and dimethylsulfoxide

Germany

Employment restrictions	: Observe restrictions according Act on the Protection of Working Mothers (MuSchG). Observe restrictions according Act on the Protection of Young People in Employment (JArbSchG).
Water hazard class (WGK)	: WGK 3, Highly hazardous to water (Classification according to AwSV, Annex 1).
Hazardous Incident Ordinance (12. BImSchV)	: Is not subject of the Hazardous Incident Ordinance (12. BImSchV)

Netherlands

ABM category	: A(3) - hazardous for aquatic organisms, may have longterm hazardous effects in aquatic environment
SZW-lijst van kankerverwekkende stoffen	: None of the components are listed
SZW-lijst van mutagene stoffen	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Borstvoeding	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Vruchtbaarheid	: None of the components are listed
SZW-lijst van reprotoxische stoffen – Ontwikkeling	: None of the components are listed

Denmark

Classification remarks	: Emergency management guidelines for the storage of flammable liquids must be followed
Danish National Regulations	: Young people below the age of 18 years are not allowed to use the product Pregnant/breastfeeding women working with the product must not be in direct contact with the product

Switzerland

Storage class (LK)	: LK 10/12 - Liquids
--------------------	----------------------

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 2 (Dermal)	Acute toxicity (dermal), Category 2
Acute Tox. 2 (Inhalation)	Acute toxicity (inhal.), Category 2
Acute Tox. 3 (Oral)	Acute toxicity (oral), Category 3
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment – Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment – Chronic Hazard, Category 1
Aquatic Chronic 2	Hazardous to the aquatic environment – Chronic Hazard, Category 2

FARECLA PROFILE 400 ADVANCED PLUS FAST MEDIUM CUT LIQUID COMPOUND

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Full text of H- and EUH-statements:

Asp. Tox. 1	Aspiration hazard, Category 1
EUH208	Contains 1,2-benzisothiazol-3(2H)-one(2634-33-5), 5-Chloro-2-methyl-3(2H)-isothiazolone, mixture with 2-methyl-3(2H)-isothiazolone(55965-84-9). May produce an allergic reaction.
EUH210	Safety data sheet available on request.
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
H272	May intensify fire; oxidiser.
H301	Toxic if swallowed.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
H411	Toxic to aquatic life with long lasting effects.
Ox. Sol. 3	Oxidising Solids, Category 3
Skin Corr. 1A	Skin corrosion/irritation, Category 1, Sub-Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1, Sub-Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1, Sub-Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
Skin Sens. 1A	Skin sensitisation, category 1A

The classification complies with : ATP 12

Safety Data Sheet (SDS), EU

While Farecla Products Ltd. believes that the data and information contained herein are factual and the opinions are those of qualified experts, they are not to be taken as a warranty or representation for which Farecla assumes any legal responsibility. They are offered solely for the consideration, investigation, data and information in accordance with applicable laws and regulations.