



Safety Data Sheet

© 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	28-1026-5	Version number:	2.00
Issue Date:	20/09/2020	Supersedes date:	22/12/2016

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

IDENTIFICATION:

1.1. Product identifier

3M™ Panel Bonding Adhesive PN 38315, 58115

Product Identification Numbers

60-4550-6968-6

1.2. Recommended use and restrictions on use

Recommended use

Automotive.

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

This product is a kit or a multipart product which consists of multiple, independently packaged components. A Safety Data Sheet for each of these components is included. Please do not separate the component Safety Data Sheets from this cover page. The document numbers of the SDSs for components of this product are:

32-4327-6, 09-3599-9

One or more components of this KIT is classified as a hazardous substance in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and the Hazardous Substances (Minimum Degrees of Hazard) Notice 2017.

TRANSPORT INFORMATION

The Dangerous Goods Classification for the complete Kit is provided below.

UN No.: UN3267

Proper shipping name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S., (BIS(3-AMINOPROPYL) ETHER OF

DIETHYLENE GLYCOL, POLYMERIC DIAMIDE)

Class/Division: 8

Packing Group: II

Marine Pollutant: Not applicable.

Hazchem Code: 2X

IERG: 37

New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport

Special Instructions: Limited quantity may apply

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

Special Instructions: Limited quantity may apply

Revision information:

Complete document review.

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>



Safety Data Sheet

© 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	32-4327-6	Version number:	2.00
Issue Date:	13/09/2020	Supersedes date:	22/12/2016

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Panel Bonding Adhesive Part B PN 08115, 38315

1.2. Recommended use and restrictions on use

Recommended use

Automotive., Structural Panel Bonding Adhesive

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Acute Toxicity (inhalation): Category 5	6.1E Acute toxicity (inhalation)
Serious Eye Damage/Irritation: Category 2	6.4A Irritating to the eye
Skin Corrosion/Irritation: Category 2	6.3A Irritating to the skin
Skin Sensitiser: Category 1	6.5B Skin sensitiser
Carcinogenicity: Category 2	6.7B Suspected human carcinogen
Germ Cell Mutagenicity: Category 2	6.6B Suspected human mutagen
Chronic Aquatic Toxicity: Category 2	9.1B Aquatic toxicity (chronic)

Acute Aquatic Toxicity: Category 2	9.1D Aquatic toxicity (acute)
------------------------------------	-------------------------------

2.2. Label elements

SIGNAL WORD

WARNING!

Symbols:

Exclamation mark | Health Hazard | Environment |

Pictograms



HAZARD STATEMENTS:

H333	May be harmful if inhaled.
H319	Causes serious eye irritation.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H341	Suspected of causing genetic defects.
H411	Toxic to aquatic life with long lasting effects.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P280A	Wear eye/face protection.
P280E	Wear protective gloves.
P273	Avoid release to the environment.
P264B	Wash exposed skin thoroughly after handling.
P272A	Contaminated work clothing must not be allowed out of the workplace.

Response:

P304 + P312	IF INHALED: Call a POISON CENTER or doctor/physician if you feel unwell.
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P337 + P313	If eye irritation persists: Get medical advice/attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P332 + P313	If skin irritation occurs: Get medical advice/attention.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see Notes to Physician on this label).

Storage:

P405	Store locked up.
------	------------------

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Oxide Glass Chemicals	65997-17-3	10 - 30
Silica, vitreous	60676-86-0	7 - 13
Acrylate Polymer	Trade Secret	5 - 10
Silicon dioxide	7631-86-9	1 - 5
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	0.5 - 1.5
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	0.5 - 1.5
Carbon black	1333-86-4	< 0.5

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately wash with soap and water. Remove contaminated clothing and wash before reuse. If signs/symptoms develop, get medical attention.

Eye contact

Immediately flush with large amounts of water. Remove contact lenses if easy to do. Continue rinsing. Get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. If you feel unwell, get medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Not applicable

SECTION 5: Fire-fighting measures**5.1. Suitable extinguishing media**

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

5.3. Special protective actions for fire-fighters

When fire fighting conditions are severe and total thermal decomposition of the product is possible, wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, tunic and trousers (leggings), bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: Not applicable.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Keep out of reach of children. Do not handle until all safety precautions have been read and understood. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store away from acids. Store away from strong bases. Store away from oxidising agents. Store away from amines.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Carbon black	1333-86-4	ACGIH	TWA(inhalable fraction):3 mg/m ³	A3: Confirmed animal carcinogen.
Carbon black	1333-86-4	New Zealand WES	TWA(8 hours): 3 mg/m ³	Class-subclass 6.7, carc HCB
Silica, vitreous	60676-86-0	New Zealand WES	TWA(as respirable dust)(8 hours): 0.2 mg/m ³	
Ceramic fibres	65997-17-3	ACGIH	TWA(as fiber):0.2 fiber/cc	A2: Suspected human carcin.
Glass filaments	65997-17-3	New Zealand	TWA(Respirable fibers)(8	

		WES	hours):1 f/mL;TWA(as respirable dust)(8 hours):1 f/mL;TWA(as inhalable dust)(8 hours):5 mg/m ³	
Oxide Glass Chemicals	65997-17-3	Manufacturer determined	TWA(as non-fibrous, respirable)(8 hours):3 mg/m ³ ;TWA(as non-fibrous, inhalable fraction)(8 hours):10 mg/m ³	
SPECIAL PURPOSE GLASS FIBERS	65997-17-3	ACGIH	TWA(as fiber):1 fiber/cc	A3: Confirmed animal carcinogen.

ACGIH : American Conference of Governmental Industrial Hygienists
 AIHA : American Industrial Hygiene Association
 CMRG : Chemical Manufacturer's Recommended Guidelines
 New Zealand WES : New Zealand Workplace Exposure Standards.
 TWA: Time-Weighted-Average
 STEL: Short Term Exposure Limit
 ppm: parts per million
 mg/m³: milligrams per cubic metre
 CELL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:
 Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity.
 Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Colour	Black
Odour	Acrylic
Odour threshold	No data available.
pH	No data available.
Melting point/Freezing point	No data available.
Boiling point/Initial boiling point/Boiling range	>= 35 °C
Flash point	>= 104.4 °C [Test Method: Closed Cup]
Evaporation rate	<= 1 Units not available or not applicable. [Ref Std: BUOAC=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits (LEL)	No data available.
Flammable Limits (UEL)	No data available.
Vapour pressure	<= 186,158.4 Pa
Vapor Density and/or Relative Vapor Density	No data available.
Density	1.2 kg/l
Relative density	1.2 [Ref Std: WATER=1]
Water solubility	Negligible
Solubility- non-water	No data available.
Partition coefficient: n-octanol/water	No data available.
Autoignition temperature	No data available.
Decomposition temperature	No data available.
Viscosity/Kinematic Viscosity	100,000 mPa-s - 225,000 mPa-s [Test Method: Brookfield]
Volatile organic compounds (VOC)	15 g/l [Test Method: calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	1.6 % weight [Test Method: calculated per CARB title 2]
Percent volatile	1.6 % weight
VOC less H ₂ O & exempt solvents	15 g/l [Test Method: calculated SCAQMD rule 443.1]
Molecular weight	No data available.

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material may be reactive with certain agents under certain conditions - see the remaining headings in this section

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

Sparks and/or flames.

10.5 Incompatible materials

Amines.
Strong acids.
Strong bases.
Strong oxidising agents.

10.6 Hazardous decomposition products

<u>Substance</u>	<u>Condition</u>
Aldehydes.	Not specified.
Carbon monoxide.	Not specified.
Carbon dioxide.	Not specified.
Hydrogen Chloride	Not specified.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

Skin Irritation: Signs/symptoms may include localized redness, swelling, itching, dryness, cracking, blistering, and pain. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness, swelling, blistering, and itching. May cause additional health effects (see below).

Eye contact

Severe eye irritation: Signs/symptoms may include significant redness, swelling, pain, tearing, cloudy appearance of the cornea, and impaired vision.

Ingestion

Gastrointestinal irritation: Signs/symptoms may include abdominal pain, stomach upset, nausea, vomiting and diarrhoea. May cause additional health effects (see below).

Additional Health Effects:

Genotoxicity:

Genotoxicity and Mutagenicity: May interact with genetic material and possibly alter gene expression.

Carcinogenicity:

Contains a chemical or chemicals which can cause cancer.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

3M™ Panel Bonding Adhesive Part B PNs 08115, 38315, 58115**Acute Toxicity**

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE >5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE >5,000 mg/kg
Oxide Glass Chemicals	Dermal		LD50 estimated to be > 5,000 mg/kg
Oxide Glass Chemicals	Ingestion		LD50 estimated to be 2,000 - 5,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
Acrylate Polymer	Dermal	Rabbit	LD50 > 5,000 mg/kg
Acrylate Polymer	Ingestion	Rat	LD50 > 5,000 mg/kg
Silicon dioxide	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silicon dioxide	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silicon dioxide	Ingestion	Rat	LD50 > 5,110 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Rabbit	LD50 4,000 mg/kg
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 5.3 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Rat	LD50 7,010 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product With Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Carbon black	Dermal	Rabbit	LD50 > 3,000 mg/kg
Carbon black	Ingestion	Rat	LD50 > 8,000 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Oxide Glass Chemicals	Professional judgement	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Acrylate Polymer	Professional judgement	Minimal irritation
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Mild irritant
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

Serious Eye Damage/Irritation

Name	Species	Value
Oxide Glass Chemicals	Professional judgement	No significant irritation
Silica, vitreous	Rabbit	No significant irritation
Acrylate Polymer	Professional	Mild irritant

3M™ Panel Bonding Adhesive Part B PNs 08115, 38315, 58115

	judgement	
Silicon dioxide	Rabbit	No significant irritation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product With Silica	Rabbit	No significant irritation
Carbon black	Rabbit	No significant irritation

Sensitisation:**Skin Sensitisation**

Name	Species	Value
Silica, vitreous	Human and animal	Not classified
Silicon dioxide	Human and animal	Not classified
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Guinea pig	Not classified
Dimethyl Siloxane, Reaction Product With Silica	Human and animal	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Oxide Glass Chemicals	In Vitro	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	In Vitro	Not mutagenic
Silicon dioxide	In Vitro	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In vivo	Not mutagenic
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	In Vitro	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product With Silica	In Vitro	Not mutagenic
Carbon black	In Vitro	Not mutagenic
Carbon black	In vivo	Some positive data exist, but the data are not sufficient for classification

Carcinogenicity

Name	Route	Species	Value
Oxide Glass Chemicals	Inhalation	Multiple animal species	Some positive data exist, but the data are not sufficient for classification
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Silicon dioxide	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Dermal	Mouse	Not carcinogenic
Dimethyl Siloxane, Reaction Product With Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Carbon black	Dermal	Mouse	Not carcinogenic
Carbon black	Ingestion	Mouse	Not carcinogenic
Carbon black	Inhalation	Rat	Carcinogenic.

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure
------	-------	-------	---------	-------------	----------

3M™ Panel Bonding Adhesive Part B PNs 08115, 38315, 58115

					Duration
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Silicon dioxide	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silicon dioxide	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	1 generation
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	Not classified for development	Rat	NOAEL 3,000 mg/kg/day	during organogenesis
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product With Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis

Target Organ(s)
Specific Target Organ Toxicity - single exposure

For the component/components, either no data are currently available or the data are not sufficient for classification.

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Oxide Glass Chemicals	Inhalation	respiratory system	Not classified	Human	NOAEL not available	occupational exposure
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Silicon dioxide	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	Ingestion	heart endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system kidney and/or bladder respiratory system	Not classified	Rat	NOAEL 1,000 mg/kg/day	28 days
Dimethyl Siloxane, Reaction Product With Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Carbon black	Inhalation	pneumoconiosis	Not classified	Human	NOAEL Not available	occupational exposure

Aspiration Hazard

For the component/components, either no data are currently available or the data are not sufficient for classification.

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Ecotoxic to the aquatic environment.

Acute Aquatic Toxicity: Category 2 (HSNO 9.1D Aquatic toxicity)

Chronic Aquatic Toxicity: Category 2 (HSNO 9.1B Aquatic toxicity)

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Water flea	Experimental	72 hours	EC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Zebra Fish	Experimental	96 hours	LC50	>1,000 mg/l
Oxide Glass Chemicals	65997-17-3	Green algae	Experimental	72 hours	NOEC	>=1,000 mg/l
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Acrylate Polymer	Trade Secret		Data not available or insufficient for classification			
Silicon dioxide	7631-86-9		Data not available or insufficient for classification			
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Common Carp	Experimental	96 hours	LC50	55 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Crustacea other	Experimental	48 hours	LC50	324 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green algae	Experimental	96 hours	EC50	350 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Green Algae	Experimental	96 hours	NOEC	130 mg/l
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Water flea	Experimental	21 days	NOEC	>=100 mg/l

3M™ Panel Bonding Adhesive Part B PNs 08115, 38315, 58115

xysilane						
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7		Data not available or insufficient for classification			
Carbon black	1333-86-4		Data not available or insufficient for classification			

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Oxide Glass Chemicals	65997-17-3	Data not availbl- insufficient			N/A	
Silica, vitreous	60676-86-0	Data not availbl- insufficient			N/A	
Acrylate Polymer	Trade Secret	Data not availbl- insufficient			N/A	
Silicon dioxide	7631-86-9	Data not availbl- insufficient			N/A	
[3-(2,3-epoxypropoxy) propyl]trimetho xysilane	2530-83-8	Experimental Hydrolysis		Hydrolytic half-life	6.5 hours (t 1/2)	Other methods
[3-(2,3-epoxypropoxy) propyl]trimetho xysilane	2530-83-8	Experimental Biodegradation	28 days	Dissolv. Organic Carbon Deplet	37 % weight	Other methods
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	Data not availbl- insufficient			N/A	
Carbon black	1333-86-4	Data not availbl- insufficient			N/A	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Oxide Glass Chemicals	65997-17-3	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Acrylate	Trade Secret	Data not	N/A	N/A	N/A	N/A

3M™ Panel Bonding Adhesive Part B PNs 08115, 38315, 58115

Polymer		available or insufficient for classification				
Silicon dioxide	7631-86-9	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
[3-(2,3-epoxypropoxy)propyl]trimethoxysilane	2530-83-8	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Siloxane, Reaction Product With Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Carbon black	1333-86-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of waste product in a permitted industrial waste facility. As a disposal alternative, incinerate in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Combustion products will include halogen acid (HCl/HF/HBr). Facility must be capable of handling halogenated materials. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information**New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport**

UN No.: Not applicable.

Proper Shipping Name: Not applicable.

Class/Division: Not applicable.

Sub Risk: Not applicable.

Packing Group: Not applicable.

Hazchem Code: Not applicable.

IERG: Not applicable.

International Air Transport Association (IATA) - Air Transport**UN No.:** Not applicable.**Proper Shipping Name:** Not applicable.**Class/Division:** Not applicable.**Sub Risk:** Not applicable.**Packing Group:** Not applicable.**International Maritime Dangerous Goods Code (IMDG) - Marine Transport****UN No.:** Not applicable.**Proper Shipping Name:** Not applicable.**Class/Division:** Not applicable.**Sub Risk:** Not applicable.**Packing Group:** Not applicable.**Marine Pollutant:** Not applicable.**SECTION 15: Regulatory information**

HSNO Approval number	HSR002679
Group standard name	Surface Coatings and Colourants (Toxic [6.7]) Group Standard 2017
HSNO Hazard classification	Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for all other substances)
Secondary containment	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for all other substances)
Tracking	Not required
Warning signage	100 L or 100 kg (for a HSNO 9.1A substance); or 1,000 L or 1,000 kg (for a HSNO 8.3A, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for a HSNO 6.1D or 9.1D substance)

SECTION 16: Other information**Revision information:**

Complete document review.

Document group:	32-4327-6	Version number:	2.00
Issue Date:	13/09/2020	Supersedes date:	22/12/2016

Key to abbreviations and acronyms**GHS** means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013**HSNO** means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT

PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>



Safety Data Sheet

© 2020, 3M Company All rights reserved. Copying and/or downloading of this information for the purpose of properly utilizing 3M products is allowed provided that: (1) the information is copied in full with no changes unless prior written agreement is obtained from 3M, and (2) neither the copy nor the original is resold or otherwise distributed with the intention of earning a profit thereon.

Document group:	09-3599-9	Version number:	5.00
Issue Date:	13/09/2020	Supersedes date:	22/12/2016

This Safety Data Sheet has been prepared in accordance with the New Zealand, Hazardous Substances (Safety Data Sheets) Notice 2017.

SECTION 1: Identification

1.1. Product identifier

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315

1.2. Recommended use and restrictions on use

Recommended use

Automotive. Use with Part B, SDS 32-4327-6

For Industrial or Professional use only

1.3. Supplier's details

Address:	3M New Zealand Ltd, 94 Apollo Drive, Rosedale 0632, Auckland
Telephone:	(09) 477 4040
E Mail:	innovation@nz.mmm.com
Website:	3m.co.nz

1.4. Emergency telephone number

24 hr Medical Emergency, National Poisons Centre, 0800 764 766 (0800 POISON)

SECTION 2: Hazard identification

Classified as hazardous in accordance with the relevant criteria of the HSNO Act 1996, the Hazardous Substances (Classification) Notice 2017 and Hazardous Substances (Minimum Degrees of Hazard) Notice 2017. Refer to Section 14 of this Safety Data Sheet for product Dangerous Goods Classification.

2.1. Classification of the substance or mixture

GHS	HSNO
Acute Toxicity (oral): Category 5	6.1E Acute toxicity (oral)
Acute Toxicity (dermal): Category 5	6.1E Acute toxicity (skin)
Acute Toxicity (inhalation): Category 5	6.1E Acute toxicity (inhalation)
Serious Eye Damage/Irritation: Category 1	8.3A Corrosive to eye
Skin Corrosion/Irritation: Category 1B	8.2B Corrosive to skin
Skin Sensitiser: Category 1	6.5B Skin sensitiser
Reproductive Toxicity: Category 1B	6.8A Known/presumed human

	reproductive/developmental toxicant
Specific Target Organ Toxicity (single exposure): Category 1	6.9A Toxic to human target organs/systems
Specific Target Organ Toxicity (repeated exposure): Category 1	6.9A Toxic to human target organs/systems
Specific Target Organ Toxicity (single exposure): Category 3	6.9B Narcotic effects
No GHS Equivalent	9.3C Terrestrial vertebrate toxicity

2.2. Label elements

SIGNAL WORD

DANGER!

Symbols:

Corrosion | Exclamation mark | Health Hazard |

Pictograms



HAZARD STATEMENTS:

H303	May be harmful if swallowed.
H313	May be harmful in contact with skin.
H333	May be harmful if inhaled.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H360	May damage fertility or the unborn child.
H336	May cause drowsiness or dizziness.
H370	Causes damage to organs: blood or blood-forming organs
H372	Causes damage to organs through prolonged or repeated exposure: respiratory system
H433	Harmful to terrestrial vertebrates.

PRECAUTIONARY STATEMENTS

Prevention:

P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P271	Use only outdoors or in a well-ventilated area.
P280D	Wear protective gloves, protective clothing, and eye/face protection.
P270	Do not eat, drink or smoke when using this product.
P273	Avoid release to the environment.
P264B	Wash exposed skin thoroughly after handling.
P272A	Contaminated work clothing must not be allowed out of the workplace.

Response:

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
-------------	--

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or doctor/physician.
P333 + P313	If skin irritation or rash occurs: Get medical advice/attention.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P301 + P330 + P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P308 + P313	IF exposed or concerned: Get medical advice/attention.
P321	Specific treatment (see Notes to Physician on this label).
P303 + P361 + P353A	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Storage:

P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P405	Store locked up.

Disposal:

P501	Dispose of contents/container in accordance with applicable local/regional/national/international regulations.
------	--

2.3. Other hazards

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines. - May cause chemical gastrointestinal burns. All or part of the classification is based on toxicity test data.

SECTION 3: Composition/information on ingredients

Ingredient	CAS Nbr	% by Weight
Polymeric Diamide	68911-25-1	15 - 40
Butadiene Acrylonitrile Copolymer	68683-29-4	9 - 30
Silica, vitreous	60676-86-0	10 - 30
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	7 - 13
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	90-72-2	5 - 10
Amine Epoxy Curing Agent	288-32-4	1 - 5
Calcium Nitrate	10124-37-5	1 - 5
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	1 - 5
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0	0.1 - 1.5
N-Aminoethylpiperazine	140-31-8	0.1 - 1.5
Toluene	108-88-3	< 0.5

SECTION 4: First aid measures**4.1. Description of first aid measures****Inhalation**

Remove person to fresh air. If you feel unwell, get medical attention.

Skin contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contaminated clothing. Get immediate medical attention. Wash clothing before reuse.

Eye contact

Immediately flush with large amounts of water for at least 15 minutes. Remove contact lenses if easy to do. Continue rinsing. Immediately get medical attention.

A product risk assessment is recommended to determine if eye wash facilities may be required when using this product in the workplace.

If swallowed

Rinse mouth. Do not induce vomiting. Get immediate medical attention.

4.2. Most important symptoms and effects, both acute and delayed

See Section 11.1 Information on toxicological effects

4.3. Indication of any immediate medical attention and special treatment required

Overexposure to this product may result in methemoglobinemia. Methemoglobinemia may be clinically suspected by the presence of clinical "cyanosis" in the presence of a normal PaO₂ (as obtained by arterial blood gases). Routine pulse oximetry may be inaccurate for monitoring oxygen saturation in the presence of methemoglobinemia, and should not be used to make the diagnosis of this disorder. If the patient is symptomatic or if the methemoglobin level is >20%, specific therapy with methylene blue should be considered as part of the medical management.

SECTION 5: Fire-fighting measures

5.1. Suitable extinguishing media

In case of fire: Use a fire fighting agent suitable for ordinary combustible material such as water or foam to extinguish.

5.2. Special hazards arising from the substance or mixture

None inherent in this product.

Hazardous Decomposition or By-Products

Substance

Carbon monoxide.

Carbon dioxide.

Condition

During combustion.

During combustion.

5.3. Special protective actions for fire-fighters

Wear full protective clothing, including helmet, self-contained, positive pressure or pressure demand breathing apparatus, bunker coat and pants, bands around arms, waist and legs, face mask, and protective covering for exposed areas of the head.

5.4. Hazchem code: 2X

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Evacuate area. Ventilate the area with fresh air. For large spill, or spills in confined spaces, provide mechanical ventilation to disperse or exhaust vapors, in accordance with good industrial hygiene practice. Refer to other sections of this SDS for information regarding physical and health hazards, respiratory protection, ventilation, and personal protective equipment.

6.2. Environmental precautions

Avoid release to the environment. For larger spills, cover drains and build dykes to prevent entry into sewer systems or bodies of water.

6.3. Methods and material for containment and cleaning up

Contain spill. Working from around the edges of the spill inward, cover with bentonite, vermiculite, or commercially available inorganic absorbent material. Mix in sufficient absorbent until it appears dry. Remember, adding an absorbent material does not remove a physical, health, or environmental hazard. Collect as much of the spilled material as possible. Place in a closed container approved for transportation by appropriate authorities. Clean up residue with an appropriate solvent selected by a qualified and authorised person. Ventilate the area with fresh air. Read and follow safety precautions on the solvent label and Safety Data Sheet. Seal the container. Dispose of collected material as soon as possible in accordance with applicable local/regional/national/international regulations.

SECTION 7: Handling and storage

Refer to Section 15 - Controls for more information

7.1. Precautions for safe handling

Do not use in a confined area with minimal air exchange. Do not handle until all safety precautions have been read and understood. Do not breathe dust/fume/gas/mist/vapours/spray. Do not get in eyes, on skin, or on clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Contaminated work clothing should not be allowed out of the workplace. Avoid release to the environment. Wash contaminated clothing before reuse. Avoid contact with oxidising agents (eg. chlorine, chromic acid etc.) Use personal protective equipment (eg. gloves, respirators...) as required.

7.2. Conditions for safe storage including any incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store away from acids. Store away from oxidising agents.

7.3. Certified handler

Not required

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Occupational exposure limits

If a component is disclosed in section 3 but does not appear in the table below, an occupational exposure limit is not available for the component.

Ingredient	CAS Nbr	Agency	Limit type	Additional comments
Toluene	108-88-3	ACGIH	TWA:20 ppm	A4: Not class. as human carcinogen
Toluene	108-88-3	New Zealand WES	TWA(8 hours): 188 mg/m ³ (50 ppm)	Skin
Silica, vitreous	60676-86-0	New Zealand WES	TWA(as respirable dust)(8 hours): 0.2 mg/m ³	

ACGIH : American Conference of Governmental Industrial Hygienists

AIHA : American Industrial Hygiene Association

CMRG : Chemical Manufacturer's Recommended Guidelines

New Zealand WES : New Zealand Workplace Exposure Standards.

TWA: Time-Weighted-Average

STEL: Short Term Exposure Limit

ppm: parts per million

mg/m³: milligrams per cubic metre

CEL: Ceiling

8.2. Exposure controls

8.2.1. Engineering controls

Use general dilution ventilation and/or local exhaust ventilation to control airborne exposures to below relevant Exposure Limits and/or control dust/fume/gas/mist/vapours/spray. If ventilation is not adequate, use respiratory protection equipment.

8.2.2. Personal protective equipment (PPE)

Eye/face protection

Select and use eye/face protection to prevent contact based on the results of an exposure assessment. The following eye/face protection(s) are recommended:

Full face shield.

Indirect vented goggles.

Refer AS/NZS 1336 - Recommended practices for occupational eye protection and for performance specifications AS/NZS 1337, Parts 1 - 6 - Personal eye-protection.

Skin/hand protection

Select and use gloves and/or protective clothing approved to relevant local standards to prevent skin contact based on the results of an exposure assessment. Selection should be based on use factors such as exposure levels, concentration of the substance or mixture, frequency and duration, physical challenges such as temperature extremes, and other use conditions. Consult with your glove and/or protective clothing manufacturer for selection of appropriate compatible gloves/protective clothing. Note: Nitrile gloves may be worn over polymer laminate gloves to improve dexterity. Gloves made from the following material(s) are recommended: Polymer laminate

If this product is used in a manner that presents a higher potential for exposure (eg. spraying, high splash potential etc.), then use of protective coveralls may be necessary. Select and use body protection to prevent contact based on the results of an exposure assessment. The following protective clothing material(s) are recommended: Apron - polymer laminate

Respiratory protection

An exposure assessment may be needed to decide if a respirator is required. If a respirator is needed, use respirators as part of a full respiratory protection program. Based on the results of the exposure assessment, select from the following respirator type(s) to reduce inhalation exposure:

Half facepiece or full facepiece air-purifying respirator suitable for organic vapors and particulates

For questions about suitability for a specific application, consult with your respirator manufacturer.

Refer AS/NZS 1715 - Selection, use and maintenance of respiratory protective equipment and AS/NZS 1716 - Respiratory protective devices.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	Liquid.
Specific Physical Form:	Viscous liquid
Colour	Tan
Odour	Slight Amine
Odour threshold	<i>No data available.</i>
pH	<i>Not applicable.</i>
Melting point/Freezing point	<i>Not applicable.</i>
Boiling point/Initial boiling point/Boiling range	>=110 °C
Flash point	110 °C [<i>Test Method</i> :Closed Cup]
Evaporation rate	<=1 [<i>Ref Std</i> :BUOAC=1]
Flammability (solid, gas)	Not applicable.
Flammable Limits(LEL)	<i>No data available.</i>
Flammable Limits(UEL)	<i>No data available.</i>
Vapour pressure	<=26,664.4 Pa [<i>@ 20 °C</i>]
Vapor Density and/or Relative Vapor Density	<i>No data available.</i>
Density	1.2 g/ml
Relative density	1.2 [<i>Ref Std</i> :WATER=1]
Water solubility	<i>No data available.</i>
Solubility- non-water	<i>No data available.</i>
Partition coefficient: n-octanol/water	<i>No data available.</i>
Autoignition temperature	<i>No data available.</i>
Decomposition temperature	<i>No data available.</i>
Viscosity/Kinematic Viscosity	100,000 mPa-s - 225,000 mPa-s [<i>Test Method</i> :Brookfield]

Volatile organic compounds (VOC)	4 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Volatile organic compounds (VOC)	0.4 % weight [<i>Test Method</i> :calculated per CARB title 2]
Percent volatile	0.4 % weight
VOC less H2O & exempt solvents	4 g/l [<i>Test Method</i> :calculated SCAQMD rule 443.1]
Molecular weight	No data available.

Nanoparticles

This material contains nanoparticles.

SECTION 10: Stability and reactivity

10.1 Reactivity

This material is considered to be non reactive under normal use conditions

10.2 Chemical stability

Stable.

10.3 Possibility of hazardous reactions

Hazardous polymerisation will not occur.

10.4 Conditions to avoid

None known.

10.5 Incompatible materials

Strong oxidising agents.

10.6 Hazardous decomposition products

Substance

Condition

None known.

Refer to Section 5.2 for hazardous decomposition products during combustion.

SECTION 11: Toxicological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. In addition, toxicological data on ingredients may not be reflected in the material classification and/or the signs and symptoms of exposure, because an ingredient may be present below the threshold for labelling, an ingredient may not be available for exposure, or the data may not be relevant to the material as a whole.

11.1 Information on Toxicological effects

Signs and Symptoms of Exposure

Based on test data and/or information on the components, this material may produce the following health effects:

Inhalation

May be harmful if inhaled. Respiratory tract irritation: Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain. May cause additional health effects (see below).

Skin contact

May be harmful in contact with skin.

Corrosive (skin burns): Signs/symptoms may include localised redness, swelling, itching, intense pain, blistering, ulceration, and tissue destruction. Allergic skin reaction (non-photo induced): Signs/symptoms may include redness,

swelling, blistering, and itching.

Eye contact

Corrosive (eye burns): Signs/symptoms may include cloudy appearance of the cornea, chemical burns, severe pain, tearing, ulcerations, significantly impaired vision or complete loss of vision.

Ingestion

May be harmful if swallowed.

Gastrointestinal corrosion: Signs/symptoms may include severe mouth, throat and abdominal pain, nausea, vomiting, and diarrhea; blood in the faeces and/or vomitus may also be seen. May cause additional health effects (see below).

Additional Health Effects:

Single exposure may cause target organ effects:

Methemoglobinemia: Signs/symptoms may include headache, dizziness, nausea, difficulty breathing, and generalised weakness. Central nervous system (CNS) depression: Signs/symptoms may include headache, dizziness, drowsiness, incoordination, nausea, slowed reaction time, slurred speech, giddiness, and unconsciousness.

Prolonged or repeated exposure may cause target organ effects:

Respiratory effects: Signs/symptoms may include cough, shortness of breath, chest tightness, wheezing, increased heart rate, bluish coloured skin (cyanosis), sputum production, changes in lung function tests, and respiratory failure.

Reproductive/Developmental Toxicity:

Contains a chemical or chemicals which can cause birth defects or other reproductive harm.

Additional information:

Persons previously sensitised to amines may develop a cross-sensitisation reaction to certain other amines.

Toxicological Data

If a component is disclosed in section 3 but does not appear in a table below, either no data are available for that endpoint or the data are not sufficient for classification.

Acute Toxicity

Name	Route	Species	Value
Overall product	Dermal		No data available; calculated ATE2,000 - 5,000 mg/kg
Overall product	Inhalation-Dust/Mist(4 hr)		No data available; calculated ATE5 - 12.5 mg/l
Overall product	Ingestion		No data available; calculated ATE2,000 - 5,000 mg/kg
Polymeric Diamide	Dermal	Rat	LD50 > 2,000 mg/kg
Polymeric Diamide	Ingestion	Rat	LD50 > 2,000 mg/kg
Silica, vitreous	Dermal	Rabbit	LD50 > 5,000 mg/kg
Silica, vitreous	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Silica, vitreous	Ingestion	Rat	LD50 > 5,110 mg/kg
Butadiene Acrylonitrile Copolymer	Dermal	Rabbit	LD50 > 3,000 mg/kg
Butadiene Acrylonitrile Copolymer	Ingestion	Rat	LD50 > 15,300 mg/kg
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Dermal	Rabbit	LD50 2,500 mg/kg
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Ingestion	Rat	LD50 3,160 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	Rat	LD50 1,280 mg/kg
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Ingestion	Rat	LD50 1,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Dermal	Rabbit	LD50 > 5,000 mg/kg
Dimethyl Siloxane, Reaction Product with Silica	Inhalation-Dust/Mist (4 hours)	Rat	LC50 > 0.691 mg/l
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Rat	LD50 > 5,110 mg/kg
Amine Epoxy Curing Agent	Ingestion	Rat	LD50 970 mg/kg
Amine Epoxy Curing Agent	Dermal	similar	LD50 400 mg/kg

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

		compound	
Calcium Nitrate	Ingestion	Rat	LD50 >300, <2000 mg/kg
Calcium Nitrate	Dermal	similar compound	LD50 > 2,000 mg/kg
Bis[(Dimethylamino)Methyl]Phenol	Ingestion		LD50 estimated to be 300 - 2,000 mg/kg
N-Aminoethylpiperazine	Dermal	Rabbit	LD50 865 mg/kg
N-Aminoethylpiperazine	Ingestion	Rat	LD50 1,470 mg/kg
Toluene	Dermal	Rat	LD50 12,000 mg/kg
Toluene	Inhalation-Vapor (4 hours)	Rat	LC50 30 mg/l
Toluene	Ingestion	Rat	LD50 5,550 mg/kg

ATE = acute toxicity estimate

Skin Corrosion/Irritation

Name	Species	Value
Overall product	Rabbit	Corrosive
Polymeric Diamide	Rat	Irritant
Silica, vitreous	Rabbit	No significant irritation
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Rabbit	Corrosive
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Amine Epoxy Curing Agent	Rabbit	Corrosive
Calcium Nitrate	similar compound	No significant irritation
Bis[(Dimethylamino)Methyl]Phenol	similar compound	Corrosive
N-Aminoethylpiperazine	Rabbit	Corrosive
Toluene	Rabbit	Irritant

Serious Eye Damage/Irritation

Name	Species	Value
Overall product	similar health hazards	Corrosive
Polymeric Diamide	In vitro data	Severe irritant
Silica, vitreous	Rabbit	No significant irritation
Bis(3-Aminopropyl) Ether of Diethylene Glycol	similar health hazards	Corrosive
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Rabbit	Corrosive
Dimethyl Siloxane, Reaction Product with Silica	Rabbit	No significant irritation
Amine Epoxy Curing Agent	Rabbit	Corrosive
Calcium Nitrate	Rabbit	Corrosive
Bis[(Dimethylamino)Methyl]Phenol	similar compound	Corrosive
N-Aminoethylpiperazine	Rabbit	Corrosive
Toluene	Rabbit	Moderate irritant

Sensitisation:**Skin Sensitisation**

Name	Species	Value
Overall product	Guinea	Sensitising

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

Polymeric Diamide	pig Guinea pig	Sensitising
Silica, vitreous	Human and animal	Not classified
Butadiene Acrylonitrile Copolymer	Guinea pig	Not classified
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Guinea pig	Not classified
Dimethyl Siloxane, Reaction Product with Silica	Human and animal	Not classified
Calcium Nitrate	similar compounds	Not classified
N-Aminoethylpiperazine	Guinea pig	Sensitising
Toluene	Guinea pig	Not classified

Respiratory Sensitisation

For the component/components, either no data are currently available or the data are not sufficient for classification.

Germ Cell Mutagenicity

Name	Route	Value
Polymeric Diamide	In Vitro	Not mutagenic
Silica, vitreous	In Vitro	Not mutagenic
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	In Vitro	Not mutagenic
Dimethyl Siloxane, Reaction Product with Silica	In Vitro	Not mutagenic
Amine Epoxy Curing Agent	In Vitro	Not mutagenic
Amine Epoxy Curing Agent	In vivo	Not mutagenic
Calcium Nitrate	In Vitro	Not mutagenic
N-Aminoethylpiperazine	In vivo	Not mutagenic
N-Aminoethylpiperazine	In Vitro	Some positive data exist, but the data are not sufficient for classification
Toluene	In Vitro	Not mutagenic
Toluene	In vivo	Not mutagenic

Carcinogenicity

Name	Route	Species	Value
Silica, vitreous	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Dimethyl Siloxane, Reaction Product with Silica	Not specified.	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Dermal	Mouse	Some positive data exist, but the data are not sufficient for classification
Toluene	Ingestion	Rat	Some positive data exist, but the data are not sufficient for classification
Toluene	Inhalation	Mouse	Some positive data exist, but the data are not sufficient for classification

Reproductive Toxicity**Reproductive and/or Developmental Effects**

Name	Route	Value	Species	Test result	Exposure Duration
Polymeric Diamide	Ingestion	Not classified for female reproduction	Rat	NOAEL 1,000 mg/kg/day	prematuring into lactation
Polymeric Diamide	Ingestion	Not classified for male reproduction	Rat	NOAEL 1,000 mg/kg/day	29 days

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

Polymeric Diamide	Ingestion	Not classified for development	Rat	NOAEL 1,000 mg/kg/day	premating into lactation
Silica, vitreous	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Silica, vitreous	Inhalation	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Silica, vitreous	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for female reproduction	Rat	NOAEL 509 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for male reproduction	Rat	NOAEL 497 mg/kg/day	1 generation
Dimethyl Siloxane, Reaction Product with Silica	Ingestion	Not classified for development	Rat	NOAEL 1,350 mg/kg/day	during organogenesis
Amine Epoxy Curing Agent	Ingestion	Toxic to development	Rat	NOAEL 60 mg/kg/day	during organogenesis
Calcium Nitrate	Ingestion	Not classified for female reproduction	similar compounds	NOAEL 1,500 mg/kg/day	premating into lactation
Calcium Nitrate	Ingestion	Not classified for male reproduction	similar compounds	NOAEL 1,500 mg/kg/day	28 days
Calcium Nitrate	Ingestion	Not classified for development	similar compounds	NOAEL 1,500 mg/kg/day	premating into lactation
N-Aminoethylpiperazine	Ingestion	Not classified for female reproduction	Rat	NOAEL 598 mg/kg/day	premating & during gestation
N-Aminoethylpiperazine	Ingestion	Not classified for male reproduction	Rat	NOAEL 409 mg/kg/day	32 days
N-Aminoethylpiperazine	Ingestion	Toxic to development	Rabbit	NOAEL 75 mg/kg/day	during gestation
Toluene	Inhalation	Not classified for female reproduction	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	Not classified for male reproduction	Rat	NOAEL 2.3 mg/l	1 generation
Toluene	Ingestion	Toxic to development	Rat	LOAEL 520 mg/kg/day	during gestation
Toluene	Inhalation	Toxic to development	Human	NOAEL Not available	poisoning and/or abuse

Target Organ(s)
Specific Target Organ Toxicity - single exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polymeric Diamide	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	Irritation Positive	
Polymeric Diamide	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Rat	NOAEL Not available	
Bis(3-Aminopropyl) Ether of Diethylene Glycol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Amine Epoxy Curing Agent	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Calcium Nitrate	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	similar health hazards	NOAEL Not available	
Calcium Nitrate	Ingestion	methemoglobinemia	Causes damage to organs	Human	NOAEL Not available	environmental

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

		a			available	exposure
N-Aminoethylpiperazine	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification		NOAEL Not available	
Toluene	Inhalation	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	
Toluene	Inhalation	respiratory irritation	Some positive data exist, but the data are not sufficient for classification	Human	NOAEL Not available	
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL 0.004 mg/l	3 hours
Toluene	Ingestion	central nervous system depression	May cause drowsiness or dizziness	Human	NOAEL Not available	poisoning and/or abuse

Specific Target Organ Toxicity - repeated exposure

Name	Route	Target Organ(s)	Value	Species	Test result	Exposure Duration
Polymeric Diamide	Ingestion	heart skin endocrine system gastrointestinal tract bone, teeth, nails, and/or hair hematopoietic system liver immune system muscles nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
Silica, vitreous	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Tris(2,4,6-Dimethylaminomonomethyl)Phenol	Dermal	skin liver nervous system auditory system hematopoietic system eyes	Not classified	Rat	NOAEL 125 mg/kg/day	28 days
Dimethyl Siloxane, Reaction Product with Silica	Inhalation	respiratory system silicosis	Not classified	Human	NOAEL Not available	occupational exposure
Amine Epoxy Curing Agent	Ingestion	kidney and/or bladder	Not classified	Rat	NOAEL 60 mg/kg/day	90 days
Amine Epoxy Curing Agent	Ingestion	heart liver blood nervous system eyes	Not classified	Rat	NOAEL 180 mg/kg/day	90 days
Calcium Nitrate	Ingestion	heart skin endocrine system bone, teeth, nails, and/or hair hematopoietic system liver immune system nervous system eyes kidney and/or bladder respiratory system vascular system	Not classified	similar compounds	NOAEL 1,500 mg/kg/day	28 days
N-Aminoethylpiperazine	Dermal	skin	Not classified	Rat	NOAEL 100 mg/kg/day	29 days
N-Aminoethylpiperazine	Dermal	hematopoietic system nervous system kidney and/or bladder	Not classified	Rat	NOAEL 1,000 mg/kg/day	29 days
N-Aminoethylpiperazine	Inhalation	respiratory system	Causes damage to organs through prolonged or repeated exposure	Rat	NOAEL 0.2 mg/m3	13 weeks
N-Aminoethylpiperazine	Inhalation	hematopoietic system eyes	Not classified	Rat	NOAEL 53.8 mg/m3	13 weeks

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

		kidney and/or bladder				
N-Aminoethylpiperazine	Ingestion	heart endocrine system hematopoietic system liver nervous system kidney and/or bladder	Not classified	Rat	NOAEL 598 mg/kg/day	28 days
Toluene	Inhalation	auditory system eyes olfactory system	Causes damage to organs through prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	nervous system	May cause damage to organs though prolonged or repeated exposure	Human	NOAEL Not available	poisoning and/or abuse
Toluene	Inhalation	respiratory system	Some positive data exist, but the data are not sufficient for classification	Rat	LOAEL 2.3 mg/l	15 months
Toluene	Inhalation	heart liver kidney and/or bladder	Not classified	Rat	NOAEL 11.3 mg/l	15 weeks
Toluene	Inhalation	endocrine system	Not classified	Rat	NOAEL 1.1 mg/l	4 weeks
Toluene	Inhalation	immune system	Not classified	Mouse	NOAEL Not available	20 days
Toluene	Inhalation	bone, teeth, nails, and/or hair	Not classified	Mouse	NOAEL 1.1 mg/l	8 weeks
Toluene	Inhalation	hematopoietic system vascular system	Not classified	Human	NOAEL Not available	occupational exposure
Toluene	Inhalation	gastrointestinal tract	Not classified	Multiple animal species	NOAEL 11.3 mg/l	15 weeks
Toluene	Ingestion	nervous system	Some positive data exist, but the data are not sufficient for classification	Rat	NOAEL 625 mg/kg/day	13 weeks
Toluene	Ingestion	heart	Not classified	Rat	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	liver kidney and/or bladder	Not classified	Multiple animal species	NOAEL 2,500 mg/kg/day	13 weeks
Toluene	Ingestion	hematopoietic system	Not classified	Mouse	NOAEL 600 mg/kg/day	14 days
Toluene	Ingestion	endocrine system	Not classified	Mouse	NOAEL 105 mg/kg/day	28 days
Toluene	Ingestion	immune system	Not classified	Mouse	NOAEL 105 mg/kg/day	4 weeks

Aspiration Hazard

Name	Value
Toluene	Aspiration hazard

Please contact the address or phone number listed on the first page of the SDS for additional toxicological information on this material and/or its components.

SECTION 12: Ecological information

The information below may not be consistent with the material classification in Section 2 if specific ingredient classifications are mandated by a competent authority. Additional information leading to material classification in Section 2 is available upon request. In addition, environmental fate and effects data on ingredients may not be reflected in this section because an ingredient is present below the threshold for labelling, an ingredient is not expected to be available for exposure, or the data is considered not relevant to the material as a whole.

12.1. Toxicity

Ecotoxic to terrestrial vertebrates
9.3C Terrestrial vertebrate toxicity

No product test data available.

Material	CAS Number	Organism	Type	Exposure	Test endpoint	Test result
Polymeric Diamide	68911-25-1	Fathead minnow	Experimental	96 hours	Lethal Level 50%	2.16 mg/l
Polymeric Diamide	68911-25-1	Green algae	Experimental	72 hours	Effect Level 50%	0.43 mg/l
Polymeric Diamide	68911-25-1	Water flea	Experimental	48 hours	Effect Level 50%	0.57 mg/l
Polymeric Diamide	68911-25-1	Green algae	Experimental	72 hours	No obs Effect Level	0.28 mg/l
Butadiene Acrylonitrile Copolymer	68683-29-4		Data not available or insufficient for classification			
Silica, vitreous	60676-86-0	Common Carp	Experimental	72 hours	LC50	>10,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Golden Orfe	Experimental	96 hours	LC50	>1,000 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Green algae	Experimental	72 hours	EC50	>500 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Water flea	Experimental	48 hours	EC50	218.16 mg/l
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Green algae	Experimental	72 hours	Effect Concentration 10%	5.4 mg/l
Tris(2,4,6-Dimethylamino monomethyl)P henol	90-72-2	Common Carp	Experimental	96 hours	LC50	175 mg/l
Tris(2,4,6-Dimethylamino monomethyl)P henol	90-72-2	Grass Shrimp	Experimental	96 hours	LC50	718 mg/l
Tris(2,4,6-Dimethylamino monomethyl)P henol	90-72-2	Green algae	Experimental	72 hours	EC50	84 mg/l
Tris(2,4,6-Dimethylamino monomethyl)P	90-72-2	Green algae	Experimental	72 hours	NOEC	6.25 mg/l

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

henol						
Amine Epoxy Curing Agent	288-32-4	Green algae	Experimental	72 hours	EC50	133 mg/l
Amine Epoxy Curing Agent	288-32-4	Water flea	Experimental	48 hours	EC50	341.5 mg/l
Amine Epoxy Curing Agent	288-32-4	Green algae	Experimental	72 hours	NOEC	25 mg/l
Calcium Nitrate	10124-37-5	Guppy	Estimated	96 hours	LC50	1,378 mg/l
Calcium Nitrate	10124-37-5	Fathead minnow	Estimated	30 days	NOEC	58 mg/l
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7		Data not available or insufficient for classification			
Bis[(Dimethylamino)Methyl]Phenol	71074-89-0		Data not available or insufficient for classification			
N-Aminoethylpiperazine	140-31-8	Golden Orfe	Experimental	96 hours	LC50	368 mg/l
N-Aminoethylpiperazine	140-31-8	Green Algae	Experimental	72 hours	EC50	>1,000 mg/l
N-Aminoethylpiperazine	140-31-8	Water flea	Experimental	48 hours	EC50	58 mg/l
N-Aminoethylpiperazine	140-31-8	Green Algae	Experimental	72 hours	NOEC	31 mg/l
Toluene	108-88-3	Coho Salmon	Experimental	96 hours	LC50	5.5 mg/l
Toluene	108-88-3	Fish other	Experimental	96 hours	LC50	6.41 mg/l
Toluene	108-88-3	Green Algae	Experimental	72 hours	EC50	12.5 mg/l
Toluene	108-88-3	Water flea	Experimental	48 hours	EC50	3.78 mg/l
Toluene	108-88-3	Coho salmon	Experimental	40 days	NOEC	3.2 mg/l
Toluene	108-88-3	Water flea	Experimental	7 days	NOEC	0.74 mg/l

12.2. Persistence and degradability

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Polymeric Diamide	68911-25-1	Experimental Aquatic Biodegrad. - Aerobic	28 days	BOD	0 % BOD/ThBOD	OECD 301F - Manometric respirometry
Butadiene Acrylonitrile Copolymer	68683-29-4	Data not available - insufficient			N/A	
Silica, vitreous	60676-86-0	Data not available - insufficient			N/A	
Bis(3-Aminopropyl)	4246-51-9	Estimated Photolysis		Photolytic half-life (in air)	2.96 hours (t _{1/2})	Other methods

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

Ether of Diethylene Glycol						
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Experimental Biodegradation	25 days	CO2 evolution	-8 %CO2 evolution/THC O2 evolution	OECD 301B - Modified sturm or CO2
Tris(2,4,6-Dimethylamino monomethyl)P henol	90-72-2	Experimental Biodegradation	28 days	BOD	4 % weight	OECD 301D - Closed bottle test
Amine Epoxy Curing Agent	288-32-4	Experimental Biodegradation	18 days	Dissolv. Organic Carbon Deplet	98 % weight	OECD 301A - DOC Die Away Test
Calcium Nitrate	10124-37-5	Data not availbl- insufficient			N/A	
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not availbl- insufficient			N/A	
Bis[(Dimethylamino)Methyl]P henol	71074-89-0	Estimated Biodegradation	28 days	BOD	20 % weight	OECD 301C - MITI test (I)
N-Aminoethylpiperazine	140-31-8	Experimental Biodegradation	28 days	BOD	0 % BOD/ThBOD	OECD 301C - MITI test (I)
Toluene	108-88-3	Experimental Photolysis		Photolytic half-life (in air)	5.2 days (t 1/2)	Other methods
Toluene	108-88-3	Experimental Biodegradation	20 days	BOD	80 % weight	

12.3 : Bioaccumulative potential

Material	CAS Number	Test type	Duration	Study Type	Test result	Protocol
Polymeric Diamide	68911-25-1	Estimated Bioconcentration		Bioaccumulation factor	42	Other methods
Butadiene Acrylonitrile Copolymer	68683-29-4	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Silica, vitreous	60676-86-0	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis(3-Aminopropyl) Ether of Diethylene Glycol	4246-51-9	Experimental Bioconcentration		Log Kow	-1.25	Other methods
Tris(2,4,6-Dimethylamino	90-72-2	Experimental Bioconcentration		Log Kow	-0.66	Other methods

3M™ Panel Bonding (90 Minutes) Adhesive Part A (Accelerator) PN 08115, 38315, 58115

monomethylphenol		on				
Amine Epoxy Curing Agent	288-32-4	Experimental Bioconcentration		Log Kow	-0.08	Other methods
Calcium Nitrate	10124-37-5	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Dimethyl Siloxane, Reaction Product with Silica	67762-90-7	Data not available or insufficient for classification	N/A	N/A	N/A	N/A
Bis[(Dimethylamino)Methyl]phenol	71074-89-0	Estimated Bioconcentration		Log Kow	-2.34	Estimated: Octanol-water partition coefficient
N-Aminoethylpiperazine	140-31-8	Experimental Bioconcentration		Log Kow	0.3	Other methods
Toluene	108-88-3	Experimental Bioconcentration		Log Kow	2.73	Other methods

12.4. Mobility in soil

Please contact manufacturer for more details

12.5 Other adverse effects

No information available.

SECTION 13: Disposal considerations**13.1. Disposal methods**

In accordance with the Hazardous Substances (Disposal) Notice 2017 and the relevant criteria of the HSNO Act 1996.

Dispose of completely cured (or polymerized) material in a permitted industrial waste facility. As a disposal alternative, incinerate uncured product in a permitted waste incineration facility. Proper destruction may require the use of additional fuel during incineration processes. Empty drums/barrels/containers used for transporting and handling hazardous chemicals (chemical substances/mixtures/preparations classified as Hazardous as per applicable regulations) shall be considered, stored, treated & disposed of as hazardous wastes unless otherwise defined by applicable waste regulations. Consult with the respective regulating authorities to determine the available treatment and disposal facilities.

Packaging (that may or may not contain any residual substance) may be lawfully disposed of by householders or other consumers through public or commercial waste collection services.

SECTION 14: Transport Information**New Zealand Land Transport Rule: Dangerous Goods - Road/Rail Transport**

UN No.: UN3267

Proper Shipping Name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ((BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL , BIS((DIMETHYLAMINO)METHYL)PHENOL))

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: II

Special Instructions: Limited quantity may apply

Hazchem Code: 2X

IERG: 37

International Air Transport Association (IATA) - Air Transport

UN No.: UN3267

Proper Shipping Name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ((BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL , BIS((DIMETHYLAMINO)METHYL)PHENOL))

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: II

International Maritime Dangerous Goods Code (IMDG) - Marine Transport

UN No.: UN3267

Proper Shipping Name: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. , ((BIS(3-AMINOPROPYL) ETHER OF DIETHYLENE GLYCOL , BIS((DIMETHYLAMINO)METHYL)PHENOL))

Class/Division: 8

Sub Risk: Not applicable.

Packing Group: II

Marine Pollutant: Not applicable.

Special Instructions: Limited quantity may apply

SECTION 15: Regulatory information

HSNO Approval number HSR002658
Group standard name Surface Coatings and Colourants (Corrosive) Group Standard 2017
HSNO Hazard classification Refer to Section 2: Hazard identification

NZ Inventory of Chemicals (NZIoC) Status

All applicable chemical ingredients in this material are in compliance with NZIoC listing requirements.

Controls in accordance with the Health and Safety at Work (Hazardous Substances) Regulations 2017

Certified handler	Not required
Location Compliance Certificate	Not required
Hazardous atmosphere zone	Not required
Fire extinguishers	Not required
Emergency response plan	1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 8.2B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for all other substances)
Secondary containment	1,000 L or 1,000 kg (for a HSNO 6.1D, 6.5A, 6.5B, 8.2B, 9.1B or 9.1C substance); or 10,000 L or 10,000 kg (for all other substances)
Tracking	Not required
Warning signage	250 L or 250 kg (for a HSNO 8.2B substance); or 1,000 L or 1,000 kg (for all other substances)

SECTION 16: Other information

Revision information:

Complete document review.

Document group:	09-3599-9	Version number:	5.00
Issue Date:	13/09/2020	Supersedes date:	22/12/2016

Key to abbreviations and acronyms

GHS means the Globally Harmonised System of Classification and Labelling of Chemicals, 5th revised edition 2013

HSNO means Hazardous Substances and New Organisms Act 1996

The information in this Safety Data Sheet (SDS) is believed to be correct as of the date of issue. TO THE EXTENT PERMITTED BY LAW, 3M MAKES NO WARRANTY, EXPRESSED OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY, OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE OR COURSE OF PERFORMANCE OR USAGE OF TRADE. User is responsible for determining whether the 3M product is fit for a particular purpose and suitable for user's method of use or application. Given the variety of factors that can affect the use and application of a 3M product, some of which are uniquely within the user's knowledge and control, it is essential that the user evaluates the 3M product to determine whether it is fit for a particular purpose and suitable for user's method of use or application. 3M provides information in electronic form as a service to customers. Due to the remote possibility of electronic transfer may have resulted in errors, omissions or alterations in this information; 3M makes no representations as to its completeness or accuracy. In addition, information obtained from a database may not be as current as the information in the SDS available directly from 3M.

3M New Zealand SDS are available at 3M New Zealand Website: <http://solutions.3mnz.co.nz>