

Safety Data Sheet in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

1 Identification of the substance or mixture and of the supplier

· Product identifier**· Trade name:** BRUNOX® epoxy® - AEROSOL**· Relevant identified uses of the substance or mixture and uses advised against****· Sector of Use**

SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

SU21 Consumer uses: Private households / general public / consumers

SU22 Professional uses: Public domain (administration, education, entertainment, services, craftsmen)

· Product category

PC9a Coatings and paints, thinners, paint removers

PC14 Metal surface treatment products

· Process category

PROC5 Mixing or blending in batch processes

PROC7 Industrial spraying

PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

PROC9 Transfer of substance or mixture into small containers (dedicated filling line, including weighing)

PROC10 Roller application or brushing

PROC11 Non industrial spraying

PROC13 Treatment of articles by dipping and pouring

· Environmental release category

ERC8c Widespread use leading to inclusion into/onto article (indoor)

ERC8f Widespread use leading to inclusion into/onto article (outdoor)

· Application of the substance / the mixture Coating material**· Details of the supplier of the safety data sheet****· Manufacturer/Supplier:**

BRUNOX Korrosionsschutz GmbH

Adlzreiterstrasse 13, 85051 Ingolstadt

Postfach 100127, 85001 Ingolstadt

Tel. + 49/ (0) 841 961 29 04

Fax + 49/ (0) 841 961 29 13

E-mail: office@brunox.com

UFI info / E-mail: ufi@brunox.com

www.brunox.de

BRUNOX AG

Tunnelstrasse 6

CH - 8732 Neuhaus/SG

Tel. +41/ (0)55 285 80 80

Fax +41/ (0)55 285 80 81

E-mail: office@brunox.com

www.brunox.swiss

UFI info / E-mail: ufi@brunox.com

Distributor in New Zealand

Pacer Car Clean Products NZ LTD

33 Ha Crescent, Wiri, Auckland,
New Zealand

Telephone: +64 9 25000 91

Fax: +64 9 25000 92

Web: www.pacer.co.nz

24hr Emergency Assistance in New Zealand

National Poison Control Center: 0800 Poison [764 766]

(Contd. on page 2)

NZ

Safety Data Sheet
in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 1)

· Further information obtainable from:

Abteilung Produktsicherheit / Product Safety Department:

Tel. - Switzerland: +41/ (0)55 285 80 80

Tel. - Germany: +49 / (0)841 961 29 04

Mo - Do / Mon - Thu: 08:00 - 16:00 Uhr

Fr / Fri: 08:00 - 12:00 Uhr

· Emergency telephone number:

Toxikologisches Informationszentrum

CH - 8030 Zürich, Freiestrasse 16

Tel. +41/ 044 251 51 51

Notruf - CH, STIZ : 145

Notruf - D - : Giftnotrufzentrale 030 19240

Notruf - BE - : 070 -245 245

EUROPÄISCHE NOTRUFNR. : 112

Notruf - GB - : 844 892 0111

Notruf - IE - : + 353 1 837 9964 (medical professionals); + 353 1 809 2166 (public)

Notruf - IS - : + 354 543 22 22

Notruf - JP - : + 81 72 727 2499; + 81 29 852 9999

Notruf - NZ - : 0800 764 766

Notruf - PK - : + 92 21 9920509; + 92 21 35686535

Notruf - PH - : + 632 524 10 78; + 632 544 84 00; local 2311

Notruf - SA - : + 966 146 77 353, + 966 3 8155 646; Ext. 280, 282, 283

Notruf - TH - : + 66 201 1086

Notruf - UAE - : 800 424

Notruf - ZA - : + 27 824 910 160

2 Hazards identification**· Classification of the substance or mixture**

flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Skin Irrit. 2 H315 Causes skin irritation.

Eye Irrit. 2A H319 Causes serious eye irritation.

Acute Tox. 5 H333 May be harmful if inhaled.

· Classification according to Directive 67/548/EEC or Directive 1999/45/EC

Not applicable.

(Contd. on page 3)

NZ

Safety Data Sheet in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 2)



Xi; Irritant

R36: Irritating to eyes.



F+; Extremely flammable

R12: Extremely flammable.

R67: Vapours may cause drowsiness and dizziness.

Information concerning particular hazards for human and environment:

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurised container.

Classification system:

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

Label elements**GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

GHS02 GHS07

Signal word Danger**Hazard-determining components of labelling:**

formic acid

Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

Other hazards**Results of PBT and vPvB assessment****PBT:** Not applicable.

(Contd. on page 4)

NZ

Safety Data Sheet in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 3)

· **vPvB:** Not applicable.

3 Composition/Information on ingredients

· **Chemical characterisation: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous components:**

CAS: 115-10-6	dimethyl ether	25-50%
EINECS: 204-065-8	 F+ R12	
	 Press. Gas C, H280	
CAS: 67-64-1	acetone	10-25%
EINECS: 200-662-2	 Xi R36	
	 F R11	
	R66-67	
	 Flam. Liq. 2, H225	
	 Eye Irrit. 2, H319; STOT SE 3, H336	
	Acute Tox. 5, H333	
CAS: 107-98-2	1-methoxy-2-propanol	2.5-10%
EINECS: 203-539-1	R10-67	
	 Flam. Liq. 3, H226	
	 STOT SE 3, H336	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5-10%
EINECS: 203-603-9	R10	
	 Flam. Liq. 3, H226	
	Acute Tox. 5, H333	
CAS: 67-63-0	propan-2-ol	2.5-10%
EINECS: 200-661-7	 Xi R36	
	 F R11	
	R67	
	 Flam. Liq. 2, H225	
	 Eye Irrit. 2, H319; STOT SE 3, H336	
	Acute Tox. 5, H333	
CAS: 112-34-5	2-(2-butoxyethoxy)ethanol	2.5-10%
EINECS: 203-961-6	 Xi R36	
	 Eye Irrit. 2, H319	
	Acute Tox. 5, H313	
CAS: 64-18-6	formic acid	≤2%
EINECS: 200-579-1	 C R35	
	 Acute Tox. 3, H331	
	 Skin Corr. 1C, H314	
	 Acute Tox. 4, H302	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

NZ
(Contd. on page 5)

Safety Data Sheet **in accordance with HSNO**

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 4)

4 First aid measures

- **Description of first aid measures**
- **General information:**
 - Take affected persons out into the fresh air.
 - Do not leave affected persons unattended.
 - Position and transport stably in side position.
 - Seek medical treatment.
- **After inhalation:** Supply fresh air; consult doctor in case of complaints.
- **After skin contact:** Generally the product does not irritate the skin.
- **After eye contact:**
 - Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:**
 - Rinse out mouth and then drink plenty of water.
 - A person vomiting while laying on their back should be turned onto their side.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed**
 - Dizziness
 - Dizziness
- **Indication of any immediate medical attention and special treatment needed**
 - No further relevant information available.

5 Fire fighting measures

- **Extinguishing media**
- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Special hazards arising from the substance or mixture**
 - In case of fire, the following can be released:
 - Carbon monoxide (CO)
- **Advice for firefighters**
- **Protective equipment:**
 - Do not inhale explosion gases or combustion gases.
 - Wear self-contained respiratory protective device.
- **Additional information**
 - Cool endangered receptacles with water spray.
 - Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
 - Ensure adequate ventilation
 - Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**
 - Do not allow product to reach sewage system or any water course.

(Contd. on page 6)

NZ

Safety Data Sheet **in accordance with HSNO**

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 5)

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Send for recovery or disposal in suitable receptacles.

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Use only in well ventilated areas.

Ensure good interior ventilation, especially at floor level. (Fumes are heavier than air).

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Store away from foodstuffs.

· **Further information about storage conditions:**

Keep container tightly sealed.

Do not seal receptacle gas tight.

Store in cool, dry conditions in well sealed receptacles.

Protect from heat and direct sunlight.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Additional information about design of technical facilities:** No further data; see item 7.

(Contd. on page 7)

NZ

Safety Data Sheet **in accordance with HSNO**

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 6)

· Control parameters**· Ingredients with limit values that require monitoring at the workplace:****CAS: 115-10-6 dimethyl ether**

WES Short-term value: 958 mg/m³, 500 ppm
Long-term value: 766 mg/m³, 400 ppm

CAS: 67-64-1 acetone

WES Short-term value: 2375 mg/m³, 1000 ppm
Long-term value: 1185 mg/m³, 500 ppm
bio

CAS: 107-98-2 1-methoxy-2-propanol

WES Short-term value: 553 mg/m³, 150 ppm
Long-term value: 369 mg/m³, 100 ppm

CAS: 67-63-0 propan-2-ol

WES Short-term value: 1230 mg/m³, 500 ppm
Long-term value: 983 mg/m³, 400 ppm

CAS: 64-18-6 formic acid

WES Short-term value: 19 mg/m³, 10 ppm
Long-term value: 9.4 mg/m³, 5 ppm

· Additional information: The lists valid during the making were used as basis.**· Exposure controls****· Personal protective equipment:****· General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes.
Avoid contact with the eyes and skin.

· Respiratory protection:

Short term filter device:

Filter A/P2

Filter AX

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:

Check the permeability prior to each renewed use of the glove.



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

(Contd. on page 8)

NZ

Safety Data Sheet **in accordance with HSNO**

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 7)

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

Nitrile rubber, NBR

Butyl rubber, BR

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

Form:

Aerosol

Colour:

Amber coloured

· **Odour:**

Characteristic

· **Odour threshold:**

Not determined.

· **pH-value at 20 °C:**

4.8

· **Change in condition**

Melting point/freezing point:

Undetermined.

Initial boiling point and boiling range: 82 °C

· **Flash point:**

Not applicable, as aerosol.

· **Flammability (solid, gas):**

Not applicable.

· **Ignition temperature:**

235 °C

· **Decomposition temperature:**

Not determined.

· **Auto-ignition temperature:**

Product is not selfigniting.

· **Explosive properties:**

Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

(Contd. on page 9)

NZ

Safety Data Sheet in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 8)

- **Explosion limits:**
 - Lower:** 2.6 Vol %
 - Upper:** 18.6 Vol %
- **Vapour pressure at 20 °C:** 5,200 hPa
- **Density at 20 °C:** 1 g/cm³
- **Relative density** Not determined.
- **Vapour density** Not determined.
- **Evaporation rate** Not applicable.
- **Solubility in / Miscibility with water:** Not miscible or difficult to mix.
- **Partition coefficient: n-octanol/water:** Not determined.
- **Viscosity:**
 - Dynamic:** Not determined.
 - Kinematic:** Not determined.
- **Solvent content:**
 - Organic solvents:** 67.5 %
 - Water:** 16.4 %
 - VOC (EC)** 67.54 %
- **Solids content:** 1.5 %
- **Other information** No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**
 - ATE (Acute Toxicity Estimates)**
 - Oral LD50 61,315 mg/kg (rat)

(Contd. on page 10)

NZ

Safety Data Sheet
in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 9)

Dermal LD50 134,273 mg/kg (rabbit)

Inhalative LC50/4 h 39.6 mg/l

CAS: 67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 >15,800 mg/kg (rat)
20,000 mg/kg (rabbit)

Inhalative LC50/4 h 76 mg/l (rat)

CAS: 107-98-2 1-methoxy-2-propanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 13,000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

CAS: 108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

Dermal LD50 >5,000 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

CAS: 67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)

Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

CAS: 112-34-5 2-(2-butoxyethoxy)ethanol

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 4,000 mg/kg (rabbit)

CAS: 64-18-6 formic acid

Oral LD50 1,100 mg/kg (rat)

Inhalative LC50/4 h 3 mg/l (ATE)

· Primary irritant effect:**· Skin corrosion/irritation**

Bei längeren und/oder häufigem Hautkontakt sind Reizerscheinungen möglich.

Prolonged skin contact will result in defatting of the skin, leading to irritation, and in some cases, dermatitis.

· Serious eye damage/irritation Irritating effect.**· Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

NZ

(Contd. on page 11)

Safety Data Sheet **in accordance with HSNO**

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 10)

12 Ecological information

- **Toxicity**
- **Aquatic toxicity:**
 - CAS: 115-10-6 dimethyl ether**
 - EC50 154.92 mg/kg (algae) (QSAR)
 - >4,400 mg/kg (daphnia)
 - LC50/96 h >4,100 mg/l (fish)
 - EC10 >1,600 mg/l (pseudomonas putida)
 - CAS: 67-64-1 acetone**
 - LC50/48 h 8,800 mg/l (daphnia)
 - CAS: 107-98-2 1-methoxy-2-propanol**
 - EC50 >500 mg/kg (daphnia)
 - LC50/96 h 4,600-10,000 mg/l (leuciscus idus)
 - CAS: 108-65-6 2-methoxy-1-methylethyl acetate**
 - EC50 >500 mg/kg (daphnia)
 - LC50/96 h 160 mg/l (pimephales promelas)
 - CAS: 64-18-6 formic acid**
 - EC50 120 mg/kg (daphnia)
 - LC50/48 h 122 mg/l (leuciscus idus)
- **Persistence and degradability** No further relevant information available.
- **Behaviour in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:**
 - Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water
 - Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

13 Disposal considerations

- **Waste treatment methods**
- **Recommendation**
 - Must not be disposed together with household garbage. Do not allow product to reach sewage system.

(Contd. on page 12)

NZ

Safety Data Sheet
in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 11)

· Uncleaned packaging:**· Recommendation:**

Empty contaminated packagings thoroughly. They may be recycled after thorough and proper cleaning.

14 Transport information**· UN-Number****· ADR/RID/ADN, IMDG, IATA**

UN1950

· UN proper shipping name**· ADR/RID/ADN**

1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

· Transport hazard class(es)**· ADR/RID/ADN****· Class**

2 5F Gases.

· Label

2.1

· IMDG, IATA**· Class**

2.1

· Label

2.1

· Packing group**· ADR/RID/ADN, IMDG, IATA**

Void

· Environmental hazards:**· Marine pollutant:**

No

· Special precautions for user

Warning: Gases.

· Hazard identification number (Kemler code): -**· EMS Number:**

F-D,S-U

· Stowage CodeSW1 Protected from sources of heat.
SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For AEROSOLS with a capacity above 1 litre: Category B. For WASTE AEROSOLS: Category C, Clear of living quarters.
SG69 For AEROSOLS with a maximum capacity of 1 litre:**· Segregation Code**

(Contd. on page 13)

NZ

Safety Data Sheet in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 12)

- Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
For AEROSOLS with a capacity above 1 litre:
Segregation as for the appropriate subdivision of class 2.
For WASTE AEROSOLS:
Segregation as for the appropriate subdivision of class 2.
- Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.
- Transport/Additional information:
- ADR/RID/ADN
- Limited quantities (LQ) 1L
- Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
- Transport category 2
- Tunnel restriction code D
- IMDG
- Limited quantities (LQ) 1L
- Excepted quantities (EQ) Code: E0
Not permitted as Excepted Quantity
- UN "Model Regulation": UN 1950 AEROSOLS, 2.1

*

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture
- New Zealand Inventory of Chemicals
CAS: 115-10-6 dimethyl ether
CAS: 7732-18-5 water, distilled, conductivity or of similar purity
CAS: 67-64-1 acetone
CAS: 107-98-2 1-methoxy-2-propanol
CAS: 108-65-6 2-methoxy-1-methylethyl acetate
CAS: 67-63-0 propan-2-ol
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol
CAS: 64-18-6 formic acid
CAS: 1401-55-4 Tannins
- HSNO Approval numbers
CAS: 115-10-6 dimethyl ether
CAS: 67-64-1 acetone

HSR000995

HSR001070

(Contd. on page 14)

NZ

Safety Data Sheet in accordance with HSNO

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 13)

CAS: 107-98-2 1-methoxy-2-propanol	HSR001187
CAS: 108-65-6 2-methoxy-1-methylethyl acetate	HSR001219
CAS: 67-63-0 propan-2-ol	HSR001180
CAS: 112-34-5 2-(2-butoxyethoxy)ethanol	HSR001075
CAS: 64-18-6 formic acid	HSR000979

· **GHS label elements**

The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02 GHS07

· **Signal word** Danger

· **Hazard-determining components of labelling:**

formic acid

· **Hazard statements**

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

· **Precautionary statements**

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P103 Read label before use.

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.

P251 Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

· **Directive 2012/18/EU**

· **Named dangerous substances - ANNEX I** None of the ingredients is listed.

· **Seveso category** P3a FLAMMABLE AEROSOLS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t

· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

· **Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

NEW ZEALAND:

Class 2.1.2A Aerosols Flammable

Class 6.3A Skin Irritant

Class 6.4A Eye Irritant

Class 6.1E Inhalation Hazard

HSR002515 Aerosols (Flammable)

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H225 Highly flammable liquid and vapour.

(Contd. on page 15)

NZ

Safety Data Sheet **in accordance with HSNO**

Printing date 26.02.2021

Version number 7

Revision: 23.02.2021

Trade name: BRUNOX® epoxy® - AEROSOL

(Contd. of page 14)

H226 Flammable liquid and vapour.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H313 May be harmful in contact with skin.
H314 Causes severe skin burns and eye damage.
H319 Causes serious eye irritation.
H331 Toxic if inhaled.
H333 May be harmful if inhaled.
H336 May cause drowsiness or dizziness.

R10 Flammable.
R11 Highly flammable.
R12 Extremely flammable.
R35 Causes severe burns.
R36 Irritating to eyes.
R66 Repeated exposure may cause skin dryness or cracking.
R67 Vapours may cause drowsiness and dizziness.

• Contact:**• Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Aerosol 1: Aerosols – Category 1
Press. Gas C: Gases under pressure – Compressed gas
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Acute Tox. 4: Acute toxicity – Category 4
Acute Tox. 3: Acute toxicity – Category 3
Acute Tox. 5: Acute toxicity – Category 5
Skin Corr. 1C: Skin corrosion/irritation – Category 1C
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2: Serious eye damage/eye irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

• * Data compared to the previous version altered.

NZ