

**1 Identification of the substance or mixture and of the supplier****Other means of identification**Trade name: **696 AIR DRY CLEAR HS SR 2:1**

Article number: W028

Relevant identified uses of the substance or mixture and uses advised against

Product category PC9a Coatings and paints, thinners, paint removers

Application of the substance / the mixture Surface protection

**Details of the supplier of the safety data sheet**

Manufacturer/Supplier:

HB BODY S.A.

B' ENTRANCE BLOCK 50 DA9 &amp; MB6 Str

THESSALONIKI INDUSTRIAL AREA

57.022, SINDOS

THESSALONIKI, GREECE

Ph: +30 2310 790 000

Fax: +30 2310 790 033

www.hbbody.com

email: hbbody@hbbody.com

Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

**2 Hazards identification****Classification of the substance or mixture**

GHS02 flame

Flammable liquids Category 3

H226 Flammable liquid and vapour.



GHS08 health hazard

Carcinogenicity – Category 2

H351 Suspected of causing cancer.

Reproductive toxicity Category 1

H360 May damage fertility or the unborn child.



GHS07

Eye irritation Category 2

H319 Causes serious eye irritation.

Specific target organ toxicity - single exposure Category 3 H336 May cause drowsiness or dizziness.

Additional information:

3.1B Flammable liquid

3.1C Flammable liquid

8.3A Substances that are corrosive to ocular tissue

6.9 (Narcotic) Substances that are harmful to human target organs or systems

6.4A Substances that are irritating to the eye

## Trade name: 696 AIR DRY CLEAR HS SR 2:1

6.8B Substances that are suspected human reproductive or developmental toxicants

### Label elements

- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- Hazard pictograms



GHS02 GHS07 GHS08

- Signal word Danger
- Hazard-determining components of labelling:
  - n-butyl ester
  - 4-methylpentan-2-one
  - dibutyltin dilaurate
  - acetone
  - butanone
- Hazard statements
  - H226 Flammable liquid and vapour.
  - H319 Causes serious eye irritation.
  - H351 Suspected of causing cancer.
  - H360 May damage fertility or the unborn child.
  - H336 May cause drowsiness or dizziness.
- Precautionary statements
  - P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
  - P241 Use explosion-proof [electrical/ventilating/lighting] equipment.
  - P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].
  - P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
  - P405 Store locked up.
  - P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- Other hazards
- Results of PBT and vPvB assessment
  - This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT). This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- PBT: Not applicable.
- vPvB: Not applicable.

## 3 Composition/Information on ingredients
















### Chemical characterisation: Mixtures

- Description: Mixture of hazardous substances listed below with nonhazardous additions.
- Dangerous components:

CAS: 123-86-4	n-butyl ester	≥25-<45%
EINECS: 204-658-1	Flammable liquids Category 3, H226	
Index number: 607-025-00-1	Specific target organ toxicity - single exposure Category 3, H336	
RTECS: AF 7350000		
CAS: 1330-20-7	xylene	5-<10%
Index number: 601-022-00-9	Flammable liquids Category 3, H226	
	Acute dermal toxicity Category 4, H312; Acute inhalation toxicity Category 4, H332; Skin irritation Category 2, H315	
CAS: 67-64-1	acetone	5-<10%
EINECS: 200-662-2	Flammable liquids Category 2, H225	
Index number: 606-001-00-8	Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H336	
RTECS: AL 3150000		

Continue on page 3  
NZ

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

CAS: 108-10-1	4-methylpentan-2-one	5-<10%
EINECS: 203-550-1	 Flammable liquids Category 2, H225	
Index number: 606-004-00-4	 Carcinogenicity – Category 2, H351	
RTECS: SA 9275000	 Acute inhalation toxicity Category 4, H332; Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H336	
CAS: 78-93-3	butanone	≥0-<5%
EINECS: 201-159-0	 Flammable liquids Category 2, H225	
Index number: 606-002-00-3	 Eye irritation Category 2, H319; Specific target organ toxicity - single exposure Category 3, H336	
RTECS: EL 6475000		
CAS: 64-19-7	acetic acid	≥0-<5%
EINECS: 200-580-7	 Flammable liquids Category 3, H226	
Index number: 607-002-00-6	 Skin corrosion Category 1A, H314	
RTECS: AF 1225000	 Acute dermal toxicity Category 4, H312	
	Specific concentration limits: Skin corrosion Category 1A; H314: C ≥ 90 %	
	Skin corrosion Category 1B; H314: 25 % ≤ C < 90 %	
	Skin irritation Category 2; H315: 10 % ≤ C < 25 %	
	Eye irritation Category 2; H319: 10 % ≤ C < 25 %	
CAS: 41556-26-7	bis(1,2,2,6,6-pentamethyl-4-piperidyl)sebacate	≥0.1-<0.25%
EINECS: 255-437-1	 Hazardous to the aquatic environment acute Category 1, H400 (M=1); Hazardous to the aquatic environment chronic Category 1, H410 (M=1)	
	 Skin sensitisation Category 1, H317	
CAS: 77-58-7	dibutyltin dilaurate	≥0-<0.3%
EINECS: 201-039-8	 Acute oral toxicity Category 3, H301	
Index number: 050-030-00-3	 Germ cell mutagenicity Category 2, H341; Reproductive toxicity Category 1, H360; Specific target organ toxicity - repeated exposure Category 1, H372	
RTECS: WH 7000000		
CAS: 97-86-9	isobutyl methacrylate	≥0.1-<0.25%
EINECS: 202-613-0	 Flammable liquids Category 3, H226	
Index number: 607-113-00-X	 Hazardous to the aquatic environment acute Category 1, H400 (M=1)	
RTECS: OZ 4900000	 Skin irritation Category 2, H315; Eye irritation Category 2, H319; Skin sensitisation Category 1, H317; Specific target organ toxicity - single exposure Category 3, H335	

· Additional information: For the wording of the listed hazard phrases refer to section 16.

**4 First aid measures**· **Description of first aid measures**

· General information: Immediately remove any clothing soiled by the product.

· After inhalation: Supply fresh air; consult doctor in case of complaints.

· After skin contact: Immediately rinse with water.

· After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor. Remove contact lenses in case of eye contamination and irrigate copiously with clean water for at least 15 minutes trying to hold the eye lids open.

· After swallowing: If symptoms persist consult doctor.

· Information for doctor:

· Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed

No further relevant information available.

NZ

Continue on page 4

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

\* **5 Fire fighting measures**

· **Extinguishing media**

· Suitable extinguishing agents:

CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· For safety reasons unsuitable extinguishing agents: Water with full jet

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

· Special protective equipment and fire fighting procedures: No special measures required.

· **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

HAZ CHEM CODE: 3YE

\* **6 Accidental release measures**

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:** Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

**7 Handling and storage**

· **Handling:**

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· Storage:

· Requirements to be met by storerooms and receptacles: No special requirements.

· Information about storage in one common storage facility: Not required.

· Further information about storage conditions: Keep container tightly sealed.

· **Specific end use(s)** No further relevant information available.

**8 Exposure controls/personal protection**

· **Control parameters**

· Ingredients with limit values that require monitoring at the workplace:

**123-86-4 n-butyl ester**

WES (New Zealand) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm

Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

IOELV (EU) Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

**1330-20-7 xylene**

WES (New Zealand) Long-term value: 217 mg/m<sup>3</sup>, 50 ppm  
oto, bio

IOELV (EU) Short-term value: 442 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 221 mg/m<sup>3</sup>, 50 ppm  
Skin

**67-64-1 acetone**

WES (New Zealand) Short-term value: 2375 mg/m<sup>3</sup>, 1000 ppm  
Long-term value: 1185 mg/m<sup>3</sup>, 500 ppm  
bio

IOELV (EU) Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm

**108-10-1 4-methylpentan-2-one**

WES (New Zealand) Short-term value: 307 mg/m<sup>3</sup>, 75 ppm  
Long-term value: 205 mg/m<sup>3</sup>, 50 ppm

IOELV (EU) Short-term value: 208 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 83 mg/m<sup>3</sup>, 20 ppm

**78-93-3 butanone**

WES (New Zealand) Short-term value: 890 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 445 mg/m<sup>3</sup>, 150 ppm  
bio

IOELV (EU) Short-term value: 900 mg/m<sup>3</sup>, 300 ppm  
Long-term value: 600 mg/m<sup>3</sup>, 200 ppm

**64-19-7 acetic acid**

WES (New Zealand) Short-term value: 37 mg/m<sup>3</sup>, 15 ppm  
Long-term value: 25 mg/m<sup>3</sup>, 10 ppm

IOELV (EU) Short-term value: 50 mg/m<sup>3</sup>, 20 ppm  
Long-term value: 25 mg/m<sup>3</sup>, 10 ppm

**77-58-7 dibutyltin dilaurate**

WES (New Zealand) Short-term value: 0.1 0.02\* mg/m<sup>3</sup>  
Long-term value: 0.05 mg/m<sup>3</sup>  
\* if irritant; as Sn; skin

· **Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

· Additional information: The lists valid during the making were used as basis.

· **Exposure controls**

· Personal protective equipment:

· General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

- The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.  
Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.  
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation
- Material of gloves  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.
  - Penetration time of glove material  
The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.
  - For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
  - For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:  
Rubber gloves
  - Eye protection:



Tightly sealed goggles

- Body protection: Protective work clothing

**9 Physical and chemical properties**

**Information on basic physical and chemical properties**

- General Information
- Appearance:
- Form: Liquid
- Colour: Clear
- Odour: Characteristic
- Odour threshold: Not determined.
- pH-value: Mixture is non-soluble (in water).
- Change in condition
- Melting point/freezing point: Undetermined.
- Initial boiling point and boiling range: 55.8-56.6 °C
- Flash point: 23 - 60 °C
- Flammability: Flammable.
- Autoignition temperature: 370 °C
- Decomposition temperature: Not determined.
- Ignition temperature: Product is not selfigniting.
- Explosive properties: Risk of explosion by shock, friction, fire or other sources of ignition.
- Explosion limits:
- Lower: 1.2 Vol %
- Upper: 7.5 Vol %
- Vapour pressure at 20 °C: 10.7 hPa
- **Vapour pressure at 50 °C:** 55 hPa
- Density at 20 °C: >0.68396-<1.46504 g/cm<sup>3</sup>
- Bulk density: 1 kg/m<sup>3</sup>
- Relative density: Not determined.
- Vapour density: Not determined.
- Evaporation rate: Not determined.
- Solubility in / Miscibility with
- water: Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water: Not determined.

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

- Viscosity:
- Dynamic at 40 °C: >14-<37 mPas
- Kinematic at 40 °C: 20-25 mm²/s
- Solvent content:
- Organic solvents: 46.4-<62.9 %
- VOC (EC) >317.6-<921.2 g/l
- Solids content (volume): >37.1-53.6 %
- **Other information**
- Particle characteristics Not applicable.
- Physical state Liquid

**10 Stability and reactivity**

- **Reactivity** No further relevant information available.
- **Chemical stability**
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

**11 Toxicological information**· **Information on toxicological effects**

- Acute toxicity
- LD/LC50 values relevant for classification:

**ATE (Acute Toxicity Estimates)**

Oral LD50 >128,676 mg/kg (rat)  
 Dermal LD50 >25,113-30,277 mg/kg (rabbit)  
 Inhalative LC50/4 h 89.2-122 mg/l

**123-86-4 n-butyl ester**

Oral LD50 13,100 mg/kg (rat)  
 Dermal LD50 >5,000 mg/kg (rabbit)  
 Inhalative LC50/4 h >21 mg/l (rat)

**1330-20-7 xylene**

Oral LD50 4,300 mg/kg (rat)  
 Dermal LD50 2,000 mg/kg (rabbit)  
 Inhalative LC50/4 h 11 mg/l (ATE)

**67-64-1 acetone**

Oral LD50 5,800 mg/kg (rat)  
 Dermal LD50 20,000 mg/kg (rabbit)

**108-10-1 4-methylpentan-2-one**

Oral LD50 2,080 mg/kg (rat)  
 Dermal LD50 16,000 mg/kg (rab)  
 Inhalative LC50/4 h 11 mg/l (ATE)  
 8.3-16.6 mg/l (rat)

**78-93-3 butanone**

Oral LD50 3,300 mg/kg (rat)  
 Dermal LD50 5,000 mg/kg (rabbit)



**Trade name: 696 AIR DRY CLEAR HS SR 2:1****64-19-7 acetic acid**

Oral LD50 3,310 mg/kg (rat)  
Dermal LD50 1,060 mg/kg (rabbit)

**77-58-7 dibutyltin dilaurate**

Oral LD50 175 mg/kg (rat)

**97-86-9 isobutyl methacrylate**

Oral LD50 11,990 mg/kg (mouse)

- Primary irritant effect:
- Skin corrosion/irritation No irritant effect.
- Serious eye damage/irritation Irritating effect.
- Respiratory or skin sensitisation Sensitising effect through inhalation is possible by prolonged exposure.

**· Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

- CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)  
Carcinogenicity – Category 2, Reproductive toxicity Category 1

**\* 12 Ecological information****· Toxicity****· Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**· Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

**· Behaviour in environmental systems:**

- Bioaccumulative potential No further relevant information available.
- Mobility in soil No further relevant information available.

**· Additional ecological information:****· General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

**· Results of PBT and vPvB assessment**

- PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- vPvB: Not applicable.

**· Other adverse effects No further relevant information available.****13 Disposal considerations****· Waste treatment methods****· Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

**· Uncleaned packaging:**

- Recommendation: Disposal must be made according to official regulations.

**14 Transport information****· UN-Number**

· NZS, IMDG, IATA

UN1263

Continue on page 9  
NZ



**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

· **UN proper shipping name**

· NZS UN1263 PAINT  
· IMDG, IATA PAINT

· **Transport hazard class(es)**

· NZS



· Class 3 (F1) Flammable liquids.  
· Label 3  
· IMDG, IATA



· Class 3 Flammable liquids.  
· Label 3

· **Packing group**

· NZS, IMDG, IATA III

· **Environmental hazards:**

Not applicable.

· **Special precautions for user**

Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E

· Stowage Category A

· **Transport in bulk according to Annex II of Marpol and the IBC Code**

Not applicable.

· **Transport/Additional information:**

· NZS

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· Transport category 3

· Tunnel restriction code D/E

· IMDG

· Limited quantities (LQ) 5L

· Excepted quantities (EQ) Code: E1

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 1000 ml

· IATA

· Remarks:

HAZ CHEM CODE: 3YE

· **UN "Model Regulation":** UN 1263 PAINT, 3, III

\* **15 Regulatory information**

· 3Y

· **Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

Continue on page 10  
NZ

## Trade name: 696 AIR DRY CLEAR HS SR 2:1

### · New Zealand Inventory of Chemicals

All ingredients are listed.

### · HSNO Approval numbers

HSNO Approval number HSR 002662  
Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006  
HSNO Hazard classification Refer to section 2

123-86-4 n-butyl ester: HSR001091

1330-20-7 xylene: HSR000983

67-64-1 acetone: HSR001070

108-10-1 4-methylpentan-2-one: HSR001194

78-93-3 butanone: HSR001190

77-58-7 dibutyltin dilaurate: HSR003610

97-86-9 isobutyl methacrylate: HSR001173

### · GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

### · Hazard pictograms



GHS02 GHS07 GHS08

### · Signal word Danger

### · Hazard-determining components of labelling:

n-butyl ester  
4-methylpentan-2-one  
dibutyltin dilaurate  
acetone  
butanone

### · Hazard statements

H226 Flammable liquid and vapour.  
H319 Causes serious eye irritation.  
H351 Suspected of causing cancer.  
H360 May damage fertility or the unborn child.  
H336 May cause drowsiness or dizziness.

### · Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P241 Use explosion-proof [electrical/ventilating/lighting] equipment.  
P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

### · Directive 2012/18/EU

### · Named dangerous substances - ANNEX I None of the ingredients is listed.

### · Seveso category P5c FLAMMABLE LIQUIDS

### · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t

### · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t

### · **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

## 16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**· **Reasons for alterations**· **Relevant phrases**

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H301 Toxic if swallowed.

H312 Harmful in contact with skin.

H314 Causes severe skin burns and eye damage.

H315 Causes skin irritation.

H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H332 Harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H341 Suspected of causing genetic defects.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H372 Causes damage to organs through prolonged or repeated exposure.

H400 Very toxic to aquatic life.

H410 Very toxic to aquatic life with long lasting effects.

· **Contact:**

HB BODY S.A

Regulatory Officer

Ms Athina Kapourani

Ph: +30 2310 790000

email: a.kapourani@hbbody.com

· **\* Data compared to the previous version altered.**

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

**Annex: Exposure scenario**

**Short title of the exposure scenario**

Product category PC9a Coatings and paints, thinners, paint removers

**Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

**Conditions of use** According to directions for use.

Duration and frequency Frequency of use:

**Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

Physical state Fluid

Concentration of the substance in the mixture The substance is main component.

**Other operational conditions**

Other operational conditions affecting environmental exposure No special measures required.

Other operational conditions affecting worker exposure

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Other operational conditions affecting consumer exposure No special measures required.

Other operational conditions affecting consumer exposure during the use of the product  
Not applicable.

**Risk management measures**

Worker protection

Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaust or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the eyes.

Tightly sealed goggles

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Environmental protection measures

Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Soil The product is only processed over the concrete collecting basin.

**Disposal measures** Ensure that waste is collected and contained.

Disposal procedures

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Waste type Partially emptied and uncleaned packaging

**Trade name: 696 AIR DRY CLEAR HS SR 2:1**

· **Exposure estimation**

· **Consumer**

This product is to be used by professional technicians only.

Not relevant for this Exposure Scenario.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ