

# Safety Data Sheet (SDS)

According to GHS (Global Harmonized System) - Hazcom 2012

Date Printed (YYYY-MM-DD): 2023-04-20

## Section 1 - Product and Company Information

**Product Name:** Low-VOC Plastic Magic

**Product Part Number(s):** 1051-4, 1051-1, 1051-4

**Recommended Use:** A surface modifier that eliminates the paint peeling problems on automotive plastics.

**COMPANY IDENTIFICATION:**

Polyvance  
1128 Kirk Rd., Rainsville, Alabama, USA  
+1-256-638-4103

**NZ DISTRIBUTOR:**

Wyatt Machine Tools Rupes (NZ) Limited  
388 Church Street, Penrose, Auckland,  
New Zealand

**Information email:** info@wyatt.co.nz

**EMERGENCY TELEPHONE NUMBER:**

**24 Hour Emergency contact:** 0800 992 881  
(0800WYATT1)

**Customer Information Number:** 0800 992 881  
(0800WYATT1)

## Section 2 - Hazards Identification

**Appearance:** Clear liquid

**Odor:** Characteristic

**Hazard Statement:**

WARNING! Extremely flammable liquid and vapor. May cause an allergic skin reaction. Causes eye irritation.

**Signal Word:** WARNING!

**Signal Word Hazard:** Flammable Liquid

GHS Physical Hazard Pictogram	GHS Health Hazard Pictogram(s)	GHS Environmental Hazard Pictogram
 Flammable	 Irritant	 Environmentally Damaging

### GHS Hazards Statement Codes for This Product

Statement Type	Statement Code	Statement Text
Physical	H224	Extremely flammable liquid and vapor
Health	H317	May cause an allergic skin reaction
Health	H320	Causes eye irritation

**Precautionary Statement:**

Keep out of reach of children. Read label before use. Keep away from heat/sparks/open flames/hot surfaces - No smoking. Pressurized container - Do not pierce or burn, even after use. Store in a well ventilated place. Keep container tightly closed. Protect from sunlight. Store in a well ventilated place.

### GHS Precautionary Statement Codes for This Product

Statement Type	Statement Code	Statement Text
General	P102	Keep out of reach of children

General	P103	Read label before use
Prevention	P210	Keep away from heat/sparks/open flames/hot surfaces - No smoking
Prevention	P251	Pressurized container - Do not pierce or burn, even after use
Storage	P403+233	Store in a well ventilated place. Keep container tightly closed
Storage	P410+403	Protect from sunlight. Store in a well ventilated place

## Potential Health Effects

<b>Eye Contact:</b>	Nasal and respiratory irritation, dizziness, headache, nausea, possible unconsciousness, and asphyxiation.
<b>Skin Absorption:</b>	Moderate irritation, redness, blurred vision.
<b>Inhalation:</b>	Dizziness, breathing difficulty, headaches, and loss of coordination.
<b>Ingestion:</b>	Gastrointestinal irritation, vomiting, diarrhea.

## Section 3 - Composition / Information on Ingredients

Component	CAS #	ENIECS	REACH Reg. No.	Amount
Xylene	1330-20-7			7 - 8%
Ethyl Benzene	100-41-4			0-5%
Acetone	67-64-1			30 - 35%
Dibutyl Phthalate	87-74-2			0-5%
Tertiary Butyl Acetate	540-88-5			49 - 50%

## Section 4 - First Aid Measures

<b>Eye Contact:</b>	Immediately flush eyes with excess water for 15 minutes, lifting lower and upper eyelids occasionally.
<b>Skin Contact:</b>	Immediately flush skin with excess water for 15 minutes removing contaminated clothing.
<b>Inhalation:</b>	Remove to fresh air. If not breathing, give artificial respiration.
<b>Ingestion:</b>	Call Poison Control immediately. Aspiration hazard. Rinse mouth with cold water. Give victim 1-2 tbsps of activated charcoal mixed with 8 oz. of water.
<b>Medical Conditions Aggravated by Exposure:</b>	Bronchitis, CNS disorders, allergies, nausea.

## Section 5 - Firefighting Measures

<b>Extinguishing Media:</b>	Foam, dry chemical, water fog
<b>Unusual Fire or Explosion Hazards:</b>	Handle as a flammable liquid. Vapors form an explosive mixture in air between the lower and upper explosive limits which can be ignited by many sources such as pilot lights, open flames, electric motors and switches.
<b>Fire Fighting Procedures:</b>	Respiratory equipment should be worn to avoid inhalation of concentrated vapors. Water should not be used except as a fog to keep nearby containers cool.

## Section 6 - Accidental Release Measures

<b>Personal Precautions:</b>	Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel. Remove all ignition sources and ventilate area.
<b>Methods For Clean Up:</b>	Remove all sources of ignition. Allow volatile portion to evaporate completely. Avoid breathing

vapors and remove with inert absorbent.

**Methods for Containment:** Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do not contaminate lakes, streams or other water supply.

## Section 7 - Handling and Storage

**General Handling Practices:** Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal. Avoid spontaneous combustion of contaminated rags or other ignitable material. Keep out of reach of children.

**Handling Precautions:** Use with adequate ventilation and do not breathe dust or vapor. Avoid contact with skin, eyes, or clothing. Wash hands thoroughly after handling.

**Storage Requirements:** Do not store near heat, sparks or flame. Store in well ventilated area. Keep closure tight and container upright to prevent leakage. Do not puncture or incinerate. Do not spray near fire or open flames.

## Section 8 - Precautions to Control Exposure / Personal Protection

Component	Source	Type	Value	Remarks
Acetone	NIOSH	TWA	2500 ppm	IDLH
Acetone	ACGIH	TWA	500 ppm	
Acetone	ACGIH	STEL	750 ppm	
Acetone	NIOSH	TWA	590 mg/m3	
Acetone	OSHA	TWA	1000 ppm	
Acetone	OSHA	TWA	2400 mg/m3	
Acetone	NIOSH	TWA	250 ppm	
Dibutyl Phthalate	ACGIH	TWA	5 mg/m3	
Dibutyl Phthalate	OSHA	PEL	5 mg/m3	8 hour
Ethyl Benzene	OSHA	TWA	100 ppm	
Ethyl Benzene	ACGIH	TWA	100 ppm	
Ethyl Benzene	ACGIH	STEL	125 ppm	
Ethyl Benzene	NIOSH	TWA	435 mg/m3	
Ethyl Benzene	NIOSH	TWA	800 ppm	IDLH
Ethyl Benzene	OSHA	TWA	435 mg/m3	
Tertiary Butyl Acetate	NIOSH	TWA	1500 ppm	IDLH
Tertiary Butyl Acetate	NIOSH	TWA	950 mg/m3	
Tertiary Butyl Acetate	OSHA	TWA	950 mg/m3	
Tertiary Butyl Acetate	NIOSH	TWA	200 ppm	
Tertiary Butyl Acetate	ACGIH	TWA	200 ppm	
Tertiary Butyl Acetate	OSHA	TWA	200 ppm	
Xylene	ACGIH	TWA	100 ppm	
Xylene	ACGIH	STEL	150 ppm	

### Personal Protective Equipment (PPE):

**Eye / Face Protection:** Goggles or side-shielded safety glasses.

**Skin Protection:** Neoprene or butyl rubber gloves.

**Respiratory Protection:** Use of a NIOSH approved chemical/mechanical filter, designed to remove a combination of particles and vapors.

**Hygienic Measures:** Wash hands before eating, smoking or using the washroom.

**Other Protection** To prevent repeated or prolonged skin contact, wear impervious clothing and boots. Wash

**Measures:** contaminated clothing before reuse.

**Engineering Controls:** Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below TLV(s)

**HMIS Personal Protection:** G



Safety Glasses



Gloves



Vapor Respirator

---

## Section 9 - Physical and Chemical Properties

---

**Appearance:** Liquid

**Color:** Clear, colorless liquid.

**Odor:** Mild odor.

**Odor Threshold:** Mild Odor

**pH:** Not determined

**Melting Point:** Not available

**Freezing Point:** Not available

**Boiling Point:** 180.0

**Boiling Range:** Not available

**Flash Point:** 7 C (45 F)

**Evaporation Rate:** Greater than n-Butyl Acetate

**Flammability:** Flammable in the presence of heat, open flames, sparks, and static discharge.

**Upper Flammability Limit:** Not available

**Lower Flammability Limit:** Not available

**Vapor Pressure:** Not available

**Vapor Density:** Not available

**Specific Gravity:** 0.84

**Solubility in Water:** Not available

**Partition Coefficient:** Not available

**Autoignition Temperature:** Not available

**Decomposition Temperature:** Not available

**Viscosity:** Not available

**Percent Volatiles:** 95 - 97%

**Volatile Organic Compounds (VOC's):** 3.65 lb./gal (439 g/l)

---

## Section 10 - Stability and Reactivity

---

**Chemical Stability:** Stable

**Conditions to Avoid:** Excessive heat, poor ventilation, open flames, sources of sparks.

**Incompatible Materials:** Alkaline materials, strong acids, and oxidizing materials.

**Hazardous Decomposition Products:** Carbon monoxide, carbon dioxide, various hydrocarbons, oxides of nitrogen, chlorine and possibly acrolein.

**Hazardous Polymerization:** Will Not Occur

---

## Section 11 - Toxicological Information

---

**Ingestion Toxicity:** Not determined  
**Skin Absorption:** Not determined  
**Inhalation:** Not determined  
**Sensitization:** Not determined  
**Acute Dose:** Not determined  
**Repeated Dose:** Not determined  
**Carcinogenicity:** Not determined  
**Corrosivity:** Not determined  
**Neurological:** Not determined  
**Reproductive:** Not determined  
**Genetic:** Not determined  
**Developmental:** Not determined  
**Eye Irritation:** Not determined  
**Skin Irritation:** Not determined  
**Target Organs:** Not determined

---

## Section 12 - Ecological Information

---

**EcoToxicity:** Toxic to terrestrial and aquatic plants and animals. Do not release to the environment.

---

## Section 13 - Disposal Considerations

---

**Disposal Method:** Do not incinerate. Dispose of in accordance with local, state and federal regulations. Do not contaminate lakes, streams or other water supply.

**Container Disposal:** Disposal must be made according to official regulations.

---

## Section 14 - Transport Information

---

### DOT

**Proper Shipping Name:** Paint related material

**Hazard Class:** 3

**Identification Number:** UN1263

**Packing Group:** II

**DOT Labeling:** Flammable Liquid

### IMDG (Maritime transport)

**Proper Shipping Name:** PAINT RELATED MATERIAL

**IMDG Class:** 3

**UN Number:** UN1263

**Label:** Flammable Liquid

**EMS Number:** F-E, S-E

## IATA (Air transport)

**Proper Shipping Name:** Paint related material

**ICAO / IATA Class:** 3

**UN / ID Number:** UN1263

**Label:** Flammable Liquid

**Packing Group** II

---

## Section 15 - Regulatory Information

---

Superfund Amendments and Reauthorization Act of 1986 (Emergency Planning and Community Right-to-Know Act of 1986) Sections 311 and 312

Immediate (Acute) Health Hazard: Not available

Delayed (Chronic) Health Hazard: Not available

Fire Hazard: Not available

Reactive Hazard: Not available

Sudden Release of Pressure: Not available

---

(NZ) Statement: This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017. HSNO Group Standard – Surface Coatings/Colourants - Flammable 002662

---

**The following lists hazardous components and the regulatory lists for which they are required to be reported.**

---

**Component:** Acetone

**CAS:** 67-64-1

**Amount:** 30 - 35%

Acetone is listed with International Agency for Research on Cancer (IARC) as a possible carcinogen.

---

**Component:** Dibutyl Phthalate

**CAS:** 87-74-2

**Amount:** 1%

Dibutyl Phthalate is on the California Prop 65 Cancer list.

---

**Component:** Ethyl Benzene

**CAS:** 100-41-4

**Amount:** 1 - 2%

Ethyl Benzene is on the California Prop 65 Cancer list.

Ethyl Benzene is listed with Massachusetts Right to Know.

Ethyl Benzene is listed with Minnesota Right to Know.

Ethyl Benzene is listed with New Jersey Right to Know.

Ethyl Benzene is listed with Pennsylvania Right to Know.

---

**Component:** Tertiary Butyl Acetate

**CAS:** 540-88-5

**Amount:** 49 - 50%

Tertiary Butyl Acetate is listed with Massachusetts Right to Know.

Tertiary Butyl Acetate is listed with Minnesota Right to Know.

Tertiary Butyl Acetate is listed with New Jersey Right to Know.

Tertiary Butyl Acetate is listed with Pennsylvania Right to Know.

Tertiary Butyl Acetate is listed with Rhode Island Right to Know.

is listed with the Occupational Safety and Health Administration (OSHA) as a possible carcinogen.

---

**Component:** Xylene

**CAS:** 1330-20-7

**Amount:** 7 - 8%

Xylene is listed with the Illinois toxic substances disclosure to employee act.

Xylene is listed with Massachusetts Right to Know.

Xylene is listed with Minnesota Right to Know.

Xylene is listed with New Jersey Right to Know.

Xylene is listed with Pennsylvania Right to Know.

Xylene is listed with Rhode Island Right to Know.


---

#### HMIS Rating (0 - 4)

<b>HEALTH</b>	<b>2</b>	Health = 2
<b>FIRE</b>	<b>3</b>	Fire = 3
<b>PHYSICAL</b>	<b>1</b>	Physical = 1
<b>PERSONAL PROTECTION</b>	<b>G</b>	Personal Protection = G

---

#### NFPA Ratings




---

## Section 16 - Other Information

---

### Legend

ACGIH	American Conference of Governmental Hygienists
CFR	Code of Federal Regulations
DFG	Deutsche Forschungsgemeinschaft
HMIS	Hazardous Materials Identification System
IARC	International Agency for Research on Cancer
IDLH	Immediately Dangerous to Life or Health
MAK	Maximum Allowable Concentration (German)
NFPA	National Fire Protection Association
NIOSH	National Institute for Occupational Safety and Health
OEL	Occupational Exposure Limit
RCRA	Resource Conservation and Recovery Act
STEL	Short Term Exposure Limit
TLV	Threshold Limit Value
TWA	Time Weighted Average

---

### DISCLAIMER

This Safety Data Sheet (SDS) is prepared in compliance with GHS Hazcom 2012. The information may be based in part on information provided by component suppliers and is believed to be correct as of the date hereof. However, no warranty or merchantability, fitness for any use, or any other warranty is expressed or is to be implied regarding the accuracy of this data, the results to be obtained from the use of the material, or the hazards connected with such use. Since the information contained herein may be applied under conditions beyond our control and with which we may be unfamiliar, and since data made available subsequent to the date hereof may suggest modification of the information, we assume no responsibility for the result of its use. This information and material is furnished on the condition that the person receiving it shall make his/her own determination as the suitability of the material for his/her particular purpose and on the condition that he/she assume the risk of his/her use thereof.