



G3 Regular Grade

Paste Compound



Product Description

G3 Regular Grade Paste Compound is recommended for use on OEM and refinish paint systems.

This versatile product can be used by hand or machine. Use with a G Mop 6" Wet Use Compounding Foam (**GMC606**) for ease of use and low splatter.



Product Information

Size	Code	Ctn Qty
250g	G3-250	24
400g	G3-400	12
1kg	G3-1000	12
3kg	G3-3000	4

Key Benefits

• Reliable Cut	Removes P1500 or finer abrasive marks quickly and easily
• Permanent Finish	Contains no fillers so scratch marks will not reappear
• High Gloss System	Excellent gloss. Can be used with G3 Fine Finishing Compound for an enhanced gloss finish on dark colours
• Silicone Free	100% paintshop safe



Use With

Machine Application




G Mop 6" Wet Use
Compounding Foam
GMC606



G Mop Back Plate with
White Interface for 6" Pads
WSB
BPI601 (14mm thread)
BPI606 (16mm thread)
BPI612 (5/8" thread)



Water Spray Bottle
WSB




Farécla Finishing Cloth
FC-3 (3 x cloths)

How To Use


Machine Application




1 Soak a G Mop 6"
Wet Use Com-
pounding Foam




2 Attach pad to the
polishing machine,
spin off excess
water and knead



3 Knead tube or mix
compound well,
then apply to pad
or surface



4 Spread and
compound at
1500 - 1800rpm.
Apply more water
if necessary




5 Wipe clean with
Finishing Cloth


Hand Application



1 Soak and rinse out
a Finishing Cloth



2 Knead tube or mix
compound well,
then apply to cloth
or surface



3 Rub product on
the surface in a
back and forth
motion



4 Apply water if
necessary. Wipe
clean with Finishing
Cloth

Technical Information

Appearance: **White coloured paste**

Viscosity: **Highly viscous**

VOC Content: **177g/L**

Relative Density: **1.44**

pH: **9 - 10**

Paint Type Compliance: **MS & HS**