

Profile Premium







Coarse Cut Paste Compound

PROFILE SPECIALIST APPLICATIONS PREMIUM COARSE CUT ACTE COMPOUND Sulfests for gar controval profiled for gar controval profiled for gar controval profiled for gar controval profiled for gar controval

3.5KG (123OZ) PRP301

Product Description

Premium Paste Compound is a medium aggressive, water-based cutting compound capable of removing up to P800 sanding marks as well as delivering a high gloss finish. With added lubrication, it is also resistant to drying out in hot conditions and on large surfaces. Often used as the sole compound on white gel coats, it can be applied in the first stage of a two part compounding process where higher gloss and lower swirl is required.

Product Information

Size	Code	Ctn Qty
3.5kg (123oz)	PRP301	4

Key Benefits	
• Versatile	Engineered for both gel coats and painted finishes, removing up to P800 sanding marks and leaving a high gloss finish
High Quality Abrasive	No haze, no die back
• Water-Based	Cleans up easily and extends pad life



Use With

Machine Application



G Mop 8" Twisted Wool Pad - Single Sided GMW801



G Mop Flexible Back Plate for 8" Pads GMB814 (14mm thread) GMB858 (5/8" thread) GMB816 (16mm thread)



G Mop 8" Twisted Wool Pad - Double Sided GMW806



Adaptor for G Mop 8" Double Sided Wool Pad GMA014 (14mm thread) GMA058 (5/8" thread) GMA016 (16mm thread)

How To Use

Machine Application



Sand area - Profile Premium Liquid Compound removes up to P1200



Attach G Mop 8" Single Sided Wool Pad to a polisher



Mix product well and apply small quantity of the product to the surface or pad



Spread and compound at 1500 - 1800rpm



Wipe clean with a Finishing Cloth

*It is always recommended to test on an inconspicuous area prior to general use

Technical Information

Appearance: White coloured paste

Viscosity: **High viscosity** VOC Content: **0g/L** Relative Density: **1.65**

pH: 10

Surface Types: Marine gel coats, aerospace, wood, caravan & motorhome etc.

Additional Information

Clean applicators before and after use with a Spurring Brush to prevent dried product damaging the surface being worked on.



Spurring Brush 1090005