

TECHNICAL INFORMATION

FOR PROFESSIONAL USE ONLY

MASTER SPRAY SILVER WHEEL



PRODUCT DESCRIPTION

Fast – drying acrylic paint designed for painting steel wheels, wheels made of light metals and for wheel caps. Paint is characterized by very good adhesion and high hardness of surface. Product is resistant for scratches, impacts, petrol, UV radiations and weather condition.

PHYSICAL AND CHEMICAL INFORMATIONS

- Colour: silver
- Volume: 500 ml.
- Efficiency: 4 – 5 wheels

Drying time in room temperature:

- Dust dry 5 – 10 min
- Tack free 10 – 20 min
- Resprayable after approx. 2 h

Note: Drying time depends on air temperature, humidity and thickness of the layer.

CONTENT OF VOLATILE MATTER

VOC = 712 [g/l]

This product satisfies requirements of the European Union Directive (2004/42/WE), which for this product category (B/5) gives the limit value of content of volatile matter at the level of 800 [g/l] of the ready-for-use product.

USAGE

- Surface to be treated should be clean, dry and degreased.
- Old, loose clear coat and rust must be removed and surface should be sanded and covered with suitable primer.
- Best work temperature is 15 – 25⁰C
- Shake can before use for 2 minutes and try it on cardboard.
- During lacquering hold aerosol in 25 – 30 cm. distance from painted surface.
- Apply spray in several thin layers. Shake again aerosol before applying next layer.
- **After use clean aerosol's outlets** – hold down aerosol's valve, push the bottom and release contents for 5 seconds.
- For high gloss finish, apply a layer of acrylic clear coat.

Caution: To maintain safety, always follow the instructions given in the Safety Data Sheet for the given product.

STORAGE

Store the product in a sealed container, in dry and cool places, away from fire and heat sources, as well as direct sunlight.

WARRANTY PERIOD

5 years from production date, provided the storage condition.