Safety Data Sheet
9.BRCOARSE/8 - 9.BRCOARSE250/6

Safety Data Sheet dated 7/8/2018, version 1

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: ROTARY COARSE

Trade code: 9.BRCOARSE/8 - 9.BRCOARSE250/6

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Abrasive and polishing compound

Uses advised against:

All not indicated in the suggested uses.

1.3. Details of the supplier of the safety data sheet

Company:

RUPES SPA - Via Marconi 3A, 20080, Vermezzo (MI) – Italy

RUPES SPA - Telefono n°+3902946941

Importer:

Wyatt Machine Tools (Rupes) NZ Limited

388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

Competent person responsible for the safety data sheet:

info_rupes@rupes.it

1.4. Emergency telephone number

NZ Emergency 0800 992 881 (0800WYATT1)

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

None

Special Provisions:

EUH066 Repeated exposure may cause skin dryness or cracking.

EUH208 Contains: mixture of 5-cloro-2-metil-2H-isotiazol-3-one [EC no. 247-500-7]; 2-metil-2H-isotiazol-3-one [EC no. 220-239-6] (3:1): may produce an allergic reaction.

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:
None

2.3. Other hazards
vPvB Substances: None
PBT Substances: None
Other Hazards:
No other hazards

SECTION 3: Composition/information on ingredients

3.1. Substances
N.A.
3.2. Mixtures
Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 20% - < 25%	Alluminium oxide	CAS: 1344-28-1 EC: 215-691-6	Classification: not defined.
>= 12.5% - < 15%	hydrocarbons, C10-C12, isoalkanes, <2% aromatic	EC: 923-037-2	2.6/3 Flam. Liq. 3 H226 3.10/1 Asp. Tox. 1 H304 4.1/C4 Aquatic Chronic 4 H413 EUH066
>= 3% - <5%	Hydrocarbons C12-C16, isoalkanes, <2% Aromatics	EC: 927-676-8	3.10/1 Asp. Tox. 1 H304
>= 0.5% - < 1%	Triethanolamine	CAS: 102-71-6 EC: 203-049-8	Classification: not defined.
< 0.0015%	reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1)	Index number: 613-167-00-5 CAS: 55965-84-9	3.2/1B Skin Corr. 1B H314 3.4.2/1-1A-1B Skin Sens. 1,1A,1B H317 4.1/A1 Aquatic Acute 1 H400 4.1/C1 Aquatic Chronic 1 H410 3.1/3/Oral Acute Tox. 3 H301 3.1/3/Dermal Acute Tox. 3 H311 3.1/3/Inhal Acute Tox. 3 H331

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:
Wash with plenty of water and soap.
In case of eyes contact:
In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
In case of Ingestion:
Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.
In case of Inhalation:
Remove casualty to fresh air and keep warm and at rest.
4.2. Most important symptoms and effects, both acute and delayed
Dry skin
4.3. Indication of any immediate medical attention and special treatment needed
Treatment:
None

SECTION 5: Firefighting measures

5.1. Extinguishing media
Suitable extinguishing media:
Water.
Carbon dioxide (CO2).
Extinguishing media which must not be used for safety reasons:
None in particular.
5.2. Special hazards arising from the substance or mixture
Do not inhale explosion and combustion gases.
Burning produces heavy smoke.
5.3. Advice for firefighters
Use suitable breathing apparatus .
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures
Wear personal protection equipment.
Remove persons to safety.
See protective measures under point 7 and 8.
6.2. Environmental precautions
Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
Retain contaminated washing water and dispose it.
In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
Suitable material for taking up: absorbing material, organic, sand
6.3. Methods and material for containment and cleaning up
Wash with plenty of water.
6.4. Reference to other sections

See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.
Don't use empty container before they have been cleaned.
Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
Contamined clothing should be changed before entering eating areas.
Do not eat or drink while working.
See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep container closed when not in use. Keep only in the original container in a cool, well ventilated place away from: direct sunlight, heat and ignition sources
Store in a well-ventilated place
Keep away from food, drink and feed.
Incompatible materials:
None in particular.
Instructions as regards storage premises:
Adequately ventilated premises.

7.3. Specific end use(s)

Abrasive and polishing compound

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Alluminium oxide - CAS: 1344-28-1
- OEL Type: ACGIH - TWA(8h): 1 mg/m3

hydrocarbons, C10-C12, isoalkanes, <2% aromatic
- OEL Type: ACGIH - TWA(8h): 1200 mg/m3

Hydrocarbons C12-C16, isoalkanes, <2% Aromatics
- OEL Type: EU - TWA(8h): 200 mg/m3

Triethanolamine - CAS: 102-71-6
- OEL Type: ACGIH - TWA(8h): 5 mg/m3 - Notes: ACGIH 2014 irrt cute e oclr

DNEL Exposure Limit Values

Alluminium oxide - CAS: 1344-28-1

Worker Industry: 15.63 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
Worker Industry: 15.63 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects
Consumer: 6.58 mg/m3 - Exposure: Human Oral - Frequency: Long Term, systemic effects

Triethanolamine - CAS: 102-71-6

Worker Industry: 5 mg/m3 - Consumer: 1.25 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

Worker Industry: 5 mg/m3 - Consumer: 1.25 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, local effects
Worker Industry: 6.3 mg/kg bw/day - Consumer: 3.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects
Consumer: 13 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects

PNEC Exposure Limit Values

Triethanolamine - CAS: 102-71-6

Target: Fresh Water - Value: 0.32 mg/l
Target: Marine water - Value: 0.0032 mg/l
Target: Freshwater sediments - Value: 1.7 mg/kg
Target: Marine water sediments - Value: 0.17 mg/kg
Target: Food chain - Value: 0.0151 mg/kg

8.2. Exposure controls

Eye protection:

Not needed for normal use. Anyway, operate according good working practices.

Protection for skin:

No special precaution must be adopted for normal use.

Protection for hands:

Not needed for normal use.

Respiratory protection:

Not needed for normal use.

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	Blue paste	--	--
Odour:	characteristic	--	--
Odour threshold:	N.A.	--	--
pH:	N.A.	--	--
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	N.A.	--	--
Flash point:	108 ° C	EN ISO 3679	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--

Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	N.A.	--	--
Vapour density:	N.A.	--	--
Relative density:	N.A.	--	--
Solubility in water:		--	--
Solubility in oil:	N.A.	--	--
Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	27.000 cps (40°C)	--	--
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	N.A.	--	--

SECTION 10: Stability and reactivity

10.1. Reactivity
Stable under normal conditions
10.2. Chemical stability
Stable under normal conditions
10.3. Possibility of hazardous reactions
None
10.4. Conditions to avoid
Stable under normal conditions.
10.5. Incompatible materials
None in particular.
10.6. Hazardous decomposition products
None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects
Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

Alluminium oxide - CAS: 1344-28-1

a) acute toxicity:

Test: LC50 - Route: Oral - Species: Rat > 15900 mg/kg - Source: OECD401

Test: LC50 - Route: Inhalation - Species: Rat > 2.3 mg/l - Duration: 4h - Source: OECD 403

hydrocarbons, C10-C12, isoalkanes, <2% aromatic

a) acute toxicity:

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 5000 mg/m3 - Duration: 8h - Source: OECD 403

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit > 5000 mg/kg - Source: OECD 402

Hydrocarbons C12-C16, isoalkanes, <2% Aromatics

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg - Source: OECD401

Test: LC50 - Route: Inhalation Vapour - Species: Rat > 5000 mg/m3 - Duration: 8h - Source: OECD403

Test: LD50 - Route: Skin - Species: Rat > 5000 mg/kg - Source: OECD402

Triethanolamine - CAS: 102-71-6

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 6400 mg/kg - Source: OECD 401

Test: LD50 - Route: Skin - Species: Rabbit = 2000 mg/kg - Source: OECD 402

Test: LC50 - Route: Inhalation - Species: Rat = 1.8 mg/m3 - Duration: 8h

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7]; and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1) - CAS: 55965-84-9

a) acute toxicity:

Test: ATE - Route: Oral = 100 mg/kg

Test: ATE - Route: Skin = 300 mg/kg

Test: ATE - Route: Inhalation Vapour = 3 mg/l

Test: ATE - Route: Inhalation Mist = 0.5 mg/l

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

a) acute toxicity;
b) skin corrosion/irritation;
c) serious eye damage/irritation;
d) respiratory or skin sensitisation;
e) germ cell mutagenicity;
f) carcinogenicity;
g) reproductive toxicity;
h) STOT-single exposure;
i) STOT-repeated exposure;
j) aspiration hazard.

SECTION 12: Ecological information

12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

hydrocarbons, C10-C12, isoalkanes, <2% aromatic

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: LL50-OECD203-Oncoryhynchus mykiss
Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: EL50 - OECD 202- DAPHNIA MAGNA
Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: EL50 OECD 201- pseudokirchnerella subcapitata

b) Aquatic chronic toxicity:

Endpoint: NOELR - Species: Daphnia = 1 mg/l - Duration h: 504 - Notes: Daphnia magna

Hydrocarbons C12-C16, isoalkanes, <2% Aromatics

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish > 1000 mg/l - Duration h: 96 - Notes: LL50-OECD203-Oncorhynchus mykiss
Endpoint: EC50 - Species: Daphnia > 1000 mg/l - Duration h: 48 - Notes: EL50 - OECD 202 Daphnia Magna
Endpoint: EC50 - Species: Algae > 1000 mg/l - Duration h: 72 - Notes: EL50 OECD 201 Pseudokirchnerella subcapitata

b) Aquatic chronic toxicity:

Endpoint: NOELR 72 h - Species: Daphnia > 1 mg/l - Notes: 21 d OECD 211- dafinia magna

Triethanolamine - CAS: 102-71-6

a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 11800 mg/l - Duration h: 96 - Notes: Pimephales promelas
Endpoint: EC50 - Species: Daphnia = 609.88 mg/l - Duration h: 48 - Notes: Ceriodaphnia dubia ASTME1192
Endpoint: EC50 - Species: Algae = 512 mg/l - Duration h: 72 - Notes: Scenedesmus subspicatus DIN 38412 part 9

12.2. Persistence and degradability

N.A.

12.3. Bioaccumulative potential

N.A.

12.4. Mobility in soil

N.A.

12.5. Results of PBT and vPvB assessment

vPvB Substances:

>= 15% - < 20% hydrocarbons, C10-C12, isoalkanes, <2% aromatic -

PBT Substances: None

12.6. Other adverse effects

None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

SECTION 14: Transport information

14.1. UN number

Not classified as dangerous in the meaning of transport regulations.

14.2. UN proper shipping name

N.A.

14.3. Transport hazard class(es)

N.A.

14.4. Packing group

N.A.

14.5. Environmental hazards

N.A.

14.6. Special precautions for user

N.A.

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Dir. 98/24/EC (Risks related to chemical agents at work)
Dir. 2000/39/EC (Occupational exposure limit values)
Regulation (EC) n. 1907/2006 (REACH)
Regulation (EC) n. 1272/2008 (CLP)
Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
Regulation (EU) 2015/830
Regulation (EU) n. 286/2011 (ATP 2 CLP)
Regulation (EU) n. 618/2012 (ATP 3 CLP)
Regulation (EU) n. 487/2013 (ATP 4 CLP)
Regulation (EU) n. 944/2013 (ATP 5 CLP)
Regulation (EU) n. 605/2014 (ATP 6 CLP)
Regulation (EU) n. 2015/1221 (ATP 7 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 40

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions :

Directive 2012/18/EU (Seveso III)
Regulation (EC) nr 648/2004 (detergents).
Dir. 2004/42/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):
N.A.

This substance is not classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017

15.2. Chemical safety assessment
No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3:
H226 Flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H413 May cause long lasting harmful effects to aquatic life.
EUH066 Repeated exposure may cause skin dryness or cracking.
H314 Causes severe skin burns and eye damage.
H317 May cause an allergic skin reaction.
H400 Very toxic to aquatic life.
H410 Very toxic to aquatic life with long lasting effects.
H301 Toxic if swallowed.
H311 Toxic in contact with skin.
H331 Toxic if inhaled.

Hazard class and hazard category	Code	Description
Flam. Liq. 3	2.6/3	Flammable liquid, Category 3
Acute Tox. 3	3.1/3/Dermal	Acute toxicity (dermal), Category 3
Acute Tox. 3	3.1/3/Inhal	Acute toxicity (inhalation), Category 3
Acute Tox. 3	3.1/3/Oral	Acute toxicity (oral), Category 3
Asp. Tox. 1	3.10/1	Aspiration hazard, Category 1
Skin Corr. 1B	3.2/1B	Skin corrosion, Category 1B
Skin Sens. 1,1A,1B	3.4.2/1-1A-1B	Skin Sensitisation, Category 1,1A,1B
Aquatic Acute 1	4.1/A1	Acute aquatic hazard, category 1
Aquatic Chronic 1	4.1/C1	Chronic (long term) aquatic hazard, category 1
Aquatic Chronic 4	4.1/C4	Chronic (long term) aquatic hazard, category 4

This document was prepared by a competent person who has received appropriate training.
Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities
SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.
It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.
This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWA:	Time-weighted average
WGK:	German Water Hazard Class.