

Safety Data Sheet dated 28/7/2017, version 1

| ECTION 1: Identification of the subs | stance/mixture and of the company/undertaking |
|--|---|
| 1.1. Product identifier | |
| Mixture identification: | |
| Trade name: | 9.BRULTRAFINE/8 - 9.BRULTRAFINE250/6 |
| Trade code: | ROTARY ULTRAFINE |
| 1.2. Relevant identified uses of the su | ubstance or mixture and uses advised against |
| Recommended use: | - |
| Abrasive compound for bodywork | |
| Professional use only | |
| Uses advised against: | |
| All not indicated in the suggested use | es. |
| 1.3. Details of the supplier of the safe | |
| Company: | , |
| RUPES SPA - Via Marconi 3A | . 20080, Vermezzo (MI) – Italy |
| RUPES SPA - Telefono n°+39 | |
| Importer: | |
| Wyatt Machine Tools (Rupes) | NZ Limited |
| 388 Church Street, Penrose, A | |
| Ph (09) 525 1000; Fax (09) 52 | |
| | |
| Competent person responsible for the | e safety data sheet: |
| info_rupes@rupes.it | , |
| 1.4. Emergency telephone number | |
| NZ Emergency 0800 992 881 | (0800WYATT1) |
| Ç , | 、 |
| ECTION 2: Hazards identification | |
| 2.1. Classification of the substance o | r mixture |
| EC regulation criteria 1272/2008 (CL | P) |
| The product is not classified as | s dangerous according to Regulation EC 1272/2008 (CLP). |
| Adverse physicochemical, human he | |
| No other hazards | |
| 2.2. Label elements | |
| Hazard pictograms: | |
| None | |
| Hazard statements: | |
| None | |
| Precautionary statements: | |
| P102 Keep out of reach of chil | dren. |
| Special Provisions: | |
| EUH210 Safety data sheet ava | ailable on request. |
| | ex XVII of REACH and subsequent amendments: |
| | |
| | |

ROTARY ULTRAFINE/1 Page n. 1 of 10



None

2.3. Other hazards vPvB Substances: None - PBT Substances: None Other Hazards: No other hazards

SECTION 3: Composition/information on ingredients

- 3.1. Substances
- N.A.
- 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

| Qty | Name | Ident. Numb | er | Classification |
|-------------------|---|---------------------------------|-----------------------------------|---|
| >= 15% - < 20% | Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics | EC: REACH No.: | 920-114-2 01-21194593 47-30 | 상 3.10/1 Asp. Tox. 1 H304 |
| >= 3% - < 5% | 1-methoxy-2-propanol; monopropylene glycol methyl ether | Index number: CAS: EC: | | 2.6/3 Flam. Liq. 3 H226 3.8/3 STOT SE 3 H336 |

SECTION 4: First aid measures

4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

- 4.2. Most important symptoms and effects, both acute and delayed
 - None
- 4.3. Indication of any immediate medical attention and special treatment needed Treatment:
 - None

SECTION 5: Firefighting measures

5.1. Extinguishing media Suitable extinguishing media: Water.

ROTARY ULTRAFINE/1 Page n. 2 of 10



Carbon dioxide (CO2).

Extinguishing media which must not be used for safety reasons: None in particular.

- 5.2. Special hazards arising from the substance or mixture Do not inhale explosion and combustion gases. Burning produces heavy smoke.
- 5.3. Advice for firefighters
 - Use suitable breathing apparatus .

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
 - Wear personal protection equipment. Remove persons to safety.

See protective measures under point 7 and 8.

6.2. Environmental precautions

Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains. Retain contaminated washing water and dispose it.

In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.

Suitable material for taking up: absorbing material, organic, sand

- 6.3. Methods and material for containment and cleaning up
 - Wash with plenty of water.
- 6.4. Reference to other sections See also section 8 and 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Avoid contact with skin and eyes, inhaltion of vapours and mists.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.

Contamined clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

7.2. Conditions for safe storage, including any incompatibilities

Keep container closed when not in use. Keep only in the original container in a cool, well ventilated place away from: direct sunlight, heat and ignition sources Keep away from food, drink and feed. Incompatible materials:

None in particular.

Instructions as regards storage premises:

Adequately ventilated premises.

ROTARY ULTRAFINE/1

Page n. 3 of 10



7.3. Specific end use(s) Abrasive compound for bodywork Professional use only

SECTION 8: Exposure controls/personal protection 8.1. Control parameters 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2 - OEL Type: EU - TWA(8h): 375 mg/m3, 100 ppm - STEL: 563 mg/m3, 150 ppm -Notes: Skin - OEL Type: ACGIH - TWA(8h): 50 ppm - STEL: 100 ppm - Notes: A4 - Eye and URT irr **DNEL Exposure Limit Values** 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2 Consumer: 3.3 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects Consumer: 18.1 mg/kg - Exposure: Human Dermal - Frequency: Long Term, systemic effects Worker Professional: 50.6 mg/kg bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects Consumer: 43.9 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects Worker Professional: 369 mg/m3 - Exposure: Human Inhalation - Frequency: Long Term, systemic effects **PNEC Exposure Limit Values** 1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2 Target: STP - Value: 100 mg/l Target: gro - Value: 2.47 mg/kg Target: Freshwater sediments - Value: 41.6 mg/kg Target: Marine water sediments - Value: 4.17 mg/kg Target: Fresh Water - Value: 10 mg/l 8.2. Exposure controls Eye protection: Not needed for normal use. Anyway, operate according good working practices. Protection for skin: No special precaution must be adopted for normal use. Protection for hands: Not needed for normal use. Respiratory protection: Not needed for normal use. Thermal Hazards: None Environmental exposure controls: None Appropriate engineering controls: None

ROTARY ULTRAFINE/1 Page n. 4 of 10



SECTION 9: Physical and chemical properties 9.1. Information on basic physical and chemical properties

| Properties | Value | Method: | Notes |
|--|-----------------------|---------|-----------------------------|
| Appearance and colour: | White pasty | | |
| Odour: | characteristic | | |
| Odour threshold: | N.A. | | |
| pH: | N.A. | | |
| Melting point / freezing point: | N.A. | | |
| Initial boiling point and boiling range: | 100-355 ° C | | |
| Flash point: | N.A. | | |
| Evaporation rate: | N.A. | | |
| Solid/gas flammability: | N.A. | | |
| Upper/lower flammability or explosive limits: | N.A. | | |
| Vapour pressure: | N.A. | | |
| Vapour density: | N.A. | | |
| Relative density: | 0.98-0.99 g/cm3 | | at 20°C |
| Solubility in water: | partially miscible | | |
| Solubility in oil: | N.A. | | |
| Partition coefficient (n-octanol/water): | N.A. | | |
| Auto-ignition temperature: | N.A. | | |
| Decomposition temperature: | N.A. | | |
| Viscosity: | 20.5 mm2/s | | kinematic viscosity at 40°C |
| Explosive properties: | N.A. | | |
| Oxidizing properties: | N.A. | | |

9.2. Other information

| Properties | Value | Method: | Notes | |
|--------------------------------------|-------|---------|-------|--|
| Miscibility: | N.A. | | | |
| Fat Solubility: | N.A. | | | |
| Conductivity: | N.A. | | | |
| Substance Groups relevant properties | N.A. | | | |



SECTION 10: Stability and reactivity

- 10.1. Reactivity
 - No dangerous reactions known
- 10.2. Chemical stability stable under normal conditions
- 10.3. Possibility of hazardous reactions No dangerous reactions known
- 10.4. Conditions to avoid Direct sunlight. Extremely high or low temperatures
- 10.5. Incompatible materials
 - Strong acids. Strong bases
- 10.6. Hazardous decomposition products None.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Toxicological information of the product:

N.A.

Toxicological information of the main substances found in the product:

Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat > 5000 mg/kg

Test: LD50 - Route: Skin - Species: Rabbit > 2000 mg/kg

Test: LC50 - Route: Inhalation - Species: Rat > 5266 mg/l - Duration: 4h

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

a) acute toxicity:

Test: LD50 - Route: Oral - Species: Rat = 4016 mg/kg

Test: LD50 - Route: Skin - Species: Rat > 2000 mg/kg

Test: LCO - Route: Inhalation - Species: Rat > 7000 ppm - Duration: 6h

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

a) acute toxicity;

b) skin corrosion/irritation;

c) serious eye damage/irritation;

d) respiratory or skin sensitisation;

e) germ cell mutagenicity;

f) carcinogenicity;

g) reproductive toxicity;

h) STOT-single exposure;

i) STOT-repeated exposure;

j) aspiration hazard.

SECTION 12: Ecological information 12.1. Toxicity

ROTARY ULTRAFINE/1 Page n. 6 of 10



Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics
a) Aquatic acute toxicity: Endpoint: ELO 48H - Species: Daphnia = 1000 mg/l - Duration h: 48 Endpoint: ErLO 72h - Species: Pseudokirchneriella subcapitata = 1000 mg/l - Duration h: 72 Endpoint: LLO 96H - Species: Algae = 87556 mg/l - Duration h: 96 Endpoint: NOELR 72 h - Species: Algae = 1000 mg/l - Duration h: 72
1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2
a) Aquatic acute toxicity: Endpoint: EC50 - Species: Pseudokirchneriella subcapitata > 1000 mg/l - Notes: (7d) Endpoint: EC50 - Species: Bel > 1000 mg/l - Duration h: 3 - Notes: OECD 209

Adopt good working practices, so that the product is not released into the environment.

Endpoint: EC50 - Species: Bel > 1000 mg/l - Duration n: 3 - Notes: OECD 209 Endpoint: EC50 - Species: Leuciscus idus > 6800 mg/l - Duration h: 96 - Notes: DIN3412

Endpoint: LC50 - Species: Daphnia > 23300 mg/l - Duration h: 48

12.2. Persistence and degradability

Hydrocarbons, C14-C19, isoalkanes, cyclics, <2% aromatics

Biodegradability: Persistent and Biodegradable - Test: CO2 production - Duration h: 28d - %: 17.7 - Notes: N.A.

12.3. Bioaccumulative potential

1-methoxy-2-propanol; monopropylene glycol methyl ether - CAS: 107-98-2

Bioaccumulative - Test: Kow - Partition coefficient 0.43 - Duration h: N.A. - Notes: 25°C 12.4. Mobility in soil

- N.A.
- 12.5. Results of PBT and vPvB assessment vPvB Substances: None - PBT Substances: None
- 12.6. Other adverse effects None

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Additional disposal information:

Dispose in a safe manner in accordance with local/national regulations

SECTION 14: Transport information

- 14.1. UN number
 - Not classified as dangerous in the meaning of transport regulations.
- 14.2. UN proper shipping name
 - N.A.
- 14.3. Transport hazard class(es)
 - N.A.
- 14.4. Packing group

ROTARY ULTRAFINE/1

Page n. 7 of 10



N.A.

- 14.5. Environmental hazards
 - N.A.
- 14.6. Special precautions for user N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code N.A.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture Dir. 98/24/EC (Risks related to chemical agents at work) Dir. 2000/39/EC (Occupational exposure limit values) Regulation (EC) n. 1907/2006 (REACH) Regulation (EC) n. 1272/2008 (CLP) Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013 Regulation (EU) 2015/830 Regulation (EU) n. 286/2011 (ATP 2 CLP) Regulation (EU) n. 618/2012 (ATP 3 CLP) Regulation (EU) n. 487/2013 (ATP 4 CLP) Regulation (EU) n. 944/2013 (ATP 5 CLP) Regulation (EU) n. 605/2014 (ATP 6 CLP) Regulation (EU) n. 2015/1221 (ATP 7 CLP) Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications: Restrictions related to the product: **Restriction 40** Restrictions related to the substances contained: No restriction. Where applicable, refer to the following regulatory provisions : Directive 2012/18/EU (Seveso III) Regulation (EC) nr 648/2004 (detergents). Dir. 2004/42/EC (VOC directive) Provisions related to directive EU 2012/18 (Seveso III): N.A. This substance is not classified hazardous according to the EPA Hazardous Substances

(Classification) Notice 2017

15.2. Chemical safety assessment No Chemical Safety Assessment has been carried out for the mixture.

SECTION 16: Other information

Full text of phrases referred to in Section 3: H304 May be fatal if swallowed and enters airways.



H226 Flammable liquid and vapour. H336 May cause drowsiness or dizziness.

| Hazard class and hazard category | Code | Description |
|----------------------------------|--------|---|
| Flam. Liq. 3 | 2.6/3 | Flammable liquid, Category 3 |
| Asp. Tox. 1 | 3.10/1 | Aspiration hazard, Category 1 |
| STOT SE 3 | 3.8/3 | Specific target organ toxicity - single exposure, Category 3 |

This document was prepared by a competent person who has received appropriate training. Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

| ADR: | European Agreement concerning the International Carriage of Dangerous Goods by Road. |
|-------------|---|
| CAS: | Chemical Abstracts Service (division of the American Chemical Society). |
| CLP: | Classification, Labeling, Packaging. |
| DNEL: | Derived No Effect Level. |
| EINECS: | European Inventory of Existing Commercial Chemical Substances. |
| GefStoffVO: | Ordinance on Hazardous Substances, Germany. |
| GHS: | Globally Harmonized System of Classification and Labeling of |
| | Chemicals. |
| IATA: | International Air Transport Association. |
| IATA-DGR: | Dangerous Goods Regulation by the "International Air Transport Association" (IATA). |
| ICAO: | International Civil Áviation Organization. |
| ICAO-TI: | Technical Instructions by the "International Civil Aviation Organization" (ICAO). |
| IMDG: | International Maritime Code for Dangerous Goods. |
| INCI: | International Nomenclature of Cosmetic Ingredients. |
| KSt: | Explosion coefficient. |
| LC50: | Lethal concentration, for 50 percent of test population. |
| LD50: | Lethal dose, for 50 percent of test population. |
| PNEC: | Predicted No Effect Concentration. |

ROTARY ULTRAFINE/1 Page n. 9 of 10



| RID: | Regulation Concerning the International Transport of Dangerous Goods |
|-------|--|
| | by Rail. |
| STEL: | Short Term Exposure limit. |
| STOT: | Specific Target Organ Toxicity. |
| TLV: | Threshold Limiting Value. |
| TWA: | Time-weighted average |
| WGK: | German Water Hazard Class. |