

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Page 1/20

1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: EN 4100 PLASTOCLEAR SPRAY

• Article number: 995

· Relevant identified uses of the substance or mixture and uses advised against

- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9b Fillers, putties, plasters, modelling clay
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- · Environmental release category ERC2 Formulation into mixture
- Article category AC1 Vehicles
- · Application of the substance / the mixture Surface protection

· Details of the supplier of the safety data sheet

• Manufacturer/Supplier:

EN Chemicals S.A. 57 009 Kalochori Thessalonikil, GREECE T: +30 2310 755 428 F: +30 2310 755 428 info@enchemicals.com www.enchemicals.com

· Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited Address: 388 Church Street, Penrose, Auckland Ph (09) 525 1000; Fax (09) 525 1009

• Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

2 Hazards identification

· Classification of the substance or mixture





Page 2/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

Muta. 1A H340 May cause genetic defects. Carc. 1A H350 May cause cancer. Causes skin irritation. Skin Irrit. 2 H315 STOT SE 3 H335 May cause respiratory irritation. May be harmful in contact with skin. Acute Tox. 5 H313 Acute Tox. 5 H333 May be harmful if inhaled. · Additional information: 6.1E Substances that are acutely toxic – May be harmful, aspiration hazard 6.3A Substances that are irritating to the skin 2.1.2A Flammable aerosol 6.3A Substances that are irritating to the skin 6.9 (Respiratory tract irritant) 6.6A Substances that are known or presumed human mutagens 6.7A Substances that are known or presumed human carcinogens

· Label elements

• **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

·Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

xylene butane, pure isobutane

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H313 May be harmful in contact with skin.
- H333 May be harmful if inhaled.
- H315 Causes skin irritation.
- H340 May cause genetic defects.



Page 3/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

H350 May cause cancer. H335 May cause respiratory irritation. · Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. Pressurized container: Do not pierce or burn, even after use. P251 P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell. P405 Store locked up. P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. P501 Dispose of contents/container in accordance with local/regional/national/international regulations. · Other hazards · Results of PBT and vPvB assessment • **PBT:** Not applicable. · **vPvB:** Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of hazardous substances

· Dangerous components:

CAS: 1330-20-7	xylene	50-<60%
EINECS: 215-535-7	🛞 Flam. Liq. 3, H226	
Index number: 601-022-		
RTECS: ZE 2100000	Acute Tox. 5, H303	
CAS: 106-97-8	butane, pure	30-<35%
EINECS: 203-448-7	🛞 Flam. Gas 1, H220	
Index number: 601-004-	-00-0 🔗 Press. Gas C, H280	
RTECS: EJ 4200000	💫 Acute Tox. 3, H331	
	🕉 Muta. 1A, H340; Carc. 1A, H350	
CAS: 67-64-1	acetone	2.5-<5%
EINECS: 200-662-2	🛞 Flam. Liq. 2, H225	
Index number: 606-001-	-00-8 🔿 Eye Irrit. 2A, H319; STOT SE 3, H336	
RTECS: AL 3150000		
		Continue on page 4

- NZ —



Page 4/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

CAS: 75-28-5	isobutane	2.5-<5%
EINECS: 200-857-2	🚸 Flam. Gas 1, H220	
Index number: 601-004-	00-0 🚫 Press. Gas C, H280	
RTECS: TZ 4300000	🕉 Muta. 1A, H340; Carc. 1A, H350	
CAS: 74-98-6	propane	2.5-<5%
EINECS: 200-827-9	🚸 Flam. Gas 1, H220	
Index number: 601-003-	00-5 🔗 Press. Gas C, H280	
RTECS: TX 2275000	•	
Additional informati	• • Fourth a second in a fifth a list of her and a hard so a fault a section of f	

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· Description of first aid measures

• General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- $\cdot \textbf{After eye contact:} \ \textbf{R} inse \ \textbf{opened eye for several minutes under running water.}$
- $\cdot \mbox{After swallowing:}$ If symptoms persist consult doctor.
- ·Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.

· Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

- · Speial protective equipment and fire fighting procedures: No special measures required.
- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

- \cdot Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- Environmental precautions: Do not allow to enter sewers/ surface or ground water.



Page 5/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

• Methods and material for containment and cleaning up:

Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

·Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· Conditions for safe storage, including any incompatibilities

· Storage:

· Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

· Information about storage in one common storage facility: Not required.

- Further information about storage conditions: Keep container tightly sealed.
- Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

· Control parameters

Ingredients with limit values that require monitoring at the workplace:

1330-20-7 xylene

WES (New Zealand) Long-term value: 217 mg/m³, 50 ppm

IOELV (EU) Short-term value: 442 mg/m³, 100 ppm Long-term value: 221 mg/m³, 50 ppm Skin



Page 6/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

106-97-8 butane, pure

WES (New Zealand) Long-term value: 1900 mg/m³, 800 ppm

67-64-1 acetone

WES (New Zealand) Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm bio

IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm

74-98-6 propane

WES (New Zealand) Simple asphyxiant; may present an explosion hazard

· Regulatory information

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices IOELV (EU): (EU) 2019/1831

- Additional information: The lists valid during the making were used as basis.
- · Exposure controls
- · Personal protective equipment:
- General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

• Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.



Page 7/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

· Penetration time of glove material

- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- · Eye protection:
- Safety glasses



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

 Information on basic physical and cher General Information 	mical properties
· Appearance:	
Form:	Aerosol
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
·pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range	:-44.5 °C
·Flash point:	< 0 °C
·Flammability (solid, gas):	Not applicable.
• Autoignition temperature:	365 °C
· Decomposition temperature:	Not determined.
·Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	8.5 Vol %
	Co



Page 8/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

·Vapour pressure at 20 °C:	2,100 hPa
· Density at 20 °C:	0.869 g/cm³
· Relative density	Not determined.
·Vapour density	Not determined.
· Evaporation rate	Not applicable.
·Solubility in / Miscibility with	
water:	Fully miscible.
• Partition coefficient: n-octanol/water:	Not determined.
·Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
·Solvent content:	
Organic solvents:	93.3 %
VOC (EC)	845.5 g/l
Solids content (volume):	2.5 %
• Other information	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.

· Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

· Possibility of hazardous reactions No dangerous reactions known.

- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- ·Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)OralLD508,160 mg/kg (rat)DermalLD503.795 mg/kg (rabbit)Inhalative LC50/4 h 20.7 mg/l



Page 9/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

1330-20-7 xylene

 Oral
 LD50
 4,300 mg/kg (rat)

 Dermal
 LD50
 2,000 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

106-97-8 butane, pure

Inhalative LC50/4 h 658 mg/l (rat)

67-64-1 acetone

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

· Primary irritant effect:

· Skin corrosion/irritation Irritant to skin and mucous membranes.

- Serious eye damage/irritation No irritating effect.
- **Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version: Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Muta. 1A, Carc. 1A

12 Ecological information

· Toxicity

• Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- ·Behaviour in environmental systems:
- **Bioaccumulative potential** No further relevant information available.
- Mobility in soil No further relevant information available.
- ·Additional ecological information:
- General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water



Page 10/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

Do not allow product to reach ground water, water course or sewage system. Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- ·**vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- $\cdot \ Other \ adverse \ effects$ No further relevant information available.

13 Disposal considerations

- \cdot Waste treatment methods
- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- ·Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

· UN-Number	
· ADR, IMDG, IATA	UN1950
·UN proper shipping name	
ADR	UN1950 AEROSOLS
·IMDG	AEROSOLS
·IATA	AEROSOLS, flammable
 Transport hazard class(es) 	
·ADR	
Class	2 5F Gases.
·Label	2.1
·IMDG, IATA	
· Class	2.1
	Continue on nore 11



Page 11/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

· Label	2.1
· Packing group	Ζ,Ι
· ADR, IMDG, IATA	Void
· Environmental hazards:	Vora
· Marine pollutant:	No
· Special precautions for user	Warning: Gases.
Hazard identification number (Kemler code):	-
· EMS Number:	F-D,S-U
· Segregation groups	Liquid halogenated hydrocarbons
· Stowage Code	SW1 Protected from sources of heat.
	SW2 Clear of living guarters.
·Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.
	For AEROSOLS with a capacity above 1 litre:
	Segregation as for the appropriate subdivision of class 2.
	For WASTE AEROSOLS:
	Segregation as for the appropriate subdivision of class 2.
• Transport in bulk according to Annex II of Marpol	
the IBC Code	Not applicable.
 Transport/Additional information: 	
·ADR	
·Limited quantities (LQ)	1L
· Excepted quantities (EQ)	Code: E0
	Not permitted as Excepted Quantity
· Transport category	2
•Tunnel restriction code	D
·IMDG	
	1L
·Limited quantities (LQ)	
· Limited quantities (LQ) · Excepted quantities (EQ)	Code: E0
· Limited quantities (LQ) · Excepted quantities (EQ)	



Page 12/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

15 Regulatory information

·Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· New Zealand Inventory of Chemicals

All ingredients are listed.

· HSNO Approval numbers

HSNO Number/HSNO Group Standard HSR002515

1330-20-7 xylene: HSR000983

106-97-8 butane, pure: HSR000989

67-64-1 acetone: HSR001070

75-28-5 isobutane: HSR001003

74-98-6 propane: HSR001010

• GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

xylene

butane, pure isobutane

·Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

- H313 May be harmful in contact with skin.
- H333 May be harmful if inhaled.
- H315 Causes skin irritation.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H335 May cause respiratory irritation.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.



Page 13/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

P405 Store locked up.
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- ·National regulations:
- · Information about limitation of use:

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

• Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H303 May be harmful if swallowed.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.

H319 Causes serious eye irritation.

- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.
- H350 May cause cancer.

· Department issuing SDS: Department of Quality Control

· Contact:

EN Chemicals S.A. 57 009 Kalochori Thessalonikil, GREECE T: +30 2310 755 428



Page 14/20

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

F: +30 2310 755 428 info@enchemicals.com www.enchemicals.com • Abbreviations and acronyms: RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail) ICAO: International Civil Aviation Organisation ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent LD50: Lethal dose, 50 percent PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative Flam. Gas 1: Flammable gases – Category 1 Aerosol 1: Aerosols – Category 1 Press. Gas C: Gases under pressure - Compressed gas Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 5: Acute toxicity - oral – Category 5 Acute Tox. 4: Acute toxicity - dermal - Category 4 Acute Tox. 3: Acute toxicity - inhalation - Category 3 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Irrit. 2A: Serious eye damage/eye irritation - Category 2A Muta. 1A: Germ cell mutagenicity – Category 1A Carc. 1A: Carcinogenicity – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 * Data compared to the previous version altered. - N7 -



Page 15/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

Annex: Exposure scenario 1

- · Short title of the exposure scenario
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- · Product category PC9b Fillers, putties, plasters, modelling clay
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- **Description of the activities / processes covered in the Exposure Scenario** See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency** Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Aerosol
- Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.

\cdot Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

\cdot Other operational conditions affecting consumer exposure

No special measures required.

Keep out of the reach of children.

- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment. Ensure that suitable extractors are available on processing machines

· Personal protective measures

Avoid contact with the skin.



Page 16/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

Pregnant women should strictly avoid inhalation or skin contact.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

Keep locked up and out of the reach of children.

· Environmental protection measures

· Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- **Soil** The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- $\cdot \, {\rm Consumer}$ This product is to be used by professional technitians only.
- Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

Continue on page 17

- NZ --



Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

Annex: Exposure scenario 2

 \cdot Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- $\cdot \, {\rm Conditions} \, \, {\rm of} \, {\rm use}$ According to directions for use.
- · Duration and frequency Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.

· Other operational conditions affecting worker exposure

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure No special measures required.
- Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.



Page 18/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

Observe consumer information and advice on safe use.

· Environmental protection measures

· Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- \cdot Soil The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- Exposure estimation
- \cdot Consumer

This product is to be used by professional technitians only. Not relevant for this Exposure Scenario.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

— NZ —



Page 19/20

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

Annex: Exposure scenario 3

 \cdot Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- Conditions of use According to directions for use.
- Duration and frequency Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- · Concentration of the substance in the mixture Raw material.
- · Other operational conditions
- Other operational conditions affecting environmental exposure No special measures required.

· Other operational conditions affecting worker exposure

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure No special measures required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- \cdot Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

• Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Pregnant women should strictly avoid inhalation or skin contact.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

\cdot Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.



Page 20/20

- NZ —

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 4100 PLASTOCLEAR SPRAY

\cdot Environmental protection measures

 \cdot Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

- **Soil** The product is only processed over the concrete collecting basin.
- $\cdot \, {\rm Disposal} \ {\rm measures}$ Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation

\cdot Consumer

This product is to be used by professional technitians only. Not relevant for this Exposure Scenario.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.