

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

* 1 Identification of the substance or mixture and of the supplier

· **Product identifier**

· **Trade name: EN 7600 PAINT REMOVER**

· **Article number:** 1010

· **Relevant identified uses of the substance or mixture and uses advised against**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Environmental release category** ERC2 Formulation into mixture

· **Article category** AC1 Vehicles

· **Application of the substance / the mixture**

Paint remover

Surface protection

· **Details of the supplier of the safety data sheet**

· **Manufacturer/Supplier:**

EN Chemicals S.A.

57 009 Kalochori

Thessalonikil, GREECE

T: +30 2310 755 428

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

· **Further information obtainable from:**

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

· **Emergency telephone number:** NZ Emergency 0800 992 881 (0800WYATT1)

2 Hazards identification

· **Classification of the substance or mixture**



flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.

Continue on page 2

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER



health hazard

Carc. 2 H351 Suspected of causing cancer.

Repr. 1A H360 May damage fertility or the unborn child.

STOT SE 2 H371 May cause damage to the central nervous system and the visual organs.



Acute Tox. 4 H302 Harmful if swallowed.

Acute Tox. 5 H333 May be harmful if inhaled.

Skin Corr. 3 H316 Causes mild skin irritation.

Additional information:

6.1E Substances that are acutely toxic – May be harmful, aspiration hazard

6.3B Substances that are mildly irritating to the skin

Label elements

GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms



GHS02

GHS07

GHS08

Signal word Danger

Hazard-determining components of labelling:

dichloromethane

methanol

toluene

4-methylpentan-2-one

Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H333 May be harmful if inhaled.

H316 Causes mild skin irritation.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

Continue on page 3

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

H371 May cause damage to the central nervous system and the visual organs.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
 P241 Use explosion-proof electrical/ventilating/lighting equipment.
 P260 Do not breathe dust/fume/gas/mist/vapours/spray.
 P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P405 Store locked up.
 P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment













- **PBT:** Not applicable.
 · **vPvB:** Not applicable.

3 Composition/Information on ingredients

· Chemical characterisation: Mixtures

· Description: Mixture of hazardous substances

· Dangerous components:

CAS: 75-09-2	dichloromethane	80- \lt 90%
EINECS: 200-838-9	 Carc. 2, H351	
Index number: 602-004-00-3	 Acute Tox. 4, H302	
RTECS: PA 8050000	 Acute Tox. 5, H333	
CAS: 67-56-1	methanol	5- \lt 10%
EINECS: 200-659-6	 Flam. Liq. 2, H225	
Index number: 603-001-00-X	 Acute Tox. 3, H301; Acute Tox. 3, H311; Acute Tox. 3, H331	
RTECS: PC 1400000	 STOT SE 1, H370	
CAS: 108-10-1	4-methylpentan-2-one	2.5- \lt 5%
EINECS: 203-550-1	 Flam. Liq. 2, H225	
Index number: 606-004-00-4	 Carc. 2, H351	
RTECS: SA 9275000	 Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335	
	Acute Tox. 5, H303	
CAS: 108-88-3	toluene	2.5- \lt 5%
EINECS: 203-625-9	 Flam. Liq. 2, H225	
Index number: 601-021-00-3	 Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304	
RTECS: XS 5250000	 Skin Irrit. 2, H315	
	Acute Tox. 5, H303	
CAS: 8002-74-2	Paraffin waxes and Hydrocarbon waxes	\lt 2.5%
EINECS: 232-315-6		
RTECS: RV 0350000		

Continue on page 4

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:** Supply fresh air; consult doctor in case of complaints.

· **After skin contact:** Immediately rinse with water.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** Call for a doctor immediately.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

5 Fire fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** During heating or in case of fire poisonous gases are produced.

· **Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

· **Speial protective equipment and fire fighting procedures:** Mouth respiratory protective device.

· **Additional information**

Collect contaminated fire fighting water separately. It must not enter the sewage system.

HAZ CHEM CODE: 3YE

6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Mount respiratory protective device.

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Dilute with plenty of water.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Dispose contaminated material as waste according to item 13.

Continue on page 5

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Prevent formation of aerosols.

· **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Keep respiratory protective device available.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:** Store in a cool location.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:**

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

· **Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

75-09-2 dichloromethane

WES (New Zealand) Long-term value: 174 mg/m³, 50 ppm
suspected carcinogen

IOELV (EU) Short-term value: 706 mg/m³, 200 ppm
Long-term value: 353 mg/m³, 100 ppm
Skin

Continue on page 6

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

67-56-1 methanol

WES (New Zealand) Short-term value: 328 mg/m³, 250 ppm
Long-term value: 262 mg/m³, 200 ppm
skin, bio

IOELV (EU) Long-term value: 260 mg/m³, 200 ppm
Skin

108-10-1 4-methylpentan-2-one

WES (New Zealand) Short-term value: 307 mg/m³, 75 ppm
Long-term value: 205 mg/m³, 50 ppm

IOELV (EU) Short-term value: 208 mg/m³, 50 ppm
Long-term value: 83 mg/m³, 20 ppm

108-88-3 toluene

WES (New Zealand) Long-term value: 188 mg/m³, 50 ppm
skin

IOELV (EU) Short-term value: 384 mg/m³, 100 ppm
Long-term value: 192 mg/m³, 50 ppm
Skin

8002-74-2 Paraffin waxes and Hydrocarbon waxes

WES (New Zealand) Long-term value: 2 mg/m³

Regulatory information

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

· **Additional information:** The lists valid during the making were used as basis.

Exposure controls**Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Continue on page 7

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· Eye protection:



Tightly sealed goggles

· **Body protection:** Protective work clothing

9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form:	Fluid
Colour:	According to product specification
· Odour:	Characteristic
· Odour threshold:	Not determined.
· pH-value:	Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 40 °C

Continue on page 8

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

· Flash point:	< 23 °C
· Flammability (solid, gas):	Not applicable.
· Autoignition temperature:	455 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	13 Vol %
Upper:	22 Vol %
· Vapour pressure at 20 °C:	453 hPa
· Density at 20 °C:	1.16 g/cm ³
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not determined.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	97.4 %
VOC (EC)	1,130.3 g/l
Solids content (volume):	2.0 %
· Other information	No further relevant information available.

10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability**
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.

Continue on page 9

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

- **Incompatible materials:** No further relevant information available.
 - **Hazardous decomposition products:** No dangerous decomposition products known.
-

11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**

ATE (Acute Toxicity Estimates)

Oral LD50 1,862 mg/kg (rat)

Inhalative LC50/4 h 23.2-24.2 mg/l

75-09-2 dichloromethane

Oral LD50 1,600 mg/kg (rat)

Inhalative LC50/4 h 88 mg/l (rat)

67-56-1 methanol

Oral LD50 5,628 mg/kg (rat)

Dermal LD50 15,800 mg/kg (rabbit)

Inhalative LC50/4 h 3 mg/l (ATE)

108-10-1 4-methylpentan-2-one

Oral LD50 2,080 mg/kg (rat)

Dermal LD50 16,000 mg/kg (rab)

Inhalative LC50/4 h 8.3-16.6 mg/l (rat)

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 (static) 12,124 mg/kg (rabbit)

Inhalative LC50/4 h 5,320 mg/l (mouse)

- **Primary irritant effect:**
- **Skin corrosion/irritation** No irritant effect.
- **Serious eye damage/irritation** No irritating effect.
- **Respiratory or skin sensitisation** No sensitising effects known.

- **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Continue on page 10

— NZ —

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)Carc. 2, Repr. 1A

12 Ecological information**· Toxicity****· Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· Behaviour in environmental systems:**· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.**· Additional ecological information:****· General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment**· PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).**· vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).**· Other adverse effects** No further relevant information available.

13 Disposal considerations**· Waste treatment methods****· Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Uncleaned packaging:****· Recommendation:** Disposal must be made according to official regulations.**· Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information**· UN-Number****· ADR, IMDG, IATA**

UN1263

Continue on page 11

— NZ —

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

- UN proper shipping name
- ADR
- IMDG, IATA
- Transport hazard class(es)
- ADR

UN1263 PAINT RELATED MATERIAL, special provision 640D
PAINT RELATED MATERIAL



- Class
- Label

3 (F1) Flammable liquids.
3

- IMDG, IATA



- Class
- Label
- Packing group
- ADR, IMDG, IATA
- Environmental hazards:
- Marine pollutant:
- Special precautions for user
- Hazard identification number (Kemler code):
- EMS Number:
- Stowage Category
- Transport in bulk according to Annex II of Marpol and the IBC Code
- Transport/Additional information:

3 Flammable liquids.
3
II
No
Warning: Flammable liquids.
33
F-E,S-E
B
Not applicable.

- ADR
- Limited quantities (LQ)
- Excepted quantities (EQ)
- Transport category

5L
Code: E2
Maximum net quantity per inner packaging: 30 ml
Maximum net quantity per outer packaging: 500 ml
2

Continue on page 12

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

· Tunnel restriction code	D/E
· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
· IATA	
· Remarks:	HAZ CHEM CODE: 3YE
· UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

- 3YE
- **Safety, health and environmental regulations/legislation specific for the substance or mixture**

None of the ingredients is listed.

- **New Zealand Inventory of Chemicals**

75-09-2 dichloromethane

67-56-1 methanol

108-10-1 4-methylpentan-2-one

108-88-3 toluene

8002-74-2 Paraffin waxes and Hydrocarbon waxes

- **HSNO Approval numbers**

HSNO Approval number HSR 002662

Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Hazard classification Refer to section 2

75-09-2 dichloromethane: HSR001540

67-56-1 methanol: HSR001186

108-10-1 4-methylpentan-2-one: HSR001194

108-88-3 toluene: HSR001227

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

Continue on page 13

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER**Hazard pictograms**

GHS02 GHS07 GHS08

Signal word Danger**Hazard-determining components of labelling:**

dichloromethane

methanol

toluene

4-methylpentan-2-one

Hazard statements

H225 Highly flammable liquid and vapour.

H302 Harmful if swallowed.

H333 May be harmful if inhaled.

H316 Causes mild skin irritation.

H351 Suspected of causing cancer.

H360 May damage fertility or the unborn child.

H371 May cause damage to the central nervous system and the visual organs.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Directive 2012/18/EU**Named dangerous substances - ANNEX I** None of the ingredients is listed.**Seveso category** P5c FLAMMABLE LIQUIDS**Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**Chemical safety assessment:** A Chemical Safety Assessment has been carried out.**16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

Continue on page 14

— NZ —

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H301 Toxic if swallowed.
- H302 Harmful if swallowed.
- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H311 Toxic in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H335 May cause respiratory irritation.
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.
- H370 Causes damage to organs.
- H373 May cause damage to organs through prolonged or repeated exposure.

· **Department issuing SDS:** Department of Quality Control

· Contact:

EN Chemicals S.A.
57 009 Kalochori
Thessalonikil, GREECE
T: +30 2310 755 428
F: +30 2310 755 428
info@enchemicals.com
www.enchemicals.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative

Continue on page 15

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

Flam. Liq. 2: Flammable liquids – Category 2
Acute Tox. 3: Acute toxicity - oral – Category 3
Acute Tox. 4: Acute toxicity - oral – Category 4
Acute Tox. 5: Acute toxicity - inhalation – Category 5
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Skin Corr. 3: Skin corrosion/irritation – Category 3
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
Carc. 2: Carcinogenicity – Category 2
Repr. 1A: Reproductive toxicity – Category 1A
STOT SE 1: Specific target organ toxicity (single exposure) – Category 1
STOT SE 2: Specific target organ toxicity (single exposure) – Category 2
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· * Data compared to the previous version altered.

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

Annex: Exposure scenario

- **Short title of the exposure scenario**
- **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- **Product category** PC9a Coatings and paints, thinners, paint removers
- **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- **Article category** AC1 Vehicles
- **Environmental release category** ERC2 Formulation into mixture
- **Description of the activities / processes covered in the Exposure Scenario**
See section 1 of the annex to the Safety Data Sheet.
- **Conditions of use** According to directions for use.
- **Duration and frequency** Frequency of use:
- **Physical parameters**
The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.
- **Physical state** Fluid
- **Concentration of the substance in the mixture** The substance is main component.
- **Other operational conditions**
- **Other operational conditions affecting environmental exposure** No special measures required.
- **Other operational conditions affecting worker exposure**
Avoid contact with the skin.
Do not breathe gas/vapour/aerosol.
Take precautionary measures against static discharge.
Keep away from sources of ignition - No smoking.
- **Other operational conditions affecting consumer exposure** No special measures required.
- **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.
- **Risk management measures**
- **Worker protection**
- **Organisational protective measures**
Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.
- **Technical protective measures**
Provide explosion-proof electrical equipment.
Ensure that suitable extractors are available on processing machines
- **Personal protective measures**
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.

Continue on page 17

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7600 PAINT REMOVER

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

Pregnant women should strictly avoid inhalation or skin contact.

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer** This product is to be used by professional technicians only.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.