

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Page 1/17

1 Identification of the substance or mixture and of the supplier

· Product identifier

- Trade name: EN 7700 NITRO THINNER
- · Article number: 1034

· Relevant identified uses of the substance or mixture and uses advised against

- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- · Environmental release category ERC2 Formulation into mixture
- Article category AC1 Vehicles
- \cdot Application of the substance / the mixture
- Thinner, Diluent
- Surface protection

$\cdot\, \text{Details}$ of the supplier of the safety data sheet

· Manufacturer/Supplier:

EN Chemicals S.A. 57 009 Kalochori Thessalonikil, GREECE T: +30 2310 755 428 F: +30 2310 755 428 info@enchemicals.com www.enchemicals.com

· Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited Address: 388 Church Street, Penrose, Auckland Ph (09) 525 1000; Fax (09) 525 1009

• Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

2 Hazards identification

· Classification of the substance or mixture



Flam. Liq. 2 H225 Highly flammable liquid and vapour.



Page 2/17


Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER



- GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).
- · Hazard pictograms



· Signal word Danger

· Hazard-determining components of labelling:

toluene butan-1-ol

> Continue on page 3 — NZ —



Page 3/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

· Hazard statements

H225 Highly flammable liquid and vapour.

H303 May be harmful if swallowed.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

- Continue rinsing.
- P310 Immediately call a POISON CENTER/doctor.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations. P501

• Other hazards

· Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- **vPvB:** Not applicable.

3 Composition/Information on ingredients

- · Chemical characterisation: Mixtures
- · **Description:** Mixture of hazardous substances

· Dangerous components:

CAS: 108-88-3	toluene	70-<80%
EINECS: 203-625-9 Index number: 601-021-00-3 RTECS: XS 5250000	 Flam. Liq. 2, H225 Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304 Skin Irrit. 2, H315 Acute Tox. 5, H303 	
CAS: 67-64-1 EINECS: 200-662-2 Index number: 606-001-00-8 RTECS: AL 3150000	acetone Flam. Liq. 2, H225 S 🕐 Eye Irrit. 2A, H319; STOT SE 3, H336	10-<15%
		Continue on nora /

Continue on page 4 — NZ —



Page 4/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

CAS: 67-63-0 EINECS: 200-661-7 Index number: 603-117-00-0 RTECS: NT 8050000	propan-2-ol Flam. Liq. 2, H225 Eye Irrit. 2A, H319; STOT SE 3, H336 Acute Tox. 5, H333	5-‹10%
CAS: 71-36-3	butan-1-ol	5-<10%
EINECS: 200-751-6	🔗 Flam. Liq. 3, H226	
Index number: 603-004-00-	6 💫 Eye Dam. 1, H318	
RTECS: EO 1400000	Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336	
	Acute Tox. 5, H313	
·Additional information:	For the wording of the listed hazard phrases refer to section 16.	

4 First aid measures

· Description of first aid measures

· General information:

Immediately remove any clothing soiled by the product.

- Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.
- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- After skin contact: Immediately wash with water and soap and rinse thoroughly.
- After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- ·Information for doctor:
- Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed

Later observation for pneumonia and pulmonary oedema.

5 Fire fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
- Special hazards arising from the substance or mixture During heating or in case of fire poisonous gases are produced. • Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

- Speial protective equipment and fire fighting procedures: Mouth respiratory protective device.
- · Additional information

Collect contaminated fire fighting water separately. It must not enter the sewage system. HAZ CHEM CODE: 3YE

- NZ -



Page 5/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Mount respiratory protective device. Wear protective equipment. Keep unprotected persons away.

• Environmental precautions:

Dilute with plenty of water. Do not allow to enter sewers/ surface or ground water.

• Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Use neutralising agent. Dispose contaminated material as waste according to item 13. Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

7 Handling and storage

·Handling:

· Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care. Prevent formation of aerosols.

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges. Keep respiratory protective device available.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles: Store in a cool location.
- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

• **Specific end use(s)** No further relevant information available.



Page 6/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

8 Exposure controls/personal protection

- · Control parameters
- · Ingredients with limit values that require monitoring at the workplace:

108-88-3 toluene

WES (New Zealand) Long-term value: 188 mg/m³, 50 ppm skin IOELV (EU) Short-term value: 384 mg/m³, 100 ppm Long-term value: 192 mg/m³, 50 ppm

Skin

67-64-1 acetone

WES (New Zealand) Short-term value: 2375 mg/m³, 1000 ppm Long-term value: 1185 mg/m³, 500 ppm bio

IOELV (EU) Long-term value: 1210 mg/m³, 500 ppm

67-63-0 propan-2-ol

WES (New Zealand) Short-term value: 1230 mg/m³, 500 ppm Long-term value: 983 mg/m³, 400 ppm

71-36-3 butan-1-ol

WES (New Zealand) Ceiling limit: 150 mg/m³, 50 ppm skin

· Regulatory information

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices IOELV (EU): (EU) 2019/1831

• Additional information: The lists valid during the making were used as basis.

· Exposure controls

- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work. Store protective clothing separately. Avoid contact with the skin. Avoid contact with the eyes and skin.



Page 7/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- · Penetration time of glove material
- The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Fluid

Characteristic

Not determined.

Not determined.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves

According to product specification

• Eye protection:



Tightly sealed goggles

· Body protection: Protective work clothing

9 Physical and chemical properties

- · Information on basic physical and chemical properties
- · General Information
- Appearance:
 - Form:
 - Colour:
- · Odour:
- · Odour threshold:
- ·pH-value:



Page 8/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

-

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

 Change in condition Melting point/freezing point: Initial boiling point and boiling range 	Undetermined. : 55.8-56.6 °C
·Flash point:	< 0 °C
·Flammability (solid, gas):	Not applicable.
• Autoignition temperature:	340 °C
· Decomposition temperature:	Not determined.
·Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	1.2 Vol %
Upper:	13 Vol %
·Vapour pressure at 20 °C:	233 hPa
· Density at 20 °C:	0.85225 g/cm ³
· Relative density	Not determined.
·Vapour density	Not determined.
· Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Fully miscible.
• Partition coefficient: n-octanol/water:	Not determined.
·Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	100.0 %
VOC (EC)	852.3 g/l
Solids content (volume):	0.0 %
Other information	No further relevant information available.

10 Stability and reactivity

· **Reactivity** No further relevant information available.



Page 9/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

· Chemical stability

- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

·Information on toxicological effects

· Acute toxicity

· LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral	LD50	4,602 mg/kg (rat)
Dermal	LD50	68,000 mg/kg (rabbit)
Inhalative	LC50/4 h	429 mg/l (rat)
108-88-3	toluene	
Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50 (static)	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)
67-64-1 a	cetone	
Oral	LD50	5,800 mg/kg (rat)
Dermal	LD50	20,000 mg/kg (rabbit)

67-63-0 propan-2-ol

Oral	LD50	5,045 mg/kg (rat)
Dermal	LD50	12,800 mg/kg (rabbit)
Inhalative	LC50/4 h	30 mg/l (rat)

71-36-3 butan-1-ol

Oral	LD50	790 mg/kg (rat)
Dermal	LD50	3,400 mg/kg (rabbit)

Inhalative LC50/4 h 8,000 mg/l (rat)

· Primary irritant effect:

• Skin corrosion/irritation Irritant to skin and mucous membranes.

• Serious eye damage/irritation Strong irritant with the danger of severe eye injury.



Page 10/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

• **Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.

·Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Repr. 1A

12 Ecological information

· Toxicity

• Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- · Behaviour in environmental systems:
- · **Bioaccumulative potential** No further relevant information available.
- · Mobility in soil No further relevant information available.
- ·Additional ecological information:

General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

· Results of PBT and vPvB assessment

- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **Other adverse effects** No further relevant information available.

*13 Disposal considerations

- · Waste treatment methods
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.



Page 11/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

-

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

• Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information · UN-Number	
· ADR, IMDG, IATA	UN1263
· UN proper shipping name	
ADR	UN1263 PAINT RELATED MATERIAL, special provision 640D
· IMDG, IATA	PAINT RELATED MATERIAL
·Transport hazard class(es)	
·ADR	
· Class	3 (F1) Flammable liquids.
·Label	3
·IMDG, IATA	
·Class	3 Flammable liquids.
·Label	3
· Packing group	
· ADR, IMDG, IATA	II
· Environmental hazards:	
· Marine pollutant:	No
 Special precautions for user 	Warning: Flammable liquids.
• Hazard identification number (Kemler code):	33
· EMS Number:	F-E, <u>S-E</u>
· Stowage Category	В
• Transport in bulk according to Annex II of Marpol	
the IBC Code	Not applicable.
	Continue on page 1



Page 12/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

• Transport/Additional information:	
ADR	
·Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
Transport category	2
Tunnel restriction code	D/E
IMDG	
Limited quantities (LQ)	5L
Excepted quantities (EQ)	Code: E2
	Maximum net quantity per inner packaging: 30 ml
	Maximum net quantity per outer packaging: 500 ml
IATA	
Remarks:	HAZ CHEM CODE: 3YE
·UN "Model Regulation":	UN 1263 PAINT RELATED MATERIAL, SPECIAL PROVISION 640D, 3, II

15 Regulatory information

•3YE

· Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

• New Zealand Inventory of Chemicals

All ingredients are listed.

· HSNO Approval numbers

HSNO Approval numberHSR 002662Group standard nameSurface Coatings and Colourandts (Flammable) Group Standard 2006HSNO Hazard classificationRefer to section 2

108-88-3 toluene: HSR001227

67-64-1 acetone: HSR001070

67-63-0 propan-2-ol: HSR001180

71-36-3 butan-1-ol: HSR001096

• GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).



Page 13/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

· Hazard pictograms



· Signal word Danger

• Hazard-determining components of labelling: toluene

butan-1-ol

· Hazard statements

H225 Highly flammable liquid and vapour.

H303 May be harmful if swallowed.

H333 May be harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H360 May damage fertility or the unborn child.

H336 May cause drowsiness or dizziness.

H373 May cause damage to organs through prolonged or repeated exposure.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

- P310 Immediately call a POISON CENTER/doctor.
- P321 Specific treatment (see on this label).
- P362+P364 Take off contaminated clothing and wash it before reuse.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.
- · Directive 2012/18/EU
- \cdot Named dangerous substances ANNEX I None of the ingredients is listed.
- \cdot Seveso category <code>P5c FLAMMABLE LIQUIDS</code>
- \cdot Qualifying quantity (tonnes) for the application of lower-tier requirements $_{5,000\,t}$
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000~t

Continue on page 14

- N7 -



Page 14/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eye irritation.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

• **Department issuing SDS:** Department of Quality Control

· Contact:

EN Chemicals S.A. 57 009 Kalochori Thessalonikil, GREECE T: +30 2310 755 428 F: +30 2310 755 428 info@enchemicals.com www.enchemicals.com

• Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

 ${\sf CAS: Chemical \ Abstracts \ Service \ (division \ of \ the \ American \ Chemical \ Society)}$

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic



Page 15/17

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

vPvB: very Persistent and very Bioaccumulative Flam. Liq. 2: Flammable liquids – Category 2 Flam. Liq. 3: Flammable liquids – Category 3 Acute Tox. 4: Acute toxicity - oral – Category 4 Acute Tox. 5: Acute toxicity - oral – Category 5 Skin Irrit. 2: Skin corrosion/irritation – Category 2 Eye Dam. 1: Serious eye damage/eye irritation – Category 1 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A Repr. 1A: Reproductive toxicity – Category 1A STOT SE 3: Specific target organ toxicity (single exposure) – Category 2 Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

Continue on page 16

— NZ —



Page 16/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

Annex: Exposure scenario

- \cdot Short title of the exposure scenario
- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites
- Product category PC9a Coatings and paints, thinners, paint removers
- Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities
- · Article category AC1 Vehicles
- · Environmental release category ERC2 Formulation into mixture
- **Description of the activities / processes covered in the Exposure Scenario** See section 1 of the annex to the Safety Data Sheet.
- Conditions of use According to directions for use.
- Duration and frequency Frequency of use:
- Worker Permanent use with exposure up to 8 hrs every work day of the week.
- · Environment Indoor use
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Fluid
- Concentration of the substance in the mixture The substance is main component.
- \cdot Used amount per time or activity <code>According</code> to directions for use.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- · Other operational conditions affecting worker exposure

Avoid contact with eyes.

Avoid contact with the skin.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

- · Other operational conditions affecting consumer exposure No special measures required.
- · Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Do not inhale gases / fumes / aerosols.



Page 17/17

Safety Data Sheet

in accordance with HSNO Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 7700 NITRO THINNER

Avoid contact with the skin.

Avoid contact with the eyes.

Pregnant women should strictly avoid inhalation or skin contact.

Tightly sealed goggles

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Observe consumer information and advice on safe use.

• Environmental protection measures

· Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point. Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

- **Soil** The product is only processed over the concrete collecting basin.
- **Disposal measures** Ensure that waste is collected and contained.
- **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging

· Exposure estimation

- Worker (oral) Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.
- Worker (dermal) Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.
- Worker (inhalation) Detailed information on the exposure estimation can be found at http://www.ecetoc.org/tra.

· Environment

Detailed information on the estimation of the environmental exposure can be found at http://ecb.jrc.ec.europa.eu/euses/.

• **Consumer** This product is to be used by professional technitians only.

· Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.