



2100 RAPID SEALANT



Product Description:

- Rubber and solvent based sealant
- Anticorrosive properties
- Non shrinkink - Non cracking
- Excellent adhesion to primed metal and painted surfaces

EN 2100 RAPID SEALANT

Pretreatment Cleaning:

Surface:

- Primed metal
- Painted surfaces
- Interior of car doors
- Engine compartments
- Head light interiors

Product Application:



Apply with a cartridge gun




Protect from humidity



or
Application with brush



Close tin after use



Flash off
15-20 min / 23°C



Use protective equipment



Drying time
2-3h / 23°C
at 200µm



Product application should be done in
accordance to this
Technical Data Sheet



2K Acrylic Paints
Synthetic Paints
Basecoat Paints

EN 2100 RAPID SEALANT

Flash Point:

-26 °C/ -15°F

Specific Gravity:

1.10 g/ cm³

Solid Content (No thinner):

61% Weight

VOC (2004/42/EC)

2004/42/IIB(e)(840)280

The EU limit value for this product category in ready for use form is max 840 g/l of VOC. The VOC value of this product in ready for use form is max. 280 g/l.

Theoretical Coverage:

-

Cleaning of equipment:

Clean after use with EN 7100 SOLVENT NORMAL
EN 7700 NITRO THINNER

Remarks:

- Allow additional time for preheating up to panel temperature
- Suitable for filling and sealing visible joint and seams against corrosion
- It can be used by countries that do not adopt the VOC legislation as well.
- Store in a cool place.
Shelf life of 24 months in sealed containers.

For professional use only. The information provided on this sheet has been carefully selected through a series of laboratory researches. It is based upon our best knowledge at the time of issue. This data is only for information purposes. We are not liable for its correctness, accuracy and completeness. It is up to the user to check for updates or further information if needed for his purpose. The intellectual property of the product, trademarks and copyrights is protected. All rights reserved. The relevant Material Safety Data Sheet and warnings displayed on the label must be read carefully. We may modify and / or discontinue operation of all or portions of this information at any time in our sole discretion, without any notice and assume no responsibility to update the information. All rules set forth in this clause shall apply accordingly for any future changes and amendments.

Version 1, Dec 2011.