

Safety Data Sheet Page 1/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

1 Identification of the substance or mixture and of the supplier

- · Product identifier
- · Trade name: EN SPRAY HEADLIGHT CLEAR
- · Article number: 984
- · Relevant identified uses of the substance or mixture and uses advised against
- Sector of Use SU17 General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment
- · Product category PC9a Coatings and paints, thinners, paint removers
- · Process category PROC7 Industrial spraying
- · Environmental release category ERC2 Formulation into mixture
- · Article category AC1 Vehicles
- · Application of the substance / the mixture Surface protection
- · Details of the supplier of the safety data sheet
- · Manufacturer/Supplier:

EN Chemicals S.A.

57 009 Kalochori

Thessalonikil, GREECE

T: +30 2310 755 428

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

· Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

· Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

2 Hazards identification

· Classification of the substance or mixture



Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



Repr. 1A H360 May damage fertility or the unborn child.



Page 2/17 Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR



Eye Dam. 1 H318 Causes serious eye damage.



Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

May be harmful if swallowed. Acute Tox. 5 H303 Acute Tox. 5 H333 May be harmful if inhaled.

· Additional information:

6.1E Substances that are acutely toxic – May be harmful, aspiration hazard

6.3A Substances that are irritating to the skin

2.1.2A Flammable aerosol

8.3A Substances that are corrosive to ocular tissue

· Label elements

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms









GHS02 GHS05

GHS07 GHS08

· Signal word Danger

· Hazard-determining components of labelling:

butanol

butan-1-ol

1-methoxy-2-propanol

toluene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H303 May be harmful if swallowed. H333 May be harmful if inhaled. Causes skin irritation. H315 H318 Causes serious eye damage.



Safety Data Sheet Page 3/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

H360 May damage fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

3 Composition/Information on ingredients

· Chemical characterisation: Mixtures

· **Description:** Mixture of hazardous substances

Dangerous components:

CAS: 115-10-6 dimethyl ether 40-<45%

EINECS: 204-065-8 Flam. Gas 1, H220 Index number: 603-019-00-8 Press. Gas C, H280 Acute Tox. 5, H333

CAS: 78-83-1 butanol 15-<20%

EINECS: 201-148-0 Flam. Liq. 3, H226 Index number: 603-108-00-1 Eye Dam. 1, H318

RTECS: NP 9625000 Škin Irrit. 2, H315; STOT SE 3, H335-H336

Acute Tox. 5, H303; Acute Tox. 5, H313



Safety Data Sheet Page 4/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

CAS: 71-36-3 butan-1-ol 10-<15%

EINECS: 200-751-6 Flam. Liq. 3, H226 Index number: 603-004-00-6 Eye Dam. 1, H318

RTECS: EO 1400000 Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336

Acute Tox. 5, H313

CAS: 67-63-0 propan-2-ol 5-<10%

RTECS: NT 8050000 Acute Tox. 5, H333

CAS: 108-88-3 toluene 5-<10%

EINECS: 203-625-9 Flam. Liq. 2, H225

Index number: 601-021-00-3 (Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304

RTECS: XS 5250000 Škin Irrit. 2, H315

Acute Tox. 5, H303

CAS: 107-98-2 1-methoxy-2-propanol 2.5-<5%

EINECS: 203-539-1 Flam. Liq. 3, H226 Index number: 603-064-00-3 Acute Tox. 3, H331 RTECS: UB 7700000 STOT SE 3, H336

• Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

- · Description of first aid measures
- · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

- After inhalation: In case of unconsciousness place patient stably in side position for transportation.
- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- · Information for doctor:
- · Most important symptoms and effects, both acute and delayed No further relevant information available.
- · Indication of any immediate medical attention and special treatment needed No further relevant information available.

5 Fire fighting measures

- · Extinguishing media
- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.



Safety Data Sheet
Page 5/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

- · Special hazards arising from the substance or mixture No further relevant information available.
- · Advice for firefighters

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

- · Speial protective equipment and fire fighting procedures: No special measures required.
- · Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

· Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- · Methods and material for containment and cleaning up:

Use neutralising agent.

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

- · Handling:
- · Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

Information about fire - and explosion protection:

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

- · Conditions for safe storage, including any incompatibilities
- · Storage:
- Requirements to be met by storerooms and receptacles:

Observe official regulations on storing packagings with pressurised containers.

- · Information about storage in one common storage facility: Not required.
- Further information about storage conditions: Keep container tightly sealed.



Safety Data Sheet Page 6/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

· Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

- · Control parameters
- Ingredients with limit values that require monitoring at the workplace:

115-10-6 dimethyl ether

WES (New Zealand) Short-term value: 958 mg/m³, 500 ppm

Long-term value: 766 mg/m³, 400 ppm

IOELV (EU) Long-term value: 1920 mg/m³, 1000 ppm

78-83-1 butanol

WES (New Zealand) Long-term value: 152 mg/m³, 50 ppm

71-36-3 butan-1-ol

WES (New Zealand) Ceiling limit: 150 mg/m³, 50 ppm

skin

67-63-0 propan-2-ol

WES (New Zealand) Short-term value: 1230 mg/m³, 500 ppm

Long-term value: 983 mg/m³, 400 ppm

108-88-3 toluene

WES (New Zealand) Long-term value: 188 mg/m³, 50 ppm

skin

IOELV (EU) Short-term value: 384 mg/m³, 100 ppm

Long-term value: 192 mg/m³, 50 ppm

Skin

107-98-2 1-methoxy-2-propanol

WES (New Zealand) Short-term value: 553 mg/m³, 150 ppm

Long-term value: 369 mg/m³, 100 ppm

IOELV (EU) Short-term value: 568 mg/m³, 150 ppm

Long-term value: 375 mg/m³, 100 ppm

Skin

· Regulatory information

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

· Additional information: The lists valid during the making were used as basis.



Safety Data Sheet
Page 7/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

- · Exposure controls
- · Personal protective equipment:
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

- For the permanent contact gloves made of the following materials are suitable: Fluorocarbon rubber (Viton)
- · For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable: Rubber gloves
- · Eye protection:

Safety glasses



Tightly sealed goggles

· Body protection: Protective work clothing



Safety Data Sheet Page 8/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

9 Physical and chemical properties

Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Aerosol
Colour: Colourless
Odour: Characteristic
Odour threshold: Not determined.

pH-value: Not determined.

· Change in condition

Melting point/freezing point: Undetermined. Initial boiling point and boiling range: -24.9 °C

·Flash point: < 0 °C

· Flammability (solid, gas): Not applicable.

• Autoignition temperature: 235 °C

• **Decomposition temperature:** Not determined.

• Auto-ignition temperature: Product is not selfigniting.

• **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

 Lower:
 1.5 Vol %

 Upper:
 18.6 Vol %

· Vapour pressure at 20 °C: 5 hPa

Density at 20 °C: 0.78111 g/cm³
 Relative density Not determined.
 Vapour density Not determined.
 Evaporation rate Not applicable.

· Solubility in / Miscibility with

water: Fully miscible.Partition coefficient: n-octanol/water: Not determined.

· Viscosity:

Dynamic:Not determined.
Kinematic:
Not determined.



Safety Data Sheet Page 9/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

· Solvent content:

Organic solvents: 92.7% VOC (EC) 835.0 g/l Solids content (volume): 0.3%

• Other information No further relevant information available.

10 Stability and reactivity

- · Reactivity No further relevant information available.
- · Chemical stability
- Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Possibility of hazardous reactions No dangerous reactions known.
- · Conditions to avoid No further relevant information available.
- · Incompatible materials: No further relevant information available.
- · Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological information

- · Information on toxicological effects
- · Acute toxicity
- · LD/LC50 values relevant for classification:

ATE (Acute Toxicity Estimates)

Oral LD50 4,355 mg/kg (rat)
Dermal LD50 11,701 mg/kg (rabbit)

Inhalative LC50/4 h 82.6 mg/l (rat)

115-10-6 dimethyl ether

Inhalative LC50/4 h 308 mg/l (rat)

78-83-1 butanol

Oral LD50 2,460 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rabbit)

71-36-3 butan-1-ol

 Oral
 LD50
 790 mg/kg (rat)

 Dermal
 LD50
 3,400 mg/kg (rabbit)

 Inhalative LC50/4 h
 8,000 mg/l (rat)



Safety Data Sheet Page 10/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

67-63-0 propan-2-ol

Oral LD50 5,045 mg/kg (rat)

Dermal LD50 12,800 mg/kg (rabbit)

Inhalative LC50/4 h 30 mg/l (rat)

108-88-3 toluene

Oral LD50 5,000 mg/kg (rat)

Dermal LD50 (static) 12,124 mg/kg (rabbit)

Inhalative LC50/4 h 5,320 mg/l (mouse)

107-98-2 1-methoxy-2-propanol

 Oral
 LD50
 5,660 mg/kg (rat)

 Dermal
 LD50
 13,000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Irritant to skin and mucous membranes.
- **Serious eye damage/irritation** Strong irritant with the danger of severe eye injury.
- · **Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.
- · Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

Repr. 1A

12 Ecological information

- ·Toxicity
- · Aquatic toxicity:

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This prouduct contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

- · Behaviour in environmental systems:
- · Bioaccumulative potential No further relevant information available.
- · Mobility in soil No further relevant information available.



Safety Data Sheet Page 11/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

· Additional ecological information:

· General notes:

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

- · Results of PBT and vPvB assessment
- · PBT: This product contains no substance that is considered to be persistent, bioaccumulating or non toxic(PBT).
- · vPvB: Not applicable.
- · Other adverse effects No further relevant information available.

*13 Disposal considerations

- · Waste treatment methods
- · **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Uncleaned packaging:
- **Recommendation:** Disposal must be made according to official regulations.
- · Recommended cleansing agents: Water, if necessary together with cleansing agents.

14 Transport information

- · UN-Number
- · ADR, IMDG, IATA
- · UN proper shipping name

· ADR

·IMDG

·IATA

· Transport hazard class(es)

·ADR



UN1950

UN1950 AEROSOLS

AEROSOLS

AEROSOLS, flammable

· Class 2 5F Gases.



Page 12/17 Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

·Label 2.1

· IMDG, IATA



·Class 2.1 ·Label 2.1

· Packing group

· ADR, IMDG, IATA Void

· Environmental hazards:

· Marine pollutant:

· Special precautions for user Warning: Gases.

· Hazard identification number (Kemler code):

· EMS Number: F-D,S-U

· Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:

Segregation as for class 9. Stow "separated from" class 1 except for

division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

·Transport in bulk according to Annex II of Marpol and

the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· Transport category D

· Tunnel restriction code

·IMDG

· Limited quantities (LQ) 1L



Safety Data Sheet Page 13/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

• Excepted quantities (EQ) Code: E0

Not permitted as Excepted Quantity

· UN "Model Regulation": UN 1950 AEROSOLS, 2.1

15 Regulatory information

· Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· New Zealand Inventory of Chemicals

All ingredients are listed.

· HSNO Approval numbers

HSNO Number/HSNO Group Standard HSR002515

115-10-6 dimethyl ether: HSR000995

78-83-1 butanol: HSR001097

71-36-3 butan-1-ol: HSR001096

67-63-0 propan-2-ol: HSR001180

108-88-3 toluene: HSR001227

107-98-2 1-methoxy-2-propanol: HSR001187

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

· Hazard pictograms









GHS02

O2 GH

GHS05

GHS07

· Signal word Danger

· Hazard-determining components of labelling:

butanol

butan-1-ol

1-methoxy-2-propanol

toluene

· Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.

H303 May be harmful if swallowed.H333 May be harmful if inhaled.H315 Causes skin irritation.



Safety Data Sheet Page 14/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

H318 Causes serious eve damage.

H360 May damage fertility or the unborn child.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

· Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.
- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 500 t
- · Chemical safety assessment: A Chemical Safety Assessment has been carried out.

16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

H225 Highly flammable liquid and vapour.

H226 Flammable liquid and vapour.

H280 Contains gas under pressure; may explode if heated.

H302 Harmful if swallowed.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H319 Causes serious eve irritation.

H331 Toxic if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.



Safety Data Sheet Page 15/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

H336 May cause drowsiness or dizziness.

H360 May damage fertility or the unborn child.

H373 May cause damage to organs through prolonged or repeated exposure.

· Contact:

EN Chemicals S.A.

57 009 Kalochori

Thessalonikil, GREECE

T: +30 2310 755 428

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases — Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids — Category 3

Acute Tox. 4: Acute toxicity - oral - Category 4

Acute Tox. 3: Acute toxicity - inhalation - Category 3

Acute Tox. 5: Acute toxicity - inhalation – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Repr. 1A: Reproductive toxicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

* Data compared to the previous version altered.

- N7 -



Safety Data Sheet Page 16/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

Annex: Exposure scenario

- · Short title of the exposure scenario
- · Sector of Use SU17 General manufacturing, e.g. machinery, equipment, vehicles, other transport equipment
- · **Product category** PC9a Coatings and paints, thinners, paint removers
- · Process category PROC7 Industrial spraying
- · Article category AC1 Vehicles
- Environmental release category ERC2 Formulation into mixture
- · Description of the activities / processes covered in the Exposure Scenario

See section 1 of the annex to the Safety Data Sheet.

- · Conditions of use According to directions for use.
- · Duration and frequency Frequency of use:
- · Physical parameters

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

- · Physical state Aerosol
- · Concentration of the substance in the mixture The substance is main component.
- · Other operational conditions
- · Other operational conditions affecting environmental exposure No special measures required.
- ·Other operational conditions affecting worker exposure

Avoid contact with eyes.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

- · Other operational conditions affecting consumer exposure Keep out of the reach of children.
- ·Other operational conditions affecting consumer exposure during the use of the product Not applicable.
- · Risk management measures
- · Worker protection
- · Organisational protective measures

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· Technical protective measures

Provide explosion-proof electrical equipment.

Ensure that suitable extractors are available on processing machines

· Personal protective measures

Avoid contact with the eyes.

Pregnant women should strictly avoid inhalation or skin contact.

Tightly sealed goggles



Safety Data Sheet
Page 17/17

in accordance with HSNO

Printing date: 11.06.2020 Version no. 1 Revision date: 11.06.2020

Trade name: EN SPRAY HEADLIGHT CLEAR

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture. Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· Measures for consumer protection

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

· Environmental protection measures

·Water

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point. Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

- · **Soil** The product is only processed over the concrete collecting basin.
- · Disposal measures Ensure that waste is collected and contained.
- Disposal procedures Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- · Waste type Partially emptied and uncleaned packaging
- · Exposure estimation
- · Consumer This product is to be used by professional technitians only.
- · Guidance for downstream users

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.

NZ -