

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

### \* 1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: **EN SPRAY UNICOLOR WHITE GLOSS**

· Article number: 1021

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

· Application of the substance / the mixture Surface protection

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

EN Chemicals S.A.

57 009 Kalochori

Thessaloniki, GREECE

T: +30 2310 755 428

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

· Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

· Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

### 2 Hazards identification

· Classification of the substance or mixture



flame

Aerosol 1 H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.



health hazard

Continue on page 2

# Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

## Trade name: EN SPRAY UNICOLOR WHITE GLOSS

Muta. 1A	H340	May cause genetic defects.
Carc. 1A	H350	May cause cancer.
Repr. 1A	H360	May damage fertility or the unborn child.



Skin Irrit. 2	H315	Causes skin irritation.
Skin Sens. 1	H317	May cause an allergic skin reaction.
STOT SE 3	H335	May cause respiratory irritation.
Acute Tox. 5	H333	May be harmful if inhaled.
Aquatic Acute 3	H402	Harmful to aquatic life.
Aquatic Chronic 3	H412	Harmful to aquatic life with long lasting effects.

· **Additional information:**

- 6.1E Substances that are acutely toxic – May be harmful, aspiration hazard
- 6.3A Substances that are irritating to the skin
- 9.1D Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action
- 9.1C Substances that are harmful in the aquatic environment
- 2.1.2A Flammable aerosol
- 6.3A Substances that are irritating to the skin
- 6.9 (Respiratory tract irritant)
- 9.1D Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action
- 6.6A Substances that are known or presumed human mutagens
- 6.7A Substances that are known or presumed human carcinogens

· **Label elements**

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**



GHS02    GHS07    GHS08

· **Signal word** Danger

· **Hazard-determining components of labelling:**

butane, pure  
toluene

Continue on page 3

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

### Trade name: EN SPRAY UNICOLOR WHITE GLOSS

n-butyl acrylate  
xylene  
isobutane

#### · Hazard statements

H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.  
H333 May be harmful if inhaled.  
H315 Causes skin irritation.  
H317 May cause an allergic skin reaction.  
H340 May cause genetic defects.  
H350 May cause cancer.  
H360 May damage fertility or the unborn child.  
H335 May cause respiratory irritation.  
H412 Harmful to aquatic life with long lasting effects.

#### · Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.  
P405 Store locked up.  
P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

#### · Other hazards

#### · Results of PBT and vPvB assessment







· **PBT:** Not applicable.  
· **vPvB:** Not applicable.

## 3 Composition/Information on ingredients

#### · Chemical characterisation: Mixtures

· **Description:** Mixture of hazardous substances

#### · Dangerous components:

CAS: 106-97-8	butane, pure	30-35%
EINECS: 203-448-7	 Flam. Gas 1, H220	
Index number: 601-004-00-0	 Press. Gas C, H280	
RTECS: EJ 4200000	 Acute Tox. 3, H331	
	 Muta. 1A, H340; Carc. 1A, H350	
CAS: 1330-20-7	xylene	15-20%
EINECS: 215-535-7	 Flam. Liq. 3, H226	
Index number: 601-022-00-9	 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	
RTECS: ZE 2100000	Acute Tox. 5, H303	

Continue on page 4

## Safety Data Sheet



in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

### Trade name: EN SPRAY UNICOLOR WHITE GLOSS

CAS: 64742-95-6	Solvent naphtha (petroleum), light arom.	5-<10%
EINECS: 265-199-0	 Flam. Liq. 3, H226	
Index number: 649-356-00-4	 Asp. Tox. 1, H304	
	 Aquatic Chronic 2, H411	
	 Acute Tox. 4, H332; STOT SE 3, H335-H336	
	Acute Tox. 5, H313; Aquatic Acute 2, H401	
CAS: 108-88-3	toluene	5-<10%
EINECS: 203-625-9	 Flam. Liq. 2, H225	
Index number: 601-021-00-3	 Repr. 1A, H360; STOT RE 2, H373; Asp. Tox. 1, H304	
RTECS: XS 5250000	 Skin Irrit. 2, H315	
	Acute Tox. 5, H303	
CAS: 471-34-1	calcium carbonate	5-<10%
EINECS: 207-439-9		
RTECS: EV 9580000		
CAS: 75-28-5	isobutane	2.5-<5%
EINECS: 200-857-2	 Flam. Gas 1, H220	
Index number: 601-004-00-0	 Press. Gas C, H280	
RTECS: TZ 4300000	 Muta. 1A, H340; Carc. 1A, H350	
CAS: 74-98-6	propane	2.5-<5%
EINECS: 200-827-9	 Flam. Gas 1, H220	
Index number: 601-003-00-5	 Press. Gas C, H280	
RTECS: TX 2275000		
CAS: 67-64-1	acetone	<2.5%
EINECS: 200-662-2	 Flam. Liq. 2, H225	
Index number: 606-001-00-8	 Eye Irrit. 2A, H319; STOT SE 3, H336	
RTECS: AL 3150000		
CAS: 141-32-2	n-butyl acrylate	≥1-<2.5%
EINECS: 205-480-7	 Flam. Liq. 3, H226	
Index number: 607-062-00-3	 Acute Tox. 4, H302; Acute Tox. 4, H312; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; Skin Sens. 1, H317; STOT SE 3, H335	
RTECS: UD 3150000		
CAS: 100-42-5	styrene	≥0.1-<2.5%
EINECS: 202-851-5	 Flam. Liq. 3, H226	
Index number: 601-026-00-0	 Carc. 2, H351; Repr. 2, H361d; STOT RE 2, H373	
RTECS: WL 3675000	 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319; STOT SE 3, H335	
	Acute Tox. 5, H303	

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

### 4 First aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air and to be sure call for a doctor.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

· **After swallowing:** If symptoms persist consult doctor.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

---

### 5 Fire fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products

· **Speial protective equipment and fire fighting procedures:** No special measures required.

· **Additional information** Collect contaminated fire fighting water separately. It must not enter the sewage system.

---

### 6 Accidental release measures

· **Personal precautions, protective equipment and emergency procedures**

Wear protective equipment. Keep unprotected persons away.

· **Environmental precautions:**

Do not allow product to reach sewage system or any water course.

Inform respective authorities in case of seepage into water course or sewage system.

Do not allow to enter sewers/ surface or ground water.

· **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to item 13.

Ensure adequate ventilation.

· **Reference to other sections**

See Section 7 for information on safe handling.

Continue on page 6

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

---

## 7 Handling and storage

· **Handling:**

· **Precautions for safe handling**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

· **Information about fire - and explosion protection:**

Do not spray onto a naked flame or any incandescent material.

Keep ignition sources away - Do not smoke.

Keep respiratory protective device available.

Pressurised container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.

· **Conditions for safe storage, including any incompatibilities**

· **Storage:**

· **Requirements to be met by storerooms and receptacles:**

Observe official regulations on storing packagings with pressurised containers.

· **Information about storage in one common storage facility:** Not required.

· **Further information about storage conditions:** Keep container tightly sealed.

· **Specific end use(s)** No further relevant information available.

---

## 8 Exposure controls/personal protection

· **Control parameters**

· **Ingredients with limit values that require monitoring at the workplace:**

106-97-8 butane, pure

WES (New Zealand) Long-term value: 1900 mg/m<sup>3</sup>, 800 ppm

1330-20-7 xylene

WES (New Zealand) Long-term value: 217 mg/m<sup>3</sup>, 50 ppm

IOELV (EU) Short-term value: 442 mg/m<sup>3</sup>, 100 ppm

Long-term value: 221 mg/m<sup>3</sup>, 50 ppm

Skin

Continue on page 7

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

**108-88-3 toluene**WES (New Zealand) Long-term value: 188 mg/m<sup>3</sup>, 50 ppm  
skinIOELV (EU) Short-term value: 384 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 192 mg/m<sup>3</sup>, 50 ppm  
Skin**471-34-1 calcium carbonate**WES (New Zealand) Long-term value: 10 mg/m<sup>3</sup>**74-98-6 propane**

WES (New Zealand) Simple asphyxiant; may present an explosion hazard

**67-64-1 acetone**WES (New Zealand) Short-term value: 2375 mg/m<sup>3</sup>, 1000 ppm  
Long-term value: 1185 mg/m<sup>3</sup>, 500 ppm  
bioIOELV (EU) Long-term value: 1210 mg/m<sup>3</sup>, 500 ppm**141-32-2 n-butyl acrylate**WES (New Zealand) Short-term value: 22 mg/m<sup>3</sup>, 4 ppm  
Long-term value: 11 mg/m<sup>3</sup>, 2 ppmIOELV (EU) Short-term value: 53 mg/m<sup>3</sup>, 10 ppm  
Long-term value: 11 mg/m<sup>3</sup>, 2 ppm**100-42-5 styrene**WES (New Zealand) Short-term value: 170 mg/m<sup>3</sup>, 40 ppm  
Long-term value: 85 mg/m<sup>3</sup>, 20 ppm  
suspected carcinogen**Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

**Additional information:** The lists valid during the making were used as basis.**Exposure controls****Personal protective equipment:****General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Store protective clothing separately.

Continue on page 8

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

### Trade name: EN SPRAY UNICOLOR WHITE GLOSS

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**

Safety glasses



Tightly sealed goggles

· **Body protection:** Protective work clothing

## \* 9 Physical and chemical properties

· **Information on basic physical and chemical properties**

· **General Information**

· **Appearance:**

**Form:** Aerosol

**Colour:** According to product specification

· **Odour:** Characteristic

Continue on page 9



## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

· Odour threshold:	Not determined.
· pH-value:	Not determined.
· Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	-44.5 °C
· Flash point:	< 0 °C
· Flammability (solid, gas):	Not applicable.
· Autoignition temperature:	365 °C
· Decomposition temperature:	Not determined.
· Auto-ignition temperature:	Product is not selfigniting.
· Explosive properties:	Risk of explosion by shock, friction, fire or other sources of ignition.
· Explosion limits:	
Lower:	1.1 Vol %
Upper:	8.5 Vol %
· Vapour pressure at 20 °C:	2,100 hPa
· Density:	Not determined.
· Relative density	Not determined.
· Vapour density	Not determined.
· Evaporation rate	Not applicable.
· Solubility in / Miscibility with water:	Fully miscible.
· Partition coefficient: n-octanol/water:	Not determined.
· Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
· Solvent content:	
Organic solvents:	75.5 %
VOC (EC)	794.3-794.4 g/l
Solids content (volume):	19.3 %
· Other information	No further relevant information available.

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

### 10 Stability and reactivity

- **Reactivity** No further relevant information available.
  - **Chemical stability**
  - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
  - **Possibility of hazardous reactions** No dangerous reactions known.
  - **Conditions to avoid** No further relevant information available.
  - **Incompatible materials:** No further relevant information available.
  - **Hazardous decomposition products:** No dangerous decomposition products known.
- 

### 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity**
- **LD/LC50 values relevant for classification:**

#### ATE (Acute Toxicity Estimates)

Oral	LD50	13,249 mg/kg (rat)
Dermal	LD50	>7,641 mg/kg
Inhalative	LC50/4 h	>36.3 mg/l

#### 106-97-8 butane, pure

Inhalative	LC50/4 h	658 mg/l (rat)
------------	----------	----------------

#### 1330-20-7 xylene

Oral	LD50	4,300 mg/kg (rat)
Dermal	LD50	2,000 mg/kg (rabbit)
Inhalative	LC50/4 h	11 mg/l (ATE)

#### 64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6,800 mg/kg (rat)
Dermal	LD50	>3,400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

#### 108-88-3 toluene

Oral	LD50	5,000 mg/kg (rat)
Dermal	LD50 (static)	12,124 mg/kg (rabbit)
Inhalative	LC50/4 h	5,320 mg/l (mouse)

#### 471-34-1 calcium carbonate

Oral	LD50	6,450 mg/kg (rat)
------	------	-------------------

Continue on page 11

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

**67-64-1 acetone**

Oral LD50 5,800 mg/kg (rat)

Dermal LD50 20,000 mg/kg (rabbit)

**141-32-2 n-butyl acrylate**

Oral LD50 900 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

**100-42-5 styrene**

Oral LD50 5,000 mg/kg (rat)

Inhalative LC50/4 h 24 mg/l (rat)

**· Primary irritant effect:****· Skin corrosion/irritation** Irritant to skin and mucous membranes.**· Serious eye damage/irritation** No irritating effect.**· Respiratory or skin sensitisation**

Sensitisation possible through skin contact.

Sensitising effect through inhalation is possible by prolonged exposure.

**· Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

**· CMR effects (carcinogenicity, mutagenicity and toxicity for reproduction)**

Muta. 1A, Carc. 1A, Repr. 1A

---

**12 Ecological information****· Toxicity****· Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**· Persistence and degradability**

This product contains polyestheric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

**· Behaviour in environmental systems:****· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.

Continue on page 12

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **Additional ecological information:**

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

· **Results of PBT and vPvB assessment**

· **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).

· **vPvB:** Not applicable.

· **Other adverse effects** No further relevant information available.

### \* 13 Disposal considerations

· **Waste treatment methods**

· **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

· **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

### 14 Transport information

· UN-Number

· ADR, IMDG, IATA

UN1950

· UN proper shipping name

· ADR

UN1950 AEROSOLS

· IMDG

AEROSOLS

· IATA

AEROSOLS, flammable

· Transport hazard class(es)

· ADR



· Class

2 5F Gases.

Continue on page 13

# Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

· Label 2.1

· IMDG, IATA



· Class 2.1

· Label 2.1

· Packing group

· ADR, IMDG, IATA Void

· Environmental hazards:

· Marine pollutant: No

· Special precautions for user Warning: Gases.

· Hazard identification number (Kemler code): -

· EMS Number: F-D,S-U

· Stowage Code SW1 Protected from sources of heat.

SW2 Clear of living quarters.

· Segregation Code SG69 For AEROSOLS with a maximum capacity of 1 litre:  
Segregation as for class 9. Stow "separated from" class 1 except for division 1.4.

For AEROSOLS with a capacity above 1 litre:

Segregation as for the appropriate subdivision of class 2.

For WASTE AEROSOLS:

Segregation as for the appropriate subdivision of class 2.

· Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· ADR

· Limited quantities (LQ) 1L

· Excepted quantities (EQ) Code: E0  
Not permitted as Excepted Quantity

· Transport category 2

· Tunnel restriction code D

· IMDG

· Limited quantities (LQ) 1L

Continue on page 14

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

**· Excepted quantities (EQ)**

Code: E0

**· UN "Model Regulation":**

Not permitted as Excepted Quantity

UN 1950 AEROSOLS, 2.1

---

## 15 Regulatory information

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

---

None of the ingredients is listed.

**· New Zealand Inventory of Chemicals**

---

106-97-8 butane, pure

1330-20-7 xylene

64742-95-6 Solvent naphtha (petroleum), light arom.

108-88-3 toluene

471-34-1 calcium carbonate

75-28-5 isobutane

74-98-6 propane

67-64-1 acetone

141-32-2 n-butyl acrylate

100-42-5 styrene

1330-20-7 xylene

100-41-4 ethylbenzene

78-83-1 butanol

**· HSNO Approval numbers**

HSNO Number/HSNO Group Standard HSR002515

106-97-8 butane, pure: HSR000989

1330-20-7 xylene: HSR000983

64742-95-6 Solvent naphtha (petroleum), light arom.: HSR001503

108-88-3 toluene: HSR001227

471-34-1 calcium carbonate: HSR006678

75-28-5 isobutane: HSR001003

74-98-6 propane: HSR001010

67-64-1 acetone: HSR001070

141-32-2 n-butyl acrylate: HSR001100

100-42-5 styrene: HSR001221

Continue on page 15

**Safety Data Sheet**

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

- **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).
- **Hazard pictograms**



GHS02 GHS07 GHS08

- **Signal word** Danger
- **Hazard-determining components of labelling:**
  - butane, pure
  - toluene
  - n-butyl acrylate
  - xylene
  - isobutane

**· Hazard statements**

- H222-H229 Extremely flammable aerosol. Pressurised container: May burst if heated.
- H333 May be harmful if inhaled.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H360 May damage fertility or the unborn child.
- H335 May cause respiratory irritation.
- H412 Harmful to aquatic life with long lasting effects.

**· Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P304+P312 IF INHALED: Call a POISON CENTER/doctor if you feel unwell.
- P405 Store locked up.
- P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**· Directive 2012/18/EU**

- **Named dangerous substances - ANNEX I** None of the ingredients is listed.
- **Seveso category** P3a FLAMMABLE AEROSOLS
- **Qualifying quantity (tonnes) for the application of lower-tier requirements** 150 t
- **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

Continue on page 16

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

**· National regulations:****· Information about limitation of use:**

Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation. Exceptions can be made by the authorities in certain cases.

**· Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

---

**16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**· Relevant phrases**

- H220 Extremely flammable gas.
- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H280 Contains gas under pressure; may explode if heated.
- H302 Harmful if swallowed.
- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H313 May be harmful in contact with skin.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H331 Toxic if inhaled.
- H332 Harmful if inhaled.
- H335 May cause respiratory irritation.
- H336 May cause drowsiness or dizziness.
- H340 May cause genetic defects.
- H350 May cause cancer.
- H351 Suspected of causing cancer.
- H360 May damage fertility or the unborn child.
- H361d Suspected of damaging the unborn child.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H401 Toxic to aquatic life.
- H411 Toxic to aquatic life with long lasting effects.

**· Contact:**

EN Chemicals S.A.  
57 009 Kalochori  
Thessalonikil, GREECE  
T: +30 2310 755 428

Continue on page 17



## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

### Trade name: EN SPRAY UNICOLOR WHITE GLOSS

---

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

#### · Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Gas 1: Flammable gases – Category 1

Aerosol 1: Aerosols – Category 1

Press. Gas C: Gases under pressure – Compressed gas

Flam. Liq. 2: Flammable liquids – Category 2

Flam. Liq. 3: Flammable liquids – Category 3

Acute Tox. 5: Acute toxicity - oral – Category 5

Acute Tox. 4: Acute toxicity - dermal – Category 4

Acute Tox. 3: Acute toxicity - inhalation – Category 3

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

Skin Sens. 1: Skin sensitisation – Category 1

Muta. 1A: Germ cell mutagenicity – Category 1A

Carc. 1A: Carcinogenicity – Category 1A

Carc. 2: Carcinogenicity – Category 2

Repr. 1A: Reproductive toxicity – Category 1A

Repr. 2: Reproductive toxicity – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Acute 3: Hazardous to the aquatic environment - acute aquatic hazard – Category 3

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

#### · \* Data compared to the previous version altered.

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN SPRAY UNICOLOR WHITE GLOSS**

---

### Annex: Exposure scenario

· **Short title of the exposure scenario**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Article category** AC1 Vehicles

· **Environmental release category** ERC2 Formulation into mixture

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Aerosol

· **Concentration of the substance in the mixture** The substance is main component.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** Use only on hard ground.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Avoid long-term or repeated skin contact.

Do not breathe aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** Keep out of the reach of children.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Provide explosion-proof electrical equipment.

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

· **Personal protective measures**

Avoid contact with the skin.

Continue on page 19

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

### Trade name: EN SPRAY UNICOLOR WHITE GLOSS

---

Pregnant women should strictly avoid inhalation or skin contact.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · **Measures for consumer protection**

Ensure adequate labelling.

Keep locked up and out of the reach of children.

Observe consumer information and advice on safe use.

#### · **Environmental protection measures**

##### · **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

##### · **Soil**

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

· **Disposal measures** Ensure that waste is collected and contained.

· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

#### · **Exposure estimation**

· **Consumer** This product is to be used by professional technicians only.

#### · **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.