

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

* 1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: **EN 2K WHITE**

· Article number: 1027

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

· Application of the substance / the mixture Surface protection

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

EN Chemicals S.A.

57 009 Kalochori

Thessaloniki, GREECE

T: +30 2310 755 428

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

· Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

· Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

2 Hazards identification

· Classification of the substance or mixture



flame

Flam. Liq. 3 H226 Flammable liquid and vapour.



Continue on page 2

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

Acute Tox. 4 H332 Harmful if inhaled.

Skin Irrit. 2 H315 Causes skin irritation.

STOT SE 3 H335 May cause respiratory irritation.

Additional information:

3.1B Flammable liquid

6.3A Substances that are irritating to the skin

6.3A Substances that are irritating to the skin

6.9 (Respiratory tract irritant)

Label elements

GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms

GHS02 GHS07

Signal word Warning

Hazard-determining components of labelling:

xylene

ethylbenzene

2-butoxyethyl acetate

Hazard statements

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H335 May cause respiratory irritation.

Precautionary statements

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P241 Use explosion-proof electrical/ventilating/lighting equipment.

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards**Results of PBT and vPvB assessment**

PBT: Not applicable.

Continue on page 3

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE








· **vPvB:** Not applicable.

3 Composition/Information on ingredients

· **Chemical characterisation:** Mixtures

· **Description:** Mixture of hazardous substances

· **Dangerous components:**

CAS: 13463-67-7	titanium dioxide	25- \lt 30%
EINECS: 236-675-5	Acute Tox. 5, H333	
CAS: 1330-20-7	xylene	20- \lt 25%
EINECS: 215-535-7	 Flam. Liq. 3, H226	
Index number: 601-022-00-9	 Acute Tox. 4, H312; Acute Tox. 4, H332; Skin Irrit. 2, H315; STOT SE 3, H335	
RTECS: ZE 2100000	Acute Tox. 5, H303	
CAS: 100-41-4	ethylbenzene	5- \lt 10%
EINECS: 202-849-4	 Flam. Liq. 2, H225	
Index number: 601-023-00-4	 STOT RE 2, H373; Asp. Tox. 1, H304	
RTECS: DA 0700000	 Acute Tox. 4, H332; Skin Irrit. 2, H315; Eye Irrit. 2A, H319	
	Acute Tox. 5, H303	
CAS: 108-65-6	2-methoxy-1-methylethyl acetate	2.5- \lt 5%
EINECS: 203-603-9	 Flam. Liq. 3, H226	
Index number: 607-195-00-7	Acute Tox. 5, H333	
CAS: 112-07-2	2-butoxyethyl acetate	\lt 2.5%
EINECS: 203-933-3	 Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332	
Index number: 607-038-00-2	Flam. Liq. 4, H227	
RTECS: KJ 8925000		

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

4 First aid measures

· **Description of first aid measures**

· **General information:**

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

· **After inhalation:**

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

· **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

· **After eye contact:** Rinse opened eye for several minutes under running water.

Continue on page 4

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: **EN 2K WHITE**

- **After swallowing:** If symptoms persist consult doctor.
 - **Information for doctor:**
 - **Most important symptoms and effects, both acute and delayed** No further relevant information available.
 - **Indication of any immediate medical attention and special treatment needed** No further relevant information available.
-

* 5 Fire fighting measures

- **Extinguishing media**
 - **Suitable extinguishing agents:** CO₂, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - **Special hazards arising from the substance or mixture** No further relevant information available.
 - **Advice for firefighters**
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
 - **Speial protective equipment and fire fighting procedures:** Mouth respiratory protective device.
 - **Additional information**
Collect contaminated fire fighting water separately. It must not enter the sewage system.
HAZ CHEM CODE: 3YE
-

* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**
Wear protective equipment. Keep unprotected persons away.
 - **Environmental precautions:**
Dilute with plenty of water.
Do not allow to enter sewers/ surface or ground water.
 - **Methods and material for containment and cleaning up:**
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
 - **Reference to other sections**
See Section 7 for information on safe handling.
See Section 8 for information on personal protection equipment.
See Section 13 for disposal information.
-

7 Handling and storage

- **Handling:**
- **Precautions for safe handling**
Ensure good ventilation/exhaustion at the workplace.
Prevent formation of aerosols.

Continue on page 5

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

· Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.

· Conditions for safe storage, including any incompatibilities**· Storage:****· Requirements to be met by storerooms and receptacles:** No special requirements.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:** Keep container tightly sealed.**· Specific end use(s)** No further relevant information available.

8 Exposure controls/personal protection

· Control parameters**· Ingredients with limit values that require monitoring at the workplace:****1330-20-7 xylene**WES (New Zealand) Long-term value: 217 mg/m³, 50 ppmIOELV (EU) Short-term value: 442 mg/m³, 100 ppm
Long-term value: 221 mg/m³, 50 ppm
Skin**100-41-4 ethylbenzene**WES (New Zealand) Short-term value: 543 mg/m³, 125 ppm
Long-term value: 434 mg/m³, 100 ppmIOELV (EU) Short-term value: 884 mg/m³, 200 ppm
Long-term value: 442 mg/m³, 100 ppm
Skin**108-65-6 2-methoxy-1-methylethyl acetate**IOELV (EU) Short-term value: 550 mg/m³, 100 ppm
Long-term value: 275 mg/m³, 50 ppm
Skin**112-07-2 2-butoxyethyl acetate**IOELV (EU) Short-term value: 333 mg/m³, 50 ppm
Long-term value: 133 mg/m³, 20 ppm
Skin**· Regulatory information**

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

Continue on page 6

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

· **Additional information:** The lists valid during the making were used as basis.

· **Exposure controls**

· **Personal protective equipment:**

· **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

· **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

· **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

· **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

· **Eye protection:**



Tightly sealed goggles

· **Body protection:** Protective work clothing

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

* 9 Physical and chemical properties

· Information on basic physical and chemical properties

· General Information

· Appearance:

Form: Fluid
Colour: According to product specification

· **Odour:** Characteristic

· **Odour threshold:** Not determined.

· **pH-value:** Not determined.

· Change in condition

Melting point/freezing point: Undetermined.

Initial boiling point and boiling range: 136 °C

· **Flash point:** 23 - 60 °C

· **Flammability (solid, gas):** Not applicable.

· **Autoignition temperature:** 430 °C

· **Decomposition temperature:** Not determined.

· **Auto-ignition temperature:** Product is not selfigniting.

· **Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.

· Explosion limits:

Lower: 1.1 Vol %

Upper: 7 Vol %

· **Vapour pressure at 20 °C:** 6.7 hPa

· **Density at 20 °C:** 1.23 g/cm³

· **Relative density:** Not determined.

· **Vapour density:** Not determined.

· **Evaporation rate:** Not determined.

· **Solubility in / Miscibility with water:** Fully miscible.

· **Partition coefficient: n-octanol/water:** Not determined.

· Viscosity:

Dynamic: Not determined.

Kinematic: Not determined.

Continue on page 8

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

· Solvent content:

Organic solvents:	37.3 %
VOC (EC)	459.2 g/l

Solids content (volume):	62.7 %
--------------------------	--------

· Other information No further relevant information available.

10 Stability and reactivity

· Reactivity No further relevant information available.**· Chemical stability****· Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**· Possibility of hazardous reactions** No dangerous reactions known.**· Conditions to avoid** No further relevant information available.**· Incompatible materials:** No further relevant information available.**· Hazardous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· Information on toxicological effects**· Acute toxicity****· LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Oral LD50 11,847 mg/kg (rat)

Dermal LD50 7,265 mg/kg (rabbit)

Inhalative LC50/4 h >14.7 mg/l

13463-67-7 titanium dioxide

Oral LD50 >20,000 mg/kg (rat)

Dermal LD50 >10,000 mg/kg (rabbit)

Inhalative LC50/4 h >6.82 mg/l (rat)

1330-20-7 xylene

Oral LD50 4,300 mg/kg (rat)

Dermal LD50 2,000 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

100-41-4 ethylbenzene

Oral LD50 3,500 mg/kg (rat)

Continue on page 9

— NZ —

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

Dermal LD50 17,800 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

108-65-6 2-methoxy-1-methylethyl acetate

Oral LD50 8,532 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

112-07-2 2-butoxyethyl acetate

Oral LD50 2,400 mg/kg (rat)

Dermal LD50 1,580 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

· Primary irritant effect:**· Skin corrosion/irritation** Irritant to skin and mucous membranes.**· Serious eye damage/irritation** No irritating effect.**· Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.**· Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

12 Ecological information

· Toxicity**· Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

· Persistence and degradability

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

· Behaviour in environmental systems:**· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.**· Additional ecological information:****· General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Continue on page 10

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

Danger to drinking water if even small quantities leak into the ground.


· Results of PBT and vPvB assessment

- **PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).
- **vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).
- **Other adverse effects** No further relevant information available.

* 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agents:** Water, if necessary together with cleansing agents.

14 Transport information

- UN-Number
 - ADR, IMDG, IATA UN1263
 - UN proper shipping name
 - ADR UN1263 PAINT
 - IMDG, IATA PAINT
 - Transport hazard class(es)
 - ADR
-
- 
- Class 3 (F1) Flammable liquids.
 - Label 3

- IMDG, IATA
-
- 
- Class 3 Flammable liquids.
 - Label 3

Continue on page 11

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: **EN 2K WHITE**

· Packing group	
· ADR, IMDG, IATA	III
· Environmental hazards:	
· Marine pollutant:	No
· Special precautions for user	Warning: Flammable liquids.
· Hazard identification number (Kemler code):	30
· EMS Number:	F-E, <u>S</u> -E
· Stowage Category	A
· Transport in bulk according to Annex II of Marpol and the IBC Code	Not applicable.
· Transport/Additional information:	

· ADR	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml
· Transport category	3
· Tunnel restriction code	D/E

· IMDG	
· Limited quantities (LQ)	5L
· Excepted quantities (EQ)	Code: E1 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 1000 ml

· IATA	
· Remarks:	HAZ CHEM CODE: 3YE
· UN "Model Regulation":	UN 1263 PAINT, 3, III

15 Regulatory information

•3Y

· Safety, health and environmental regulations/legislation specific for the substance or mixture

None of the ingredients is listed.

· New Zealand Inventory of Chemicals

13463-67-7 titanium dioxide

1330-20-7 xylene

Continue on page 12

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

100-41-4 ethylbenzene

108-65-6 2-methoxy-1-methylethyl acetate

112-07-2 2-butoxyethyl acetate

125229-74-5 Copolymer of vinyl alcohol and vinyl acetate partially acetylated with 4-(2-(4-formylphenyl)ethenyl)-1-methyl-pyridinium methylsulfate

123-86-4 n-butyl acetate

122-99-6 2-Phenoxyethanol

95-63-6 1,2,4-trimethylbenzene

108-67-8 mesitylene

526-73-8 1,2,3-trimethylbenzene

98-82-8 cumene

103-65-1 propylbenzene

71-43-2 benzene

· HSNO Approval numbers

HSNO Approval number HSR 002662

Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006

HSNO Hazard classification Refer to section 2

1330-20-7 xylene: HSR000983

100-41-4 ethylbenzene: HSR001151

108-65-6 2-methoxy-1-methylethyl acetate: HSR001219

112-07-2 2-butoxyethyl acetate: HSR001155

· GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).**· Hazard pictograms**

GHS02 GHS07

· Signal word Warning**· Hazard-determining components of labelling:**

xylene

ethylbenzene

2-butoxyethyl acetate

Continue on page 13

— NZ —

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

· Hazard statements

- H226 Flammable liquid and vapour.
- H332 Harmful if inhaled.
- H315 Causes skin irritation.
- H335 May cause respiratory irritation.

· Precautionary statements

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.
- P241 Use explosion-proof electrical/ventilating/lighting equipment.
- P261 Avoid breathing dust/fume/gas/mist/vapours/spray.
- P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P405 Store locked up.
- P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· Directive 2012/18/EU**· Named dangerous substances - ANNEX I** None of the ingredients is listed.**· Seveso category** P5c FLAMMABLE LIQUIDS**· Qualifying quantity (tonnes) for the application of lower-tier requirements** 5,000 t**· Qualifying quantity (tonnes) for the application of upper-tier requirements** 50,000 t**· Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

***16 Other information**

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

- H225 Highly flammable liquid and vapour.
- H226 Flammable liquid and vapour.
- H227 Combustible liquid.
- H302 Harmful if swallowed.
- H303 May be harmful if swallowed.
- H304 May be fatal if swallowed and enters airways.
- H312 Harmful in contact with skin.
- H315 Causes skin irritation.
- H319 Causes serious eye irritation.
- H332 Harmful if inhaled.
- H333 May be harmful if inhaled.
- H335 May cause respiratory irritation.
- H373 May cause damage to the hearing organs through prolonged or repeated exposure.

· Department issuing SDS: Department of Quality Control

Continue on page 14

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

· Contact:

EN Chemicals S.A.
57 009 Kalochori
Thessalonikil, GREECE
T: +30 2310 755 428
F: +30 2310 755 428
info@enchemicals.com
www.enchemicals.com

· Abbreviations and acronyms:

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)
ICAO: International Civil Aviation Organisation
ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)
IMDG: International Maritime Code for Dangerous Goods
IATA: International Air Transport Association
EINECS: European Inventory of Existing Commercial Chemical Substances
ELINCS: European List of Notified Chemical Substances
CAS: Chemical Abstracts Service (division of the American Chemical Society)
VOC: Volatile Organic Compounds (USA, EU)
LC50: Lethal concentration, 50 percent
LD50: Lethal dose, 50 percent
PBT: Persistent, Bioaccumulative and Toxic
vPvB: very Persistent and very Bioaccumulative
Flam. Liq. 2: Flammable liquids – Category 2
Flam. Liq. 3: Flammable liquids – Category 3
Flam. Liq. 4: Flammable liquids – Category 4
Acute Tox. 4: Acute toxicity - dermal – Category 4
Acute Tox. 5: Acute toxicity - inhalation – Category 5
Skin Irrit. 2: Skin corrosion/irritation – Category 2
Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A
STOT SE 3: Specific target organ toxicity (single exposure) – Category 3
STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2
Asp. Tox. 1: Aspiration hazard – Category 1

· * Data compared to the previous version altered.

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

Annex: Exposure scenario

· **Short title of the exposure scenario**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Article category** AC1 Vehicles

· **Environmental release category** ERC2 Formulation into mixture

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency**

5 workdays/week.

Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** The substance is main component.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** No special measures required.

· **Other operational conditions affecting worker exposure**

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

No special measures required.

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Continue on page 16

Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

Trade name: EN 2K WHITE

Avoid contact with the skin.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

· **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

· **Environmental protection measures**

· **Water**

No special measures required.

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

· **Soil** The product is only processed over the concrete collecting basin.

· **Disposal measures**

Disposal must be made according to official regulations.

Ensure that waste is collected and contained.

· **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **Waste type** Partially emptied and uncleaned packaging

· **Exposure estimation**

· **Consumer**

Not relevant for this Exposure Scenario.

This product is to be used by professional technicians only.

· **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.