

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

### \* 1 Identification of the substance or mixture and of the supplier

· Product identifier

· Trade name: **EN 7200 SLOW ACRYLIC THINNER**

· Article number: 1003

· Relevant identified uses of the substance or mixture and uses advised against

· Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· Product category PC9a Coatings and paints, thinners, paint removers

· Process category PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· Environmental release category ERC2 Formulation into mixture

· Article category AC1 Vehicles

· Application of the substance / the mixture

Thinner, Diluent

Surface protection

· Details of the supplier of the safety data sheet

· Manufacturer/Supplier:

EN Chemicals S.A.

57 009 Kalochori

Thessalonikil, GREECE

T: +30 2310 755 428

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

· Further information obtainable from:

Wyatt Machine Tools (Rupes) NZ Limited

Address: 388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

· Emergency telephone number: NZ Emergency 0800 992 881 (0800WYATT1)

### 2 Hazards identification

· Classification of the substance or mixture



flame

Flam. Liq. 3

H226

Flammable liquid and vapour.

Continue on page 2

# Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---



corrosion

Eye Dam. 1      H318      Causes serious eye damage.



environment

Aquatic Chronic 2 H411      Toxic to aquatic life with long lasting effects.



Acute Tox. 4      H332      Harmful if inhaled.

Skin Irrit. 2      H315      Causes skin irritation.

STOT SE 3      H335-H336      May cause respiratory irritation. May cause drowsiness or dizziness.

Aquatic Acute 2      H401      Toxic to aquatic life.

**Additional information:**

3.1B Flammable liquid

6.3A Substances that are irritating to the skin

8.3A Substances that are corrosive to ocular tissue

**Label elements****GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).**Hazard pictograms**

GHS02

GHS05

GHS07

GHS09

**Signal word** Danger**Hazard-determining components of labelling:**

Solvent naphtha (petroleum), light arom.

butan-1-ol

1-methoxy-2-propanol

2-butoxyethyl acetate

**Hazard statements**

H226      Flammable liquid and vapour.

Continue on page 3

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

- H332 Harmful if inhaled.  
H315 Causes skin irritation.  
H318 Causes serious eye damage.  
H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.  
H411 Toxic to aquatic life with long lasting effects.

**· Precautionary statements**

- P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.  
P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P310 Immediately call a POISON CENTER/doctor.  
P321 Specific treatment (see on this label).  
P362+P364 Take off contaminated clothing and wash it before reuse.  
P405 Store locked up.  
P501 Dispose of contents/container in accordance with local/regional/national/international regulations.


**· Other hazards****· Results of PBT and vPvB assessment**

- **PBT:** Not applicable.  
· **vPvB:** Not applicable.

---

### 3 Composition/Information on ingredients

**· Chemical characterisation: Mixtures****· Description:** Mixture of hazardous substances**· Dangerous components:**

|                            |  |        |
|----------------------------|--|--------|
| CAS: 123-86-4              | n-butyl acetate  | 30-35% |
| EINECS: 204-658-1          |  Flam. Liq. 3, H226 |        |
| Index number: 607-025-00-1 |  STOT SE 3, H336    |        |
| RTECS: AF 7350000          | Acute Tox. 5, H333   |        |

Continue on page 4

— NZ —

## Safety Data Sheet













in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

### Trade name: EN 7200 SLOW ACRYLIC THINNER

|                            |   |         |
|----------------------------|---|---------|
| CAS: 64742-95-6            | Solvent naphtha (petroleum), light arom.  | 30-<35% |
| EINECS: 265-199-0          |  Flam. Liq. 3, H226  |         |
| Index number: 649-356-00-4 |  Asp. Tox. 1, H304   |         |
|                            |  Aquatic Chronic 2, H411                                       |         |
|                            |  Acute Tox. 4, H332; STOT SE 3, H335-H336                      |         |
|                            | Acute Tox. 5, H313; Aquatic Acute 2, H401   |         |
| CAS: 71-36-3               | butan-1-ol  | 10-<15% |
| EINECS: 200-751-6          |  Flam. Liq. 3, H226  |         |
| Index number: 603-004-00-6 |  Eye Dam. 1, H318  |         |
| RTECS: EO 1400000          |  Acute Tox. 4, H302; Skin Irrit. 2, H315; STOT SE 3, H335-H336 |         |
|                            | Acute Tox. 5, H313  |         |
| CAS: 107-98-2              | 1-methoxy-2-propanol  | 10-<15% |
| EINECS: 203-539-1          |  Flam. Liq. 3, H226  |         |
| Index number: 603-064-00-3 |  Acute Tox. 3, H331  |         |
| RTECS: UB 7700000          |  STOT SE 3, H336  |         |
| CAS: 108-65-6              | 2-methoxy-1-methylethyl acetate   | 10-<15% |
| EINECS: 203-603-9          |  Flam. Liq. 3, H226  |         |
| Index number: 607-195-00-7 | Acute Tox. 5, H333  |         |
| CAS: 112-07-2              | 2-butoxyethyl acetate   | 10-<15% |
| EINECS: 203-933-3          |  Acute Tox. 4, H302; Acute Tox. 4, H312; Acute Tox. 4, H332  |         |
| Index number: 607-038-00-2 | Flam. Liq. 4, H227  |         |
| RTECS: KJ 8925000          |   |         |

· **Additional information:** For the wording of the listed hazard phrases refer to section 16.

## 4 First aid measures

### · Description of first aid measures

#### · General information:

Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

#### · After inhalation:

Supply fresh air. If required, provide artificial respiration. Keep patient warm. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

#### · After skin contact: Immediately wash with water and soap and rinse thoroughly.

#### · After eye contact: Rinse opened eye for several minutes under running water. Then consult a doctor.

#### · After swallowing: If symptoms persist consult doctor.

#### · Information for doctor:

#### · Most important symptoms and effects, both acute and delayed No further relevant information available.

Continue on page 5

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

---

· **Indication of any immediate medical attention and special treatment needed** No further relevant information available.

---

### \* 5 Fire fighting measures

- **Extinguishing media**
  - **Suitable extinguishing agents:** CO<sub>2</sub>, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
  - **Special hazards arising from the substance or mixture** No further relevant information available.
  - **Advice for firefighters**  
Firefighters should always protective equipment and breathing apparatus when handling fire coming from these products
  - **Speial protective equipment and fire fighting procedures:** Mouth respiratory protective device.
  - **Additional information**  
Collect contaminated fire fighting water separately. It must not enter the sewage system.  
HAZ CHEM CODE: 3YE
- 

### \* 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
  - **Environmental precautions:**  
Do not allow product to reach sewage system or any water course.  
Inform respective authorities in case of seepage into water course or sewage system.  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
  - **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralising agent.  
Dispose contaminated material as waste according to item 13.  
Ensure adequate ventilation.
  - **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.
- 

### 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.

Continue on page 6

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

**· Information about fire - and explosion protection:**

Keep ignition sources away - Do not smoke.  
Protect against electrostatic charges.

**· Conditions for safe storage, including any incompatibilities****· Storage:****· Requirements to be met by storerooms and receptacles:** Unsuitable material for receptacle: glass or ceramic.**· Information about storage in one common storage facility:** Not required.**· Further information about storage conditions:** Keep container tightly sealed.**· Specific end use(s)** No further relevant information available.

---

## 8 Exposure controls/personal protection

**· Control parameters****· Ingredients with limit values that require monitoring at the workplace:****123-86-4 n-butyl acetate**

WES (New Zealand) Short-term value: 950 mg/m<sup>3</sup>, 200 ppm  
Long-term value: 713 mg/m<sup>3</sup>, 150 ppm

IOELV (EU) Short-term value: 723 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 241 mg/m<sup>3</sup>, 50 ppm

**71-36-3 butan-1-ol**

WES (New Zealand) Ceiling limit: 150 mg/m<sup>3</sup>, 50 ppm  
skin

**107-98-2 1-methoxy-2-propanol**

WES (New Zealand) Short-term value: 553 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 369 mg/m<sup>3</sup>, 100 ppm

IOELV (EU) Short-term value: 568 mg/m<sup>3</sup>, 150 ppm  
Long-term value: 375 mg/m<sup>3</sup>, 100 ppm  
Skin

**108-65-6 2-methoxy-1-methylethyl acetate**

IOELV (EU) Short-term value: 550 mg/m<sup>3</sup>, 100 ppm  
Long-term value: 275 mg/m<sup>3</sup>, 50 ppm  
Skin

**112-07-2 2-butoxyethyl acetate**

IOELV (EU) Short-term value: 333 mg/m<sup>3</sup>, 50 ppm  
Long-term value: 133 mg/m<sup>3</sup>, 20 ppm  
Skin

Continue on page 7

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

### Trade name: EN 7200 SLOW ACRYLIC THINNER

---

#### · Regulatory information

WES (New Zealand): Workplace Exposure Standards and Biological Exposure Indices

IOELV (EU): (EU) 2019/1831

· **Additional information:** The lists valid during the making were used as basis.

#### · Exposure controls

#### · Personal protective equipment:

#### · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the skin.

Avoid contact with the eyes and skin.

#### · Respiratory protection:

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

#### · Protection of hands:



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### · Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

· **For the permanent contact gloves made of the following materials are suitable:** Fluorocarbon rubber (Viton)

· **For the permanent contact of a maximum of 15 minutes gloves made of the following materials are suitable:**

Rubber gloves

#### · Eye protection:



Tightly sealed goggles

Continue on page 8

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

---

**· Body protection:** Protective work clothing

---

### \* 9 Physical and chemical properties

**· Information on basic physical and chemical properties****· General Information****· Appearance:**

**Form:** Fluid  
**Colour:** According to product specification

**· Odour:** Characteristic**· Odour threshold:** Not determined.**· pH-value:** Not determined.**· Change in condition**

**Melting point/freezing point:** Undetermined.

**Initial boiling point and boiling range:** 116-118 °C

**· Flash point:** 23 - 60 °C**· Flammability (solid, gas):** Not applicable.**· Autoignition temperature:** 270 °C**· Decomposition temperature:** Not determined.**· Auto-ignition temperature:** Product is not selfigniting.**· Explosive properties:** Risk of explosion by shock, friction, fire or other sources of ignition.**· Explosion limits:**

**Lower:** 0.7 Vol %

**Upper:** 20 Vol %

**· Vapour pressure at 20 °C:** 12 hPa**· Density at 20 °C:** 0.89288 g/cm<sup>3</sup>**· Relative density** Not determined.**· Vapour density** Not determined.**· Evaporation rate** Not determined.**· Solubility in / Miscibility with water:**

Fully miscible.

**· Partition coefficient: n-octanol/water:** Not determined.

Continue on page 9

— NZ —



## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

**· Viscosity:****Dynamic:** Not determined.**Kinematic:** Not determined.**· Solvent content:****Organic solvents:** 100.0 %**VOC (EC)** 892.9 g/l**Solids content (volume):** 0.0 %**· Other information** No further relevant information available.

---

## 10 Stability and reactivity

**· Reactivity** No further relevant information available.**· Chemical stability****· Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.**· Possibility of hazardous reactions** No dangerous reactions known.**· Conditions to avoid** No further relevant information available.**· Incompatible materials:** No further relevant information available.**· Hazardous decomposition products:** No dangerous decomposition products known.

---

## 11 Toxicological information

**· Information on toxicological effects****· Acute toxicity****· LD/LC50 values relevant for classification:****ATE (Acute Toxicity Estimates)**

Oral LD50 5,944 mg/kg (rat)

Dermal LD50 &gt;5,527 mg/kg

Inhalative LC50/4 h &gt;13.8 mg/l

**123-86-4 n-butyl acetate**

Oral LD50 13,100 mg/kg (rat)

Dermal LD50 &gt;5,000 mg/kg (rabbit)

Inhalative LC50/4 h &gt;21 mg/l (rat)

**64742-95-6 Solvent naphtha (petroleum), light arom.**

Oral LD50 &gt;6,800 mg/kg (rat)

Dermal LD50 &gt;3,400 mg/kg (rab)

Continue on page 10

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

Inhalative LC50/4 h &gt;10.2 mg/l (rat)

**71-36-3 butan-1-ol**

Oral LD50 790 mg/kg (rat)

Dermal LD50 3,400 mg/kg (rabbit)

Inhalative LC50/4 h 8,000 mg/l (rat)

**107-98-2 1-methoxy-2-propanol**

Oral LD50 5,660 mg/kg (rat)

Dermal LD50 13,000 mg/kg (rabbit)

Inhalative LC50/4 h 6 mg/l (rat)

**108-65-6 2-methoxy-1-methylethyl acetate**

Oral LD50 8,532 mg/kg (rat)

Inhalative LC50/4 h 35.7 mg/l (rat)

**112-07-2 2-butoxyethyl acetate**

Oral LD50 2,400 mg/kg (rat)

Dermal LD50 1,580 mg/kg (rabbit)

Inhalative LC50/4 h 11 mg/l (ATE)

**· Primary irritant effect:****· Skin corrosion/irritation** Irritant to skin and mucous membranes.**· Serious eye damage/irritation** Strong irritant with the danger of severe eye injury.**· Respiratory or skin sensitisation** Sensitising effect through inhalation is possible by prolonged exposure.**· Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Harmful

Irritant

---

## 12 Ecological information

**· Toxicity****· Aquatic toxicity:**

This product is not toxic for the aquatic life. Nevertheless do not dispose the product or any cleaning solvents used along with this product into the sea

**· Persistence and degradability**

This product contains polyesteric molecules and organic solvents and is not known to be bioaccumulative. It can be considered as biodegradable in small quantities. In case of disposal, it should be treated as a hazardous material and should be disposed accordingly. Do not just throw it away

Continue on page 11

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

**· Behaviour in environmental systems:****· Bioaccumulative potential** No further relevant information available.**· Mobility in soil** No further relevant information available.**· Ecotoxicological effects:****· Remark:** Toxic for fish**· Additional ecological information:****· General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Must not reach sewage water or drainage ditch undiluted or unneutralised.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

**· Results of PBT and vPvB assessment****· PBT:** This product contains no substance that is considered to be persistent, bioaccumulating or non toxic (PBT).**· vPvB:** This mixture contains no substance that is considered to be very persistent or very bioaccumulating (vPvB).**· Other adverse effects** No further relevant information available.

---

**\* 13 Disposal considerations****· Waste treatment methods****· Recommendation** Must not be disposed together with household garbage. Do not allow product to reach sewage system.**· Uncleaned packaging:****· Recommendation:** Disposal must be made according to official regulations.**· Recommended cleansing agents:** Water, if necessary together with cleansing agents.

---

**14 Transport information****· UN-Number****· ADR, IMDG, IATA**

UN1263

**· UN proper shipping name****· ADR**

UN1263 PAINT RELATED MATERIAL, ENVIRONMENTALLY HAZARDOUS

**· IMDG**PAINT RELATED MATERIAL (Solvent naphtha (petroleum), light arom.),  
MARINE POLLUTANT**· IATA**

PAINT RELATED MATERIAL

Continue on page 12

# Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

· Transport hazard class(es)

· ADR



· Class 3 (F1) Flammable liquids.

· Label 3

· IMDG



· Class 3 Flammable liquids.

· Label 3

· IATA



· Class 3 Flammable liquids.

· Label 3

· Packing group

· ADR, IMDG, IATA III

· Environmental hazards: Product contains environmentally hazardous substances: Solvent naphtha (petroleum), light arom.

· Marine pollutant: Yes

· Special marking (ADR): Symbol (fish and tree)

· Special precautions for user Warning: Flammable liquids.

· Hazard identification number (Kemler code): 30

· EMS Number: F-E,S-E

· Stowage Category A

· Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.

Continue on page 13

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

---

**· Transport/Additional information:**

---

**· ADR**

- Limited quantities (LQ) 5L
  - Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
  - Transport category 3
  - Tunnel restriction code D/E
- 

**· IMDG**

- Limited quantities (LQ) 5L
  - Excepted quantities (EQ) Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml
- 

**· IATA**

- Remarks: HAZ CHEM CODE: 3YE
  - UN "Model Regulation": UN 1263 PAINT RELATED MATERIAL, 3, III, ENVIRONMENTALLY HAZARDOUS
- 

---

## 15 Regulatory information

•3Y

**· Safety, health and environmental regulations/legislation specific for the substance or mixture**

---

None of the ingredients is listed.

**· New Zealand Inventory of Chemicals**

---

All ingredients are listed.

**· HSNO Approval numbers**

- HSNO Approval number HSR 002662
- Group standard name Surface Coatings and Colourants (Flammable) Group Standard 2006
- HSNO Hazard classification Refer to section 2
  - 123-86-4 n-butyl acetate: HSR001091
  - 64742-95-6 Solvent naphtha (petroleum), light arom.: HSR001503
    - 71-36-3 butan-1-ol: HSR001096
    - 107-98-2 1-methoxy-2-propanol: HSR001187
    - 108-65-6 2-methoxy-1-methylethyl acetate: HSR001219
    - 112-07-2 2-butoxyethyl acetate: HSR001155

Continue on page 14

**Safety Data Sheet**

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

· **GHS label elements** The product is classified and labelled according to the Globally Harmonised System (GHS).

· **Hazard pictograms**

GHS02 GHS05 GHS07 GHS09

· **Signal word** Danger

· **Hazard-determining components of labelling:**

Solvent naphtha (petroleum), light arom.

butan-1-ol

1-methoxy-2-propanol

2-butoxyethyl acetate

· **Hazard statements**

H226 Flammable liquid and vapour.

H332 Harmful if inhaled.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H335-H336 May cause respiratory irritation. May cause drowsiness or dizziness.

H411 Toxic to aquatic life with long lasting effects.

· **Precautionary statements**

P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

P310 Immediately call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P362+P364 Take off contaminated clothing and wash it before reuse.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Directive 2012/18/EU**· **Named dangerous substances - ANNEX I** None of the ingredients is listed.· **Seveso category**

E2 Hazardous to the Aquatic Environment

P5c FLAMMABLE LIQUIDS

· **Qualifying quantity (tonnes) for the application of lower-tier requirements** 200 t· **Qualifying quantity (tonnes) for the application of upper-tier requirements** 500 t

Continue on page 15

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

---

· **Chemical safety assessment:** A Chemical Safety Assessment has been carried out.

---

---

### 16 Other information

This information is based on our current knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant phrases**

H226 Flammable liquid and vapour.

H227 Combustible liquid.

H302 Harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

H312 Harmful in contact with skin.

H313 May be harmful in contact with skin.

H315 Causes skin irritation.

H318 Causes serious eye damage.

H331 Toxic if inhaled.

H332 Harmful if inhaled.

H333 May be harmful if inhaled.

H335 May cause respiratory irritation.

H336 May cause drowsiness or dizziness.

H401 Toxic to aquatic life.

H411 Toxic to aquatic life with long lasting effects.

· **Department issuing SDS:** Department of Quality Control

· **Contact:**

EN Chemicals S.A.

57 009 Kalochori

Thessalonikil, GREECE

T: +30 2310 755 428

F: +30 2310 755 428

info@enchemicals.com

www.enchemicals.com

· **Abbreviations and acronyms:**

RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

ICAO: International Civil Aviation Organisation

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

Continue on page 16

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

### Trade name: EN 7200 SLOW ACRYLIC THINNER

---

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 3: Flammable liquids – Category 3

Flam. Liq. 4: Flammable liquids – Category 4

Acute Tox. 3: Acute toxicity - inhalation – Category 3

Acute Tox. 4: Acute toxicity - inhalation – Category 4

Acute Tox. 5: Acute toxicity - inhalation – Category 5

Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Dam. 1: Serious eye damage/eye irritation – Category 1

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

Asp. Tox. 1: Aspiration hazard – Category 1

Aquatic Acute 2: Hazardous to the aquatic environment - acute aquatic hazard – Category 2

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2

· **\* Data compared to the previous version altered.**



## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

**Trade name: EN 7200 SLOW ACRYLIC THINNER**

---

### Annex: Exposure scenario

· **Short title of the exposure scenario**

· **Sector of Use** SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

· **Product category** PC9a Coatings and paints, thinners, paint removers

· **Process category** PROC8a Transfer of substance or mixture (charging and discharging) at non-dedicated facilities

· **Article category** AC1 Vehicles

· **Environmental release category** ERC2 Formulation into mixture

· **Description of the activities / processes covered in the Exposure Scenario**

See section 1 of the annex to the Safety Data Sheet.

· **Conditions of use** According to directions for use.

· **Duration and frequency** Frequency of use:

· **Physical parameters**

The data on the physical - chemical properties in the Exposure Scenario is based on the properties of the preparation.

· **Physical state** Fluid

· **Concentration of the substance in the mixture** The substance is main component.

· **Other operational conditions**

· **Other operational conditions affecting environmental exposure** Use only on hard ground.

· **Other operational conditions affecting worker exposure**

Avoid contact with eyes.

Avoid contact with the skin.

Do not breathe gas/vapour/aerosol.

Take precautionary measures against static discharge.

Keep away from sources of ignition - No smoking.

· **Other operational conditions affecting consumer exposure** No special measures required.

· **Other operational conditions affecting consumer exposure during the use of the product** Not applicable.

· **Risk management measures**

· **Worker protection**

· **Organisational protective measures**

Ensure good ventilation. This can be achieved by using a local exhaustion or general exhaust system. If these measures are insufficient to keep the solvent vapour concentration below the workplace limit, wear an adequate respiratory protective device.

· **Technical protective measures**

Use product only in enclosed systems.

Ensure that suitable extractors are available on processing machines

Provide explosion-proof electrical equipment.

· **Personal protective measures**

Do not inhale gases / fumes / aerosols.

Avoid contact with the skin.

Continue on page 18

## Safety Data Sheet

in accordance with HSNO

Printing date: 11.06.2020

Version no. 1

Revision date: 11.06.2020

---

### Trade name: EN 7200 SLOW ACRYLIC THINNER

---

Avoid contact with the eyes.

Tightly sealed goggles

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### · **Measures for consumer protection**

Ensure adequate labelling.

Observe consumer information and advice on safe use.

#### · **Environmental protection measures**

##### · **Water**

Do not allow to reach sewage system. Dispose of this product and its container at hazardous or special waste collection point.

Do not allow to reach sewage system.

Generally, prior to the introduction of wastewater into wastewater treatment plants a neutralisation is required.

##### · **Soil**

Prevent contamination of soil.

The product is only processed over the concrete collecting basin.

#### · **Disposal measures** Ensure that waste is collected and contained.

#### · **Disposal procedures** Must not be disposed together with household garbage. Do not allow product to reach sewage system.

#### · **Waste type** Partially emptied and uncleaned packaging

#### · **Exposure estimation**

#### · **Consumer** This product is to be used by professional technicians only.

#### · **Guidance for downstream users**

Whether the downstream user acts within the scope of the Exposure Scenario can be verified based on the information in sections 1 to 8.