



## Safety Data Sheet

### 9.CCG401

Safety Data Sheet dated 21/1/2016, version 1

---

#### SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Mixture identification:

Trade name: 9.CCG401

Trade code: G401

1.2. Relevant identified uses of the substance or mixture and uses advised against

Recommended use:

Car care product. Professional use.

Uses advised against:

All not indicated in the suggested uses.

1.3. Details of the supplier of the safety data sheet

Company:

RUPES SPA - Via Marconi 3A, 20080, Vermezzo (MI) – Italy

RUPES SPA - Telefono n°+3902946941

Importer:

Wyatt Machine Tools (Rupes) NZ Limited

388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

Competent person responsible for the safety data sheet:

info\_rupes@rupes.it

1.4. Emergency telephone number

NZ Emergency 0800 992 881 (0800WYATT1)

---

#### SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP)

The product is not classified as dangerous according to Regulation EC 1272/2008 (CLP).

Adverse physicochemical, human health and environmental effects:

No other hazards

2.2. Label elements

Hazard pictograms:

None

Hazard statements:

None

Precautionary statements:

P102 Keep out of reach of children.

Special Provisions:

EUH210 Safety data sheet available on request.

Special provisions according to Annex XVII of REACH and subsequent amendments:

None

2.3. Other hazards

## Safety Data Sheet

### 9.CCG401

vPvB Substances: None - PBT Substances: None  
 Other Hazards:  
 No other hazards






#### SECTION 3: Composition/information on ingredients

##### 3.1. Substances

N.A.

##### 3.2. Mixtures

Hazardous components within the meaning of the CLP regulation and related classification:

Qty	Name	Ident. Number	Classification
>= 3% - < 5%	ethanol; ethyl alcohol	Index number: 603-002-00-5 CAS: 64-17-5 EC: 200-578-6	 2.6/2 Flam. Liq. 2 H225
>= 3% - < 5%	propan-2-ol; isopropyl alcohol; isopropanol	Index number: 603-117-00-0 CAS: 67-63-0 EC: 200-661-7	  2.6/2 Flam. Liq. 2 H225  3.3/2 Eye Irrit. 2 H319  3.8/3 STOT SE 3 H336

#### SECTION 4: First aid measures

##### 4.1. Description of first aid measures

In case of skin contact:

Wash with plenty of water and soap.

In case of eyes contact:

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

In case of Ingestion:

Do not under any circumstances induce vomiting. OBTAIN A MEDICAL EXAMINATION IMMEDIATELY.

In case of Inhalation:

Remove casualty to fresh air and keep warm and at rest.

##### 4.2. Most important symptoms and effects, both acute and delayed

None

##### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment:

None

#### SECTION 5: Firefighting measures

##### 5.1. Extinguishing media

Suitable extinguishing media:

Water.

Carbon dioxide (CO<sub>2</sub>).



## Safety Data Sheet

### 9.CCG401

Extinguishing media which must not be used for safety reasons:  
None in particular.

- 5.2. Special hazards arising from the substance or mixture
  - Do not inhale explosion and combustion gases.
  - Burning produces heavy smoke.
- 5.3. Advice for firefighters
  - Use suitable breathing apparatus .
  - Collect contaminated fire extinguishing water separately. This must not be discharged into drains.
  - Move undamaged containers from immediate hazard area if it can be done safely.

---

#### SECTION 6: Accidental release measures

- 6.1. Personal precautions, protective equipment and emergency procedures
  - Wear personal protection equipment.
  - Remove all sources of ignition.
  - Remove persons to safety.
  - See protective measures under point 7 and 8.
- 6.2. Environmental precautions
  - Do not allow to enter into soil/subsoil. Do not allow to enter into surface water or drains.
  - Retain contaminated washing water and dispose it.
  - In case of gas escape or of entry into waterways, soil or drains, inform the responsible authorities.
  - Suitable material for taking up: absorbing material, organic, sand
- 6.3. Methods and material for containment and cleaning up
  - Wash with plenty of water.
- 6.4. Reference to other sections
  - See also section 8 and 13

---

#### SECTION 7: Handling and storage

- 7.1. Precautions for safe handling
  - Avoid contact with skin and eyes, inhalation of vapours and mists.
  - Don't use empty container before they have been cleaned.
  - Before making transfer operations, assure that there aren't any incompatible material residuals in the containers.
  - Contaminated clothing should be changed before entering eating areas.
  - Do not eat or drink while working.
  - See also section 8 for recommended protective equipment.
- 7.2. Conditions for safe storage, including any incompatibilities
  - Keep container closed when not in use. Keep only in the original container in a cool, well ventilated place away from: direct sunlight, heat and ignition sources
  - Keep away from food, drink and feed.
  - Incompatible materials:
    - None in particular.
  - Instructions as regards storage premises:
    - Adequately ventilated premises.

## Safety Data Sheet

### 9.CCG401

- 7.3. Specific end use(s)  
Car care product. Professional use.

---

#### SECTION 8: Exposure controls/personal protection

##### 8.1. Control parameters

- ethanol; ethyl alcohol - CAS: 64-17-5
  - OEL Type: ACGIH - STE: 1000 ppm
  - OEL Type: WEL - LTE: 1920 mg/m<sup>3</sup>, 1000 ppm
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
  - OEL Type: ACGIH - LTE(8h): 200 ppm - STE: 400 ppm
  - OEL Type: WEL - LTE(8h): 999 mg/m<sup>3</sup>, 400 ppm
  - OEL Type: WEL - STE(15min): 1250 mg/m<sup>3</sup>, 500 ppm

##### DNEL Exposure Limit Values

- ethanol; ethyl alcohol - CAS: 64-17-5
  - Consumer: 87 mg/kg bw/day - Exposure: Human Oral - Frequency: Short Term, systemic effects
  - Consumer: 950 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Short Term (acute)
  - Consumer: 114 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Worker Professional: 343 mg/kg bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Professional: 950 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
  - Consumer: 26 mg/kg bw/day - Exposure: Human Oral - Frequency: Long Term, systemic effects
  - Consumer: 319 mg/kg bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Consumer: 89 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects
  - Worker Professional: 888 mg/kg bw/day - Exposure: Human Dermal - Frequency: Long Term, systemic effects
  - Worker Professional: 500 mg/m<sup>3</sup> - Exposure: Human Inhalation - Frequency: Long Term, systemic effects

##### PNEC Exposure Limit Values

- ethanol; ethyl alcohol - CAS: 64-17-5
  - Target: Soil (agricultural) - Value: 0.63 mg/kg
  - Target: Microorganisms in sewage treatments - Value: 580 mg/l
  - Target: Marine water - Value: 0.79 mg/l
  - Target: Marine water sediments - Value: 2.9 mg/kg
  - Target: Fresh Water - Value: 0.96 mg/l
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
  - Target: Soil (agricultural) - Value: 28 mg/kg
  - Target: Marine water - Value: 104.9 mg/l
  - Target: Marine water sediments - Value: 552 mg/kg



## Safety Data Sheet

### 9.CCG401

Target: Fresh Water - Value: 552 mg/kg

Target: Freshwater sediments - Value: 140.9 mg/kg

#### 8.2. Exposure controls

Eye protection:

Wear eye/face protection

Protection for skin:

Wear suitable protective clothing

Protection for hands:

When handling with chemical substances, protective gloves must be worn with the CE-Label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances

Respiratory protection:

In case of inadequate ventilation wear respiratory protection

Thermal Hazards:

None

Environmental exposure controls:

None

Appropriate engineering controls:

None

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Properties	Value	Method:	Notes
Appearance and colour:	clear blue liquid	--	--
Odour:	characteristic	--	--
Odour threshold:	N.A.	--	--
pH:	8	--	at 20°C
Melting point / freezing point:	N.A.	--	--
Initial boiling point and boiling range:	82 ° C	--	--
Flash point:	48.5 ° C	EN ISO 1523	--
Evaporation rate:	N.A.	--	--
Solid/gas flammability:	N.A.	--	--
Upper/lower flammability or explosive limits:	N.A.	--	--
Vapour pressure:	48 g/cm3	--	--
Vapour density:	0.98	--	at 20°C
Relative density:	N.A.	--	--
Solubility in water:	easily soluble	--	--
Solubility in oil:	N.A.	--	--



## Safety Data Sheet

### 9.CCG401

Partition coefficient (n-octanol/water):	N.A.	--	--
Auto-ignition temperature:	N.A.	--	--
Decomposition temperature:	N.A.	--	--
Viscosity:	2.5-7.5 mpa s	--	at 20°C
Explosive properties:	N.A.	--	--
Oxidizing properties:	N.A.	--	--

#### 9.2. Other information

Properties	Value	Method:	Notes
Miscibility:	N.A.	--	--
Fat Solubility:	N.A.	--	--
Conductivity:	N.A.	--	--
Substance Groups relevant properties	9.95%	--	solvent content

## SECTION 10: Stability and reactivity

- 10.1. Reactivity  
No dangerous reactions known
- 10.2. Chemical stability  
stable under normal conditions
- 10.3. Possibility of hazardous reactions  
No dangerous reactions known
- 10.4. Conditions to avoid  
Direct sunlight. Extremely high or low temperatures
- 10.5. Incompatible materials  
None in particular.
- 10.6. Hazardous decomposition products  
None.

## SECTION 11: Toxicological information

- 11.1. Information on toxicological effects  
Toxicological information of the mixture:  
N.A.  
Toxicological information of the main substances found in the mixture:  
ethanol; ethyl alcohol - CAS: 64-17-5
  - a) acute toxicity:  
Test: LD50 - Route: Oral - Species: Rat = 6200 mg/kg - Source: IUCLID  
Test: LD50 - Route: Skin - Species: Rabbit > 20000 mg/kg - Source: OECD TG 402  
Test: LC50 - Route: Inhalation Vapour - Species: Rat > 8000 mg/l - Duration: 4h
- propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0
  - a) acute toxicity:



## Safety Data Sheet

### 9.CCG401

Test: LD50 - Route: Oral - Species: Rat = 5280 mg/kg  
Test: LD50 - Route: Skin - Species: Rabbit = 12800 mg/kg

If not differently specified, the information required in Regulation (EU)2015/830 listed below must be considered as N.A.:

- a) acute toxicity;
- b) skin corrosion/irritation;
- c) serious eye damage/irritation;
- d) respiratory or skin sensitisation;
- e) germ cell mutagenicity;
- f) carcinogenicity;
- g) reproductive toxicity;
- h) STOT-single exposure;
- i) STOT-repeated exposure;
- j) aspiration hazard.

---

#### SECTION 12: Ecological information

##### 12.1. Toxicity

Adopt good working practices, so that the product is not released into the environment.

ethanol; ethyl alcohol - CAS: 64-17-5

##### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 8140 mg/l - Duration h: 96

Endpoint: ErC50 - Species: Algae > 100 mg/l - Notes: OECD TG 201

Endpoint: EC50 - Species: Daphnia = 9268-14221 mg/l - Duration h: 48 - Notes:  
IUCRID

propan-2-ol; isopropyl alcohol; isopropanol - CAS: 67-63-0

##### a) Aquatic acute toxicity:

Endpoint: LC50 - Species: Fish = 9640 mg/l - Duration h: 96

Endpoint: ErC50 - Species: Algae > 1000 mg/l - Duration h: 72

Endpoint: EC50 - Species: Daphnia = 13299 mg/l - Duration h: 48

Species: bacteria = 5175 mg/l

##### 12.2. Persistence and degradability

N.A.

##### 12.3. Bioaccumulative potential

N.A.

##### 12.4. Mobility in soil

N.A.

##### 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

##### 12.6. Other adverse effects

None

---

#### SECTION 13: Disposal considerations

##### 13.1. Waste treatment methods

## Safety Data Sheet

### 9.CCG401

Recover if possible. In so doing, comply with the local and national regulations currently in force.

---

#### SECTION 14: Transport information

- 14.1. UN number  
Not classified as dangerous in the meaning of transport regulations.
- 14.2. UN proper shipping name  
N.A.
- 14.3. Transport hazard class(es)  
N.A.
- 14.4. Packing group  
N.A.
- 14.5. Environmental hazards  
N.A.
- 14.6. Special precautions for user  
N.A.
- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code  
N.A.

---

#### SECTION 15: Regulatory information

- 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture
  - Dir. 98/24/EC (Risks related to chemical agents at work)
  - Dir. 2000/39/EC (Occupational exposure limit values)
  - Regulation (EC) n. 1907/2006 (REACH)
  - Regulation (EC) n. 1272/2008 (CLP)
  - Regulation (EC) n. 790/2009 (ATP 1 CLP) and (EU) n. 758/2013
  - Regulation (EU) 2015/830
  - Regulation (EU) n. 286/2011 (ATP 2 CLP)
  - Regulation (EU) n. 618/2012 (ATP 3 CLP)
  - Regulation (EU) n. 487/2013 (ATP 4 CLP)
  - Regulation (EU) n. 944/2013 (ATP 5 CLP)
  - Regulation (EU) n. 605/2014 (ATP 6 CLP)

Restrictions related to the product or the substances contained according to Annex XVII Regulation (EC) 1907/2006 (REACH) and subsequent modifications:

Restrictions related to the product:

Restriction 40

Restrictions related to the substances contained:

No restriction.

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.

Regulation (EC) nr 648/2004 (detergents).

1999/13/EC (VOC directive)

Provisions related to directive EU 2012/18 (Seveso III):

N.A.



## Safety Data Sheet

### 9.CCG401

**This substance is not classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017**

15.2. Chemical safety assessment  
No

---

#### SECTION 16: Other information

Full text of phrases referred to in Section 3:

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre,  
Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van  
Nostrand Reinold

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This MSDS cancels and replaces any preceding release.

ADR:	European Agreement concerning the International Carriage of Dangerous Goods by Road.
CAS:	Chemical Abstracts Service (division of the American Chemical Society).
CLP:	Classification, Labeling, Packaging.
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GefStoffVO:	Ordinance on Hazardous Substances, Germany.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
INCI:	International Nomenclature of Cosmetic Ingredients.
KSt:	Explosion coefficient.
LC50:	Lethal concentration, for 50 percent of test population.



## Safety Data Sheet

### 9.CCG401

LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).
WGK:	German Water Hazard Class.