



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Wyatt Machine Tools (Rupes) NZ Limited
388 Church Street, Penrose
Auckland, New Zealand
PH: (09) 525 1000
FAX: (09) 525 1009

Product identifier..... PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY

Recommended use and restrictions on .. Paints. Primer.
use

Chemical family..... Mixture.

NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.

HMIS..... H: 2* F: 4 R: 0.

24 hour emergency number..... NZ Emergency 0800 992 881 (0800WYATT1).

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Aerosols — Category 1. Gases Under Pressure: Liquefied Gas. Skin Sensitizer — Category 1. Eye Irritation — Category 2A. Specific Target Organ Toxicity — Single Exposure — Category 3. (narcotic effects). (respiratory system). Carcinogenicity — Category 2. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 1.

Hazard Description..... H222 Extremely flammable aerosol. H229 Pressurized container: may burst if heated. H280 Contains gas under pressure; may explode if heated. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H351 This product contains ingredients that are suspected of causing cancer. H361 Suspected of damaging fertility or the unborn child. H372 Causes damage to organs through prolonged or repeated exposure.

Prevention..... P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P260 Do not breathe the mist, vapours, or spray. P264 Wash thoroughly after handling. P270 Do not eat drink or smoke while using this product. P271 Use only outdoors or in a well ventilated area. P272 Contaminated work clothing should not be allowed out of the workplace. P280 Wear protective gloves and eye protection.

Response P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P302 + P352 - If on skin: wash with plenty of water. P362 + P364 - Take off contaminated clothing and wash before reuse. P333 + P313 If skin irritation or rash occurs, get medical advice/attention. P305 + P351 + P338 If in eyes rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing until medical help arrives. P337 + P313 - If eye irritation persists get medical attention. P308 + P313 If exposed or concerned, get medical advice/attention.

Storage..... P403 + P233 Store in a well ventilated area. Keep container tightly closed. P405 Store locked up. P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

Note This product mixture has been classified based on its ingredients.

PRODUCT: PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

| CHEMICAL NAME AND SYNONYMS | CAS # | WT. % |
|----------------------------|------------|-------|
| Acetone | 67-64-1 | 15-40 |
| Propane | 74-98-6 | 10-30 |
| Talc | 14807-96-6 | 5-10 |
| Isobutyl Acetate | 110-19-0 | 5-10 |
| tert-Butyl acetate | 540-88-5 | 5-10 |
| Isobutane | 75-28-5 | 5-10 |
| Methyl Isobutyl Ketone | 108-10-1 | 5-10 |
| Methyl Ethyl Ketone | 78-93-3 | 3-7 |
| n-Butyl Acetate | 123-86-4 | 1-5 |
| Titanium Dioxide | 13463-67-7 | 1-5 |
| Ethyl 3-Ethoxypropionate | 763-69-9 | 1-5 |
| Xylene | 1330-20-7 | 0.1-1 |
| Bisphenol A - Epoxy Resin | 25068-38-6 | 0.1-1 |
| Ethylbenzene | 100-41-4 | 0.1-1 |
| Carbon Black | 1333-86-4 | < 0.1 |
| Toluene | 108-88-3 | <0.1 |

SECTION 04: FIRST-AID MEASURES

| | |
|--|--|
| Eye contact..... | Check for and remove any contact lenses, if safe and easy to do so. In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention. |
| Skin contact..... | Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention. |
| Inhalation..... | If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention. |
| Ingestion..... | If ingestion is suspected, contact physician or poison control center immediately. Do not induce vomiting. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person. |
| Most important symptoms and effects, whether acute or delayed | Harmful if swallowed, in contact with skin or if inhaled. Causes serious eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Direct contact with eyes may cause temporary irritation. Can cause skin sensitization. Vapors have a narcotic effect and may cause headache, fatigue, dizziness and nausea. This product contains ingredients that may cause cancer. This product contains ingredients that are suspected of damaging fertility or the unborn child. Causes damage to organs through prolonged or repeated exposure. |
| Additional information..... | Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet. |

SECTION 05: FIRE-FIGHTING MEASURES

| | |
|--|--|
| Suitable and unsuitable extinguishing media | "Alcohol" foam, CO ₂ , dry chemical. Water fog. Do not use water in a jet. |
| Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products | Extremely flammable aerosol. Aerosol can will explode if heated. Thermal decomposition products are toxic. May include: Oxides of carbon (CO, CO ₂). Hydrocarbon fumes and smoke. |
| Special protective equipment and precautions for fire-fighters | Extremely flammable aerosol. Heat will cause pressure buildup and may cause explosive rupture. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Keep run-off water from entering sewers and other waterways. Dike for water control. |

PRODUCT: PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY**SECTION 06: ACCIDENTAL RELEASE MEASURES**

| | |
|---|---|
| Personal precautions, protective equipment and emergency procedures | No action shall be taken involving any personal risk or without suitable training. Isolate area and keep unauthorized people away. Do not walk through spilled material. Wear recommended protective equipment. Ventilate. Open windows and doors to allow air circulation. Dike area to prevent spreading. The use of absorbent socks or spill pillows may be required. Stop leak if safe to do so. Prevent runoff into drains, sewers, and other waterways. Equipment should be grounded. Use non-sparking tools and equipment to pick up the spilled material. |
| Methods and materials for containment and cleaning up Leak/spill..... | Evacuate all non-essential personnel. Ventilate. Eliminate all sources of ignition. Avoid all personal contact. Contain the spill. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Place in metal containers for recovery or disposal. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. |

SECTION 07: HANDLING AND STORAGE

| | |
|--|--|
| Precautions for safe handling..... | Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Keep away from heat, sparks, and open flame. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Ground handling equipment. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Avoid breathing vapours or mist. Handle and open container with care. Employees should wash hands and face before eating or drinking. |
| Conditions for safe storage, including any incompatibilities | Keep away from heat, sparks, and open flames. Store away from oxidizing and reducing materials. Keep container closed when not in use. Store away from sunlight. Do not store above 50 deg C. |

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

| INGREDIENTS | TWA | ACGIH TLV STEL | PEL | OSHA PEL STEL | REL | NIOSH |
|---------------------------|-----------------|-------------------|-----------------|--------------------|------------------------|-------|
| Acetone | 250 ppm TLV | 500 ppm | 1,000 ppm | Not established | 250 ppm | |
| Propane | 1,000 ppm | Not established | 1,000 ppm | Not established | 1,000 ppm | |
| Talc | 2 mg/m3 | Not established | 2 mg/m3 TWA | 3 mg/m3 - QUE | Not established | |
| Isobutyl Acetate | 50 ppm | 150 ppm | 150 ppm | Not established | 150 ppm | |
| tert-Butyl acetate | 200 ppm | Not established | 200 ppm | Not established | 200 ppm | |
| Isobutane | Not established | Not established | Not established | Not established | 800 ppm | |
| Methyl Isobutyl Ketone | 50 ppm | 75 ppm | 100 ppm | Not established | 50 ppm / STEL 75 ppm | |
| Methyl Ethyl Ketone | 200 ppm | 300 ppm | 200 ppm | Not established | 200 ppm TWA | |
| n-Butyl Acetate | 50 ppm | 150 ppm | 150 ppm | 200 ppm | 150 ppm / STEL 200 ppm | |
| Titanium Dioxide | 10 mg/m3 | Not established | 15 mg/m3 | Not established | Not established | |
| Ethyl 3-Ethoxypropionate | Not established | Not established | Not established | Not established | Not established | |
| Xylene | 50 ppm | 150 ppm | 100 ppm TWA | Not established | Not established | |
| Bisphenol A - Epoxy Resin | Not established | Not established | Not established | Not established | Not established | |
| Ethylbenzene | 100 ppm | 125 ppm | 100 ppm | Not established | 100 ppm / STEL 125 ppm | |
| Carbon Black | 3.5 mg/m3 | Not established | 3.5 mg/m3 | Not established | 3.5 mg/m3 | |
| Toluene | 20 ppm | Not established | 200 ppm | 500 ppm 10 minutes | 100 ppm / STEL 150 ppm | |

PRODUCT: PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

| | |
|--|--|
| Appropriate engineering controls..... | Provide natural or mechanical ventilation to control exposure levels below airborne exposure limits. Local mechanical exhaust ventilation should be used at sources of air contamination, such as open process equipment, or during purging operations, to capture gases and fumes that may be emitted. Standard reference sources regarding industrial ventilation (ie. ACGIH industrial ventilation) should be consulted for guidance about adequate ventilation. Explosion-proof exhaust ventilation. |
| Personal Protective Equipment Respiratory/type..... | Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits. |
| Eye/type..... | Chemical safety goggles. Chemical safety goggles and full faceshield if splash hazard exists. |
| Gloves/ type..... | Wear skin protection equipment. The selection of this equipment depends on the nature of the work to be done. |
| Clothing/type..... | Wear adequate protective clothes. |
| Footwear/type..... | Safety boots per local regulations. |
| Other/type..... | Emergency showers and eye wash stations should be available. Employees should wash their hands and face before eating, drinking, or using tobacco products. |

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

| | |
|--|---|
| Appearance/Physical state..... | Aerosol. |
| Colour..... | Gray. |
| Odour..... | Aromatic. Sweet odour. |
| Odour threshold (ppm)..... | Not available. |
| pH..... | Not applicable. |
| Melting / Freezing point (deg C)..... | Not available. |
| Initial boiling point / boiling range (deg C)..... | (acetone). 56°C (133 F). |
| Flash point (deg C), method..... | -18°C. (acetone). |
| Evaporation rate..... | No data. |
| Flammability (solids and gases)..... | Flammable aerosol. |
| Upper flammable limit (% vol)..... | 9.5. (Propane). |
| Lower flammable limit (% vol)..... | 2.0. (Propane). |
| Vapour pressure (mm Hg)..... | Aerosol vapour pressure: 55-65 psig @ 20°C. |
| Vapour density (air=1)..... | No data. |
| Relative Density (Specific Gravity)..... | 0.85-0.89. |
| Pounds / USG..... | 7.10 - 7.43. |
| Solubility..... | No data. |
| Partition coefficient — n-octanol/water..... | Not available. |
| Auto ignition temperature (deg C)..... | (Propane). 450°C. |
| Decomposition temperature..... | Not available. |
| Viscosity..... | Not available. |
| VOC..... | 3.34 lbs/USG. |

SECTION 10: STABILITY AND REACTIVITY

| | |
|---|---|
| Reactivity | Product is stable; hazardous polymerization will not occur. |
| Chemical stability..... | Stable at normal temperatures and pressures. |
| Possibility of hazardous reactions..... | Hazardous polymerization will not occur. |
| Conditions to avoid, including static discharge, shock or vibration | Keep away from heat. Electrostatic charge. |
| Incompatible materials..... | Strong oxidizing agents. Keep away from heat. |
| Hazardous decomposition products..... | See hazardous combustion products section 5. |

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|--------------------|-------------------------------------|--|
| Acetone | 50,100 mg/m3 8 hours rat inhalation | 5,800 mg/kg rat oral |
| Propane | >1,464 mg/L 15 minutes rat | Not available |
| Talc | Not available | Not available |
| Isobutyl Acetate | >13.24 mg/L /6 h rat | 15400 mg/kg (rat oral) > 17400 mg/kg (rabbit dermal) |
| tert-Butyl acetate | >2,230 mg/m3 4 hours rat | 4,100 mg/kg rat oral >2,000 mg/kg rabbit dermal |
| Isobutane | 52 mg/L 1 hour mouse | Not available |

PRODUCT: PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY

SECTION 11: TOXICOLOGICAL INFORMATION

| INGREDIENTS | LC50 | LD50 |
|---------------------------|---|--|
| Methyl Isobutyl Ketone | 8.2 - 16.4 mg/L 4 hours rat | 2080 mg/kg rat oral >16,000 mg/kg rabbit dermal |
| Methyl Ethyl Ketone | >5,000 ppm (6 hours, rat) 11000 ppm (45 minutes, mouse) | 3,400 mg/kg (rat, oral) >8000 mg/kg (rabbit, dermal) 670 mg/kg (mouse, oral) |
| n-Butyl Acetate | 390 ppm (4 hr.) | 10768 mg/kg (rat oral) 17600 mg/kg (rabbit dermal) |
| Titanium Dioxide | Not Available | > 10,000 mg/kg rat oral > 10,000 mg/kg rabbit dermal |
| Ethyl 3-Ethoxypropionate | >998 ppm 6 hours | 4,309 mg/kg rat oral 4,080 mg/kg rabbit dermal |
| Xylene | 6350 ppm 4 hours rat | >3523 mg/kg rat oral |
| Bisphenol A - Epoxy Resin | Not Available | >2,000 mg/kg rat oral. 500-2000 mg/kg mouse oral. |
| Ethylbenzene | No data | 3,500 mg/kg rat oral 17,800 mg/kg rabbit dermal |
| Carbon Black | Not available | >10,000 mg/kg oral rat 3,000 mg/kg dermal rabbit |
| Toluene | 8000 ppm rat inhalation 400 ppm mouse inhalation 24hr | 5,000 mg/kg rat oral; 12,124 mg/kg rabbit dermal |

Route of exposure.....
Effects of acute exposure.....

Eye contact. Skin contact. Inhalation.
Can cause eye irritation. Symptoms include stinging, tearing, redness, and swelling of eyes. Can cause skin irritation. Symptoms may include redness and burning of skin, and other skin damage. Skin contact with adhesive that is not fully cured may cause an allergic skin reaction or other skin irritation. Passage of this material into the body through the skin is possible, but it is unlikely that this would result in harmful effects during safe handling and use. Swallowing this material may be harmful or fatal. Symptoms may include severe stomach and intestinal irritation (nausea, vomiting, diarrhea), abdominal pain, and vomiting of blood. Swallowing this material may cause burns and destroy tissue in the mouth, throat, and digestive tract. Low blood pressure and shock may occur as a result of severe tissue injury. Breathing this material may be harmful or fatal. Symptoms may include severe irritation and burns to the nose, throat, and respiratory tract. Symptoms are not expected at air concentrations below the recommended exposure limits, if applicable (see Section 8.). Prolonged or repeated breathing of dust may result in progressive and permanent lung disease (fibrosis) which may cause death from respiratory and/or heart failure. Symptoms include coughing and difficult breathing which becomes worse with physical activity. Another form of fibrosis, acute silicosis, can occur with exposures to very high concentrations of respirable silica over shorter periods of time, sometimes as short as a few months. Symptoms of acute silicosis include progressive shortness of breath, fever, cough and weight loss. Acute silicosis is fatal. Breathing of glass fibers can cause short-term irritation of the mouth, nose, and throat. Other symptoms may include coughing and wheezing. Because of the structure of the fibers, they do not enter the lungs (See Other Health Effects). The aromatic hydrocarbon solvents in this product can be irritating to the eyes, nose and throat. In high concentration, they may cause central nervous system depression and narcosis characterized by nausea, lightheadedness and dizziness from overexposure by inhalation. May be harmful if absorbed through the skin. Aspiration of material into the lungs can cause chemical pneumonitis which can be fatal.

Effects of chronic exposure..... Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. May cause damage to organs as a result of repeated or prolonged exposure. Chronic exposure to organic solvent vapours have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.

Carcinogenicity of material..... Methyl Isobutyl Ketone is possibly carcinogenic to humans (IARC Group 2B). IARC has classified Titanium Dioxide as a group 2B carcinogen. Xylene has been listed by IARC as a Group 3; not classifiable as to its carcinogenicity to humans. IARC has classified Toluene as a Group 3 (Not classifiable as to its carcinogenicity to humans); ACGIH has classified Toluene as a Group A4 (Not classifiable as a human carcinogen). IARC has classified Carbon Black as "Group 2B", possibly carcinogenic to humans, based on laboratory animal inhalation studies. Ethylbenzene is classified as an A3 known animal carcinogen.

PRODUCT: PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY**SECTION 11: TOXICOLOGICAL INFORMATION**

| | |
|---|--|
| Reproductive effects..... | High level exposure to Xylene in some animal studies have been reported to cause health effects on the developing embryo/fetus. The relevance of this to humans is not known. Toluene is fetotoxic in rats and mice at maternally toxic levels. Prolonged and repeated exposure of pregnant animals (>1500 ppm) to Toluene have been reported to cause adverse fetal developmental effects. In one study, Methyl Ethyl Ketone has been found to cause embryol toxicity in large concentrations. Methyl isobutyl ketone passes through the placental barrier. |
| Sensitizing capability of material..... | May cause sensitization by skin contact. |
| Specific Target Organ Toxicity | May cause drowsiness or dizziness. May cause respiratory irritation. Causes damage to organs through prolonged or repeated exposure . |

SECTION 12: ECOLOGICAL INFORMATION

| | |
|------------------------------------|--|
| Environmental..... | Do not allow to enter waters, waste water or soil. |
| Persistence and degradability..... | Not available. |

SECTION 13: DISPOSAL CONSIDERATIONS

| | |
|---|---|
| Information on safe handling for disposal and methods of disposal, including any contaminated packaging | Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. |
|---|---|

SECTION 14: TRANSPORT INFORMATION

| | |
|-----------------------------------|--|
| TDG Classification..... | UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre. |
| DOT Classification (Road)..... | UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons). |
| IATA Classification (Air)..... | UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity. Do not ship by air without checking appropriate IATA regulations. |
| IMDG Classification (Marine)..... | UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity. Check IMDG regulations for limited quantity exemptions. |
| Marine Pollutant..... | No. |
| Proof of Classification..... | In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct. . |

SECTION 15: REGULATORY INFORMATION

| | |
|--|---|
| CEPA status..... | On Domestic Substances List (DSL). |
| TSCA inventory status..... | All components are listed. |
| OSHA..... | This product is considered hazardous under the OSHA Hazard Communication Standard. |
| SARA Title III | |
| Section 302 - extremely hazardous substances | None. |
| Section 311/312 - hazard categories..... | Immediate health, delayed health, fire hazard. |
| Section 313..... | Ethylbenzene. Methyl Isobutyl Ketone. Toluene. Xylene. |
| EPA hazardous air pollutants (HAPS) 40CFR63 | Ethylbenzene. Methyl Isobutyl Ketone. Toluene. Xylene. |
| California Proposition 65..... | *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause birth defects or other reproductive harm. (Toluene). *** ! WARNING: This product can expose you to chemicals including [see below], which are known to the State of California to cause cancer . (Carbon black - airborne, unbound particles of respirable size). (Ethyl benzene). (Silica, crystalline (airborne particles of respirable size). (Titanium dioxide - airborne, unbound particles of respirable size). For more information, go to www.P65Warnings.ca.gov . |
| (NZ) Statement..... | This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017. |
| (NZ) HSNO Classifications..... | 2.1.1A. 6.5B. 6.4A. 6.7B. 6.8B. 6.9A. |
| (NZ) HSNO Group Standard..... | Aerosols - Flammable Toxic 6.7 HSR002517. |

SECTION 16: OTHER INFORMATION

| | |
|------------------------|--|
| Prepared by: | REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com . |
| Telephone number:..... | (800) 387-7981. |
| Disclaimer:..... | DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only |

PRODUCT: PF 13002 1K HIGH BUILD PRIMER AEROSOL GREY**SECTION 16: OTHER INFORMATION**

Disclaimer:..... ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Date of the latest revision of the safety .. 2019-11-12
data sheet