



Pro Form Products Ltd.
604 McGeachie Drive
Milton, Ontario, L9T 3Y5
Canada
905-878-4990

PRODUCT: PF 18302 HEAVY DUTY TRIM ADHESIVE AEROSOL

SECTION 01: IDENTIFICATION

Initial supplier identifier..... Wyatt Machine Tools (Rupes) NZ Limited
388 Church Street, Penrose
Auckland, New Zealand
PH: (09) 525 1000
FAX: (09) 525 1009

Product identifier..... PF 18302 HEAVY DUTY TRIM ADHESIVE AEROSOL

Recommended use and restrictions on .. Adhesive applications. This product should not be used for any other purpose other than use the ones described in this section.

Chemical family..... Mixture.

Hazard rating

NFPA rating..... Health: 2 Fire: 4 Reactivity: 0.

HMIS..... H: 3 F: 4 R: 0.

24 hour emergency number:..... NZ Emergency 0800 992 881 (0800WYATT1).

SECTION 02: HAZARD IDENTIFICATION



Signal Word..... DANGER.

Hazard Classification..... Flammable Aerosol 1. Gas under pressure: Compressed Gas. Aspiration Toxicity 1. Skin Irritation — Category 2. Eye Irritant 2. Specific Target Organ Toxicity — Single Exposure — Category 3. Reproductive Toxicity — Category 2. Specific Target Organ Toxicity — Repeated Exposure — Category 2.

Hazard Description..... H222 Extremely flammable aerosol. H280 Contains gas under pressure; may explode if heated. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H319 Causes serious eye irritation. H336 May cause drowsiness or dizziness. H361 Suspected of damaging fertility or the unborn child. H373 May cause damage to the liver and kidneys through prolonged or repeated contact.

Prevention..... P210 Keep away from heat, sparks, open flames and hot surfaces. No smoking. P211 Do not spray on an open flame or other ignition sources. P251 Do not pierce or burn container, even after use. P264 Wash thoroughly after handling. P280 Wear protective gloves and eye protection. P271 Use only outdoors or in a well ventilated area. P201 Obtain special instructions before use. P202 Do not handle this product until all safety instructions have been read and understood. P260 Do not breathe mist, vapours, or spray.

Response P301 + P310 If swallowed IMMEDIATELY CALL A POISON CONTROL CENTRE and follow instructions provided by the centre. P331 Do NOT induce vomiting. P302 + P352 - If on skin: wash with plenty of water. P321 - For specific treatment see section 4 on this SDS. P332 + P313 - If skin irritation occurs get medical attention or advice. P362 + P364 - Take off contaminated clothing and wash before reuse. P337 + P313 - If eye irritation persists get medical attention. P304 + P340 - If inhaled remove person to fresh air and keep comfortable for breathing. P312 Call a POISON CENTER/doctor if you feel unwell. P308 + P313 If exposed or concerned, get medical advice/attention. P314 - Get medical advice/attention if you feel unwell.

Storage..... P410 Protect from sunlight. P412 Do not expose to temperature exceeding 50°C / 122°F. P405 Store locked up. P403 + P233 Store in a well ventilated area. Keep container tightly closed.

Disposal..... P501 Dispose all unused, waste or empty containers in accordance with local regulations.

SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS

CHEMICAL NAME AND SYNONYMS	CAS #	WT. %
Hexane	110-54-3	30-60
Acetone	67-64-1	25-40
Polypertene resin	PROPRIETARY	5-20

PRODUCT: PF 18302 HEAVY DUTY TRIM ADHESIVE AEROSOL**SECTION 03: COMPOSITION / INFORMATION ON INGREDIENTS**

Propane	74-98-6	10-30
SBR RUBBER	25038-32-8	5-20
Isobutane	75-28-5	7-13
Silica, amorphous, fumed, cryst.-free	112945-52-5	<5

SECTION 04: FIRST-AID MEASURES

Eye contact.....	In case of contact, immediately flush eyes, keeping eyelids open, with plenty of water for at least 15 minutes. Obtain medical attention.
Skin contact.....	Remove all contaminated clothing and immediately wash the exposed areas with copious amounts of water for a minimum of 30 minutes or up to 60 minutes for critical body areas. If irritation persists, seek medical attention.
Inhalation.....	If inhaled, remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen, obtain medical attention.
Ingestion.....	Do not induce vomiting. If ingestion is suspected, contact physician or poison control center immediately. If spontaneous vomiting occurs have victim lean forward with head down to prevent aspiration of fluid into the lungs. Never give anything by mouth to an unconscious person.
Additional information.....	Treat victims symptomatically. The main hazard from ingestion is aspiration of the liquid into the lungs producing chemical pneumonitis. In the event of an incident involving this product ensure that medical authorities are provided a copy of this safety data sheet.

SECTION 05: FIRE-FIGHTING MEASURES

Suitable and unsuitable extinguishing media	"Alcohol" foam, CO ₂ , dry chemical. In cases of larger fires, water spray should be used.
Specific hazards arising from the hazardous product, such as the nature of any hazardous combustion products	Oxides of carbon (CO, CO ₂).
Special protective equipment and precautions for fire-fighters	Firefighter should be equipped with self-contained breathing apparatus and full protective clothing to protect against potentially toxic and irritating fumes. Cool fire-exposed containers with cold water spray. Heat will cause pressure buildup and may cause explosive rupture. Keep run-off water from entering sewers and other waterways. Dike for water control.

SECTION 06: ACCIDENTAL RELEASE MEASURES

Leak/spill.....	Ventilate. Eliminate all sources of ignition. Contain the spill. Avoid all personal contact. Spilled material and water rinses are classified as chemical waste, and must be disposed of in accordance with current local, provincial, state, and federal regulations. Evacuate all non-essential personnel. Prevent runoff into drains, sewers, and other waterways. Absorb with earth, sand, or another dry inert material. Shovel into suitable unsealed containers, transport to well-ventilated area (outside) and treat with neutralizing solution: mixture of water (80%) with non-ionic surfactant Tergitol TMN-10 (20%); or water (90%), concentrated ammonia (3-8%) and detergent (2%).
-----------------	---

SECTION 07: HANDLING AND STORAGE

Precautions for safe handling.....	Pressurized container: Do not pierce or burn, even after use. Do not use if spray button is missing or defective. Do not spray on a naked flame or any other incandescent material. Do not smoke while using or until sprayed surface is thoroughly dry. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose empty containers to heat, sparks or open flames. Always adopt precautionary measures against build-up of static which may arise from appliances, handling and the containers in which product is packed. Avoid breathing vapours or mist. Ground handling equipment. Handle and open container with care. Avoid all skin contact and ventilate adequately, otherwise wear an appropriate breathing apparatus. Employees should wash hands and face before eating or drinking.
Conditions for safe storage, including any incompatibilities	Pressurized container, do not expose to temperatures exceeding 50°C (122°F). Do not puncture, incinerate or crush container. Keep away from heat, sparks, and open flames. Keep container closed when not in use. Store away from oxidizing and reducing materials. Store away from sunlight.

SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION

PRODUCT: PF 18302 HEAVY DUTY TRIM ADHESIVE AEROSOL**SECTION 08: EXPOSURE CONTROLS / PERSONAL PROTECTION**

INGREDIENTS	TWA	ACGIH TLV STEL	PEL	OSHA PEL STEL	REL NIOSH
Hexane	50 ppm	Not Established	500 ppm	Not Established	50 ppm
Acetone	250 ppm TLV	500 ppm	1,000 ppm	Not established	250 ppm
Polypertene resin	Not established	Not established	Not established	Not established	Not established
Propane	1,000 ppm	Not established	1,000 ppm	Not established	1,000 ppm
SBR RUBBER	Not established	Not established	Not established	Not established	Not established
Isobutane	Not established	Not established	Not established	Not established	800 ppm
Silica, amorphous, fumed, cryst.-free	Not established	Not established	80mg/m ³ (Silica)	Not established	6mg/m ³ (Silica)
Personal Protective Equipment					
Eye/type.....	Liquid chemical goggles.				
Respiratory/type.....	Local exhaust ventilation is recommended. Wear an appropriate, properly fitted respirator when contaminant levels exceed the recommended exposure limits.				
Gloves/ type.....	Chemical resistant gloves.				
Clothing/type.....	Wear adequate protective clothes.				
Footwear/type.....	Safety boots per local regulations.				
Other/type.....	Emergency showers and eye wash stations should be available.				
Appropriate engineering controls.....	Local exhaust at points of emission.				

SECTION 09: PHYSICAL AND CHEMICAL PROPERTIES

Appearance/Physical state.....	Aerosol.
Colour.....	Opaque. White.
Odour.....	Hydrocarbon odour.
Odour threshold (ppm).....	Not available.
Vapour density (air=1).....	>1.
Vapour pressure (mm Hg).....	Aerosol vapour pressure: 60-75 psig @ 21C.
pH.....	Not available.
Relative Density (Specific Gravity).....	0.769.
Density.....	6.42 lb/usg - 0.769 g/mL.
Melting / Freezing point (deg C).....	Not available.
Solubility.....	Not soluble in water.
Initial boiling point / boiling range (deg C).....	-11.72°C (10.9°F) for propellant.
Evaporation rate.....	Slower than n-butyl acetate.
Flash point (deg C), method.....	-26. (estimated). This is a liquified compressed gas and flammability can not be expressed by conventional flash point tests. A blowtorch effect results when spray is within 12 inches of an ignition source.
Auto ignition temperature (deg C).....	234°C.
Upper flammable limit (% vol).....	13.
Lower flammable limit (% vol).....	1.2.
Partition coefficient — n-octanol/water.....	Not available.
VOC.....	3.78 lbs/USG; 0.453.
Viscosity.....	Not available.

SECTION 10: STABILITY AND REACTIVITY

Chemical stability.....	Stable at normal temperatures and pressures.
Reactivity	Avoid heat, sparks and flames. Explosive reactions can occur in the presence of strong oxidizing agents.
Conditions to avoid, including static	Keep away from heat. Incompatible with strong oxidizers.
discharge, shock or vibration	
Hazardous decomposition products.....	By fire: Dense black smoke. Oxides of carbon (CO,CO2).
Possibility of hazardous reactions.....	High temperatures .

SECTION 11: TOXICOLOGICAL INFORMATION

INGREDIENTS	LC50	LD50
Hexane	48,000 ppm rat <4 hours	28,710 rat oral
Acetone	50,100 mg/m ³ 8 hours rat inhalation	5,800 mg/kg rat oral
Polypertene resin	No data	No data

PRODUCT: PF 18302 HEAVY DUTY TRIM ADHESIVE AEROSOL**SECTION 11: TOXICOLOGICAL INFORMATION**

INGREDIENTS	LC50	LD50
Propane	>1,464 mg/L 15 minutes rat	Not available
SBR RUBBER	No data	No data
Isobutane	52 mg/L 1 hour mouse	Not available
Silica, amorphous, fumed, cryst.-free	No data	No data
Route of exposure.....	Eye contact. Skin contact. Inhalation.	
Skin contact.....	Can cause moderate irritation, defatting and dermatitis.	
Skin absorption.....	May be harmful if absorbed through the skin.	
Eye contact.....	Can cause redness, irritation, tissue destruction.	
Ingestion.....	May be harmful or fatal if swallowed. Aspiration of material into lungs can cause chemical pneumonitis which can be fatal.	
Inhalation (acute).....	Excessive inhalation of vapours can cause respiratory irritation, dizziness, headache, vomiting and unconsciousness.	
Inhalation (chronic).....	Chronic exposure to organic solvent vapors have been associated with various neurotoxic effects including permanent brain and/or nervous system damage, kidney, liver, blood damage and reproductive effects among women. Symptoms may include nausea, vomiting, abdominal pain, headache, impaired memory, loss of coordination, insomnia and breathing difficulties.	
Effects of chronic exposure.....	Breathing high concentrations of vapour may cause anesthetic effects and serious health effects. Prolonged or repeated skin contact may cause drying or cracking of skin. Possible damage to liver and kidneys. Peripheral neuropathy. Intentional misuse by deliberately concentrating and inhaling this product may be harmful or fatal.	
Carcinogenicity of material.....	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as a carcinogen.	
Reproductive effects.....	None known.	

SECTION 12: ECOLOGICAL INFORMATION

Environmental.....	Do not allow to enter waters, waste water or soil.
Persistence and degradability.....	Not available.

SECTION 13: DISPOSAL CONSIDERATIONS

Information on safe handling for disposal and methods of disposal, including any contaminated packaging	Contents under pressure. Do not puncture, incinerate or expose to heat, even when empty. This material and its container must be disposed of as hazardous waste. Avoid release to the environment. Dispose of waste in accordance with all applicable Federal, Provincial/State and local regulations.
---	--

SECTION 14: TRANSPORT INFORMATION

TDG Classification.....	UN1950 - AEROSOLS, flammable - Class 2.1 - This product meets limited quantity exemption when shipped in containers less than 1 Litre.
DOT Classification (Road).....	UN1950 - AEROSOLS, flammable - Class 2.1 - Ltd Qty (1 Liter/0.26 Gallons).
IATA Classification (Air).....	UN1950 - AEROSOLS, flammable - Class 2.1 - Limited Quantity.
IMDG Classification (Marine).....	UN1950 - AEROSOLS - Class 2.1 - EmS: F-D, S-U - Limited Quantity.
Marine Pollutant.....	Potential marine pollutant.
Proof of Classification.....	In accordance with Part 2.2.1 of the Transportation of Dangerous Goods Regulations (July 2, 2014) - we certify that classification of this product is correct.

SECTION 15: REGULATORY INFORMATION

WHMIS 1988 classification.....	D2A. A. B5. D2B.
CEPA status.....	On Domestic Substances List (DSL).
TSCA inventory status.....	All components are listed.
OSHA.....	This product is considered hazardous under the OSHA Hazard Communication Standard.
SARA Title III	
Section 302 - extremely hazardous substances	None.
Section 311/312 - hazard categories.....	Immediate health, delayed health, fire hazard.
Section 313.....	Hexane.
EPA hazardous air pollutants (HAPS)	Hexane.
40CFR63	
California Proposition 65.....	This product does not contain any chemical(s) known to the State of California to cause cancer or reproductive toxicity.
(NZ) Statement.....	This substance is classified hazardous according to the EPA Hazardous Substances (Classification) Notice 2017.

PRODUCT: PF 18302 HEAVY DUTY TRIM ADHESIVE AEROSOL**SECTION 15: REGULATORY INFORMATION**

(NZ) HSNO Classifications..... 2.1.1A. 6.1E. 6.3A. 6.4A. 6.9B. 6.8B.
(NZ) HSNO Group Standard..... Aerosols - Flammable HSR002515.

SECTION 16: OTHER INFORMATION

Prepared by: REGULATORY AFFAIRS. Trivalent Data Systems Ltd. www.trivalent.com.
Telephone number:..... (800) 387-7981.
Disclaimer:..... DISCLAIMER: All information appearing herein is based upon data obtained from experience and recognized technical sources. To the best of our knowledge, it is believed to be correct as of the date of issue but we make no representations as to its accuracy or sufficiency and do not suggest or guarantee that any hazards listed herein are the only ones which exist. The hazard information contained herein is offered solely for the consideration of the user, subject to his own investigation and verification of compliance with applicable regulations, including the safe use of the product under every foreseeable condition. The information relates only to the product designated herein, and does not relate to its use in combination with any other material or in any other process.

Date of the latest revision of the safety .. 2019-11-14
data sheet