

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 1: IDENTIFICATION

1.1 Product identifier: HARDENER for EPOXY PRIMER 1:10

1.2 Recommended uses and any restrictions on use or supply:

Relevant uses: Car repair. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Supplier's details:

Troton Sp. z o.o.
Ząbrowo 14A
78-120 Gościno - Zachodniopomorskie - Polska
Phone.: +48 94 35 123 94 - Fax: +48 94 35 126 22
troton@troton.com.pl
www.troton.pl

Distributor:
Wyatt Machine Tools (Rupes) NZ Limited
388 Church Street, Penrose, Auckland
Ph (09) 525 1000; Fax (09) 525 1009

1.4 Emergency phone number: (8am-4pm)+48 094 35 123 94; 112
NZ Emergency 0800 992 881 (0800WYATT1)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

HSNO Act:

This product was classified in accordance with HSNO Act

- 3.1C: Flammable liquids: medium hazard, H226
- 6.1E: Substances that are acutely toxic (Respiratory tract irritant), H335
- 6.1E: Substances that are acutely toxic, H313
- 6.3A: Substances that are irritating to the skin, H315
- 6.3B: Substances that are mildly irritating to the skin, H316
- 6.9B: Substances that are harmful to human target organs or systems, H373
- 8.3A: Substances that are corrosive to ocular tissue, H318

2.2 Label elements, including precautionary statements:

HSNO Act:

Danger



Hazard statements:

- 3.1C: H226 - Flammable liquid and vapour
- 6.1E: H335 - May cause respiratory irritation
- 6.1E: H313 - May be harmful in contact with skin
- 6.3A: H315 - Causes skin irritation
- 6.3B: H316 - Causes mild skin irritation
- 6.9B: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
- 8.3A: H318 - Causes serious eye damage

Precautionary statements:

- P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
- P280: Wear protective gloves/protective clothing/eye protection/face protection
- P302+P352: IF ON SKIN: Wash with plenty of soap and water
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
- P370+P378: In case of fire: Use ABC powder extinguisher to put it out
- P403+P233: Store in a well-ventilated place. Keep container tightly closed
- P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 2: HAZARDS IDENTIFICATION (continued)

Substances that contribute to the classification

Polyamidoamine adduct; Xylene; 1-butanol

2.3 Other hazards which do not result in classification:

Non-applicable

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances:








Non-applicable

3.2 Mixtures:

Chemical description: Mixture composed of chemical products

Components:

In accordance with Part B: Concentration cut-offs for ingredients in mixtures for purpose of section 3 of Hazardous Substances (Safety Data Sheets) Notice 2017, the product contains:

| Identification | Chemical name/Classification | Concentration |
|---------------------|---|----------------------|
| CAS: Non-applicable | Polyamidoamine adduct 8.3A: H318 - Danger  | 50 - <75 % |
| CAS: 1330-20-7 | Xylene 3.1C: H226; 6.1D: H312+H332; 6.1E : H304; 6.1E: H303; 6.1E: H335; 6.3A: H315; 6.4A: H319; 6.9B: H373 - Danger    | 25 - <50 % |
| CAS: 71-36-3 | 1-butanol 3.1C: H226; 6.1D: H302; 6.1E: H313; 6.1E: H335; 6.3A: H315; 6.9B: H336; 8.3A: H318 - Danger    | 10 - <25 % |

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST-AID MEASURES

4.1 First aid instructions according to each relevant route of exposure;:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of medical attention and its urgency:

Non-applicable

SECTION 5: FIRE-FIGHTING MEASURES

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 5: FIRE-FIGHTING MEASURES (continued)

5.1 Information on the appropriate type of extinguishers or fire-fighting agents:

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Advice on specific hazards that may arise from the substance:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Special protective equipment and precautions for fire-fighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

6.2 Environmental precautions from accidental spills and release::

This product is not classified as hazardous to the environment. Keep product away from drains, surface and underground water.

6.3 Advice on how to contain and clean up a spill or release:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 7: HANDLING AND STORAGE (continued)

Minimum Temp.: 15 °C
 Maximum Temp.: 25 °C
 Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Occupational exposure limits:

Substances whose workplace exposure standards (WES) have to be monitored in the work environment

| Identification | OEL | | |
|---------------------------|--------|-----------------------|-------|
| | TWA | STEL | Other |
| Xylene CAS: 1330-20-7 | 50 ppm | 217 mg/m ³ | |
| | | | |
| 1-butanol CAS: 71-36-3 | 50 ppm | 150 mg/m ³ | |
| | 50 ppm | 150 mg/m ³ | |


8.2 Engineering controls:

A.- Identification of the specific types of personal protective equipment


As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection


| Pictogram | PPE | Remarks |
|---|---------------------------------------|--|
|  Mandatory respiratory tract protection | Filter mask for gases and vapours (A) | Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment. |

C.- Specific protection for the hands

| Pictogram | PPE | Remarks |
|--|--|--|
|  Mandatory hand protection | NON-disposable chemical protective gloves (NRL), Breakthrough Time 480 min, thickness 0.4 mm | The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin. |

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application

D.- Ocular and facial protection

| Pictogram | PPE | Remarks |
|--|---|---|
|  Mandatory face protection | Panoramic glasses against splash/projections. | Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing. |

E.- Bodily protection

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10



Printing: 2/03/2020

Date of compilation: 27/06/2011



Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

| Pictogram | PPE | Remarks |
|---|---|---|
|  Mandatory complete body protection | Disposable clothing for protection against chemical risks, with antistatic and fireproof properties | For professional use only. Clean periodically according to the manufacturer's instructions. |
|  Mandatory foot protection | Safety footwear for protection against chemical risk, with antistatic and heat resistant properties | Replace boots at any sign of deterioration. |

F.- Additional emergency measures

| Emergency measure | Standards | Emergency measure | Standards |
|---|---|--|--|
|  Emergency shower | ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011 |  Eyewash stations | DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011 |

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C: Liquid
 Appearance: Fluid
 Colour:  Brown
 Odour: Solvent
 Odour threshold: Non-applicable *

Volatility:

Initial boiling point and boiling range: 120 °C
 Vapour pressure at 20 °C: 812 Pa
 Vapour pressure at 50 °C: 4671.24 Pa (4.67 kPa)
 Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 935.4 kg/m³
 Relative density at 20 °C: 0.935
 Dynamic viscosity at 20 °C: 30000 cP
 Kinematic viscosity at 20 °C: 32070.8 cSt
 Kinematic viscosity at 40 °C: Non-applicable *
 Concentration: Non-applicable *
 pH: 10 at 50 %
 Vapour density at 20 °C: 0.9 kg/m³
 Partition coefficient n-octanol/water 20 °C: Non-applicable *
 Solubility in water at 20 °C: 20 kg/m³
 Solubility properties: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Decomposition temperature: Non-applicable *
 Melting point/freezing point: Non-applicable *
 Explosive properties: Non-applicable *
 Oxidising properties: Non-applicable *

Flammability:

Flash Point: 27 °C (ISO 1516)
 Flammability (solid, gas): Non-applicable *
 Autoignition temperature: 300 °C
 Lower flammability limit: 1 % Volume
 Upper flammability limit: 11.3 % Volume

Explosive:

Lower explosive limit: Non-applicable *
 Upper explosive limit: Non-applicable *

9.2 Other information:

Surface tension at 20 °C: Non-applicable *
 Refraction index: Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Chemical reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 List of conditions to avoid or prevent a hazardous situation:

Applicable for handling and storage at room temperature:

| Shock and friction | Contact with air | Increase in temperature | Sunlight | Humidity |
|--------------------|------------------|-------------------------|---------------------|----------------|
| Not applicable | Not applicable | Risk of combustion | Avoid direct impact | Not applicable |

10.5 Information on incompatible substances or materials:

| Acids | Water | Oxidising materials | Combustible materials | Others |
|--------------------|----------------|---------------------|-----------------------|-------------------------------|
| Avoid strong acids | Not applicable | Avoid direct impact | Not applicable | Avoid alkalis or strong bases |

10.6 Information on hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.
IARC: Xylene (3)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

| Identification | Acute toxicity | | Genus |
|--|-----------------|----------------------|--------|
| | | | |
| 1-butanol CAS: 71-36-3 | LD50 oral | 2292 mg/kg | Rat |
| | LD50 dermal | 3400 mg/kg | Rabbit |
| | LC50 inhalation | 24.66 mg/L (4 h) | Rat |
| Polyamidoamine adduct CAS: Non-applicable | LD50 oral | >5000 mg/kg | |
| | LD50 dermal | >5000 mg/kg | |
| | LC50 inhalation | >20 mg/L (4 h) | |
| Xylene CAS: 1330-20-7 | LD50 oral | 2100 mg/kg | Rat |
| | LD50 dermal | 1100 mg/kg (ATEi) | Rat |
| | LC50 inhalation | 11 mg/L (4 h) (ATEi) | |

SECTION 12: ECOLOGICAL INFORMATION

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 12: ECOLOGICAL INFORMATION (continued)

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Ecotoxicity (aquatic and terrestrial):

| Identification | Acute toxicity | | Species | Genus |
|---------------------------|----------------|------------------|-------------------------|------------|
| Xylene CAS: 1330-20-7 | LC50 | 13.5 mg/L (96 h) | Oncorhynchus mykiss | Fish |
| | EC50 | 3.4 mg/L (48 h) | Ceriodaphnia dubia | Crustacean |
| | EC50 | 10 mg/L (72 h) | Skeletonema costatum | Algae |
| 1-butanol CAS: 71-36-3 | LC50 | 1740 mg/L (96 h) | Pimephales promelas | Fish |
| | EC50 | 1983 mg/L (48 h) | Daphnia magna | Crustacean |
| | EC50 | 500 mg/L (96 h) | Scenedesmus subspicatus | Algae |

12.2 Persistence and degradability:

| Identification | Degradability | | Biodegradability | |
|---------------------------|---------------|----------------|------------------|----------------|
| | | | | |
| Xylene CAS: 1330-20-7 | BOD5 | Non-applicable | Concentration | Non-applicable |
| | COD | Non-applicable | Period | 28 days |
| | BOD5/COD | Non-applicable | % Biodegradable | 88 % |
| 1-butanol CAS: 71-36-3 | BOD5 | 1.71 g O2/g | Concentration | Non-applicable |
| | COD | 2.46 g O2/g | Period | 19 days |
| | BOD5/COD | 0.69 | % Biodegradable | 98 % |

12.3 Potential to be bioaccumulative:

| Identification | Bioaccumulation potential | |
|---------------------------|---------------------------|------|
| Xylene CAS: 1330-20-7 | BCF | 9 |
| | Pow Log | 2.77 |
| | Potential | Low |
| 1-butanol CAS: 71-36-3 | BCF | 1 |
| | Pow Log | 0.88 |
| | Potential | Low |

12.4 Mobility in soil:

| Identification | Absorption/desorption | | Volatility | |
|---------------------------|-----------------------|----------------------|------------|--------------------------------|
| Xylene CAS: 1330-20-7 | Koc | 202 | Henry | 524.86 Pa·m ³ /mol |
| | Conclusion | Moderate | Dry soil | Yes |
| | Surface tension | Non-applicable | Moist soil | Yes |
| 1-butanol CAS: 71-36-3 | Koc | 2.44 | Henry | 5.39E-2 Pa·m ³ /mol |
| | Conclusion | Very High | Dry soil | Yes |
| | Surface tension | 2.567E-2 N/m (25 °C) | Moist soil | Yes |

12.5 Results of PBT and vPvB assessment:

Non-applicable

12.6 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Appropriate and achievable disposal methods:

Special precautions to be taken during disposal:

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See epigraph 6.2.

Regulations related to waste management:

Legislation related to waste management:

Imports and Exports (Restrictions) Prohibition Order (No 2) 2004

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to NZS 5433.1:2012 Transport of dangerous goods on land



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 UN dangerous goods class and subsidiary risk:** 3
- Labels:** 3
- 14.4 UN Packing Group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

Transport of dangerous goods by sea:

With regard to IMDG 38-16:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 UN dangerous goods class and subsidiary risk:** 3
- Labels:** 3
- 14.4 UN Packing Group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

Transport of dangerous goods by air:

With regard to IATA/ICAO 2020:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 UN dangerous goods class and subsidiary risk:** 3
- Labels:** 3
- 14.4 UN Packing Group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations specific for the product in question:

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

Relevant regulatory requirements:

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

HARDENER for EPOXY PRIMER 1:10

Printing: 2/03/2020

Date of compilation: 27/06/2011

Revised: 13/08/2019

Version: 5 (Replaced 4)

SECTION 15: REGULATORY INFORMATION (continued)

Health and Safety at Work (Hazardous Substances) Regulations 2017
 Health and Safety at Work Act 2015
 Hazardous Substances (Classification) Notice 2017
 Hazardous Substances (Labelling) Notice 2017

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with Schedule 1: Content and format of safety data sheets of Hazardous Substances (Safety Data Sheets) Notice 2017

Texts of the legislative phrases mentioned in section 2:

- H315: Causes skin irritation
- H316: Causes mild skin irritation
- H318: Causes serious eye damage
- H335: May cause respiratory irritation
- H373: May cause damage to organs through prolonged or repeated exposure (Oral)
- H313: May be harmful in contact with skin
- H226: Flammable liquid and vapour

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

HSNO Act:

- 3.1C: H226 - Flammable liquid and vapour
- 6.1D: H302 - Harmful if swallowed
- 6.1D: H312+H332 - Harmful in contact with skin or if inhaled
- 6.1E : H304 - May be fatal if swallowed and enters airways
- 6.1E: H303 - May be harmful if swallowed
- 6.1E: H313 - May be harmful in contact with skin
- 6.1E: H335 - May cause respiratory irritation
- 6.3A: H315 - Causes skin irritation
- 6.4A: H319 - Causes serious eye irritation
- 6.9B: H336 - May cause drowsiness or dizziness
- 6.9B: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
- 8.3A: H318 - Causes serious eye damage

Advice related to training:

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<https://www.epa.govt.nz/>

Abbreviations and acronyms:

- HSNO Act: Hazardous substances and new organisms Act
- IMDG: International maritime dangerous goods code
- IATA: International Air Transport Association
- ICAO: International Civil Aviation Organisation
- COD: Chemical Oxygen Demand
- BOD5: 5-day biochemical oxygen demand
- BCF: Bioconcentration factor
- LD50: Lethal Dose 50
- CL50: Lethal Concentration 50
- EC50: Effective concentration 50
- Log-POW: Octanol-water partition coefficient
- Koc: Partition coefficient of organic carbon

Other information:

GROUP STANDARD
 HSR002662

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.