

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 1: IDENTIFICATION**

**1.1 Product identifier:** ANTICORROSIVE EPOXY PRIMER 4:1

**1.2 Recommended uses and any restrictions on use or supply:**

Relevant uses: Car repair; base for coatings. For professional user only.

Uses advised against: All uses not specified in this section or in section 7.3

**1.3 Supplier's details:**

Troton Sp. z o.o.

Ząbrowo 14A

78-120 Gościno - Zachodniopomorskie - Polska

Phone.: +48 94 35 123 94 - Fax: +48 94 35 126 22

troton@troton.com.pl

www.troton.pl

Distributor:

Wyatt Machine Tools (Rupes) NZ Limited

388 Church Street, Penrose, Auckland

Ph (09) 525 1000; Fax (09) 525 1009

**1.4 Emergency phone number:** ( 8am-4pm)+48 094 35 123 94; 112  
 NZ Emergency 0800 992 881 (0800WYATT1)

**SECTION 2: HAZARDS IDENTIFICATION**

**2.1 Classification of the substance or mixture:**

This product contains less than 1% respirable crystalline silica, so it does not require classification

**HSNO Act:**

This product was classified in accordance with HSNO Act

3.1C: Flammable liquids: medium hazard, H226

6.1E: Substances that are acutely toxic (Respiratory tract irritant), H335

6.1E: Substances that are acutely toxic, H313

6.3A: Substances that are irritating to the skin, H315

6.3B: Substances that are mildly irritating to the skin, H316

6.5B: Substances that are contact sensitizers, H317

6.9B: Substances that are harmful to human target organs or systems, H373

8.3A: Substances that are corrosive to ocular tissue, H318

9.1C: Substances that are harmful in the aquatic environment, H412

9.1D: Substances that are slightly harmful to the aquatic environment or are otherwise designed for biocidal action, H402

**2.2 Label elements, including precautionary statements:**

**HSNO Act:**

**Danger**



**Hazard statements:**

3.1C: H226 - Flammable liquid and vapour

6.1E: H335 - May cause respiratory irritation

6.1E: H313 - May be harmful in contact with skin

6.3A: H315 - Causes skin irritation

6.3B: H316 - Causes mild skin irritation

6.5B: H317 - May cause an allergic skin reaction

6.9B: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)

8.3A: H318 - Causes serious eye damage

9.1C: H412 - Harmful to aquatic life with long lasting effects

**Precautionary statements:**

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 2: HAZARDS IDENTIFICATION (continued)**

P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking  
 P280: Wear protective gloves/protective clothing/eye protection/face protection  
 P302+P352: IF ON SKIN: Wash with plenty of soap and water  
 P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing  
 P370+P378: In case of fire: Use ABC powder extinguisher to put it out  
 P403+P233: Store in a well-ventilated place. Keep container tightly closed  
 P501: Dispose of contents and / or containers in accordance with regulations on hazardous waste or packaging and packaging waste respectively

**Substances that contribute to the classification**

reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100); Xylene; Xylene; 1-butanol

**2.3 Other hazards which do not result in classification:**

Non-applicable

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**

**3.1 Substances:**

Non-applicable

**3.2 Mixtures:**

**Chemical description:** Mixture composed of chemical products

**Components:**

In accordance with Part B: Concentration cut-offs for ingredients in mixtures for purpose of section 3 of Hazardous Substances (Safety Data Sheets) Notice 2017, the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 25068-38-6	<b>reaction product: bisphenol-A-(epichlorhydrin) (700 &lt; MW &lt; 1100)</b> 6.3A: H315; 6.4A: H319; 6.5B: H317 - Warning	10 - <25 %
CAS: 1330-20-7	<b>Xylene</b> 3.1C: H226; 6.1D: H312+H332; 6.1E : H304; 6.1E: H303; 6.1E: H335; 6.3A: H315; 6.4A: H319; 6.9B: H373 - Danger	10 - <25 %
CAS: 1330-20-7	<b>Xylene</b> 3.1C: H226; 6.1D: H312+H332; 6.1E: H303; 6.3A: H315 - Warning	5 - <10 %
CAS: 71-36-3	<b>1-butanol</b> 3.1C: H226; 6.1D: H302; 6.1E: H313; 6.1E: H335; 6.3A: H315; 6.9B: H336; 8.3A: H318 - Danger	2,5 - <5 %
CAS: 100-41-4	<b>Ethylbenzene</b> 3.1B: H225; 6.1D: H332; 6.1E: H303 - Danger	1 - <2,5 %
CAS: 7779-90-0	<b>trizinc bis(orthophosphate)</b> 9.1A: H400; 9.1A: H410 - Warning	1 - <2,5 %
CAS: 1314-13-2	<b>Zinc oxide</b> 9.1A: H400; 9.1A: H410 - Warning	<1 %

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

**SECTION 4: FIRST-AID MEASURES**

**4.1 First aid instructions according to each relevant route of exposure;:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

**By inhalation:**

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

**By skin contact:**

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 4: FIRST-AID MEASURES (continued)**

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

**By eye contact:**

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, as this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

**By ingestion/aspiration:**

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

**4.2 Most important symptoms and effects, acute and delayed:**

Acute and delayed effects are indicated in sections 2 and 11.

**4.3 Indication of medical attention and its urgency:**

Non-applicable

**SECTION 5: FIRE-FIGHTING MEASURES**

**5.1 Information on the appropriate type of extinguishers or fire-fighting agents:**

If possible use polyvalent powder fire extinguishers (ABC powder), alternatively use foam or carbon dioxide extinguishers (CO2). IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

**5.2 Advice on specific hazards that may arise from the substance:**

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

**5.3 Special protective equipment and precautions for fire-fighters:**

Depending on the magnitude of the fire it may be necessary to use full protective clothing and individual respiratory equipment. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...)

**Additional provisions:**

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Destroy any source of ignition. In case of fire, refrigerate the storage containers and tanks for products susceptible to inflammation, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

**6.1 Personal precautions, protective equipment and emergency procedures:**

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Destroy any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

**6.2 Environmental precautions from accidental spills and release::**

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

**6.3 Advice on how to contain and clean up a spill or release:**

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

**6.4 Reference to other sections:**

See sections 8 and 13.

**SECTION 7: HANDLING AND STORAGE**

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 7: HANDLING AND STORAGE (continued)**

**7.1 Precautions for safe handling:**

A.- Precautions for safe manipulation

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Transfer in well ventilated areas, preferably through localized extraction. Fully control sources of ignition (mobile phones, sparks,...) and ventilate during cleaning operations. Avoid the existence of dangerous atmospheres inside containers, applying inertization systems where possible. Transfer at a slow speed to avoid the creation of electrostatic charges. Against the possibility of electrostatic charges: ensure a perfect equipotential connection, always use groundings, do not wear work clothes made of acrylic fibres, preferably wearing cotton clothing and conductive footwear. Comply with the essential security requirements for equipment and systems and with the minimum requirements for protecting the security and health of workers. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations to prevent ergonomic and toxicological risks

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

**7.2 Conditions for safe storage, including any incompatibilities:**

A.- Technical measures for storage

- Minimum Temp.: 15 °C
- Maximum Temp.: 25 °C
- Maximum time: 12 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

**7.3 Specific end use(s):**

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**8.1 Occupational exposure limits:**

Substances whose workplace exposure standards (WES) have to be monitored in the work environment

Identification	OEL		
	TWA	STEL	mg/m <sup>3</sup>
Xylene CAS: 1330-20-7	50 ppm		217 mg/m <sup>3</sup>
Xylene CAS: 1330-20-7	50 ppm		217 mg/m <sup>3</sup>
1-butanol CAS: 71-36-3	50 ppm		150 mg/m <sup>3</sup>
		50 ppm	150 mg/m <sup>3</sup>
Ethylbenzene CAS: 100-41-4	100 ppm		434 mg/m <sup>3</sup>
		125 ppm	543 mg/m <sup>3</sup>
Zinc oxide CAS: 1314-13-2			3 mg/m <sup>3</sup>
			10 mg/m <sup>3</sup>

**8.2 Engineering controls:**

A.- Identification of the specific types of personal protective equipment

As a preventative measure it is recommended to use basic Personal Protection Equipment. For more information on Personal Protection Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)**

Pictogram	PPE	Remarks
<p>Mandatory respiratory tract protection</p>	Filter mask for gases and vapours (A)	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Remarks
<p>Mandatory hand protection</p>	NON-disposable chemical protective gloves (NBR), Breakthrough Time 480 min, thickness 0.4 mm	The Breakthrough Time indicated by the manufacturer must exceed the period during which the product is being used. Do not use protective creams after the product has come into contact with skin.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application

D.- Ocular and facial protection

Pictogram	PPE	Remarks
<p>Mandatory face protection</p>	Panoramic glasses against splash/projections.	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Bodily protection

Pictogram	PPE	Remarks
<p>Mandatory complete body protection</p>	Disposable clothing for protection against chemical risks, with antistatic and fireproof properties	For professional use only. Clean periodically according to the manufacturer's instructions.
<p>Mandatory foot protection</p>	Safety footwear for protection against chemical risk, with antistatic and heat resistant properties	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
<p>Emergency shower</p>	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	<p>Eyewash stations</p>	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

**Environmental exposure controls:**

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES**

**9.1 Information on basic physical and chemical properties:**

For complete information see the product datasheet.

**Appearance:**

Physical state at 20 °C:

Liquid

Appearance:

Viscous

Colour:

Grey

\*Not relevant due to the nature of the product, not providing information property of its hazards.

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)**

Odour:	Characteristic
Odour threshold:	Non-applicable *
<b>Volatility:</b>	
Initial boiling point and boiling range:	134 °C
Vapour pressure at 20 °C:	793 Pa
Vapour pressure at 50 °C:	4438.23 Pa (4.44 kPa)
Evaporation rate at 20 °C:	Non-applicable *
<b>Product description:</b>	
Density at 20 °C:	1560 kg/m <sup>3</sup>
Relative density at 20 °C:	Non-applicable *
Dynamic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 20 °C:	Non-applicable *
Kinematic viscosity at 40 °C:	>20.5 cSt
Concentration:	Non-applicable *
pH:	Non-applicable *
Vapour density at 20 °C:	Non-applicable *
Partition coefficient n-octanol/water 20 °C:	Non-applicable *
Solubility in water at 20 °C:	Non-applicable *
Solubility properties:	Non-applicable *
Decomposition temperature:	Non-applicable *
Melting point/freezing point:	Non-applicable *
Explosive properties:	Non-applicable *
Oxidising properties:	Non-applicable *
<b>Flammability:</b>	
Flash Point:	26 °C
Flammability (solid, gas):	Non-applicable *
Autoignition temperature:	230 °C
Lower flammability limit:	Not available
Upper flammability limit:	Not available
<b>Explosive:</b>	
Lower explosive limit:	Non-applicable *
Upper explosive limit:	Non-applicable *
<b>9.2 Other information:</b>	
Surface tension at 20 °C:	Non-applicable *
Refraction index:	Non-applicable *

\*Not relevant due to the nature of the product, not providing information property of its hazards.

**SECTION 10: STABILITY AND REACTIVITY**

**10.1 Chemical reactivity:**

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

**10.2 Chemical stability:**

Chemically stable under the conditions of storage, handling and use.

**10.3 Possibility of hazardous reactions:**

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

CONTINUED ON NEXT PAGE

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 10: STABILITY AND REACTIVITY (continued)**

**10.4 List of conditions to avoid or prevent a hazardous situation:**

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Risk of combustion	Avoid direct impact	Not applicable

**10.5 Information on incompatible substances or materials:**

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases

**10.6 Information on hazardous decomposition products:**

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO<sub>2</sub>), carbon monoxide and other organic compounds.

**SECTION 11: TOXICOLOGICAL INFORMATION**

**11.1 Information on toxicological effects:**

The experimental information related to the toxicological properties of the product itself is not available

**Dangerous health implications:**

In case of exposure that is repetitive, prolonged or at concentrations higher than recommended by the occupational exposure limits, it may result in adverse effects on health depending on the means of exposure:

A- Ingestion (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
- Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.

B- Inhalation (acute effect):

- Acute toxicity : Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

C- Contact with the skin and the eyes (acute effect):

- Contact with the skin: Produces skin inflammation.
- Contact with the eyes: Produces serious eye damage after contact.

D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):

- Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for the effects mentioned. For more information see section 3.  
IARC: Ethylbenzene (2B); Xylene (3); Titanium dioxide (2B); Silicon dioxide (RCS < 1%) (3); Carbon black (2B); Talc (3); Xylene (3); Toluene (3); Quartz (1 %< RCS < 10%) (1)
- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

E- Sensitizing effects:

- Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous with sensitising effects. For more information see section 3.
- Cutaneous: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.

F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.

G- Specific target organ toxicity (STOT)-repeated exposure:

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 11: TOXICOLOGICAL INFORMATION (continued)**

- Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can cause a breakdown in the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
- Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as dangerous for this effect. For more information see section 3.

H- Aspiration hazard:

Based on available data, the classification criteria are not met, however it does contain substances classified as dangerous for this effect. For more information see section 3.

**Other information:**

Non-applicable

**Specific toxicology information on the substances:**

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100) CAS: 25068-38-6	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
Ethylbenzene CAS: 100-41-4	LD50 oral	3500 mg/kg	Rat
	LD50 dermal	15354 mg/kg	Rabbit
	LC50 inhalation	17.2 mg/L (4 h)	Rat
Xylene CAS: 1330-20-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
Xylene CAS: 1330-20-7	LD50 oral	2100 mg/kg	Rat
	LD50 dermal	1100 mg/kg (ATEi)	Rat
	LC50 inhalation	11 mg/L (4 h) (ATEi)	
trizinc bis(orthophosphate) CAS: 7779-90-0	LD50 oral	>5000 mg/kg	
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L (4 h)	
1-butanol CAS: 71-36-3	LD50 oral	2292 mg/kg	Rat
	LD50 dermal	3400 mg/kg	Rabbit
	LC50 inhalation	24.66 mg/L (4 h)	Rat
Zinc oxide CAS: 1314-13-2	LD50 oral	7950 mg/kg	Mouse
	LD50 dermal	>5000 mg/kg	
	LC50 inhalation	>5 mg/L	

**SECTION 12: ECOLOGICAL INFORMATION**

The experimental information related to the eco-toxicological properties of the product itself is not available

**12.1 Ecotoxicity (aquatic and terrestrial):**

Identification	Acute toxicity		Species	Genus
	LC50	EC50		
Xylene CAS: 1330-20-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
Xylene CAS: 1330-20-7	LC50	13.5 mg/L (96 h)	Oncorhynchus mykiss	Fish
	EC50	3.4 mg/L (48 h)	Ceriodaphnia dubia	Crustacean
	EC50	10 mg/L (72 h)	Skeletonema costatum	Algae
1-butanol CAS: 71-36-3	LC50	1740 mg/L (96 h)	Pimephales promelas	Fish
	EC50	1983 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	500 mg/L (96 h)	Scenedesmus subspicatus	Algae
Ethylbenzene CAS: 100-41-4	LC50	42.3 mg/L (96 h)	Pimephales promelas	Fish
	EC50	75 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	63 mg/L (3 h)	Chlorella vulgaris	Algae

CONTINUED ON NEXT PAGE

Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Acute toxicity		Species	Genus
trizinc bis(orthophosphate) CAS: 7779-90-0	LC50	0.1 - 1 mg/L (96 h)		Fish
	EC50	0.1 - 1 mg/L		Crustacean
	EC50	0.1 - 1 mg/L		Algae
Zinc oxide CAS: 1314-13-2	LC50	0.82 mg/L (96 h)	Oncorhynchus kisutch	Fish
	EC50	3.4 mg/L (48 h)	Daphnia magna	Crustacean
	EC50	Non-applicable		

**12.2 Persistence and degradability:**

Identification	Degradability		Biodegradability	
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100) CAS: 25068-38-6	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	0 %
Xylene CAS: 1330-20-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
Xylene CAS: 1330-20-7	BOD5	Non-applicable	Concentration	Non-applicable
	COD	Non-applicable	Period	28 days
	BOD5/COD	Non-applicable	% Biodegradable	88 %
1-butanol CAS: 71-36-3	BOD5	1.71 g O2/g	Concentration	Non-applicable
	COD	2.46 g O2/g	Period	19 days
	BOD5/COD	0.69	% Biodegradable	98 %
Ethylbenzene CAS: 100-41-4	BOD5	Non-applicable	Concentration	100 mg/L
	COD	Non-applicable	Period	14 days
	BOD5/COD	Non-applicable	% Biodegradable	90 %

**12.3 Potential to be bioaccumulative:**

Identification	Bioaccumulation potential	
reaction product: bisphenol-A-(epichlorhydrin) (700 < MW < 1100) CAS: 25068-38-6	BCF	4
	Pow Log	2.8
	Potential	Low
Xylene CAS: 1330-20-7	BCF	9
	Pow Log	2.77
	Potential	Low
Xylene CAS: 1330-20-7	BCF	9
	Pow Log	2.77
	Potential	Low
1-butanol CAS: 71-36-3	BCF	1
	Pow Log	0.88
	Potential	Low
Ethylbenzene CAS: 100-41-4	BCF	1
	Pow Log	3.15
	Potential	Low

**12.4 Mobility in soil:**

Identification	Absorption/desorption		Volatility	
Xylene CAS: 1330-20-7	Koc	202	Henry	524.86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
Xylene CAS: 1330-20-7	Koc	202	Henry	524.86 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	Non-applicable	Moist soil	Yes
1-butanol CAS: 71-36-3	Koc	2.44	Henry	5.39E-2 Pa·m <sup>3</sup> /mol
	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.567E-2 N/m (25 °C)	Moist soil	Yes

CONTINUED ON NEXT PAGE

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020      Date of compilation: 26/06/2011      Revised: 29/11/2019      Version: 5 (Replaced 4)

**SECTION 12: ECOLOGICAL INFORMATION (continued)**

Identification	Absorption/desorption		Volatility	
Ethylbenzene CAS: 100-41-4	Koc	520	Henry	798.44 Pa·m <sup>3</sup> /mol
	Conclusion	Moderate	Dry soil	Yes
	Surface tension	2.859E-2 N/m (25 °C)	Moist soil	Yes

**12.5 Results of PBT and vPvB assessment:**

Non-applicable

**12.6 Other adverse effects:**

Not described

**SECTION 13: DISPOSAL CONSIDERATIONS**

**13.1 Appropriate and achievable disposal methods:**

**Special precautions to be taken during disposal:**

Consult the authorized waste service manager on the assessment and disposal operations. In case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. We do not recommended disposal down the drain. See epigraph 6.2.

**Regulations related to waste management:**

Legislation related to waste management:

Imports and Exports (Restrictions) Prohibition Order (No 2) 2004

**SECTION 14: TRANSPORT INFORMATION**

**Transport of dangerous goods by land:**

With regard to NZS 5433.1:2012 Transport of dangerous goods on land



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 UN dangerous goods class and subsidiary risk:** 3
- Labels: 3
- 14.4 UN Packing Group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

**Transport of dangerous goods by sea:**

With regard to IMDG 38-16:



- 14.1 UN number:** UN1263
- 14.2 UN proper shipping name:** PAINT
- 14.3 UN dangerous goods class and subsidiary risk:** 3
- Labels: 3
- 14.4 UN Packing Group:** III
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**  
Physico-Chemical properties: see section 9
- 14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:** Non-applicable

**Transport of dangerous goods by air:**

CONTINUED ON NEXT PAGE

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 14: TRANSPORT INFORMATION (continued)**

With regard to IATA/ICAO 2020:



- |   |                |
|---|----------------|
| <b>14.1 UN number:</b>  | UN1263         |
| <b>14.2 UN proper shipping name:</b>  | PAINT          |
| <b>14.3 UN dangerous goods class and subsidiary risk:</b>                             | 3              |
| Labels:   | 3              |
| <b>14.4 UN Packing Group:</b>   | III            |
| <b>14.5 Environmental hazards:</b>  | No             |
| <b>14.6 Special precautions for user</b>  |                |
| Physico-Chemical properties:  | see section 9  |
| <b>14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:</b> | Non-applicable |

**SECTION 15: REGULATORY INFORMATION**

**15.1 Safety, health and environmental regulations specific for the product in question:**

**Specific provisions in terms of protecting people or the environment:**

It is recommended to use the information included in this safety data sheet as data used in a risk evaluation of the local circumstances in order to establish the necessary risk prevention measures for the manipulation, use, storage and disposal of this product.

**Relevant regulatory requirements:**

- Health and Safety at Work (Hazardous Substances) Regulations 2017
- Health and Safety at Work Act 2015
- Hazardous Substances (Classification) Notice 2017
- Hazardous Substances (Labelling) Notice 2017

**SECTION 16: OTHER INFORMATION**

**Legislation related to safety data sheets:**

This safety data sheet has been designed in accordance with Schedule 1: Content and format of safety data sheets of Hazardous Substances (Safety Data Sheets) Notice 2017

**Texts of the legislative phrases mentioned in section 2:**

- H315: Causes skin irritation
- H316: Causes mild skin irritation
- H318: Causes serious eye damage
- H317: May cause an allergic skin reaction
- H335: May cause respiratory irritation
- H373: May cause damage to organs through prolonged or repeated exposure (Oral)
- H402: Harmful to aquatic life
- H412: Harmful to aquatic life with long lasting effects
- H313: May be harmful in contact with skin
- H226: Flammable liquid and vapour

**Texts of the legislative phrases mentioned in section 3:**

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

**HSNO Act:**

## Safety data sheet

According to Hazardous Substances (Safety Data Sheets) Notice 2017

**ANTICORROSIVE EPOXY PRIMER 4:1**

Printing: 2/03/2020

Date of compilation: 26/06/2011

Revised: 29/11/2019

Version: 5 (Replaced 4)

**SECTION 16: OTHER INFORMATION (continued)**

- 3.1B: H225 - Highly flammable liquid and vapour
- 3.1C: H226 - Flammable liquid and vapour
- 6.1D: H302 - Harmful if swallowed
- 6.1D: H312+H332 - Harmful in contact with skin or if inhaled
- 6.1D: H332 - Harmful if inhaled
- 6.1E : H304 - May be fatal if swallowed and enters airways
- 6.1E: H303 - May be harmful if swallowed
- 6.1E: H313 - May be harmful in contact with skin
- 6.1E: H335 - May cause respiratory irritation
- 6.3A: H315 - Causes skin irritation
- 6.4A: H319 - Causes serious eye irritation
- 6.5B: H317 - May cause an allergic skin reaction
- 6.9B: H336 - May cause drowsiness or dizziness
- 6.9B: H373 - May cause damage to organs through prolonged or repeated exposure (Oral)
- 8.3A: H318 - Causes serious eye damage
- 9.1A: H400 - Very toxic to aquatic life
- 9.1A: H410 - Very toxic to aquatic life with long lasting effects

**Advice related to training:**

Minimal training is recommended to prevent industrial risks for staff using this product, in order to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

**Principal bibliographical sources:**

<https://www.epa.govt.nz/>

**Abbreviations and acronyms:**

HSNO Act: Hazardous substances and new organisms Act  
 IMDG: International maritime dangerous goods code  
 IATA: International Air Transport Association  
 ICAO: International Civil Aviation Organisation  
 COD: Chemical Oxygen Demand  
 BOD5: 5-day biochemical oxygen demand  
 BCF: Bioconcentration factor  
 LD50: Lethal Dose 50  
 CL50: Lethal Concentration 50  
 EC50: Effective concentration 50  
 Log-POW: Octanol-water partition coefficient  
 Koc: Partition coefficient of organic carbon

**Other information:**

GROUP STANDARD  
 HSR002662

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

END OF SAFETY DATA SHEET